INSPECTION OF RIGGING HARDWARE

INSPECTION FREQUENCY PER ASME B30.26

A VISUAL INSPECTION SHALL BE PERFORMED BY THE USER OR DESIGNATED PERSON EACH DAY BEFORE THE RIGGING HARDWARE IS USED.

A PERIODIC INSPECTION SHALL BE PERFORMED BY A DESIGNATED PERSON, AT LEAST ANNUALLY. THE RIGGING HARDWARE SHALL BE EXAMINED AND A DETERMINATION MADE AS TO WHETHER THEY CONSTITUTE A HAZARD. WRITTEN RECORDS ARE NOT REQUIRED.

SEMI-PERMANENT AND INACCESSIBLE LOCATIONS WHERE FREQUENT INSPECTIONS ARE NOT FEASIBLE SHALL HAVE PERIODIC INSPECTIONS PERFORMED.

REJECTION CRITERIA PER ASME B30.26

MISSING OR ILLEGIBLE MANUFACTURER'S NAME OR TRADEMARK AND/OR RATED LOAD IDENTIFICATION (OR SIZE AS REQUIRED)

A 10% OR MORE REDUCTION OF THE ORIGINAL DIMENSION

BENT, TWISTED, DISTORTED, STRETCHED, ELONGATED, CRACKED OR BROKEN LOAD BEARING COMPONENTS

EXCESSIVE NICKS, GOUGES, PITTING AND CORROSION

INDICATIONS OF HEAT DAMAGE INCLUDING WELD SPATTER OR ARC STRIKES, EVIDENCE OF UNAUTHORIZED WELDING

LOOSE OR MISSING NUTS, BOLTS, COTTER PINS, SNAP RINGS, OR OTHER FASTENERS AND RETAINING DEVICES

UNAUTHORIZED REPLACEMENT COMPONENTS OR OTHER VISIBLE CONDITIONS THAT CAUSE DOUBT AS TO THE CONTINUED USE OF THE SLING

ADDITIONALLY, INSPECT WIRE ROPE CLIPS FOR:

1. INSUFFICIENT NUMBER OF CLIPS
2. INCORRECT SPACING BETWEEN CLIPS
3. IMPROPERLY TIGHTENED CLIPS
4. INDICATIONS OF DAMAGED WIRE ROPE OR WIRE ROPE SLIPPAGE
5. IMPROPER ASSEMBLY

ADDITIONALLY, INSPECT WEDGE SOCKETS FOR:

1. INDICATIONS OF DAMAGED WIRE ROPE OR WIRE ROPE SLIPPAGE
2. IMPROPER ASSEMBLY

ADDITIONAL REJECTION CRITERIA AND INFORMATION PER ASME B30.10 - HOOKS

- ANY VISIBLY APPARENT BEND OR TWIST FROM THE PLANE OF THE UNBENT HOOK
- ANY DISTORTION CAUSING AN INCREASE IN THROAT OPENING OF 5%, NOT TO EXCEED 1/4"
- MISSING OR ILLEGIBLE RATED LOAD IDENTIFICATION
- MISSING OR ILLEGIBLE HOOK MANUFACTURER'S IDENTIFICATION OR SECONDARY MFG. IDENTIFICATION
- HOOKS SHALL NOT BE RETURNED TO SERVICE UNTIL APPROVED BY A QUALIFIED PERSON
- HOOKS REQUIRE A WRITTEN RECORD OF THE PERIODIC INSPECTION, MINIMUM OF ONCE PER YEAR

INSPECTION OF SLINGS

INSPECTION FREQUENCY PER ASME B30.9

A VISUAL INSPECTION FOR DAMAGE SHALL BE PERFORMED BY A DESIGNATED PERSON EACH DAY OR SHIFT THE SLING IS USED. A COMPLETE INSPECTION FOR DAMAGE SHALL BE PERFORMED PERIODICALLY BY A DESIGNATED PERSON, AT LEAST ANNUALLY.

REJECTION CRITERIA PER ASME B30.9

MISSING OR ILLEGIBLE SLING IDENTIFICATION; EVIDENCE OF HEAT DAMAGE; SLINGS THAT ARE KNOTTED; FITTINGS THAT ARE PITTED, CORRODED, CRACKED, BENT, TWISTED, GOUGED, OR BROKEN; OTHER CONDITIONS, INCLUDING VISIBLE DAMAGE, THAT CAUSE DOUBT AS TO THE CONTINUED USE OF THE SLING.

WIRE ROPE SLINGS

EXCESSIVE BROKEN WIRES, FOR STRAND-LAID AND SINGLE PART SLINGS, TEN RANDOMLY DISTRIBUTED BROKEN WIRES IN ONE ROPE LAY OR FIVE BROKEN WIRES IN ONE STRAND IN ONE ROPE LAY

SEVERE LOCALIZED ABRASION OR SCRAPING, KINKING, CRUSHING, BIRDCAGING

ANY OTHER DAMAGE RESULTING IN DAMAGE TO THE ROPE STRUCTURE

SEVERE CORROSION OF THE ROPE OR END ATTACHMENTS

DOCUMENTATION THAT THE MOST RECENT PERIODIC INSPECTION WAS PERFORMED SHALL BE MAINTAINED

INSPECTION RECORDS OF INDIVIDUAL SLINGS ARE NOT REQUIRED

CHAIN SLINGS

CRACKS OR BREAKS

EXCESSIVE WEAR, NICKS OR GOUGES

STRETCHED CHAIN LINKS OR COMPONENTS

BENT, TWISTED OR DEFORMED CHAIN LINKS OR COMPONENTS

EXCESSIVE PITTING OR CORROSION

LACK OF ABILITY OF CHAIN OR COMPONENTS TO HINGE FREELY

WELD SPATTER

A WRITTEN RECORD OF THE INITIAL INSPECTION REFERENCING INDIVIDUAL SLING IDENTIFICATION IS REQUIRED

A WRITTEN RECORD OF THE MOST RECENT PERIODIC INSPECTION SHALL BE MAINTAINED AND SHALL INCLUDE THE CONDITION OF THE SLING

WEB SLINGS

ACID OR CAUSTIC BURNS

MELTING OR CHARRING OF ANY PART OF THE SLING

HOLES, TEARS, CUTS OR SNAGS

BROKEN OR WORN STITCHING IN LOAD BEARING SPLICES

EXCESSIVE ABRASIVE WEAR DISCOLORATION AND BRITTLE

OR STIFF AREAS ON ANY PART OF THE SLING, WHICH

MAY MEAN CHEMICAL OR ULTRAVIOLET / SUNLIGHT DAMAGE

DOCUMENTATION THAT THE MOST RECENT PERIODIC INSPECTION WAS PERFORMED SHALL BE MAINTAINED

ROUND SLINGS

ACID OR CAUSTIC BURNS EVIDENCE OF HEAT DAMAGE

HOLES, TEARS, CUTS, ABRASIVE WEAR OR SNAGS THAT EXPOSE THE CORE YARNS

BROKEN OR DAMAGED CORE YARNS

WELD SPATTER THAT EXPOSES CORE YARNS

DISCOLORATION AND BRITTLE OR STIFF AREAS ON ANY PART OF THE SLINGS, WHICH MAY MEAN CHEMICAL OR OTHER DAMAGE

DOCUMENTATION THAT THE MOST RECENT PERIODIC INSPECTION WAS PERFORMED SHALL BE MAINTAINED

Copyright © 2019 The Crosby Group LLC All Rights Reserved