- **Maintenance and Inspection**

  A preventive maintenance program based on the crane manufacturer's recommendations should be utilized. Also, in accordance with ASME B30.5, and OSHA guidelines, frequent and periodic inspections are to be performed. In addition to the performance of these inspections, equipment must be inspected to ensure that it is capable of safe and reliable operation when initially placed in service and after any major repairs or design modification. OSHA and ASME guidelines are to be followed when performing inspections. The following inspections apply:

  - Frequent inspections - Prior to the start of each job, the crane is to be visually inspected by a competent person and a written record of the inspection should be completed prior to performing any crane operations. Qualified crane Operator's are the Company's designated competent persons to perform routine crane inspections. See the Crane Inspection report for a list of items to be inspected. Slings and related attachments need to be inspected for damage, defects or signs of wear. Crane Inspection report forms may be obtained from a Safety Manager or from the Safety Office.

    Any defect noted during the inspection is to be discussed with the job Supervisor immediately. After careful examination, the job Supervisor, with input from the crane Operator, shall make a determination as to whether the defect or deficiency poses a safety hazard. If it is determined that a potential safety hazard exists, the crane is not to be operated until the defect is remedied. If the determination is made that the crane can be operated safely despite the deficiency, the Supervisor should ensure that the Crane Inspection report indicates the issue and that the proper maintenance personnel are contacted and made aware of the issue.

  - Periodic inspections – A monthly crane inspection will be performed and documented by a crane Operator or trained Mechanic. A crane inspection by a certified crane inspector is to be performed on an annual basis, or sooner, if circumstances such as activity, environment, or severity of service indicate the necessity. The inspection is to be made by a reputable crane inspection company as approved by management, or a competent employee whom, for the purposes of this inspection, includes any employee who has attended and passed a crane inspection class taught by a reputable crane inspection school. At the inspector's discretion, serious defects noted in this inspection must be repaired prior to operation. A defect that poses no hazard or risk of further or future damage should be scheduled for repair as soon as practicable. All Periodic Inspection reports should be kept on file in the Marshall terminal for as long as the Company owns the crane.

  - After shutdown or storage - In accordance with 29 CFR 1910.180 (d)(5)(i), subsequent to any crane coming out of storage or shutdown, all wire ropes are to be inspected prior to use. All rope which has been idle for a period of one month or more, but less than six months, due to shutdown or storage of a crane on which it is installed shall be given a thorough inspection before it is used. This inspection shall be for all types of deterioration and shall be performed by an appointed or authorized person whose approval shall be required for further use of the rope. A certification record which includes the date of inspection, the signature of the person who performed the inspection and an identifier for the rope which was inspected shall be prepared and kept readily available.

  - Rated load tests – All cranes are to come with written reports indicating the manufacturer's rated load tests. Any alteration that may affect the crane's ability to perform at its original rated load requires a separate rated load test be performed to confirm the adequacy of the alteration.

- **Equipment Inventory**
  - Rig Runner Inc maintains its equipment inventory, within the PCS Express Fleet management module, to track equipment and, Equipment
    records within the asset management module contain a variety of data including asset description, Unique Identifiers, model number, serial number, location.