```
mojtaba@ubuntu:~/docker-course/redis-image$ ^C
mojtaba@ubuntu:~/docker-course/redis-image$ sudo docker build .
Sending build context to Docker daemon  2.048kB
Step 1/3 : FROM alpine
latest: Pulling from library/alpine
df20fa9351a1: Pull complete
Digest: sha256:185518070891758909c9f839cf4ca393ee977ac378609f700f60a771a2dfe321
Status: Downloaded newer image for alpine:latest
 ---> a24bb4013296
Step 2/3 : RUN apk add --update redis
 ---> Running in 74db29fb509e
fetch http://dl-cdn.alpinelinux.org/alpine/v3.12/main/x86_64/APKINDEX.tar.gz
fetch http://dl-cdn.alpinelinux.org/alpine/v3.12/community/x86_64/APKINDEX.tar.gz
(1/1) Installing redis (5.0.9-r0)
Executing redis-5.0.9-r0.pre-install
Executing redis-5.0.9-r0.post-install
Executing busybox-1.31.1-r16.trigger
OK: 7 MiB in 15 packages
Removing intermediate container 74db29fb509e
 ---> f54093711d4b
Step 3/3 : CMD [ "redis-server" ]
 ---> Running in b8308980036b
Removing intermediate container b8308980036b
 ---> 50bf233f827e
Successfully built 50bf233f827e
mojtaba@ubuntu:~/docker-course/redis-image$ docker run ^C
mojtaba@ubuntu:~/docker-course/redis-image$ sudo docker run 50bf233f827e
```

بعد اینکه اجرا تموش شد منبع کامنده و ساختار intermediate container رو container
intermediate container رو حذف می‌کنه و بعنویس نتیجه رو توی یه image
ذخیره می‌کنه. وخلاصه end result
میشه image (step 2/3) که ممکنه actually
توی آموزش دیدیم که اینجوری نیستکه درقدم اول یه
intermediate container
(اجرا میشه دستورات تکه اول
ثمکه بعد ازاینکه اجراینش میشه یا این اجرابیم؟ (دقیقا مشمیم پنم؟ کی اجراشه دستور؟ (شایه دراست صحت؟)
کی دستورا اجرا بیه یه intermediate ایجا بشه؟ (زیدی خیزره؟)
container