FEATURES

- Internally frequency compensated for unity gain
- Large DC voltage gain : 100dB
- Wide power supply range : 3V~32V(or±1.5V~16V)
- Input common-mode voltage range includes ground
- Large output voltage swing : 0V DC to V_{CC}-1.5V DC
- Power drain suitable for battery operation
- Moisture Sensitivity Level 3
- LM358G is Halogen Free product

SOP-8 PKG

DIP-8 PKG

SOP8/ DIP8 PIN Configulation



ORDERING INFORMATION

Device	Package
LM358D	8 SOP
LM358GD	
LM358N	8 DIP

DUAL OPERATIONAL AMPLIFIERS

LM358 is consists of four independent, high gain, internally frequency compensated operational amplifiers which were designed specifically to operate from a single power supply over a wide range of voltage. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage.
Application areas include transducer amplifier, DC gain blocks and all the conventional OP amp circuits which now can be easily implemented in single power supply systems.

EQUIVALENT CIRCUIT



ABSOLUTE MAXIMUM RATINGS

CHARACTERISTIC	SYMBOL	VALUE	UNIT
Supply Voltage	V_{CC}	±16 or 32	V
Differential Input Voltage	$V_{I(DIFF)}$	±32	V
Input Voltage	V_I	-0.3 to +32	V
Output Short Circuit to GND		Continuous	
V_{CC}≤V T_A=25℃ (One Amp)			
Operating Temperature Range	T_{OPR}	0~+70	℃
Storage Temperature Range	T_{STG}	-65 to +150	℃

Electrical characterisitics at specified free-air temperature, V_{CC}=5V(unless otherwise noted)

PARAMETER	TEST CONDITIONS*		LM358 MIN	LM358 TYP	LM358 MAX	UNIT
V_{IO} Input Offset Voltage	V_{CC}=5V to MAX, V_{IC}=V_{ICR}MIN, V_O=1.4V	25℃		3	7	mV
		Full Range			9	
αV_{IO} Average Temperature Coefficient of Input Offset Voltage		Full Range		7		μV/℃
I_{IO} Input Offset Current	V_O=1.4V	25℃		2	50	nA
		Full Range			150	
αIio Average Temperature Coefficient of Input Offset Current		Full Range		10		pA/℃
I_{IB} Input Bias Current	V_O=1.4V	25℃		-20	-250	nA
		Full Range			-500	
V_{ICR} Common-Mode Input Voltage Range	V_{CC}=5V to MAX	25℃	0toV_{CC}-1.5			V
		Full Range	0toV_{CC}-2			
V_{OH} High-Level Output Voltage	R_L≥2kΩ	25℃	V_{CC}-1.5			V
	V_{CC}=MAX, R_L=2kΩ	Full Range	26			
	V_{CC}=MAX, R_L≥10kΩ	Full Range	27	28		
V_{OL} Low-Level Output Voltage	R_L≥10kΩ	Full Range		5	20	mV
A_{VD} Large-Signal Differential Voltage Amplification	V_{CC}=15V, V_O=1V to 11V, R_L≥2kΩ	25℃	25	100		V/mV
		Full Range	15			
THD Total Harmonic Distortion	f=1kHz, Av=20dB, RL=2kΩ Vo=2Vpp, CL=100pF, Vo=2Vpp	25℃		0.02		%
CMRR Common-Mode Rejection Ratio	V_{CC}=5V to MAX, V_{IC}=V_{ICR}MIN	25℃	65	80		dB
K_{SVR} Supply Voltage Rejection Ratio($\Delta V_{CC}/\Delta V_{IO}$)	V_{CC}=5V to MAX	25℃	65	100		dB
V_{01}/V_{02} Crosstalk Attenuation	f=1 kHz to 20kHz	25℃		120		dB
I_O Output Current	V_{CC}=15V, V_{ID}=1V, V_O=0	25℃	-20	-30		mA
		Full Range	-10			
	V_{CC}=15V, V_{ID}=-1V, V_O=15V	25℃	10	20		
		Full Range	5			
	V_{ID}=-1V, V_O=200mV	25℃	12	30		μA
I_{OS} Short-Circuit Output Current	V_{CC} at 5V, GND at -5V, V_O=0	25℃		±40	±60	mA
I_{CC} Supply Current (Two Amplifiers)	V_O=2.5V, No Load	Full Range		0.7	1.2	mA
	V_{CC}=MAX, V_O=0.5V_{CC}, No Load	Full Range		1	2	

* All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified <<MAX>> V_{CC} for testing purpose is 30V. Full range is 0℃ to 70℃.

TYPICAL PERFORMANCE CHARACTERISTICS

SUPPLY CURRENT



CURRENT LIMITING



VOLTAGE GAIN



OPEN-LOOP FREQUENCY RESPONSE



LARGE-SIGNAL FREQUENCY RESPONSE



VOLTAGE-FOLLOWER PULSE RESPONSE



VOLTAGE-FOLLOWER PULSE RESPONSE (SMALL-SIGNAL)



OUTPUT CHARACTERISITICS CURRENT SOURCING



OUTPUT CHARACTERISITICS CURRENT SINKING



TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUIED)



TYPICAL APPLICATIONS



SINGLE SUPPLY INVERTING AMPLIFIER



INPUT BIASING VOLTAGE POLLOWER



NON-INVERTING AMPLIFIER