M.M.C.O.E.

Page No. : Date :

Name : Mokshada Hejib SY1 AI PRN: B25ET1013

Experiment-1 FAQ

1.) What is a string?

Ans- A string in C is a sequence of characters stored in a character array and terminated by the null character \0. For example, char s[] = "Hello"; stores five letters followed by the null terminator.

2.) Explain string functions strcmp(), strlen(), strcat(), strcpy()

Ans- Strcmp(S1, S2): compares two lexicographically; returns zero when equal, a negative value when S1 comes ~~becomes~~ before S2, and a positive value when S1 comes after S2.

Strlen() : returns the number of characters, excluding the null terminator

Strcat(dest, src); appends src to end of dest.

Strcpy(dest, src); copies src, including its null terminator, into dest. The destination must have sufficient space.

3.) In string comparisons, if two strings are same, what will be the result of comparison?

Ans- The function strcmp() returns 0 when strings are identical

M.M.C.O.E.

Page No. | Date

4.) What is length of string "Data Structures"?

Ans- The length is 15 characters: 4 letters in "Data", 1 space and 10 letters in "structures". The terminating null character is not counted.

5.) Explain how to use strcpy() function()

Ans- Include <string.h> and call strcpy(destination, source) Example: Example char src[] = "Hello"; char dest[2]; strcpy(dest, src); now dest contains "Hello".

6.) What is strncat(): string function?

Ans strncat(dest, src, n) appends at most n characters from src to the end of dest and then adds a null terminator The destination needs enough available space.

7.) What is strrev()?

Ans strrev() reverses the characters of a string in place in some (compilers. It is not part of standard C; for portable programs reverse the string using a loop or swaps.

8.) which function is more appropriate for reading multiword string?

Ans- fgets() is preferable because it can read spaces, and limits the no. of characters read. Example: fgets(s, sizeof s, stdin): It may retain the trailing newline.

9.) What are the application of strings?

Ans - Strings are used to store and process names, messages and addresses, search or compare text; count words; validate user input, and manage text based records.

10.) What is the limitation of array of pointers to strings?

Ans - An array of character pointer holds addresses, not character storage for each string. Each pointer must refer to valid memory, modifying a string literal is undefined behaviour.