Name: Mokshada Hejib PRN: B25ETI1013
class: AI

Experiment - 13 FAQs.

Q1 Which header file is required for file handling in C++?

Ans The fstream header provides file stream classes such as ifstream ofstream and fstream. These classes support from and writing to file.

Q2 What is the difference between ifstream ofstream and fstream?

Ans: ifstream is mainly used to read from while ofstream is mainly used to write to files. fstream suppots both input and output operations.

Q3 Why should a file stream be checked after opening

Ans: Opening can fail if the file does not exist, the path is incorrect or permissions are insufficient. Checking for stream prevents the program from continuing as if file were opened successfully.

Q4 what does rdbuf() represent in program?

Ans rdbuf() provides access to the stream's underlying stream buffer. Sending the

input file's buffer to the output stream can copy its contents without a manual character-by-character loop.

Q5 How can a program be modified for binary files?

Ans Open both files with the ios::binary mode flag. Copy the bytes without text mode translation so the destination preserves the source data.

Q6 What is the purpose of the open() function

Ans The open() function associates a file stream object with a specified file and mode. It can be used when the file name is not supplied to the stream constructor.

Q7 What is the purpose of the close() function

Ans The close() function closes the associated file and releases the file resource. It also finalizes pending output, so it is good practice to check for write errors when needed

Q8 What is ios::in mode?

Ans ios::in opens a file for input meaning the program can read from it. It is commonly used with ifstream or with fstream when reading is required.