M.M.C.O.E.

Page No. : Date :

Name: Mokshada Hejib PRN: B25ET1013

class : A1

Experiment - 2 FAQs.

1. What does the modulo operator return?

Ans: The modulo operator %, returns the remainder after integer division.
For example: 7%2 gives 1.

2. How is an even number detected in C++?

Ans: A number is even if dividing it by 2 leaves no remainder. In C++, test this using n%2==0.

3 What is a reference variable in C++? Give an example.

Ans A reference is another name for an existing variable and is declared using &.
For example: int a=5, int &r=a; means changing r also changes a.

4 Can the same result be obtained by incrementing the loop by 2?

Ans Yes, start the loop at 2 and increase the value by 2 until 50. Every generated value is even, so a separate modulo check is unnecessory.

M.M.C.O.E.

Page No. : Date :

5. What changes are needed to find the sum of odd numbers?

Ans Change the condition to i %2 != 0, or start from 1 and increment by 2. keep the sum initialized to zero.

6. what is statement terminator in C++?

Ans A semicolon (;) terminates most statements in C++. It tells the compiler where that statement ends.

7 Explain the functionalities of Cin and Cout?

Ans Cin takes input from the standard input, usually the keyboard using >>, Cout displays output on the screen using <<.

8 Why do we include the iostream header file?

Ans The <iostream> header provides standard input/output stream objects and operators including Cin and Cout. Without it, these names may not be declared.