M.M.C.O.E.
Page No. : Date :

Name: Mokshada Hejib PRN: B25ET1013
class : AI

Experiment - 7 FAQs

1. What is the purpose of a constructor?
Ans A constructor initializes an object when it is created. It can allocate the required memory and place the object in a valid initial state.

2 When is a destructor called?
Ans A destructor is called automatically when an object's lifetime ends, such as when a local object goes out of scope. It is used to release resource owned by the object.

3 What is a deep copy and why is it required here?
Ans A deep copy allocates separate memory and copies the characters into it. It prevents two string objects from sharing the same dynamically allocated character array.

4. Why is the destructor needed and why is delete [] used?
Ans The destructor releases dynamically allocated memory to prevent memory

leaks. Since the memory was allocated using new[]. It must be released using the matching delete[].

5. What problem can occur with the compile generated copy constructor and raw pointers?

Ans It may only the pointer address, creating a shallow copy. But objects then point to the same memory which can cause unitended sharing or double deletion

6 Explain different types of constructor with examples.

Ans A default constructor takes no arguments such as Mystring(). A parameterised constructor accepts values such as MyString(const char*s). While a copy constructor creates an object from the same clas?

7 Explain Constructor overloading?

Ans Constructor ~~toa~~ overloading means defining multiple constrors with different parameter list in the same class. It lets objects be initiated in different ways such with no value or with an inilial string