



You are here: [Home](#) > [Projects](#) > [SSL Server Test](#) > zero.webappsecurity.com

SSL Report: zero.webappsecurity.com (54.82.22.214)

Assessed on: Thu, 28 May 2026 05:53:49 UTC | [Hide](#) | [Clear cache](#)

[Scan Another »](#)

Summary

Overall Rating

F

Certificate

Protocol Support

Key Exchange

Cipher Strength

0 20 40 60 80 100

Visit our [documentation page](#) for more information, configuration guides, and books. Known issues are documented [here](#).

This server's certificate is not trusted, see [below](#) for details.

This server supports SSL 2, which is obsolete and insecure, and can be used against TLS (DROWN attack). Grade set to F. [MORE INFO »](#)

This server supports insecure cipher suites (see below for details). Grade set to F.

This server supports insecure Diffie-Hellman (DH) key exchange parameters (Logjam). Grade set to F. [MORE INFO »](#)

This server supports 512-bit export suites and might be vulnerable to the FREAK attack. Grade set to F. [MORE INFO »](#)

This server is vulnerable to the POODLE attack. If possible, disable SSL 3 to mitigate. Grade capped to C. [MORE INFO »](#)

This server is vulnerable to MITM attacks because it supports [insecure renegotiation](#). Grade set to F.

This server does not mitigate the [CRIME attack](#). Grade capped to C.

The server supports only older protocols, but not the current best TLS 1.2 or TLS 1.3. Grade capped to C. [MORE INFO »](#)

This server accepts RC4 cipher, but only with older protocols. Grade capped to B. [MORE INFO »](#)

There is no support for secure renegotiation. [MORE INFO »](#)

This server does not support Forward Secrecy with the reference browsers. Grade capped to B. [MORE INFO »](#)

This server does not support Authenticated encryption (AEAD) cipher suites. Grade capped to B. [MORE INFO »](#)

This server supports TLS 1.0. Grade capped to B. [MORE INFO »](#)

This server does not support TLS 1.3. [MORE INFO »](#)

This server does not support PQC (Post-Quantum Cryptography) key exchange.

Certificate #1: RSA 2048 bits (SHA256withRSA)



Server Key and Certificate #1

Subject

zero.webappsecurity.com

Fingerprint SHA256: b02a9cda23385967209ce506fea915a0926b4683eb89a81f015b8c312bb93cfd

Pin SHA256: iTZeCJz9Qejr55NuPqDUfs2PN5Py8m8blg7cUrA02k=

Common names

zero.webappsecurity.com

Alternative names

zero.webappsecurity.com

Serial Number

04b63f6f4401bac5f089ec7afc0a5287

Server Key and Certificate #1

Valid from	Mon, 26 Apr 2021 00:00:00 UTC
Valid until	Wed, 04 May 2022 23:59:59 UTC (expired 4 years ago) EXPIRED
Key	RSA 2048 bits (e 65537)
Weak key (Debian)	No
Issuer	DigiCert TLS RSA SHA256 2020 CA1 AIA: http://cacerts.digicert.com/DigiCertTLRSASHA2562020CA1.crt
Signature algorithm	SHA256withRSA
Extended Validation	No
Certificate Transparency	Yes (certificate)
OCSP Must Staple	No
Revocation information	CRL, OCSP CRL: http://crl3.digicert.com/DigiCertTLRSASHA2562020CA1.crl OCSP: http://ocsp.digicert.com
Revocation status	Unchecked (only trusted certificates can be checked)
DNS CAA	No (more info)
Trusted	No NOT TRUSTED (Why?) Mozilla Apple Android Java Windows



Additional Certificates (if supplied)

Certificates provided	2 (2996 bytes)
Chain issues	None

#2

Subject	DigiCert TLS RSA SHA256 2020 CA1 Fingerprint SHA256: 25768713d3b459f9382d2a594f85f34709fd2a8930731542a4146ffb246bec69 Pin SHA256: RQeZkB42znUfsDIIFWIRiYEckI7nHwNFwWCmMMJbVc=
Valid until	Mon, 23 Sep 2030 23:59:59 UTC (expires in 4 years and 3 months)
Key	RSA 2048 bits (e 65537)
Issuer	DigiCert Global Root CA
Signature algorithm	SHA256withRSA



Certification Paths

Mozilla Apple Android Java Windows

Path #1: Not trusted (validity check failed)

1	Sent by server	zero.webappsecurity.com Fingerprint SHA256: b02a9cda23385967209ce506fea915a0926b4683eb89a81f015b8c312bb93cfd Pin SHA256: iTZeCJz9Qejir55NuPqDUfs2PN5Py8m8blg7cUrA02k= RSA 2048 bits (e 65537) / SHA256withRSA Valid until: Wed, 04 May 2022 23:59:59 UTC EXPIRED
2	Sent by server	DigiCert TLS RSA SHA256 2020 CA1 Fingerprint SHA256: 25768713d3b459f9382d2a594f85f34709fd2a8930731542a4146ffb246bec69 Pin SHA256: RQeZkB42znUfsDIIFWIRiYEckI7nHwNFwWCmMMJbVc= RSA 2048 bits (e 65537) / SHA256withRSA
3	In trust store	DigiCert Global Root CA Self-signed Fingerprint SHA256: 4348a0e9444c78cb265e058d5e8944b4d84f9662bd26db257f8934a443c70161 Pin SHA256: r/mlkG3eEpVdm+u/ko/cwxzOMo1bk4TyHilByibiA5E= RSA 2048 bits (e 65537) / SHA1withRSA Weak or insecure signature, but no impact on root certificate

Configuration



Protocols

TLS 1.3	No
TLS 1.2	No
TLS 1.1	No
TLS 1.0	Yes

Protocols

SSL 3	INSECURE	Yes
SSL 2	INSECURE	Yes



Cipher Suites

# TLS 1.0 (server has no preference)		
TLS_RSA_EXPORT_WITH_RC4_40_MD5 (0x3)	INSECURE	40
TLS_RSA_EXPORT_WITH_RC2_CBC_40_MD5 (0x6)	INSECURE	40
TLS_RSA_EXPORT_WITH_DES40_CBC_SHA (0x8)	INSECURE	40
TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA (0x14)	DH 512 bits FS INSECURE	40
TLS_RSA_WITH_DES_CBC_SHA (0x9)	INSECURE	56
TLS_DHE_RSA_WITH_DES_CBC_SHA (0x15)	DH 1024 bits FS INSECURE	56
TLS_RSA_WITH_3DES_EDE_CBC_SHA (0xa)	WEAK	112
TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA (0x16)	DH 1024 bits FS WEAK	112
TLS_RSA_WITH_AES_128_CBC_SHA (0x2f)	WEAK	128
TLS_DHE_RSA_WITH_AES_128_CBC_SHA (0x33)	DH 1024 bits FS WEAK	128
TLS_RSA_WITH_RC4_128_MD5 (0x4)	INSECURE	128
TLS_RSA_WITH_RC4_128_SHA (0x5)	INSECURE	128
TLS_RSA_WITH_AES_256_CBC_SHA (0x35)	WEAK	256
TLS_DHE_RSA_WITH_AES_256_CBC_SHA (0x39)	DH 1024 bits FS WEAK	256
# SSL 3 (server has no preference)		
TLS_RSA_EXPORT_WITH_RC4_40_MD5 (0x3)	INSECURE	40
TLS_RSA_EXPORT_WITH_RC2_CBC_40_MD5 (0x6)	INSECURE	40
TLS_RSA_EXPORT_WITH_DES40_CBC_SHA (0x8)	INSECURE	40
TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA (0x14)	DH 512 bits FS INSECURE	40
TLS_RSA_WITH_DES_CBC_SHA (0x9)	INSECURE	56
TLS_DHE_RSA_WITH_DES_CBC_SHA (0x15)	DH 1024 bits FS INSECURE	56
TLS_RSA_WITH_3DES_EDE_CBC_SHA (0xa)	WEAK	112
TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA (0x16)	DH 1024 bits FS WEAK	112
TLS_RSA_WITH_AES_128_CBC_SHA (0x2f)	WEAK	128
TLS_DHE_RSA_WITH_AES_128_CBC_SHA (0x33)	DH 1024 bits FS WEAK	128
TLS_RSA_WITH_RC4_128_MD5 (0x4)	INSECURE	128
TLS_RSA_WITH_RC4_128_SHA (0x5)	INSECURE	128
TLS_RSA_WITH_AES_256_CBC_SHA (0x35)	WEAK	256
TLS_DHE_RSA_WITH_AES_256_CBC_SHA (0x39)	DH 1024 bits FS WEAK	256
# SSL 2 (client selects suite)		
SSL_CK_RC4_128_WITH_MD5 (0x10080)	INSECURE	128
SSL_CK_RC4_128_EXPORT40_WITH_MD5 (0x20080)	INSECURE	40
SSL_CK_RC2_128_CBC_WITH_MD5 (0x30080)	INSECURE	128
SSL_CK_RC2_128_CBC_EXPORT40_WITH_MD5 (0x40080)	INSECURE	40
SSL_CK_DES_64_CBC_WITH_MD5 (0x60040)	INSECURE	56
SSL_CK_DES_192_EDE3_CBC_WITH_MD5 (0x700c0)	INSECURE	112



Handshake Simulation

Android 2.3.7 No SNI ²	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_RC4_128_MD5 No FS RC4
Android 4.0.4	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Android 4.1.1	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Android 4.2.2	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Android 4.3	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Android 4.4.2	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Android 5.0.0	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Android 6.0	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Android 7.0	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Android 8.0	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS

Handshake Simulation

Android 8.1	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Android 9.0	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Baidu Jan 2015	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
BingPreview Jan 2015	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Chrome 49 / XP SP3	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Chrome 69 / Win 7 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Chrome 70 / Win 10	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Chrome 80 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Chrome 131 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Firefox 31.3.0 ESR / Win 7	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_128_CBC_SHA DH 1024 FS
Firefox 47 / Win 7 R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_128_CBC_SHA DH 1024 FS
Firefox 49 / XP SP3	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_128_CBC_SHA DH 1024 FS
Firefox 62 / Win 7 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Firefox 73 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_128_CBC_SHA DH 1024 FS
Firefox 135 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Googlebot Feb 2018	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
IE 6 / XP No FS ¹ No SNI ²	RSA 2048 (SHA256)	SSL 3	TLS_RSA_WITH_RC4_128_MD5 RC4
IE 7 / Vista	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
IE 8 / XP No FS ¹ No SNI ²	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_RC4_128_MD5 RC4
IE 8-10 / Win 7 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
IE 11 / Win 7 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
IE 11 / Win 8.1 R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
IE 10 / Win Phone 8.0	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
IE 11 / Win Phone 8.1 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
IE 11 / Win Phone 8.1 Update R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
IE 11 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Edge 15 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Edge 16 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Edge 18 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Edge 131 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Edge 13 / Win Phone 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Java 6u45 No SNI ²	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_RC4_128_MD5 No FS RC4
Java 7u25	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Java 8u161	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Java 11.0.3	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Java 12.0.1	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
OpenSSL 0.9.8y	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
OpenSSL 1.0.1j R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
OpenSSL 1.0.2s R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
OpenSSL 1.1.0k R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
OpenSSL 1.1.1c R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Opera 117 / Win 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Safari 5.1.9 / OS X 10.6.8	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Safari 6 / iOS 6.0.1	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Safari 6.0.4 / OS X 10.8.4 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Safari 7 / iOS 7.1 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Safari 7 / OS X 10.9 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_128_CBC_SHA No FS
Safari 8 / iOS 8.4 R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Safari 8 / OS X 10.10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
Safari 9 / iOS 9 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Safari 9 / OS X 10.11 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Safari 10 / iOS 10 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Safari 10 / OS X 10.12 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Safari 12.1.2 / MacOS 10.14.6 Beta R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS

Handshake Simulation

Safari 12.1.1 / iOS 12.3.1 R	RSA 2048 (SHA256)	TLS 1.0	TLS_RSA_WITH_AES_256_CBC_SHA No FS
Yahoo Slurp Jan 2015	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS
YandexBot Jan 2015	RSA 2048 (SHA256)	TLS 1.0	TLS_DHE_RSA_WITH_AES_256_CBC_SHA DH 1024 FS

Not simulated clients (Protocol mismatch)

[Apple ATS 9 / iOS 9](#) R Protocol mismatch (not simulated)

- (1) Clients that do not support Forward Secrecy (FS) are excluded when determining support for it.
(2) No support for virtual SSL hosting (SNI). Connects to the default site if the server uses SNI.
(3) Only first connection attempt simulated. Browsers sometimes retry with a lower protocol version.
(R) Denotes a reference browser or client, with which we expect better effective security.
(All) We use defaults, but some platforms do not use their best protocols and features (e.g., Java 6 & 7, older IE).
(All) Certificate trust is not checked in handshake simulation, we only perform TLS handshake.



Protocol Details

Secure Renegotiation	Not supported ACTION NEEDED (more info)
Secure Client-Initiated Renegotiation	No
Insecure Client-Initiated Renegotiation	Supported INSECURE (more info)
BEAST attack	Not mitigated server-side (more info) SSL 3: 0x6, TLS 1.0: 0x6
POODLE (SSLv3)	Vulnerable INSECURE (more info) SSL 3: 0x6
POODLE (TLS)	No (more info)
Zombie POODLE	No (more info) TLS 1.0 : 0x000a
GOLDENDOODLE	No (more info) TLS 1.0 : 0x000a
OpenSSL 0-Length	No (more info) TLS 1.0 : 0x000a
Sleeping POODLE	No (more info) TLS 1.0 : 0x000a
Downgrade attack prevention	No, TLS_FALLBACK_SCSV not supported (more info)
SSL/TLS compression	Yes INSECURE (more info)
RC4	Yes INSECURE (more info)
Heartbeat (extension)	No
Heartbleed (vulnerability)	No (more info)
Ticketbleed (vulnerability)	No (more info)
OpenSSL CCS vuln. (CVE-2014-0224)	Probably, but not exploitable (investigate to confirm and patch) (more info)
OpenSSL Padding Oracle vuln. (CVE-2016-2107)	No (more info)
ROBOT (vulnerability)	No (more info)
Forward Secrecy	Insecure key exchange INSECURE
ALPN	No
NPN	No
Session resumption (caching)	Yes
Session resumption (tickets)	No
OCSP stapling	No
Strict Transport Security (HSTS)	No
HSTS Preloading	Not in: Chrome Edge Firefox IE
Public Key Pinning (HPKP)	No (more info)
Public Key Pinning Report-Only	No
Public Key Pinning (Static)	No (more info)
Long handshake intolerance	No
TLS extension intolerance	No
TLS version intolerance	TLS 2.152
Incorrect SNI alerts	No
Uses common DH primes	Yes Replace with custom DH parameters if possible (more info)
DH public server param (Ys) reuse	No
ECDH public server param reuse	No, ECDHE suites not supported
Supported Named Groups	-
PQC Key Exchange	Not Supported
Supported PQC Groups	-
SSL 2 handshake compatibility	Yes



1 <https://zero.webappsecurity.com/> (HTTP/1.1 200 OK)



Miscellaneous

Test date	Thu, 28 May 2026 05:52:11 UTC
Test duration	97.723 seconds
HTTP status code	200
HTTP server signature	Apache/2.2.6 (Win32) mod_ssl/2.2.6 OpenSSL/0.9.8e mod_jk/1.2.40
Server hostname	ec2-54-82-22-214.compute-1.amazonaws.com

Why is my certificate not trusted?

There are many reasons why a certificate may not be trusted. The exact problem is indicated on the report card in bright red. The problems fall into three categories:

1. Invalid certificate
2. Invalid configuration
3. Unknown Certificate Authority

1. Invalid certificate

A certificate is invalid if:

- It is used before its activation date
- It is used after its expiry date
- Certificate hostnames don't match the site hostname
- It has been revoked
- It has insecure signature
- It has been blacklisted

2. Invalid configuration

In some cases, the certificate chain does not contain all the necessary certificates to connect the web server certificate to one of the root certificates in our trust store. Less commonly, one of the certificates in the chain (other than the web server certificate) will have expired, and that invalidates the entire chain.

3. Unknown Certificate Authority

In order for trust to be established, we must have the root certificate of the signing Certificate Authority in our trust store. SSL Labs does not maintain its own trust store; instead we use the store maintained by Mozilla.

If we mark a web site as not trusted, that means that the average web user's browser will not trust it either. For certain special groups of users, such web sites can still be secure. For example, if you can securely verify that a self-signed web site is operated by a person you trust, then you can trust that self-signed web site too. Or, if you work for an organisation that manages its own trust, and you have their own root certificate already embedded in your browser. Such special cases do not work for the general public, however, and this is what we indicate on our report card.

4. Interoperability issues

In some rare cases trust cannot be established because of interoperability issues between our code and the code or configuration running on the server. We manually review such cases, but if you encounter such an issue please feel free to contact us. Such problems are very difficult to troubleshoot and you may be able to provide us with information that might help us determine the root cause.

SSL Report v2.4.2