



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim : To Perform various GIT operations on local and Remote repositories using GIT Cheat-Sheet

Objective: Objective is to acquire proficiency in common Git commands and workflows, enabling efficient version control, collaboration, and project management in software development projects, both locally and across distributed teams

Theory :

Git

Commands

For Setup :

- `git config --global user.name "Enter User name of Github Account"`
- `git config --global user.email "Enter email of Github Account"`

For Initialization :

- `git init` : Initialize an existing Directory as a Git Repository.
- `git clone [url]` : Retrieve an entire repository from a hosted location via URL (Paste HTTPS OR SSH key From your gitHub)

Stage and SnapShot :

(Following commands works with respect to staging area)

- `git status` : show modified files in working directory, staged for your next commit
- `git add [file]` : add a file to a staging area
- `git reset [file]` : (get file back from staging area)unstage a file while retaining the changes in working directory
- `git diff` : diff of what is changed but not staged
- `git diff --staged` : diff of what is staged but not yet committed
- `git commit -m "[type a message]"` : commit your staged content as a new commit snapshot

Branch & merge :

(work in branches, changing context, and integrating changes)

- `git branch` : list your branches. a * means currently active branch
- `git branch [branch-name]` : create a new branch at the current commit



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

- git checkout : switch to another branch and check it out into your working directory
- git merge [branch] : merge the specified branch's history into the current one
- git log : show all commits in the current branch's history

Inspect & compare

- git log : show the commit history for the currently active branch
- git log : branchB..branchA : show the commits on branchA that are not on branchB
- git log --follow [file] : show the commits that changed file, even across renames
- git diff branchB...branchA : show the diff of what is in branchA that is not in branchB
- git show [SHA] : show any object in Git in human-readable format

Share & update :

(Retrieving updates from another repository and updating local repos)

- git remote add [alias] [url] : add a git URL as an alias
- git fetch [alias] : fetch down all the branches from that Git remote
- git merge [alias]/[branch] : merge a remote branch into your current branch to bring it up to date
- git push [alias] [branch] : Transmit local branch commits to the remote repository branch
- git pull : fetch and merge any commits from the tracking remote branch

Tracking path changes :

(Versioning file removes and path changes)

- git rm [file] : delete the file from project and stage the removal for commit
- git mv [existing-path] [new-path] : change an existing file path and stage the move
- git log --stat -M : show all commit logs with indication of any paths that moved

Rewrite history

(Rewriting branches, updating commits and clearing history)

- git rebase [branch] : apply any commits of current branch ahead of specified one
- git reset --hard [commit] : clear staging area, rewrite working tree from specified commit



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

- git stash : Save modified and staged changes
- git stash list : list stack-order of stashed file changes
- git stash pop : write working from top of stash stack
- git stash drop : discard the changes from top of stash stack

Conclusion :

Q1. How to retrieve an entire repository from a hosted location via URL ?

To retrieve an entire repository from a hosted location via URL, you can use the 'git clone [url]' command. Simply replace [url] with the URL of the repository you want to clone.

Q2. How to change an existing file path ?

To change an existing file path, you can use the `git mv [existing-path] [new-path]` command. Replace [existing-path] with the current path of the file and [new-path] with the desired new path. This command will stage the move of the file to the new path for the next commit.