



AppCodes Development Team

Hitasoft Technology Solutions Private Limited

Digital Marketplace: <https://appcodes.com>

Corporate website: www.hitasoft.com



Airfinch

Server Installation Document



AppKodes Development Team

Hitasoft Technology Solutions Private Limited

Digital Marketplace: <https://appkodes.com>

Corporate website: www.hitasoft.com

Steps for Installing Airfinch script

Step 1: Filezilla

(By using username , password)

1. Goto **file** select **Site Manager**

Site Manager window will be appeared.

2. In this window click **New Site** and change your site name.

i) In **Host**, you have to specify the ip address or the hostname.

ii) In **Protocol**, select SSH File Transfer Protocol.

iii) In **Logon Type**, select normal.

iv) In **User**, specify the user name

v) In **Password**, specify the password .

vi) Finally click **Connect** to establish the server.

(OR)

(By using keyfile)

1. Goto **Edit** select **settings**

Settings window will be appeared.

2. In this window click **Add Keyfile** for upload the keyfile.

3. Choose your keyfile and click **open**.

4. Finally click **OK** to upload the file.

5. Goto **file** select **Site Manager**

Site Manager form will be appeared.



AppKodes Development Team

Hitasoft Technology Solutions Private Limited

Digital Marketplace: <https://appkodes.com>

Corporate website: www.hitasoft.com

6. In this form click **New Site** and change your site name.

i) In **Host**, you have to specify the ip address or the sitename.

ii) In **Protocol**, select SSH file transfer protocol.

iii) In **Logon Type**, select normal.

iv) In **User**, specify the user name

v) Finally click **Connect** to establish the server.

Step 2: Filezilla

1. Right hand side of the filezilla, **Remote site** have the default path,so you have to change the path as **/var/www/html**.

2. Left hand side of the filezilla,load your package from the **Local Site**.

3. Right click on your package select **Upload** for upload your package in remote site **/var/www/html/**

4. You have to unzip the file by using putty.

Step 3: Putty

(By using username , password)

1. In **Host Name**, specify the ip address or the hostname and click **open** to connect the server.

2. Putty window will be appeared.

3. In putty window specify the username and password.

4. Change the path **/var/www/html** (by using the command **cd /var/www/html**).



AppKodes Development Team

Hitasoft Technology Solutions Private Limited

Digital Marketplace: <https://appkodes.com>

Corporate website: www.hitasoft.com

5. Unzip the file by using the command **unzip filename.zip**

(OR)

(By using keyfile)

1. In **Host Name**, specify the ip address or the hostname and click open to connect the server.

2. In the **Category** side select **SSH => Auth.**

3. **Browse** your keyfile and click **open**.

4. In putty window specify the username

5. Change the path /var/www/html (by using the command **cd /var/www/html**).

6. Unzip the file by using the command **unzip filename.zip**

Step 4: Filezilla

1. The file will be extracted in **/var/www/html/folder name**

2. Select all files and move to the path **/var/www/html**

3. Change the permission to 755 for the mentioned main directory

i. **/var/www/html/folder name** (Using the following command in putty :

sudo chmod -R 755 /var/www/html/folder name)

4. Change the permission to 777 for the mentioned below directories and its files.

Backend Folder

i. **backend/web/assets/** (Using the following command in putty :

sudo chmod -R 777 backend/ web/assets/)



AppKodes Development Team

Hitasoft Technology Solutions Private Limited

Digital Marketplace: <https://appkodes.com>

Corporate website: www.hitasoft.com

ii. backend/runtime/ (Using the following command in putty : **sudo**

chmod -R 777 backend/runtime/)

iii. backend/images/ (Using the following command in putty : **sudo**

chmod -R 777 backend/images/)

Frontend Folder

i. frontend/web/assets/ (Using the following command in putty :

sudo chmod -R 777 frontend/ web/assets/)

ii. frontend/runtime/ (Using the following command in putty : **sudo**

chmod -R 777 frontend/runtime/)

iii. frontend//web/albums/images/* (Using the following command

in putty : **sudo chmod -R 777 frontend/web/albums/images/***) -

(Note: 777 permission no needed for the folder

frontend/web/albums/images, Please mention 777 permission

folders within images)

5. Select the file **common/config/main-local.php**.

6. Right click on the main-local.php and select **view/edit**.

7. In this file you have to change the dbname,username and password.

Step 5: Putty

Connect the putty by following step 3

Now you have to install nodejs in the path **/var/www/html** by executing the

following commands. (NODE JS version: 10.15.3 and NPM Version: 6.7.0)



AppKodes Development Team

Hitasoft Technology Solutions Private Limited

Digital Marketplace: <https://appkodes.com>

Corporate website: www.hitasoft.com

1. `curl -sL https://deb.nodesource.com/setup_10.x | sudo -E bash -`
2. `sudo apt-get install -y nodejs`
3. `sudo apt-get install npm`
4. `sudo nodejs -v` (For version check)
5. `sudo npm install forever`
6. Check installation by running “forever list”

If reporting **forever command not found** use the below

```
sudo npm install forever -g
```

Check installation by running “forever list”

If reporting **/usr/bin/env: node: no such file or directory**. Run the following

command

```
ln -s /usr/bin/nodejs /usr/bin/node
```

6. `forever list`
7. Navigate to main folder (`/var/www/html/folder name`) and start forever process

```
> forever start frontend/web/js/nodeServer.js
```

Check: No forever process running (not working)

Forever processing running (working)

Step 6: Filezilla

Find the **nodeClient.js** file in the **var/www/html/js** folder and edit the first line of the file



AppKodes Development Team

Hitasoft Technology Solutions Private Limited

Digital Marketplace: <https://appkodes.com>

Corporate website: www.hitasoft.com

```
var socket = io.connect('http://yourservername:8080');
```

Note: Without :8080, nodeJS will not work.

Step 7: Putty

Connect the putty by following step 3

Now you have to install crontab

1. Using the command **crontab -e** to install the crontab.
2. Select an editor by entering **2** for **/bin/nano**. The file will be opened.
3. Now add the line **0 */6 * * * curl https://sitename/payupdate** at the end of the file. (Stripe Cron Pay Settlement)
4. Now add the line ***/1 * * * * curl https://sitename/currencyupdate** at the end of the file. (Update every currency rates) - (This cron will be executed every minute, if needed please update to hours or days).