


EdgeDroid

An Experimental Approach to Benchmarking Human-in-the-Loop Applications

M. Olguín Muñoz $^{\dagger},$ J. Wang $^{\ddagger},$ M. Satyanarayanan ‡ and J. $Gross^{\dagger}$

† KTH Royal Institute of Technology

[‡] Carnegie Mellon University






















Need to understand and optimize these applications:

- How do they interact with each other?
- How do they interact with infrastructure?
- How do they scale?


With which methodology can we study these behaviors?



Need to understand and optimize these applications:

- How do they interact with each other?
- How do they interact with infrastructure?
- How do they scale?


With which methodology can we study these behaviors?



Need to understand and optimize these applications:

- ► How do they interact with each other?
- ► How do they interact with infrastructure?
- How do they scale?

With which methodology can we study these behaviors?




Need to understand and optimize these applications:


- ► How do they interact with each other?
- ► How do they interact with infrastructure?
- How do they scale?

With which methodology can we study these behaviors?




Costly, poor repeatability






Our Contributions

► A methodology for benchmarking human-in-the-loop applications.



Our Contributions


- ► A methodology for benchmarking human-in-the-loop applications.
- ► EdgeDroid: A benchmarking tool-suite.



Our Contributions


- ► A methodology for benchmarking human-in-the-loop applications.
- ► EdgeDroid: A benchmarking tool-suite.
- Experiments and measurements which show the effectiveness of the approach.

Approach




Benchmarking human-in-the-loop applications is HARD

Approach



What if we could do away with the human users?


Approach




What if we could do away with the human users?


Repeatable, scalable!

Task-guidance Wearable Cognitive Assistance [1]






User Model




User Model



Currently working on a more thorough characterization of human behavior.


Implementation



nttps://github.com/molguin92/EdgeDroid


Evaluation

Insert pictures of LEGO Assistant



Results


Figure labels



I haven't explained the task model, maybe skip this graph?


Results

Figure labels



Results

Figure labels



Conclusions


Future Work

- More accurate user model.
- Expand to other types of Applications.

Summary

- ► There's a need to study the scaling of Human-in-the-Loop applications.
 - This is difficult due to human users.
- We present a methodology + tool suite for benchmarking:
 - EdgeDroid
 - ► Trace based.
 - Model of human behavior.
- We present results which show the utility of EdgeDroid.






Requirements


- Generate realistic, high-dimensional, real-time inputs.
- Correctly and realistically react to feedback.
- KPI: Delays.

Trace of pre-recorded inputs & a model of user behavior


Tracing



Trace Replay



Timestamping



Clocks are synchronized previous to the experiment.

Timestamps at key points to obtain:

$$\Delta T_{\rm up} = t_r' - t_s \tag{1}$$

$$\Delta T_{\rm proc} = t_s' - t_r' \tag{2}$$

$$\Delta T_{\text{down}} = t_r - t_s' \tag{3}$$

$$\Delta T_{\text{total}} = \Delta T_{\text{up}} + \Delta T_{\text{proc}} + \Delta T_{\text{down}} = t_r - t_s \tag{4}$$

References I



K. Ha *et al.*, "Towards wearable cognitive assistance," in *Proceedings of the 12th Annual International Conference on Mobile Systems, Applications, and Services*, ser. MobiSys '14, Bretton Woods, New Hampshire, USA: ACM, 2014, pp. 68–81, ISBN: 978-1-4503-2793-0. DOI: 10.1145/2594368.2594383. [Online]. Available: http://doi.acm.org/10.1145/2594368.2594383.



Z. Chen *et al.*, "Early implementation experience with wearable cognitive assistance applications," in *Proceedings of the 2015 Workshop on Wearable Systems and Applications*, ser. WearSys '15, Florence, Italy: ACM, 2015, pp. 33–38, ISBN: 978-1-4503-3500-3. DOI: 10.1145/2753509.2753517. [Online]. Available: http://doi.acm.org/10.1145/2753509.2753517.



D. Chatzopoulos *et al.*, "Hyperion: A wearable augmented reality system for text extraction and manipulation in the air," in *Proceedings of the 8th ACM on Multimedia Systems Conference*, ser. MMSys'17, Taipei, Taiwan: ACM, 2017, pp. 284–295, ISBN: 978-1-4503-5002-0. DOI: 10.1145/3083187.3084017. [Online]. Available: http://doi.acm.org/10.1145/3083187.3084017.

References II



Z. Chen *et al.*, "An empirical study of latency in an emerging class of edge computing applications for wearable cognitive assistance," in *Proceedings of the Second ACM/IEEE Symposium on Edge Computing*, ser. SEC '17, San Jose, California: ACM, 2017, 14:1–14:14, ISBN: 978-1-4503-5087-7. DOI: 10.1145/3132211.3134458. [Online]. Available: http://doi.acm.org/10.1145/3132211.3134458.



H. Al-Zubaidy *et al.*, "Performance of in-network processing for visual analysis in wireless sensor networks," in *Proceedings of the IFIP Networking Conference*, ser. IFIP NETWORKING'15, 2015.



S. Schiessl *et al.*, "Finite-length coding in edge computing scenarios," in *Proceedings of the International Workshop on Smart Antennas*, ser. ITG WSA '17, 2017.



M. Satyanarayanan *et al.*, "The case for VM-based cloudlets in mobile computing," *IEEE Pervasive Computing*, vol. 8, no. 4, 2009.



J. Flinn, "Cyber foraging: Bridging mobile and cloud computing," *Synthesis Lectures on Mobile and Pervasive Computing*, vol. 7, no. 2, pp. 1–103, 2012.



K. Sasaki *et al.*, "Vehicle control system coordinated between cloud and mobile edge computing," in 2016 55th Annual Conference of the Society of Instrument and Control Engineers of Japan (SICE), 2016, pp. 1122–1127. DOI: 10.1109/SICE.2016.7749210.

References III



- T. Bittmann, "The edge will eat the cloud," Gartner Research, no. G00338633, 2017.
- K. Kumar *et al.*, "Cloud computing for mobile users: Can offloading computation save energy?" *IEEE Computer*, vol. 43, no. 4, pp. 51–56, 2010.
- E. Cuervo et al., "Maui: Making smartphones last longer with code offload," in Proceedings of the International Conference on Mobile Systems, Applications, and Services, ser. ACM MOBISYS'10, 2010.
- K. Ha *et al.*, "The impact of mobile multimedia applications on data center consolidation," in 2013 *IEEE International Conference on Cloud Engineering (IC2E)*, 2013, pp. 166–176. DOI: 10.1109/IC2E.2013.17.
- K. Ha et al., "Just-in-time provisioning for cyber foraging," in Proceeding of the 11th Annual International Conference on Mobile Systems, Applications, and Services, ser. MobiSys '13, Taipei, Taiwan: ACM, 2013, pp. 153–166, ISBN: 978-1-4503-1672-9. DOI: 10.1145/2462456.2464451. [Online]. Available: http://doi.acm.org/10.1145/2462456.2464451.
 - (2018). Docker, [Online; accessed 14. Aug. 2018], [Online]. Available: https://www.docker.com.

References IV



(2018). Network Time Protocol, [Online; accessed 24. Sep. 2018], [Online]. Available: https://www.eecis.udel.edu/~mills/ntp/html/index.html.



(2018). TOML, [Online; accessed 25. Sep. 2018], [Online]. Available: https://github.com/toml-lang/tomll.



K. Kim *et al.*, "Workload synthesis: Generating benchmark workloads from statistical execution profile," in *2014 IEEE International Symposium on Workload Characterization (IISWC)*, 2014, pp. 120–129. DOI: 10.1109/IISWC.2014.6983051.



E. Deniz *et al.*, "Minime: Pattern-aware multicore benchmark synthesizer," *IEEE Transactions on Computers*, vol. 64, no. 8, pp. 2239–2252, 2015, ISSN: 0018-9340. DOI: 10.1109/TC.2014.2349522.



M. Olguín *et al.*, "Demo: Scaling on the Edge – A Benchmarking Suite for Human-in-the-Loop Applications," in *Proceedings of The Third ACM/IEEE Symposium on Edge Computing*, ser. SEC '18, Accepted Submission, Extended Abstract, 2018. [Online]. Available: https://olguin.se/files/demo-scaling-edge.pdf.