

```
// routes/cases.js
// Handles creating and listing
cases. Every route here requires a
valid login
// (enforced by requireAuth
middleware, applied in server.js).

const express = require('express');
const pool = require('../db/pool');

const router = express.Router();

// GET /api/cases
// Returns all cases belonging to the
logged-in user.
router.get('/', async (req, res) => {
  try {
    const result = await pool.query(
      'SELECT * FROM cases WHERE
user_id = $1 ORDER BY created_at
DESC',
      [req.userId] // req.userId was
attached by requireAuth middleware
    );
    res.json(result.rows);
  } catch (err) {
```

```
        console.error(err);
        res.status(500).json({ error:
'Something went wrong.' });
    }
});

// POST /api/cases
// Creates a new case for the logged-
in user.
router.post('/', async (req, res) =>
{
    const { client_name, case_type,
status, date_opened } = req.body;

    if (!client_name) {
        return res.status(400).json({
error: 'client_name is required.' });
    }

    try {
        const result = await pool.query(
            `INSERT INTO cases (user_id,
client_name, case_type, status,
date_opened)
            VALUES ($1, $2, $3,
COALESCE($4, 'open'), COALESCE($5,
CURRENT_DATE))
            RETURNING *`,
            [req.userId, client_name,
```

```

    case_type, status, date_opened]
    );

    res.status(201).json(result.rows[0]);
  } catch (err) {
    console.error(err);
    res.status(500).json({ error:
'Something went wrong.' });
  }
});

// PATCH /api/cases/:id
// Updates a case (e.g. changing
status from "open" to "closed").
router.patch('/:id', async (req, res)
=> {
  const { id } = req.params;
  const { client_name, case_type,
status } = req.body;

  try {
    // We check user_id = $X too, so
users can't edit each other's cases.
    const result = await pool.query(
      `UPDATE cases
      SET client_name = COALESCE($1,
client_name),
      case_type = COALESCE($2,
case_type),

```

```
        status = COALESCE($3,
status)
        WHERE id = $4 AND user_id = $5
        RETURNING *`,
        [client_name, case_type,
status, id, req.userId]
    );

    if (result.rows.length === 0) {
        return res.status(404).json({
error: 'Case not found.' });
    }

    res.json(result.rows[0]);
} catch (err) {
    console.error(err);
    res.status(500).json({ error:
'Something went wrong.' });
}
});

module.exports = router;
```