Accelerated Alternating Direction Method of Multipliers for Frictional Contact *

Yoshihiro Kanno [†]

Algorithm Coulomb 1

The previous algorithm can be reformulated as well. As the upshot, the fast ADMM (Algorithm??) for solving problem (??) is formally stated in Algorithm 1.

Algorithm 1 Fast ADMM for problem (??).

Require: $\tilde{u}^0 = \hat{u}^0$, $\zeta^0 = \hat{\zeta}^0$, $\tau_0 = 1$, and $\rho > 0$.

1: **for** $k = 0, 1, 2, \dots$ **do**

2:
$$\mathbf{v}^{k+1}$$
 solves $\left[M + \rho H^{\top} H\right] \mathbf{v} = -\mathbf{f} + \rho H^{\top} (\tilde{\mathbf{u}}^k - \mathbf{b}(s) - \hat{\boldsymbol{\zeta}}^k)$

3:
$$ilde{oldsymbol{u}}^{k+1} := \Pi_{K_{e,u}^*}(Holdsymbol{v}^{k+1} + \hat{\hat{oldsymbol{\zeta}}}^k + oldsymbol{b}(oldsymbol{s}))$$

4:
$$\boldsymbol{\zeta}^{k+1} := \hat{\boldsymbol{\zeta}}^k + H \boldsymbol{v}^{k+1} - \tilde{\boldsymbol{u}}^{k+1} + \boldsymbol{b}(s)$$

5: $\tau_{k+1} := \frac{1}{2} \left(1 + \sqrt{1 + 4\tau_k^2} \right)$

5:
$$\tau_{k+1} := \frac{1}{2} \left(1 + \sqrt{1 + 4\tau_k^2} \right)$$

6:
$$\hat{\boldsymbol{u}}^{k+1} := \hat{\boldsymbol{u}}^k + \frac{\tau_k - 1}{\tau_{k+1}} (\tilde{\boldsymbol{u}}^{k+1} - \tilde{\boldsymbol{u}}^k)$$

6:
$$\hat{\boldsymbol{u}}^{k+1} := \hat{\boldsymbol{u}}^k + \frac{\tau_k - 1}{\tau_{k+1}} (\tilde{\boldsymbol{u}}^{k+1} - \tilde{\boldsymbol{u}}^k)$$
7: $\hat{\boldsymbol{\zeta}}^{k+1} := \hat{\boldsymbol{\zeta}}^k + \frac{\tau_k - 1}{\tau_{k+1}} (\boldsymbol{\zeta}^{k+1} - \boldsymbol{\zeta}^k)$

8: end for

In step 2 of Algorithm 1, the coefficient matrix of the system of linear equations is common to all the iterations. Hence, we carry out the Cholesky factorization only at the first iteration (i.e., k=0); at the following iterations, we can compute v^{k+1} only with the back-substitutions. The projection in step 3 can be computed explicitly by using the formula in (7). The computations in the other steps are only matrix-vector products and vector additions. Therefore, the computational cost required for one iteration is small, even for a large-scale problem.

In a similar manner, we can apply Algorithm?? to problem (??), as formally stated in Algorithm 2.

• To solve the friction problem, parameter s in problem (??) should be updated. This corresponds to updating b_i and d_i in problem (??). One obvious way is that, once we solve problem (??) with fixed b_i and d_i by the fast ADMM (with restart), then update b_i and d_i by using the obtained solution, and repeat this procedure. Another possibility is to update b_i and d_i at each iteration of the fast ADMM (with restart). Intuitively, the latter saves the total computational cost, but stability of the algorithm in this case is not clear.

^{*/}doc/contact/admm/

[†]Laboratory for Future Interdisciplinary Research of Science and Technology, Institute of Innovative Research, Tokyo Institute of Technology, Nagatsuta 4259, Yokohama 226-8503, Japan. E-mail: kanno.y.af@m.titech.ac.jp.

Algorithm 2 Fast ADMM for problem with restart (??)

Require:
$$\tilde{u}^0 = \hat{u}^0$$
, $\zeta^0 = \hat{\zeta}^0$, $\tau_0 = 1$, and $\rho > 0$.

1: for $k = 0, 1, 2, ...$ do

2: v^{k+1} solves $\left[M + \rho H^\top H\right] v = -f + \rho H^\top (\tilde{u}^k - b(s) - \hat{\zeta}^k)$

3: $\tilde{u}^{k+1} := \prod_{K_{\epsilon,\mu}^*} (Hv^{k+1} + \hat{\zeta}^k + b(s))$

4: $\zeta^{k+1} := \hat{\zeta}^k + Hv^{k+1} - \tilde{u}^{k+1} + b(s)$

5: if $e_k < \eta e_{k-1}$ then

6: $\tau_{k+1} := \frac{1}{2} \left(1 + \sqrt{1 + 4\tau_k^2}\right)$

7: $\hat{u}^{k+1} := \hat{u}^k + \frac{\tau_k - 1}{\tau_{k+1}} (\tilde{u}^{k+1} - \tilde{u}^k)$

8: $\hat{\zeta}^{k+1} := \hat{\zeta}^k + \frac{\tau_k - 1}{\tau_{k+1}} (\zeta^{k+1} - \zeta^k)$

9: else

10: $\tau_{k+1} := 1$

11: $\hat{u}^{k+1} := \tilde{u}^k$

12: $\hat{\zeta}^{k+1} := \xi^k$

13: $e_k \leftarrow e_{k-1}/\eta$

14: end if

2 Projection onto second order cone

$$\Pi_{K_{e,\mu}}(\boldsymbol{x}) = \begin{cases}
0 & \text{if } \|\boldsymbol{x_2}\| \le -\frac{1}{\mu}x_1, \\
\boldsymbol{x} & \text{if } \|\boldsymbol{x_2}\| \le \mu x_1, \\
\frac{1}{1+\mu^2} \left(x_1 + \mu \|\boldsymbol{x_2}\|\right) \begin{bmatrix} 1 \\ \mu \boldsymbol{x_2}/\|\boldsymbol{x_2}\| \end{bmatrix} & \text{if } -\mu \|\boldsymbol{x_2}\| < x_1 < \frac{1}{\mu} \|\boldsymbol{x_2}\|,
\end{cases} (1)$$

$$\Pi_{K_{e,\mu}^*}(\boldsymbol{x}) = \begin{cases}
0 & \text{if } \|\boldsymbol{x_2}\| \le -\mu x_1, \\
\boldsymbol{x} & \text{if } \|\boldsymbol{x_2}\| \le \frac{1}{\mu} x_1, \\
\frac{\mu^2}{1+\mu^2} \left(x_1 + \frac{1}{\mu} \|\boldsymbol{x_2}\|\right) \begin{bmatrix} 1 \\ \frac{1}{\mu} \boldsymbol{x_2} / \|\boldsymbol{x_2}\| \end{bmatrix} & \text{if } -\frac{1}{\mu} \|\boldsymbol{x_2}\| < x_1 < \mu \|\boldsymbol{x_2}\|,
\end{cases} (2)$$

2.1 Projection onto Coulomb's friction cone

For vector $\mathbf{x} = (x_1, \mathbf{x}_2) \in \mathbb{R} \times \mathbb{R}^{n-1}$, its spectral factorization with respect to $K_{e,\mu}$ is defined by [8]

$$x = \lambda_1 u^1 + \lambda_2 u^2. \tag{3}$$

Here, $\lambda_1, \lambda_2 \in \mathbb{R}$ are the spectral values given by

$$\lambda_i = x_1 + (-1)^i \,\mu^{(-1)^i} \|\boldsymbol{x}_2\|,\tag{4}$$

and $\boldsymbol{u}^1,\,\boldsymbol{u}^2\in\mathbb{R}^n$ are the spectral vectors given by

$$\mathbf{u}^{i} = \begin{cases} \frac{1}{1+\mu^{2}} \begin{bmatrix} \mu^{2(2-i)} \\ (-1)^{i} \mu \mathbf{x}_{2} / \|\mathbf{x}_{2}\| \end{bmatrix} & \text{if } \mathbf{x}_{2} \neq \mathbf{0}, \\ \frac{1}{1+\mu^{2}} \begin{bmatrix} \mu^{2(2-i)} \\ (-1)^{i} \mu \mathbf{\omega} \end{bmatrix} & \text{if } \mathbf{x}_{2} = \mathbf{0}, \end{cases}$$
(5)

with $\boldsymbol{\omega} \in \mathbb{R}^{n-1}$ satisfying $\|\boldsymbol{\omega}\| = 1$.

For $\boldsymbol{x} \in \mathbb{R}^n$, let $\Pi_{K_{e,\mu}}(\boldsymbol{x}) \in \mathbb{R}^n$ denote the projection of \boldsymbol{x} onto $K_{e,\mu}$, i.e.,

$$\Pi_{K_{e,u}}(x) = \arg\min\{\|x' - x\| \mid x' \in K_{e,u}\}.$$
(6)

This can be computed explicitly as [4]

$$\Pi_{K_{e,\mu}}(\boldsymbol{x}) = \max\{0, \lambda_1\} \boldsymbol{u}^1 + \max\{0, \lambda_2\} \boldsymbol{u}^2. \tag{7}$$

Therefore the projection of x onto $K_{e,\mu}$ could be written as follows

$$\Pi_{K_{e,\mu}}(\boldsymbol{x}) = \begin{cases}
0 & \text{if } -\boldsymbol{x} \in K_{e,\mu}^* \to \lambda_i \le 0 \\
\boldsymbol{x} & \text{if } \boldsymbol{x} \in K_{e,\mu} \to \lambda_i \ge 0 \\
\frac{(x_1 + \mu \|\boldsymbol{x}_2\|)}{1 + \mu^2} \begin{bmatrix} 1 \\ \mu \boldsymbol{x}_2 / \|\boldsymbol{x}_2\| \end{bmatrix} & \text{if } -\boldsymbol{x} \notin K_{e,\mu}^* \wedge \boldsymbol{x} \notin K_{e,\mu} \to \lambda_1 < 0 \land \lambda_2 > 0
\end{cases} \tag{8}$$

Now, it is easy to see that the dual of $K_{e,\mu}$ is also a second-order cone

$$K_{e,\mu}^* = K_{e,\frac{1}{\mu}} = \{ (x_1, \boldsymbol{x}_2) \in \mathbb{R} \times \mathbb{R}^{n-1} \mid ||\boldsymbol{x}_2|| \le \frac{1}{\mu} x_1 \}$$
 (9)

Consequently, the projection of x onto $K_{e,\mu}^*$ could be written as follows

$$\Pi_{K_{e,\mu}^{*}}(\boldsymbol{x}) = \begin{cases}
0 & \text{if } -\boldsymbol{x} \in K_{e,\mu} \to \lambda_{i}^{*} \leq 0 \\
\boldsymbol{x} & \text{if } \boldsymbol{x} \in K_{e,\mu}^{*} \to \lambda_{i}^{*} \geq 0 \\
\frac{\mu^{2}\left(x_{1} + \frac{1}{\mu}\|\boldsymbol{x}_{2}\|\right)}{1 + \mu^{2}} \begin{bmatrix} 1 \\ \frac{1}{\mu}\boldsymbol{x}_{2}/\|\boldsymbol{x}_{2}\| \end{bmatrix} & \text{if } -\boldsymbol{x} \notin K_{e,\mu} \wedge \boldsymbol{x} \notin K_{e,\mu}^{*} \to \lambda_{1}^{*} < 0 \wedge \lambda_{2}^{*} > 0,
\end{cases} (10)$$

where $\lambda_i^* = x_1 + (-1)^i \mu^{(-1)^{i+1}} \| \boldsymbol{x}_2 \|$.

References

- [1] V. Acary, F. Cadoux, C. Lemaréchal, J. Malick: A formulation of the linear discrete Coulomb friction problem via convex optimization. ZAMM, 91, 155–175 (2011).
- [2] V. Acary, F. Cadoux: Applications of an existence result for the Coulomb friction problem. In: G. E. Stavroulakis (ed.), Recent Advances in Contact Mechanics, pp. 45–66, Springer-Verlag, Berlin (2013).
- [3] S. Boyd, N. Parikh, E. Chu, B. Peleato, J. Eckstein: Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends in Machine Learning*, **3**, 1–122 (2010).

- [4] M. Fukushima, Z.-Q. Luo, P. Tseng: Smoothing functions for second-order-cone complementarity problems. SIAM Journal on optimization, 12, 436–460 (2001).
- [5] P. Giselsson, S. Boyd: Diagonal scaling in Douglas–Rachford splitting and ADMM. *The 53rd IEEE Conference on Decision and Control*, 5033–5039, Los Angeles (2014).
- [6] T. Goldstein, B. O'Donoghue, S. Setzer, R. Baraniuk: Fast alternating direction optimization methods. SIAM Journal on Imaging Sciences, 7, 1588–1623 (2014).
- [7] W. Hager, C. Ngo, M. Yashtini, H.-C. Zhang: An alternating direction approximate Newton algorithm for ill-conditioned inverse problems with application to parallel MRI. *Journal of the Operations Research Society of China*, **3**, 139–162 (2015).
- [8] S. Hayashi, N. Yamashita, M. Fukushima: A combined smoothing and regularization method for monotone second-order cone complementarity problems. *SIAM Journal on Optimization*, **15**, 593-615 (2005).
- [9] J. M. C. Martins, A. Pinto da Costa: Stability of finite-dimensional nonlinear elastic systems with unilateral contact and friction. *International Journal of Solids and Structures*, **37**, 2519–2564 (2000).
- [10] J. M. C. Martins, A. Pinto da Costa, F. M. F. Simões: Some notes on friction and instabilities. In: J. A. C. Martins, M. Raous (eds.), *Friction and Instabilities*, pp. 65–136, Springer-Verlag, Wien (2002).
- [11] A. Pinto da Costa, J. A. C. Martins, I. N. Figueiredo, J. J. Júdice: The directional instability problem in systems with frictional contacts. Computer Methods in Applied Mechanics and Engineering, 193, 357–384 (2004).

Contents

1	Alg	orithm Coulomb	1
2	Pro	jection onto second order cone	2
	2.1	Projection onto Coulomb's friction cone	2