

POST /boats

-Data provided: All following attributes must be provided.

```
{ "name": str, "boat_type": str, "length": int }
```

-Action: A new boat instance is added to the database with the provided credentials. The boat's "at_sea" attribute is set to True, and the boat's id is auto-generated by the database.

GET /boats

-Action: Returns an array that contains all boat objects currently in the database.

GET /boats/{boat_id}

-Action: Returns the specified boat object (give the boat's id in the URL).

PATCH /boats/{boat_id}

-Data provided: The following are optional. A combination of these can be provided.

```
{ "name": str, "boat_type": str, "length": int }
```

-Action: The attributes provided will replace the ones currently listed in the database under the URL-specified boat. All attributes not listed in the body of the request will remain unchanged in the database.

PUT /boats/{boat_id}

-Data provided: All following attributes must be provided.

```
{ "name": str, "boat_type": str, "length": int, "at_sea": bool }
```

-Action: The attributes provided will replace the ones currently listed in the database under the URL-specified boat. If "at_sea" has been changed to False, the slip in which the boat is now stationed will have its "current_boat" and "arrival_date" fields updated. If "at_sea" has been changed to True, the slip in which the boat was stationed will have its "current_boat" and "arrival_date" fields reset. Returns the updated boat object.

DELETE /boats/{boat_id}

-Action: The URL-specified boat will be removed from the database. If the boat was occupying a slip, the slip's "current_boat" and "arrival_date" fields will be reset to indicate that it is empty.

Name: Molly Arwood
CS_496_MobileCloud
Rest Planning and Implementation

POST /slips

-Data provided: The following attribute must be provided.

{“number”: str}

-Action: A new slip instance is added to the database with the provided credential. The slip’s “current_boat” and “arrival_date” attributes are set to an empty string, and the slip’s id is auto-generated by the database.

GET /slips

-Action: Returns an array that contains all slip objects currently in the database.

GET /slips/{slip_id}

-Action: Returns the specified slip object (give the slip’s id in the URL).

PATCH /slips/{slip_id}

-Data provided: Only the number attribute is allowed to be modified by the Patch request.

{“number”: str}

-Action: The attribute provided will replace the one currently listed in the database under the URL-specified slip. All attributes not listed in the body of the request will remain unchanged in the database.

PUT /slips/{slip_id}

-Data provided: All following attributes must be provided.

{“number”: str, “current_boat”: str, “arrival_date”: str}

-Action: The attributes provided will replace the ones currently listed in the database under the URL-specified slip. Returns the updated slip object.

DELETE /slips/{slip_id}

-Action: The URL-specified slip will be removed from the database. If the slip was occupied by a boat, the boat’s “at_sea” field will be set to True.

Name: Molly Arwood
CS_496_MobileCloud
Rest Planning and Implementation

GET /slips/{slip_id}/boat

-Action: Returns the boat object listed in the URL-specified slip's "current_boat" field.

PUT /slips/{slip_id}/boat

-Data provided: All following attributes must be provided.

{ "boat": str, "arrival_date": str }

-Action: Places the specified boat's id into the URL-specified slip's "current_boat" field and places the specified arrival_date into the matching slip's field. Updates the specified boat's "at_sea" field to be False. (Sets a boat in a slip). Returns the updated slip object.

DELETE /slips/{slip_id}/boat

-Action: Removes the boat currently occupying the URL-specified slip. Sets the boat's "at_sea" field to true. Resets the slip's "current_boat" and "arrival_date" fields. Returns updated slip.