

A <Basic> C++ Course

8 – *Object-oriented programming 2*

Julien Deantoni


Outline

- Dynamic Typing
- Truncature
- Cast

Variants of class Paragraph

Definition of derived classes (1)

- We wish to have several sorts of paragraphs
 - titles, sections, enumerations, items...
- We want to **share** as much as possible the **common properties**
 - contents as a string
 - possibility to compose (crude lay out)
- But **specific properties** should be possible
 - numbering, bullets...
 - page layout





Variants of class Paragraph

Definition of derived classes (5)

- A derived class may **add** new properties
 - data members
 - member-functions
 - friend functions
- A derived class may **redefine (override)** some inherited member-functions
- Derivation depth is unlimited
- Single and multiple inheritance
 - Single: only one base class
 - Multiple: several *distinct* base classes

What happens in memory (at least conceptually)



If `compose(int, int)` is NON virtual



//...
Paragraph p("test",2);

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual





```
//...
Paragraph p("test",2);
```

```
Paragraph::Paragraph(std::string content
                    int depth)
{
    _depth = depth;
    _content = content;
}
//...
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual





//...
`Paragraph p("test",2);`

```
Paragraph::Paragraph(std::string content  
                      int depth)  
{  
    _depth = depth;  
    _content = content;  
}  
//...
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual





//...
Paragraph p("test",2);

```

Paragraph::Paragraph(std::string content
                    int depth)
{
    _depth = depth;
    _content = content;
}
//...
    
```


What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is not redefined in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');
```

```
Item_Paragraph::Item_Paragraph(string content,
                               int depth, char b)
    :Paragraph(content, depth)
{
    _bullet = b;
}
//...
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is not redefined in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');
```

```
Item_Paragraph::Item_Paragraph(string content,
                                int depth, char b)
    :Paragraph(content, depth)
{
    _bullet = b;
}
//...
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is not redefined in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');
```

```
Item_Paragraph::Item_Paragraph(string content,
                                int depth, char b)
    :Paragraph(content, depth)
{
    _bullet = b;
}
//...
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is not redefined in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');
```

```
Item_Paragraph::Item_Paragraph(string content,
                                int depth, char b)
    :Paragraph(content, depth)
{
    _bullet = b;
}
//...
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is not redefined in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');
```

```
Item_Paragraph::Item_Paragraph(string content,
                               int depth, char b)
    :Paragraph(content, depth)
{
    _bullet = b;
}
//...
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`





```

//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');
    
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`





```

//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

p.compose();
ip.compose();
    
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

p.compose();
ip.compose();
    
```

What if we create a vector of Paragraphs ??

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<Paragraph> vp;
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`





```

//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<Paragraph> vp;
vp.push_back(p);
    
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<Paragraph> vp;
vp.push_back(p);
vp.push_back(ip);
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<Paragraph> vp;
vp.push_back(p);
vp.push_back(ip);
    
```

We lost the specificities of `Item_Paragraph`

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`



```

//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');



vector<Paragraph> vp;
vp.push_back(p);
vp.push_back(ip);
    
```

We lost the specificities
of `Item_Paragraph`...

Forever !

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<paragraph*> vptr_p
    
```

What happens if we
create a vector
of paragraph pointer ?

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`





```

//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<paragraph*> vptr_p
vptr_p.push_back(&p);
vptr_p.push_back(&ip);
    
```

What happens in memory (at least conceptually)

If `compose(int, int)` is NON virtual and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<paragraph*> vp_ptr_p
vp_ptr_p.push_back(&p);
vp_ptr_p.push_back(&ip);
    
```

A call to a non-virtual function
is resolved according to
the static type of the hidden parameter

What happens in memory (at least conceptually)



If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`



```
//...
Paragraph p("test",2);
p.compose();
```

What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`





```

//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

p.compose();
ip.compose();
    
```

What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

p.compose();
ip.compose();
    
```

What happens if we create a vector of Paragraphs ??

What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<Paragraph> vp;
vp.push_back(p);
vp.push_back(ip);
    
```

We lost the specificities
of `Item_Paragraph`

What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`





```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<paragraph*> vptr_p
```

What happens if we
create a vector
of paragraph pointer ?

What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`





```

//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<paragraph*> vptr_p
vptr_p.push_back(&p);
    
```

What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<paragraph*> vp_ptr_p
vp_ptr_p.push_back(&p);
vp_ptr_p.push_back(&ip);
    
```



What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`



```



//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');

vector<paragraph*> vptr_p
vptr_p.push_back(&p);
vptr_p.push_back(&ip);
vptr_p.push_back(new Paragraph(ip));
    
```



What happens in memory (at least conceptually)

If `compose(int, int)` is **VIRTUAL** and is **REDEFINED** in `Item_Paragraph`



```
//...
Paragraph p("test",2);
Item_Paragraph ip("",1,'#');


vector<paragraph*> vptr_p
vptr_p.push_back(&p);
vptr_p.push_back(&ip);
vptr_p.push_back(new Paragraph(ip));
```



You have to use the `clone()` virtual function
(course 7-00.pdf)

Abstract classes and pure virtual functions


- Object is abstract
 - It cannot be instantiated
 - Some of its behaviors cannot be defined



→ at least one of its member function is a pure virtual function

Abstract classes and pure virtual functions

- Object is abstract
 - It cannot be instantiated
 - Some of its behaviors cannot be defined



```
#ifndef _OBJECT_H
#define _OBJECT_H

class Object
{
public:
//[...]
    virtual Object* clone() const=0;
    virtual void paint()=0;
    virtual ~Object();
};

#endif // _OBJECT_H
```

} pure virtual functions

Safe downward cast (1)

- Downward cast may be dangerous


```
class A { ... };  
class B : public A {  
    void f() { ... }    // f() not defined in A  
};
```

Safe downward cast (1)

- Downward cast may be dangerous

```
class A { ... };  
class B : public A {  
    void f() { ... }    // f() not defined in A  
};
```

```
A* pa = new B();    // OK
```




Safe downward cast (1)

- Downward cast may be dangerous

```
class A { ... };  
class B : public A {  
    void f() { ... }    // f() not defined in A  
};
```

```
A* pa = new B();    // OK  
pa->f();            // KO
```




Safe downward cast (1)

- Downward cast may be dangerous

```
class A { ... };  
class B : public A {  
    void f() { ... }    // f() not defined in A  
};
```

```
A* pa = new B();    // OK  
pa->f();            // KO
```




Safe downward cast (1)

- Downward cast may be dangerous

```
class A { ... };  
class B : public A {  
    void f() { ... }    // f() not defined in A  
};
```

```
A* pa = new B();    // OK  
pa->f();            // KO  
((B*)pa)->f();    // OK
```




Safe downward cast (1)

- Downward cast may be dangerous

```
class A { ... };
class B : public A {
    void f() { ... }    // f() not defined in A
};
```

```
A* pa = new A();    // OK
pa->f();             // KO
((B*)pa)->f();      // OK
```




Unsafe !!

Safe downward cast (1)

- Downward cast may be dangerous

```
class A { ... };  
class B : public A {  
    void f() { ... }    // f() not defined in A  
};
```

```
B* pa = new A();    // KO
```




Safe downward cast (1)

- Downward cast may be dangerous

```
class A { ... };  
class B : public A {  
    void f() { ... }    // f() not defined in A  
};
```

```
A* pa = new B();    // OK  
pa->f();            // KO  
((B*)pa)->f();      // OK  
static_cast<B*>(pa)->f(); // OK
```



Unsafe !!

Safe downward cast (2)

- Operator `dynamic_cast`

```
B *pb = dynamic_cast<B*>(pa);  
if (pb != nullptr)  
{  
    pb->f();           // OK and safe  
}
```

Safe downward cast (2)

- Operator `dynamic_cast`

```
B *pb = dynamic_cast<B*>(pa);  
if (pb != nullptr)  
    pb->f(); // OK and safe  
  
try {  
    dynamic_cast<B*>(pa)->f();  
} catch(bad_cast) {  
    cerr << "bad conversion" << endl;  
}
```

Safe downward cast (3)

- Limitation of `dynamic_cast`
 - Work only on classes with virtual functions (**polymorphic types**)
- Invoking `dynamic_cast` from a constructor or a destructor
 - **`dynamic_cast`** behaves like a virtual function
 - it is **statically bound** in a constructor or a destructor