

Staroids, Module Interface Specification

Team 20, Staroids

Moziah San Vicente, 400091284, sanvicem

Eoin Lynagh, 400067675, lynaghe

Jason Nagy, 400055130, nagyj2

November 9, 2018

The following is a series of MISes for the modules that comprise the Staroids game

Table 1: **Revision History**

Date	Version	Notes
Nov 06/18	0.1	Added basic information to template
Nov 07/18	0.2	Added Head module specification
Nov 08/18	0.3	Added all module specifications

Utilities Module

Template Module

Utilities

Uses

N/A

Syntax

Exported Types

FPS=30
SHIP_SIZE=30
TURN_SPEED=180
SHIP_THRUST=0.2
SHIP_BREAK=0.98
MIN_SPEED=0.1
MAX_SPEED=20
MAX_ACC=2
CVS_WIDTH=780
CVS_HEIGHT=620
BULLET_EXTRA=5
KILLABLE={True,False}
MAX_ASTERIODS=2
TEST={True,False}
ALIEN_SPAWN=700
KeyCode={UP,DOWN,RIGHT,LEFT,SPACE,M,P,R}
EPOCH=1
Key=?
Text=?
Game=?

Exported Access Programs

Routine name	In	Out	Exceptions
Key		Key	
isDown	KeyCode	\mathbb{N}	
onKeydown	KeyCode	\mathbb{N}	
onKeyup	KeyCode		

Semantics

State Variables

d : sequence of \mathbb{N}

State Invariant

$\forall(c : \mathbb{N} | c \in d : c > 0)$

Assumptions

- Only known keys (as defined by KeyCode) will be put into the Key object as events to be processed.

Access Routine Semantics

Key():

- transition: $d := \text{seq of KeyCode}$
- output: $out := Key$
- exception: None

isDown(e):

- output: $e \in d \Rightarrow true \wedge e \notin d \Rightarrow false$
- exception: None

onKeydown(e):

- transition: $d[e] = EPOCH$

- exception: None

onKeyUp(e):

- output: $out := d[e]$
- exception: None

Exported Access Programs

Routine name	In	Out	Exceptions
Text	Screen, Font	Text	
norm	<i>String</i> , \mathbb{Z} , \mathbb{Z}		
emph	<i>String</i> , \mathbb{Z} , \mathbb{Z}		

Semantics

State Variables

cvs: Screen *fnt*: Font

State Invariant

None

Assumptions

- Before the Text object is used, the initialization function must be run first.

Access Routine Semantics

$\text{norm}(Str, x, y)$:

- transition: $cvs[x][y] = \text{screenShow}(Str, \text{NORMAL})$
- exception: None

$\text{emph}(Str, x, y)$:

- transition: $cvs[x][y] = \text{screenShow}(Str, \text{EMPHASIS})$
- exception: None

Routine name	In	Out	Exceptions
Game			
reduceCounter	$String, \mathbb{Z}, \mathbb{Z}$		
resetMute			
resetPause			
drawLives			
addScore	\mathbb{Z}		
addSprites	OBJECT		
subLives	\mathbb{Z}		
subSprites	OBJECT		

Semantics

State Variables

$score: \mathbb{N}$ $lives: \mathbb{N}$ $sprites$: sequence of OBJECT $muteSound: \mathbb{N}$ $pauseGame: \mathbb{N}$

State Invariant

None

Assumptions

None

Access Routine Semantics

Game():

- transition: $score = 0 \wedge lives = 3 \wedge sprites = seq.of OBJECT \wedge muteSound = FPS \wedge pauseGame = FPS$
- exception: None

reduceCounter():

- transition: $muteSound := muteSound - 1 \wedge pauseGame := pauseGame - 1$
- exception: None

resetMute():

- transition: $muteSound = FPS$

- exception: None

resetPause():

- transition: $pauseGame = FPS$

- exception: None

drawLives():

- transition: $\forall (i : \mathbb{N} | i < lives : drawTriangle(i * 15))$

- exception: None

addScore(amount):

- transition: $score + amount$

- exception: None

addSprite(obj):

- transition: $sprites = sprites || obj$

- exception: None

subLives(obj):

- transition: $lives - 1$

- exception: None

subSprite(obj):

- transition: $sprites = sprites \setminus obj$

- exception: None

Sound Module

Uses

AUDIO for Sound

Syntax

Exported Access Programs

Routine name	In	Out	Exceptions
Sound		Sound	
play	Sound		
isPlay	Sound	Boolean	
pause	Sound		
unpause	Sound		
stop	Sound		
mute			
unmute			
toggle			

Semantics

State Variables

Sound: Audio object from file

State Invariant

None

Assumptions

- The constructor is called before other accesses
- The sound files are in the correct directory for the projectiles
- the sound files have the same name as expected.

Access Routine Semantics

Sound():

- transition: $-muted := true$
- exception: None

play():

- input: $in := x \in \text{Sound}$
- transition: $!in.muted : in.play()$
- exception: None

isPlay():

- input: $in := x \in \text{Sound}$
- output: $out := !in.paused()$
- exception: None

pause():

- input: $in := x \in \text{Sound}$
- transition: $in.paused := true$
- exception: None

unpause():

- input: $in := x \in \text{Sound}$
- transition: $in.paused := !true$
- exception: None

stop():

- input: $in := x \in \text{Sound}$
- transition: $in.paused := true \wedge this.currentTime := 0$
- exception: None

`mute()`:

- input: $in := x \in \text{Sound}$
- transition: $in.muted := true$
- exception: None

`unmute()`:

- input: $in := x \in \text{Sound}$
- transition: $in.muted := !true$
- exception: None

`toggle()`:

- input: $in := x \in \text{Sound}$
- transition: $in.muted := !in.muted$
- exception: None

Head Module

Uses

utilities.js, sound.js, gameobject.js, gamestate.js

Exported Constants

None

Exported Access Programs

Routine name	In	Out	Exceptions
dynamicallyLoadScript	any		

Semantics

State Variables

None

State Invariant

None

Assumptions

- The files are named the same way that the module expects

Access Routine Semantics

dynamicallyLoadScript():

- input: $in := x \in \{ "utilities.js", "sound.js", "gameobject.js", "gamestate.js" \}$
- transition: $c := \{ \}$
- output: $out := Head$
- exception: None

GameObject Module

Template Module

GameObject

Uses

N/A

Syntax

Exported Types

GameObject=? Player=? Bullet=? Alien=? AlienBullet=? Asteroid=?

Exported Constants

None

Exported Access Programs

Routine name	In	Out	Exceptions
GameObject		GameObject	
update			
activate			
deactivate			
die			
interact			
move			
action			
draw			
reset			
pass			
collide			
update			
collide			
collide			

GameObject():

- transition: *name, x, y, rot, a, visible, vel, acc, r* = name, 0, 0, 0, 0, false, (0,0), (0,0), 0

- output: $out := GameObject$
- exception: None

Routine name	In	Out	Exceptions
Player		Player	
fire		Bullet	
thrust			
turn			
brake			

Player():

- transition: $fire, thrust, turn, airbrake, bulletCountDown vel, acc, r = false, false, false, FPS/2, (0,$
- output: $out := Player$
- exception: None

Routine name	In	Out	Exceptions
Bullet	Player	Bullet	

Bullet(p):

- transition: $timeOut, vel, x, y, r, velx, vely = 200, , getX(p)+4/3*getR(p)*cos(getHeading(p)), getY(p)+4/3*getR(p)*sin(getHeading(p)), 1, getVelX(p)+BULLET_EXTRA*cos(getHeading(p)), getVelY(p)+BULLET_EXTRA * -sin(getHeading(p))$
- output: $out := Bullet$
- exception: None

Routine name	In	Out	Exceptions
Alien		Alien	

Alien():

- transition: $timeSpawn, timeOut, xOrY, lOrR, acc, r = ALIEN_SPAWN, 50, true, true, (0, 0), 12.5$
- output: $out := Alien$
- exception: None

Routine name	In	Out	Exceptions
AlienBullet		AlienBullet	

AlienBullet(a):

- transition: $timeOut, vel, x, y, r, velx, vely = 200, , getX(a)+4/3*getR(a)*cos(getHeading(a)), getY(a)+4/3*getR(a)*sin(getHeading(a)), 1, getVelX(a)+BULLET_EXTRA*cos(getHeading(a)), getVelY(a)+BULLET_EXTRA * -sin(getHeading(a))$
- output: $out := AlienBullet$
- exception: None

Routine name	In	Out	Exceptions
Asteroid		Asteroid	

Asteroid():

- transition: $x, y, scale, r, children, vel, velx, vely = 0, 0, scale, 5*scale, [], , \pm random(0, 1)*3, \pm random(0, 1)*3$
- output: $out := Asteroid$
- exception: None

Game State Module

Uses

utilities.js, gameobject.js, head.js

Exported Constants

STATE={START,PREGAME,LOAD,PLAYING,POSTGAME,PAUSE,RELOAD}
StateMachine=?

Exported Access Programs

Routine name	In	Out	Exceptions
StateMachine			
isSafe	OBJECT, seq. of OBJECT		
generateAsteroids	$x \in \mathbb{Z}$		
checkCollision	GameObject, GameObject, GameObject		
togglePause			

Semantics

State Variables

state: String *stateSave*: String *paused*: \mathbb{B}

State Invariant

$state \neq stateSave$

Assumptions

None

Access Routine Semantics

StateMachine():

- transition: $state = \text{start}$

- output: $out := StateMachine$

- exception: None

isSafe(obj,sprites)

- input: $in := object, in := sprites$

- return: $d := \forall s \in sprites : (getName(s) = "asteroid" \wedge getActivity(s) = false \wedge \exists c \in getChildren(s) : \neg isSafe(c) : false) \vee (getName(s) = "asteroid" \wedge getActivity(s) = true : checkCollision(obj, s, 50) : false) \vee (getName(s) \in \{"alien", "alienBullet"\} \wedge getActivity(s) = true \wedge checkCollision(obj, s, 50) : false)$

checkCollision(obj,other,r)

- input: $obj \in GameObject, other \in GameObject, obj \in \mathbb{Z}$

togglePause():

- transition: $pause \Rightarrow (stateSave = state \wedge state = PAUSE) \vee \neg pause \Rightarrow (state = stateSave)$

- exception: None

Local Functions

screenShow: $String \times \{NORMAL, EMPHASIS \Rightarrow ?\}$ output: $out :=$

drawTriangle: $\mathbb{N} \Rightarrow$ output: $out :=$

getName: OBJECT \Rightarrow output: $out :=$

getActivity: OBJECT \Rightarrow output: $out :=$

getChildren: OBJECT \Rightarrow output: $out :=$