Angular Advanced
03 – Content Projection

Peter Kassenaar –
info@kassenaar.com

What is Content Projection

- Re-use of content *inside* of components
- Often used when you create components *to be used* by others

- Simple use:
  - *Attribute binding* to pass data into components `[prop]="data"`
  - *Event binding* to get data out of components `(event)="handler()"`

Examples ../130-content-projection



1. Simple content projection:

```
<my-component>
    I want to re-use this text
</my-component>
```

In the parent component:

```
<app-card2>
   Free life
</app-card2>
```

In the child component:

```
<h4 class="card-title">
  <ng-content></ng-content>
</h4>
```

2. Content projection based on CSS-class

```
In the parent component:

<app-card3>

<p class="card-text">Enjoy...</p>

</app-card3>
```

```
In the child component:

<ng-content
    select=".card-text">

</ng-content>
```

3. Content projection based element selector

```
In the parent component:

<app-card4>
   <img class="card-photo"
      src="assets/img/photo-04.jpg">
    …

</app-card4>
```

```
In the child component:

<ng-content
   select="img.card-photo">
</ng-content>
```

4. Based on custom component

- Create an extra component (here: `<app-newsletter>`)
- Use content projection based on element name
- Extra: submit events from nested component back to parent

```
<div>
   <label>
      <input type="checkbox" (change)="onChange($event.target.checked)">
      Subscribe to newsletter!
   </label>
</div>
```

```
export class NewsletterComponent {

   @Output() checked: EventEmitter<boolean> = new EventEmitter<boolean>();

   onChange(value: boolean) {
      this.checked.emit(value)
   }
}
```

```
In parent Component:

<app-card5>
   …
   <app-newsletter (checked)="onChecked($event)">
   </app-newsletter>
   …
</app-card5>

…handle event on parent component class
```

```
<!-- nested component, projected from parent component -->
<ng-content select="app-newsletter"></ng-content>
```

Workshop

- Open `../130-content-projection` for examples, or use your own app
- Create a new component
- Use `<ng-content>` to project content from outside into the component.
- Add an `<ng-content>` class selector. Use it from the outside component.
- Add an `<ng-content>` element selector. Use it from the outside component.
- Create another component and nest it inside your child component. Use the element selector to project it. Optional: Propagate events up