Angular Advanced - 6
Smart components &
View components

Peter Kassenaar –
info@kassenaar.com

Smart components / View Components

- Design pattern
- Why ? Separation of concerns
  - View component is responsible for presentation (and *can* be used in a completely different environment with different component logic)
  - Smart component is responsible for logic → passing the [calculated] data to the view component.
- Smart components
  - AKA: *Container* components, *controller* components, *statefull* components
- View components
  - AKA: *pure* components, *dumb* components, stateless

Characteristics

- Smart components
  - Typically contain big(ger) chunks of logic
  - Typically have a small UI part (reference just the view component)
  - Pass the data to the view component
- View components
  - Typically contain no logic whatshowever
  - Get their data via `@Input()` decorators
  - Submit events via `@Output()` decorators
  - Have large chunks of UI

Example: ../300-smart-view-component

Home (default component) | Smart/View component

Default component- My favorite cities:

1 - Groningen	☑ Visited
2 - Hengelo	☐ Visited
3 - Den Haag	☐ Visited
4 - Enschede	☑ Visited
5 - Heerlen	☐ Visited

I Visited:

- Groningen
- Enschede

Current city: Groningen

Home – Default component

- Contains all logic and UI, combined in one component.
  - `/home/home.component.html`
  - `/home/home.component.ts`
- This typically works well for smaller applications

```
<div class="row">
   <div class="col-md-6">
      <h2>Default component- My f
      <ul class="list-group">
         <li *ngFor="let city of
            class="list-group-ite
            [class.visited]="city
            (click)="getCity(city
            {{ city.id}} - {{ cit
            <span class="pull-rig
               <label>
      </ul>
..
</div>
```

```
@Component({
   selector    : 'app-home',
   templateUrl: './home.component.html'
})
export class HomeComponent implements OnInit {
   …
   ngOnInit() {
      this.cityService.getCities()
         .subscribe(cities => this.cities = cities);
   }

   getCity(city: City) {
      this.currentCity = city;
      this.cityPhoto   = `assets/img/${this.currentCity.name}.jpg`;
   }
   …
}
```

Splitting it up in view components

- `../smart-view/smart.component.html | .ts.`
- Passing `[cities]` in
- Getting `(events)` out.
- `[cities]` can also be an Observable

```
<div class="row">
  <div class="col-md-6">
    <h2>Smart/view component- My favorite cities:</h2>
    <!-- The <city-list>-component is now
         the view component for list of cities -->
    <city-list [cities]="cities"
               (selectCity)="getCity($event)"
               (toggleVisited)="toggleCity($event)">
    </city-list>
   …
  </div>
</div>
```

<city-list> View component

- Has no logic, just `@Input()`'s and `@Output()`'s

```
import {Component, EventEmitter, Input, Output} from '@angular/core';
import {City} from '../../shared/model/city.model';

@Component({
   selector   : 'city-list',
   templateUrl: './city-list.component.html'
})
export class CityListComponent {

   @Input() cities: City[];
   @Output() selectCity: EventEmitter<City>    = new EventEmitter<City>();
   @Output() toggleVisited: EventEmitter<City> = new EventEmitter<City>();

}
```

HTML of the view component

- …/`smart-view/city-list/city-list-component.html`
- Has a nested view component to toggle `visited` state
- Choice: events are directly emitted from the HTML
  - Can also be done via small functions

```
<ul class="list-group">
   <li *ngFor="let city of cities"
      class="list-group-item"
      [class.visited]="city.visited"
      (click)="selectCity.emit(city)">
      {{ city.id}} - {{ city.name }}
      <city-visited [visited]="city.visited"
                 (toggle)="city.visited = $event; toggleVisited.emit(city)">
      </city-visited>
   </li>
</ul>
```

`<city-visited>` View component

Again – just `@Input()`'s and `@Output()`'s.

```
export class CityVisitedComponent {
  @Input() visited:boolean;
  @Output() toggle: EventEmitter<boolean>= new EventEmitter<boolean>();
}
```

HTML – again: attribute binding and event binding

```
<span class="pull-right">
   <label>
      <input type="checkbox"
            class="checkbox-inline"
            [checked]="visited"
            (change)="visited = !visited; toggle.emit(visited)"> Visited
   </label>
</span>
```

Application structure

- When following this pattern: typically more, smaller components



Workshop

- Study the example `../300-smart-view-components`
- Create two view additional components:
  - One for displaying the current city
  - One for displaying the list of visited cities
- Optional: use Observables instead of plain arrays.
  - `cities$ : Observable<City>`
  - `[cities]="cities$ | async"`



More info on Smart/View components



Smart/View Component Patterns - St. Louis Angular Lunch - Paul Spears Jan 2017

Oasis Digital Solutions Inc.

https://www.youtube.com/watch?v=ALm_JVdLT2E

Todd Motto
Owner, Ultimate Angular

Follow @toddmotto 35K followers

Blogs
About
Speaking events
Online courses
Workshops

© 2017

Search posts

ULTIMATE ANGULAR™

Master Angular with my online courses

Award winning courses trusted by thousands, there's no better place to learn

Explore courses ›

Categories: Angular AngularJS RxJS JavaScript

Stateful and stateless components, the missing manual

Oct 12, 2016 10 mins read Edit post

The goals of this article are to define what stateful and stateless components are, otherwise known as smart and dumb - or container and presentational components. For the purposes of the article, we'll be using Angular 2 Components to explain the stateful/stateless concepts. Bear in mind these concepts are not at all limited to Angular, and live in other libs/frameworks such as React.

Table of contents

LATEST COURSE
Angular Fundamentals

Angular v4+ award-winning courses, learn at your own pace online with me.

https://toddmotto.com/stateful-stateless-components

http://blog.angular-university.io/angular-2-smart-components-vs-presentation-components-whats-the-difference-when-to-use-each-and-why/