



NARADA^(R) CARD System

API SPECIFICATIONS v2.3

Version History

VERSION	AUTHOR	DATE	CHANGE
1.0	Tushar Meshram	13 MAY 2024	Document Created
1.1	Pratyusha	05 JUN 2024	Section 3 updated
1.2	Pratyusha	22 JUN 2024	Section 3 updated
1.3	Pratyusha	29 JUN 2024	Section 4 updated
1.4	Tushar Mule	22 Jul 2024	API endpoints updated
1.5	Tushar Mule	13 AUG 2024	API Request Response updated
1.6	Pratyusha	25 AUG 2024	Added UCIC ID in Customer Reg, Update Customer Details, Set and Get Limits
1.7	Pratyusha	19 SEP 2024	Added a new API for retrieving the card details to be accessed by ACS
1.8	Pratyusha	07-OCT-2024	Updated Section 4.4 by adding new fields emailId and mobileNumber to the response.
1.9	Pratyusha	21-OCT-2024	Updated Section 4.4 by adding new request headers
1.10	Pratyusha	26-OCT-2024	Updated Section 4.4 by adding new request headers
2.0	Pratyusha	22-FEB-2025	Updated Section 4 by removing the specific headers
2.1	Pratyusha	25-FEB-2025	Updated Section 4 by removing the specific headers in the sample requests
2.2	Pritam	10-MARCH-2025	Update the GET and SET Limit API By removing SOAP format add REST format.
2.2.1	Pritam	04-APR-2025	Update Request Response format, Field name, Reponse parameter added response code and text. Remove Unused Headers.
2.3	Pratyusha	05-APR-2025	Added msgHdr for every request. This will include msgId, channelType and timestamp.

Table of Contents

Contents

1. INTRODUCTION	8
1.1 Scope	8
1.2 Prerequisites.....	8
1.3 Terminology	8
2. MESSAGE STRUCTURE AND ELEMENTS.....	8
3. List Of API.....	9
4.1 Purchase a Card/Register the customer	9
4.2 Update Customer Details.....	20
4.3 Get Card Details -	24
4.4 Block / Unblock the Card	26
4.5 Card Activation	28
4.6 Card Replacement.....	30
4.7 Account Addition	33
4.8 Load Card / Funding an Account	35
4.9 Query Balance	37
4.10 Amount Refund	39
4.11 Account closure.....	41
4.12 Get X Transactions	42
4.13 Debit/Credit the Account	46
4.14 Fund Transfer.....	48
4.15 Exchange Rate	51
4.16 Card Order	53
4.17 Card Receipt	55
4.18 Update Stock Details.....	57
4.19 Get Stock Details	59
4.20 Status Request.....	61
4.21 Change Password	62
4.22 Access Rights	64
4.23 PIN Retrieval	65
4.24 ATM PIN Verification.....	67
4.25 ATM PIN Change	69
4.26 Assign override settings	72

4.27 Alert Settings - set/unset	74
4.28 Get Card number	76
4.29 Get CSC Enquiry	78
4.30 Card Order Status	79
4.31 IVR PIN Set	81
4.32 IVR PIN Change	83
4.34 IVR PIN Validation	84
4.35 Reset Web Password	86
4.36 Retrieve Web Profile	87
4.37 ATM PIN Set	89
4.38 New OTP Request	91
4.39 OTP Validation	92
4.41 Set Limit Details	94
4.42 Get Limit Details	99
4. IMPORTANT NOTIFICATIONS	106
5. SECURITY IMPLEMENTATION	107
5.1 Certificates Management	107
5.2 Keys & Certificates Usage	107
5.3 HTTPS Headers	108
5.4 JWE Header	108
5.5 JWS Header	108
5.6 Other Security Considerations	109
5.7 Sample Code Snippet:	109
5.7.1 Java Code snippet for generating JWE Header	109
5.7.2 Java Code snippet for Payload Encryption:	109
5.7.3 Java Code snippet for generating JWS Header:	110
5.7.4 Java Code snippet for Signing the Encrypted payload:	110
5.7.5 Java Code snippet for Verifying the Signed payload:	110
5.7.6 Java Code snippet for Decrypting the encrypted payload:	111
5.8 HTTPS Headers	111
7 APPENDIX	112
7.1 Transaction Summary - APIkey	112
7.2 Card Status	113
7.3 List of Error Codes	113
7.4 List of Transaction Codes	118
7.5 List of Transaction Types	129

1. INTRODUCTION

1.1 Scope

This manual provides detailed API integration guidance to Narada Prepaid Host. Some of the functionality described in this document may be restricted depending on the level of service arrangement with Yalamanchili.

1.2 Prerequisites

- API requires Username and password has to be sent along with client ID [a unique Identifier for the Service Requester].
- Profile has to be created for the ServiceRequester in the Narada system. Security Parameters can configure at the Profile Management.
- Service Requester should have a Public-Key pair and share his Public certificate to Yalamanchili.
- Public Certificate of Yalamanchili.
- Service URL (Yalamanchili Hosted).

1.3 Terminology

Narada-API

Narada-API is a secure web services used by Service Requester (Client) to initiate and process the transaction.

Service Requester

The entity using Yalamanchili Prepaid Card System.

2. MESSAGE STRUCTURE AND ELEMENTS

Narada-API Interface is used by Service Requester to avail the Prepaid Card functions using REST (Representational state transfer).

A REST API is an application programming interface (API) that conforms to the design principles of the representational state transfer architectural style. REST APIs provide a flexible, lightweight way to integrate applications and to connect components in micro services architecture.

HEADERS

Header:-

This is our default header we used for internal validation of all inbound API. Which is send in headers of API not body. Compulsory required parameter.

Parameter	Type	Description	Mandatory	Sample Values
Default Header				
apikey	String	Six character unique value for each API	Y	
clientid	String	Six alphanumeric value which decide by YCS for validation. Should be send by client.	Y	
channeltype	String	Always API	Y	
netId	String	User id of API	Y	
timeStamp	String	Current time stamp should be 12 o 16	Y	
Http headers for validation.	Params Authorization <u>Headers (14)</u> Body ● Scripts Tests Settings			
	Headers 9 hidden			
		Key	Value	
	☒	apikey	APCHDT	
	☒	clientid	SNDBOX	
	☒	channeltype	API	
	☒	netId	APIUSER	
	☒	timeStamp	01234567891212	
		Key	Value	

3. List Of API

4.1 Purchase a Card/Register the customer

This API is used to purchase a personalized prepaid card or Register the Instant Card (Non-personalized) or virtual card with the System.

The Purchase transaction involves registration of the customer, product assignment and create card Number along with proxy Number. Proxy Number is pseudo Card Number and it will be used as a proxy to prevent the exposure of card Number to external world.

Based on Business requirements cards can be activate instantly or activate later using the activation code through any of the channels and are Narada-API/ Customer Portal/ Business office Portal/ IVR. To activate via Narada-API use the “Card Activation API- **APCDAC**”.

New card Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester (12 character length) / external vendor (MASTER/VISA) 32 character length.
proxyNumber	String{16}	Optional	Mandatory for Instant Card Registration.
customerId	String {100}	Optional	UCIC ID of the Customer
nameOnCard	String {25}	Optional	Customer Preferred Name on the Card. This filed is applicable for Purchasing a personalized Card.
cardDesign	String {6}	Optional	This field can be used to mention the Plastic Design Required for the card. This is used for the personalized card issuance. If the Value not Present then Default Design will be in use.
cardActivationFlag	String {1}	Optional	Set to “Y” if cards need to be activate immediately And “N” to activate later. This field is applicable only for the Instant Card and Virtual Card. If the value is “N” then the activation code is generated and available in the New Card Response. This activation code is used to activate the card through the Card Holder Portal /IVR

alertFlag	String {1}	Optional	For Future Use.
refText1	String {32}	Optional	Used to store the value in 4 th line embossing filed. And same can be provided in embossing file to card Bureau
refText2	String {6}	Optional	Used to send the campaign code

			The campaign code is a separate fee code that is maintained in the system through the NARADA(R) Fee Management Functionality function in the front-end portal. This is usually a 6 digit code that is used to assign specific fee settings for a given card which will override the Fee Settings that is mapped to the Product. A typical example where this is used is to maintain a differential charging for VIP Customers.
refText3	String {32}	Optional	For Future Use, It is used to language field
refText4	String {32}	Optional	For Future Use, It is used to add additional fields
CustomerInfo			
title	String {5}	Yes	Customer's Title
firstName	String {25}	Yes	Customer's First Name
middleName	String {25}	Optional	Customer's Middle Name
lastName	String {25}	Yes	Customer's Last Name
Dob	String {8}	Yes	Customer's Date of Birth. Format : DDMMYYYY
gender	String {1}	Yes	Customer's Gender [M/F]
mobileNumber	String {15}	Yes	Customer's Mobile Number Format: (+) with Country Code.
emailAddress	String{50}	Optional	Customer's Email Address
image	String	No	This field is applicable for Personalized Card. Used to Upload the Customer's Photo. Format: Encode the byte to Base64 Format.
CustomerInfo/Address			
address1	String {35}	Yes	Customer's residence address Line No 1
address2	String {35}	Yes	Customer's residence address Line No 2
address3	String {35}	Optional	Customer's residence address Line No 3

address4	String {35}	Optional	Customer's residence address Line No 4
city	String {20}	Yes	Customer's residence address City Name
state	String {20}	Yes	Customer's residence address State Name
country	String {20}	Yes	Customer's residence address Country Name
postalCode	String {15}	Yes	Customer's residence address Postal Code
homeNumber	String {15}	Optional	Customer's contact Number
nationality	String {15}	Yes	Customer's nationality
customerInfo/mailAddress			
address1	String {35}	Yes	Customer's business address Line No 1
address2	String {35}	Yes	Customer's business address Line No 2
address3	String {35}	Optional	Customer's business address Line No 3
address4	String {35}	Optional	Customer's business address Line No 4
city	String {20}	Yes	Customer's business address City Name
state	String {20}	Yes	Customer's business address State Name
cuntry	String {20}	Yes	Customer's business address Country Name
postalCode	String {15}	Yes	Customer's business address Postal Code
workNumber	String {15}	Optional	Customer's business Work Telephone Number
extension	String {5}	Optional	Customer's business Work Number Extension
customerInfo /identificationType - This node can be multiple when submitting more than one proof and it is optional tag			
idType	String {25}	Yes	Customer's Identification Proof Type
idNumber	String {20}	Yes	Customer's Identification Proof Type Number
expiryDate	String {8}	Optional	Expiry Date of Customer's Identification Proof Format :DDMMYYYY
countryofIssue	String {20}	Yes	Identification proof issued county Name.
loadDetails			
productCode	String {6}	Yes	Short Code of product to map with the Card.
loadAmount	String {12}	Yes	Amount to be loaded into the Card account of the card holder
billingAmount	String {12}	Yes	This field contains the amount in the card account currency
loadCurrency	String {3}	Yes	Currency used by the Card holder to fund the card Account. For example, if Card holder used USD to load a GBP Card account, then Loading currency will be USD
billingCurrency	String {3}	Yes	This is the currency of the card account

New card Response

The following table lists the fields returned in the response from the Narada-PPH API along with Response Code and Response Text. Refer the Appendix for the Code and Information.

For Virtual card /Card Not Present Product Proxy Number will not be created. Now the Card is created and respective product will be linked .And Card Status will be inactive status which allows loading the amount to account.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the Request
proxyNumber	String {16}	Yes	For Personalized card it will be generated and set to the Field. If it is Instant card then echoed back the Proxy Number.
cardNumber	String{16}	Optional	CardNumber will be present only for Virtual Card/Card Not Present Products.
cstomerId	String {100}	Optional	Echoed back from the Request
cardExpiry	String{8}	Optional	Expiry Date Value will be set to the response only for the Virtual Card.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Request:

Below plain sample request is not real request to process. Equitas Always process Encrypted Request and below parameter or form present in payload. Below added encrypted format also.

Because in plain request we are not able to identify the request for which vender. This only happen based on bank code which received in **header B**.

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/customerregistration	
Plain Body payload Request	POST	Method
	Customer Registration	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "APNCRDffefgd06", "customerId": "C333OMERID0000088698",</pre>

		<pre> "nameOnCard": ":Tushar Mule", "cardDesign": "BASEPL", "cardActivationFlag": "N", >alertFlag": "N", "refText1": "P", "refText2": "P", "refText3": "A", "refText4": "B", "customerInfo": { "title": "Ms", "firstName": "pritam", "lastName": "Mule", "dob": "20101999", "gender": "M", "mobileNumber": "918203920747", "emailAddress": "pritam@gmail.com", "image": "wquyrwrbwkcfw", "address": { "address1": "LEVEL 10 - BUSINESS CENTRAL TOWE", "address2": "L HAMDAN STREET", "address3": "o", "address4": "k", "city": "ABU DHABI", "state": "ABU DHABI", "country": "UNITED ARAB EMIRATES", "postalCode": "456654", "homeNumber": "971554747977" }, "mailAddress": { "officeAddress1": "Y", "officeAddress2": "HAMDAN STREET", "officeAddress3": "HAMDAN STREET", "officeAddress4": "HSADGHHSDUYTYUERGYSUYDGUYUYGFDSGF", "officeCity": "ABU DHABI", "officeState": "ABU DHABI", "officeCountry": "UNITED ARAB EMIRATES", "officePostalCode": "456654", "officeWorkNumber": "971555084477", "extension": "25632" }, "identificationType": { "idType": "00000000006610", "idNumber": "IDNumber0880006699", "expiryDate": "10012024", "countryOfIssue": "USA" } }, "loadDetails": { </pre>
--	--	---

		<pre> "productCode": "MCCAED", "loadAmount": "100", "billingAmount": "100", "loadCurrency": "AED", "billingCurrency": "AED" } </pre>
Response		<pre> { "txnRefNo": "APNCRDffedfgd06", "proxyNumber": "000000013829", "cardNumber": "8246115270646025", "customerId": "C333OMERID00000877", "cardExpiry": "31-MAR-30", "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.2 Update Customer Details

Update Customer Request -

This API can be called to update the details of an existing Customer/Card holder. The details those are allowed for an update will be the email ID, mobile number and contact addresses. Customer Name cannot be updated.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester
proxyNumber	String{16}	C	Either Card Number or Proxy Number can be Accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.

customerID	String{16}	C	UCIC ID of the Customer
CustomerInfo			
title	String {5}	Yes	Customer's Title
firstName	String {25}	Yes	Customer's First Name
lastName	String {25}	Yes	Customer's Last Name
nameOnCard	String {25}	Optional	Customer's Name on Card
Dob	String {8}	Yes	Customer's Date of Birth. Format : DDMMYYYY
mobileNumber	String {15}	Yes	Customer's Mobile Number. Format : Prefix with (+) and along with Country Code Ex: +6598804000
emailAddress	String{50}	Yes	Customer's Email Address
CustomerInfo/Address - This Node will be Mandate if need to update Customer Residence Address			
address1	String {35}	Yes	Customer's residence address Line No 1
address2	String {35}	Yes	Customer's residence address Line No 2
address3	String {35}	Optional	Customer's residence address Line No 3
address4	String {35}	Optional	Customer's residence address Line No 4
city	String {20}	Yes	Customer's residence address City Name
state	String {20}	Yes	Customer's residence address State Name
country	String {20}	Yes	Customer's residence address Country Name
postalCode	String {15}	Yes	Customer's residence address Postal Code
homeNumber	String {15}	Optional	Customer's contact Number
CustomerInfo/MailAddress - This Node will be Mandate if need to update Customer Mailing Address			
address1	String {35}	Yes	Customer's business address Line No 1
address2	String {35}	Yes	Customer's business address Line No 2
address3	String {35}	Optional	Customer's business address Line No 3
address4	String {35}	Optional	Customer's business address Line No 4
city	String {20}	Yes	Customer's business address City Name
state	String {20}	Yes	Customer's business address State Name
country	String {20}	Yes	Customer's business address Country Name
postalCode	String {15}	Yes	Customer's business address Postal Code
workNumber	String {15}	Optional	Customer's business Work Number
extension	String {5}	Optional	Customer's business Work Number Extension
CustomerInfo/IdentificationType - This node can be multiple when submitting more than one proof and it is optional tag			
iDType	String {25}	Yes	Customer's Identification Proof Type
iDNumber	String {20}	Yes	Customer's Identification Proof Type Number
issueDate	String {8}	Optional	Customer's Identification Proof issue Date Format : DDMMYYYY

expiryDate	String {8}	Optional	Expiry Date of Customer's Identification Proof Format :DDMMYYYY
countryofIssue	String {20}	Yes	Identification proof issued county Name.
idImage	String	Optional	It is used to upload the identification image. Format: Encode the byte to Base64 Format. More than one images can be uploaded by giving comma separator Example : Image1,Image2
idImageName	String	Optional	It is used to upload the identification image name with any one of the following extension Image format : JPG, GIF, PNG and BMP More than one image name can be uploaded by giving comma separator Example : Image1.JPG, Image2.JPG
customerInfo/FutureUse - This Node will be future use.			
refext1	String	Optional	Future Use1
refext2	String	Optional	Future Use2
refext3	String	Optional	Future Use3

Update Customer Response

Once the data is updated successfully in the system, then you will get the response or else error will be passed in response code field, the following table lists the fields returned in the response.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Mandatory	Echoed back from the Request
proxyNumer	String {16}	Mandatory	Echoed back from the Request
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/customerupdate	
	POST	

Request	Update Customer	<pre> { "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "CSTRwe343fgt021", "proxyNumber": "000000012935", "customerInfo": { "title": "Mr", "firstName": "Pritam", "lastName": "Fulbandhe", "dob": "08071999", "mobileNumber": "917972057064", "emailAddress": "pritamfulbandhe@test.com", "address": { "address1": "nagpur", "address2": "house no.15 new vithhal mandir", "address3": "", "address4": "", "city": "nagpur", "state": "maharashtra", "country": "India", "postalCode": "441501", "homeNumber": "919545607083" }, "mailAddress": { "officeAddress1": "Y", "officeAddress2": "Nagpur", "officeAddress3": "It Park STREET", "officeAddress4": "dsdsdsdsdsd", "officeCity": "Nagpur", "officeState": "Maharashtra", "officeCountry": "India", "officePostalCode": "441503", "officeWorkNumber": "971555084478", "extension": "25632" }, "identificationType": { "idType": "121202120011", "idNumber": "121202121510201", "issueDate": "10012024", "expiryDate": "10012024", "countryofIssue": "India", "idImage": "", "idImageName": "" } } } </pre>
---------	-----------------	---

		<pre> }, "futureUse": { "refText1": "1", "refText2": "1", "refText3": "1" } } </pre>
Response		<pre> { "txnRefNo": "CSTRwe343fgt021", "proxyNumber": "000000012935", "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.3 Get Card Details -

This API can be called to retrieve the account summary of the card holder. This will return the card holder details, lists of accounts and the linked to the card number.

Get Card Details Request

Customer's Card Number is the primary field to fetch the card status, products linked to the card, amount on the account and customer details.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester
proxyNumber	String {16}	Optional	Either Card Number or Proxy Number can be accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.

customerId	String {100}	Optional	UCIC ID of the Customer
------------	--------------	----------	-------------------------

Get Card Details Response

In the response Service Requester can able to get card information like status of the card as the form of short code. (Refer the Appendix for the card status), customer details and linked account details. If the customer has multiple products mapped to single card, then those details will be presented in the response as multiple based on number of products.

In this response is modified if single UCCID having more than one card. Comma separated values will come.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String{500}	Yes	Echoed back from the request.
cardStatus	String{500}	Yes	Status of the Card
expiryDate	String {500}	Yes	Expiry Date of the Card. Format : DDMMYYYY
nameOnCard	String {1000}	Optional	Customer Preferred Name on the Card. This filed is applicable for Purchasing a personalized Card.
mobileNumber	String {500}	Optional	Customer's Mobile Number
emailId	String {500}	Optional	Customer's Email Address
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/carddetails	
Request	POST	
	Get Card Details	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "HIccdafttyU",</pre>

		<pre> "proxyNumber": "000000012845", "customerId": null } </pre>
Response		<pre> { "txnRefNo": "TusharMulfd3pfioKddlij4d5g", "proxyNumber": "000000012845", "cardStatus": "I", "expiryDate": "31-JUL-29", "nameOnCard": "sdfsdfsaf", "maskedCardNumber": "5364XXXXXXXX8508", "cvv": 768, "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.4 Block /Unblock the Card

This API is used to change the status of the card. For example when the Consumer Card's got lost or damaged or stolen then he has to block the card to avoid Fraud transaction. Various statuses can be marked to the Card in the System based on the reason to block.

- BL - Permanently Block the Card due to card Lost
- BS - Permanently Block the card due to Card Stolen
- BD - Permanently Block the Card due to physical Damage
- L - Lock the Card and this can be unlocked by giving UL flag to this API

Once the card is blocked, then online transactions (ATM, POS, and ECOM) are not allowed. But web transactions can be allowed i.e. Card Holder can use the portal to view his transaction and we can't do any of the below activity for temporarily blocked card.

- Card load
- Account Addition
- Fund Transfer
- Account closure
- Refund
- Debit/credit Account

Locked card can be unlocked, Card Holder can't place a replacement card Request for locked card. Permanently blocked cards can't be unblocked (BL/BS/BD) only card replacement can be done. To request Replacement

Card via Narada-API call “Card Replacement API-APCDRP”.

Locked card can be unlocked by sending the flag parameter as “UL” - Unlock the Card. Once the card unlocked then Card Holder can perform Online Transactions.

S.No	New Status to be changed	Allowed status of card
1	Card Locked (L)	Active
2	Card Blocked BL : lost BS : stolen BD : damaged	Active
3	Card Unlocked (UL)	Locked

Card Block/Unblock Request

The following table lists the fields which need to send in the Request.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester (12 character length) / external vendor (MASTER/VISA) 32 character length.
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
flag	String{2}	Yes	Status of the card needs to be updated. Values are BL/BS/BD/L/UL
reason	String {25}	Yes	Reason for Block/Lock/unlock.

Card Block/unblock Response

If the card is already in requested status, then system will not change the card status and send the non-successful response Code and with the description.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the Request

proxyNumber	String {16}	Yes	Echoed back from the Request
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardlockunlock	
Request	POST	
	Card Block/Unblock	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "SJGDGfhdrtf666", "proxyNumber": "000000012845", "flag": "L", "reason": "Card Lock" }</pre>
Response	<pre>{ "txnRefNo": "SJGDGfhdrtf666", "proxyNumber": "000000012845", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.5 Card Activation

Once the Card is created successfully through the “Purchase a Card API” and you will get a ProxyNumber, Card Number along with 6 digit activation code. Use the activation code along with ProxyNumber to activate the card.

Card Activation Request

The following table lists the fields which need to send in the Request.

Parameter	Type	Description	Mandatory	Sample Values
-----------	------	-------------	-----------	---------------

Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
activationCode	String {6}	Optional	Activation Code to activate the card.
customerId	String {100}	Optional	It is used to map the customer of Service Requester proprietary System with Yalamanchili Prepaid System An example is the Customer ID of the Financial Institution Core Banking system for the particular customer who is given a Payment Card

Card Activation Response

The following table lists the fields which returned in the Response.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the Request
proxyNumber	String {16}	Yes	Echoed back from the Request
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

If you want to know the status of card and balance use the “Get Card Details API - APCHDT”

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardactivation
-----	---

Request	POST	
	Card Activation	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "0000000000000CA001", "proxyNumber": "000000013810", "activationCode": null, "customerNumber": null, "appCode": null }</pre>
Response		<pre>{ "txnRefNo": "0000000000000CA001", "proxyNumber": "000000013810", "responseCode": "00", "responseText": "Transaction Success" }</pre>

4.6 Card Replacement

This API is used to place a replacement request for two types of cards

1. Replace the existing Physical Card.
2. Get Physical Card for Virtual Card with same Number.

When to Replace the existing Physical Card:-

The existing card should be blocked before applying a replacement card. Replacement process involved the creation of card, Pin mailer, Card Embossing and Card Delivery and those functions will be at the End of Day Processing. Card Replacement will be applicable based on upon the product configuration in the Narada System.

Virtual to Physical Card:-

When the customer wants to convert his virtual card to physical Card with the different Virtual card Number as physical, then use the type as “VP” - Virtual to Physical in the request parameter.

Card Replacement Request

The following table list the fields which are need to send in the request. Type is the keyword parameter to identify the replacement type.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by ServiceRequester
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be Accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
customerId	String {100}	Optional	Customer Identifier (Unique Registration Number - URN) generated by ServiceRequester and used to map the customer of ServiceRequester proprietary System with Yalamanchili Prepaid System.
type	String {2}	Yes	VP - Virtual to Physical PP - Physical to Physical.
cardDesign	String {6}	Optional	To specify the card design for the replacement. If the Value is not set then default design will be taken.
deliveryFlag	String {1}	Conditional	Based on the delivery flag card will be delivered B - Branch Address C- Customer Address It is mandatory for personalized replacement cards only

Card Replacement Response

On successful transaction, replacement card request is placed in the system and by End of Day processing card Number will get generated and once Card is created then it will be delivered to Consumer/Client based on the mailing information.

If the card is not blocked already, then system will send non successful Response Code. Note: If you receive the non-successful response and then response will not be set in the response field. The fee will be charged for the customer if it is configured for the transaction. In addition to that if the card design is not mapped for the product or Inputted Design not available for the product then request will not be processed successful.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
---------	-----------	----------	-------------

Response			
txnRefNo	String {32}	Yes	Echoed back from the Request
proxyNumber	String {16}	Yes	Echoed back from the Request
newProxyNumber	String {16}	Yes	Echoed back from the Request
newCardNumber	String {16}	Yes	Echoed back from the Request
cardAcctNo	String {16}	Optional	Echoed back from the Request
cvv	String {3}	Optional	Echoed back from the Request
expiryDate	String {10}	Yes	Echoed back from the Request
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardreplacement	
Request	GET	
	Card Replacement	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "0000000000000000CR02", "proxyNumber": "000000013667", "customerId": "SANDBOXCID0000000097", "type": "PP", "cardDesign": "BASEPL", "deliveryFlag": "B" }</pre>
Response	<pre>{ "txnRefNo": "0000000000000000CR02", "proxyNumber": "000000013667", "newProxyNumber": "000000013833", "newCardNumber": "5364XXXXXXXXX9490", "cardAcctNo": "000000018344", "cvv": null, "expiryDate": "31-MAR-30", }</pre>	

	<pre> "responseCode": "00", "responseText": "Transaction Success" } </pre>
--	--

4.7 Account Addition

Narada supports Consumer to have more than one product in a Single Card. This API is can be used whenever customer want to subscribe a new product to his card.

Account Addition Request

The following table list the fields which are need to be sent in the request. If ServiceRequester wants to add more than one product in same request, then he has to construct details element node for each product under the Product Info Node.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
Request/productInfo/details			
productCode	String {6}	Yes	Short Code of product to subscribe.
loadAmount	String {12}	Yes	Amount to be loaded into the Card account of the card holder with amount will be zero or greater than zero
billingAmount	String {12}	Yes	This field contains the amount in the card account Currency
loadCurrency	String {3}	Yes	Currency used by the Card holder to fund the card Account. For example, if Card holder used USD to load a GBP Card account, then Loading currency will be USD Format: 3 digits ISO Currency Code.

billingCurrency	String {3}	Yes	This is the currency of the card account. Format: 3 Digits ISO Currency Code.
-----------------	------------	-----	---

Account Addition Response

On the successful transaction, new product is added to the Card and now Card Holder can start using his new product. If the product is already available for the card, then system will be sent non successful response.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
ResponseXml - Root Node of the of XML			
txnRefNo	String {32}	Yes	Echoed back from the Request
proxyNumber	String {16}	Yes	Echoed back from the Request
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/accountaddition	
Request	POST	
	Account Addition	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "0000000000000AD02", "proxyNumber": "000000013680", "productInfo": { "details": { "productCode": "PAYPRD", "loadAmount": "50", "billingAmount": "10", "loadCurrency": "AED", "billingCurrency": "AED" } } }</pre>

		}
Response	<pre>{ "txnRefNo": "00000000000000AD02", "proxyNumber": null, "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.8 Load Card / Funding an Account

This API is used to load the funds in to customer account and when card is active and inactive (It is possible status before card gets activated).

Load Card Request

The following table list the fields which are need to be sent in request.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester (12 character length) / external vendor (MASTER/VISA) 32 character length.
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
Request/ProductInfo			
productCode	String {6}	Yes	Short Code of product
loadAmount	String {12}	Yes	Amount to be loaded into the Card account of the card Holder
billingAmount	String {12}	Yes	This field contains the amount in the card account Currency

loadCurrency	String {3}	Yes	Currency used by the Card holder to fund the card Account. For example, if Card holder used USD to load a GBP Card account, then Loading currency will be USD. Format: 3 digits ISO Currency Code.
billingCurrency	String {3}	Yes	This is the currency of the card account. Format: 3 Digits ISO Currency Code.

Load Card Response

Card account balance will be updated online on the Successful execution of transaction .If any fees have been configured in the Product Definition for load transaction and it will get deducted and the remaining amount will be available as balance amount of the Card account. The following table lists the fields which are returned in the response.

The scenario where transaction get fails is

- while trying for the closed card
- If Card Balance exceeds the Balance limit
- Transaction limit validation (daily, weekly, monthly) based on Limit rules configure for the Product.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request
proxyNumber	String{16}	Yes	Echoed back from the request
balanceAmt	String{12}	Yes	Available balance on the account
feeAmount	String{12}	Yes	Shows the fee amount if any charged or else value will be zero.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/accountfunding	
Request	POST	
	Load Card	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" } }</pre>

		<pre> }, "txnRefNo": "00000000000005", "proxyNumber": "000000012845", "productInfo": { "productCode": "MCCAED", "loadAmount": "30", "billingAmount": "30.00", "loadCurrency": "AED", "billingCurrency": "AED" } } </pre>
Response		<pre> { "txnRefNo": "00000000000005", "proxyNumber": "000000012845", "cardBalance": "12261.00", "feeAmount": "0.00", "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.9 Query Balance

This is API is used to get the balance of the card.

Query Balance Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.

proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be Accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
-------------	------------	-----	---

Query Balance Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the Request
proxyNumber	String{16}	Yes	Echoed back from the Request
productInfo/details			
productCode	String{6}	Yes	Short code of the product.
balanceAmount	String{12}	Yes	Balance Amount on the card.
accountCcy	String{3}	Yes	Card Account Currency. Format: 3 digits ISO Currency Code.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardbalance	
Request	GET	
	Query Balance	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "QUERY1d56dddu1", "proxyNumber": "000000012845" }</pre>
Response	<pre>{ "txnRefNo": "QUERY1d56dddu1", "proxyNumber": "000000012845", "productInfo": { "details": {</pre>	

	<pre> "productCode": "MCCAED", "balanceAmount": "12221", "accountCcy": "AED" }, "responseCode": "00", "responseText": "Transaction Success" } </pre>
--	--

4.10 Amount Refund

This API can be called to place a request for an amount to refund from a card account. Two Type of refund will be supported are Partial and Full Refund. If fees has defined in the product definition for refund transaction, then balance of the card = Refund amount - Fee. If the Refund amount + fee Amount is greater than balance then refund request will get rejected.

Refund Request

The following table list the fields which are need to send in the request.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester (12 character length) / external vendor (MASTER/VISA) 32 character length.
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be Accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
productCode	String{6}	Yes	Product from where amount to be refunded
amount	String {12}	Yes	Refund Amount. For full refund set the amount as "***" in the field. And for partial specify the exact amount to refund
requestType	String {12}	Yes	e.g. REFUND

Refund Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request
proxyNumber	String{16}	Yes	Echoed back from the request
productCode	String{6}	Yes	Echoed back from the request
balanceAmount	String{12}	Yes	Available balance (Refund amount - fee).
feeAmount	String{12}	Yes	Shows the fee amount if any charged or else value will be zero.
responseCode	String{2}	Yes	It should be 00
responseText	String{100}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/amountrefund	
Request	POST	
	Amount Refund	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "AMOUTR4wrtrtSS", "proxyNumber": "000000000041", "productCode": "MCCAED", "amount": "01.00", "requestType": "REFUND" }</pre>
Response	<pre>{ "txnRefNo": "00000000000005", "proxyNumber": "000000012845", "productCode": "MCCAED", "balanceAmount": "12261.00", "feeAmount": "0.00", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

	}

4.11 Account closure

This API can be used to close the account (Product) associated with the card based on the product code in the request parameter. If the Card linked to more than one product, then based on product send in the request alone get closed other accounts will remains in active and card also in active status.

In the scenario when the card has single product and tried for account closure, then below action are performed in system are

- Check whether the balance on the account is zero. If matched then the account will be closed.
- Check whether any other products linked to card. If no then close the card too.

Note: Account will be eligible to close when the balance is zero.

Account Closure Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be Accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
productCode	String{6}	Yes	Product from where amount to be refunded

Account Closure Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String{16}	Yes	Echoed back from the request.
productCode	String {6}	Yes	Echoed back from the request
responseCode	String{2}	Yes	It should be 00
responseText	String{100}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/accountclosure	
Request	POST	
	Account Closure	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "000000000000CC04", "proxyNumber": "000000013810", "productCode": "MCCAED" }</pre>
Response	<pre>{ "txnRefNo": "000000000000CC04", "proxyNumber": "000000013810", "productCode": null, "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.12 Get X Transactions

This API is used to fetch the transactions performed on the card. The count of the transactions required in the response should be set in field “count” as part of input parameter

If the input value for count parameter is provided as „***” then irrespective of the „From”, „To” dates, all the available transactions are set in the response (Maximum transaction returned in the response is “99”).

Number of records per page can be specified in the parameter 'COUNT'. The application logic would be that if Page Number XML Tag is filled then we will assume that COUNT contains the Number of records per page.

Get X Transaction Request

From Date Value should not be greater than six months from current date. And also difference between From Date and To Date will be three 90 days.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String{16}	Yes	Customer's Card Number.
fromDate	String{8}	Yes	From Date of the Transaction. Format : DDMMYYYY
toDate	String{8}	Yes	End Date of the Transaction. Format : DDMMYYYY
count	String{2}	Yes	Number of transaction to be returned, the count Should be <= 99. If value is set to “***” then by default maximum number of transaction available in response is “99”.

Get X Transaction Response

Transaction response will not be irrespective to the account/product of the card. For example if two products are linked to the card, then transaction will be fetched between the request date will be collection of transaction done on the two products.

This API will return settled, unsettled and declined transaction irrespective of transaction status for the given date range. Fee details will be returned in separate row along with the original transaction, Transaction reference number or auth id will be the identification field to group the original transaction and its fee

transaction

Following are the total fields applicable for transaction response as part of common API specification. Based on client requirement and usage, we can enable or disable the fields.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {12}	Yes	Echoed back from the request.
proxyNumber	String{16}	Yes	Echoed back from the request.
activateDate	String{8}	Yes	Date when card was activated. Format DDMMYYYY
transactions/detail			
txnRefNo	String{32}	Yes	Transaction reference number - 16 digits for web transaction, 32 digits for online/API transaction (APCRND,ACDSTS,APCRLD,APFNTR,APRND)
transactionDate	String{11}	Yes	The date that the transaction was processed (DD-MMM-YYYY)
transactionTime	String{8}	Yes	The time that the transaction was process (HH:MI:SS)
productCode	String{6}	Yes	Card's product code (e.g. DBPRD1,DBPRD2)
transactionCode	String{6}	Yes	Yalamanchili 's Internal transaction code, (e.g. 010000 - ATM Cash withdrawal, 000000 - POS Purchase)
transSettleDate	String{8}	Optional	Transaction settlement date, it will be null for unsettled transaction
transRefNo	String{50}	Yes	Unique transaction ID
description	String{50}	Yes	Transaction description (e.g. Purchase, ATM cash withdrawal, International cross currency fee)
transCurrency	String{3}	Yes	Transaction Currency. Format: 3 digits ISO Currency Code.
transStatus	String{100}	Yes	Transaction Status like Pending, settled, Chargeback raised, copy request raised, Outstanding marked, dispute settled, Transaction reversed and etc.
transAmt	String{12}	Yes	Transaction Amount
billingCurrency	String{3}	Yes	Currency of the card Amount. Format: 3 digits ISO Currency Code.
billingAmt	String{12}	Yes	Amount in account currency. The value is present if the amount debited / credited to the account.
drCrIndicator	String{1}	Yes	"D" - Account Debit transaction, "c" - Account Credit transaction

exRate	String{12}	Yes	The exchange rate as applied to the transaction should be available. If the transaction is happening in the card currency, then the exchange rate should be defaulted to 1.0000
authId	String{6}	Optional	Authorization Code of the transaction done. Will be Available for all ATM/POS transactions.
mccCode	String{6}	Yes	Merchant Category Code
merchantId	String{20}	Yes	Merchant Store Identification number
merchantName	String{100}	Yes	Merchant Name & Location
terminalId	String{15}	Yes	Terminal Id
merchCountryCo	String{3}	Yes	Merchant Country Code
posEntryMode	String{25}	Optional	Authentication Type, i.e. CNP, Magstripe, PIN etc.
responseCode	String{4}	Yes	Success / Decline Response Code for the transaction
responseReason	String{8}	Yes	Success / Decline Response Reason for the transaction

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/transactiondetails	
Request	GET	
	GET X Transaction s	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "13000000000000GT002", "proxyNumber": "000000012787", "fromDate": "01062024", "toDate": "01072024", "count": "1" }</pre>
Response	<pre>{ "txnRefNo": "13000000000000GT002", "proxyNumber": "000000012787", "activateDate": "25062024",</pre>	

```

"transactions": {
  "detail": [
    {
      "transactionRefNumber": "2418347656902271",
      "transactionDate": "01-Jul-2024 14:08:31",
      "transactionTime": "14:08:31",
      "transRefNo": "2418347656902271",
      "productCode": "MCCAED",
      "transactionCode": "100050",
      "transSettleDate": "01-Jul-2024",
      "description": "Branch Withdrawal",
      "transCurrency": "AED",
      "transStatus": "Approved",
      "transAmt": "100.00",
      "billingCurrency": "AED",
      "billingAmt": "100.00",
      "drCrIndicator": "D",
      "exRate": "1.0000",
      "authId": null,
      "mccCode": null,
      "merchantId": null,
      "merchantName": null,
      "terminalId": null,
      "merchLocation": null,
      "merchCountryCode": null,
      "posEntryMode": null,
      "responseCode": "00",
      "availableBalance": "0.00",
      "rrn": "2418347656902271",
      "mccCodeDescription": null,
      "responseReason": null
    }
  ]
},
"responseCode": "00",
"responseText": "Transaction Success"
}

```

4.13 Debit/Credit the Account

This API is used to charge the card holder (debit/credit) account for do any balance adjustment or to apply any additional fee apart from product definition.

Debit/Credit Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				

msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String{16}	Yes	Either Card Number or Proxy Number can be Accepted. Card Number will be 16 digits and Proxy Number will be 12 digits.
productCode	String{6}	Yes	Product code for the account to be charged
type	String {3}	Yes	Supported Transactions are Balance Adjustment.(BAT)
flag	String {2}	Yes	DR/CR - Indicates Debit/Credit the amount in the Account.
amount	String{12}	Yes	Amount to be Credit/Debit from Account.
currency	String{3}	Yes	Three digit ISO currency code for the Amount to be debit/Credit. If the currency and Account currency varies then system will apply the exchange rate.
remarks	String{25}	Yes	Specify the remarks for transaction which will be Printed in the statement.

Debit/Credit Response

Based upon the type of transaction and flag the amount will be debit/Credit from the account.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String{16}	Yes	Echoed back from the request.
productCode	String{6}	Yes	Echoed back from the request.
cardBalnce	String{12}	Yes	Balance on the account after the debit/Credit.
responseCode	String{2}	Yes	Code should be 00
responseText	String{100}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/debitcreditaccount	
Request	POST	
	Debit /Credit Account	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "00000000000000CD001", "proxyNumber": "000000013810", "productCode": "MCCAED", "type": "BAT", "flag": "D", "amount": "100.00", "currency": "AED", "remarks": "" }</pre>
Response	<pre>{ "txnRefNo": "00000000000000CD001", "proxyNumber": "000000013810", "productCode": "MCCAED", "cardBalance": "0", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.14 Fund Transfer

This API can be used to transfer fund from one card account to another card account of two different Card holders. Check performed if the Cards are in „Active“ status and „Source“ and „Destination“ accounts are linked to two different Card holders. Based on the input values such as Card numbers, target and destination accounts and the currency rate the fund transfer will be performed.

Fund Transfer Request

Transfer amount should in Destination Account currency. If it is cross currency fund transfer then exchange rate will calculated and then amount will be debited from Source account.

Parameter	Type	Description	Mandatory	Sample Values
-----------	------	-------------	-----------	---------------

Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester (12 character length) / external vendor (MASTER/VISA) 32 character length.
exchangeRate	String{12}	Optional	Exchange need not to set for Same currency Transfer. For Cross Currency specify the currency rate if not currency rate will be taken from the system which already set through Exchange Rate API.
Request/sourceAccount			
proxyNumber	String{16}	Yes	Either Source Card Number or Proxy Number where The amount to be debit. Card Number will be 16 digits and Proxy Number will be 12 digits.
productCode	String{6}	Yes	Short code of the product code.
accountCcy	String{3 }	Yes	Currency of the source card account from where the Fund transfers to be initiated.
Request/destAccount			
proxyNumber	String{16}	Yes	Either Destination Card Number or Proxy Number where the amount to be transferred. Card Number will be 16 digits and Proxy Number will be 12 digits.
productCode	String{6}	Yes	Short code of the product code.
accountCcy	String{3}	Yes	Currency of the destination account where the fund to be transferred
amount	String{12}	Yes	Amount to be Credited.

Fund Transfer Response

The amount will get transferred immediately on successful processing. If transaction got failed, the reason code will send in the response along with description.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
---------	-----------	----------	-------------

Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
exchangeRate	String{12}	Yes	Exchange rate applied for amount calculation.
response/sourceAccount			
proxyNumber	String{16}	Yes	Echoed back from the request.
productCode	String{6}	Yes	Echoed back from the request.
accountCcy	String{3 }	Yes	Echoed back from the request.
amount	String{12}	Yes	Amount debited from the source account(Excluding Fee charges)
feeAmount	String{12}	Optional	Fee Amount if any charged on source account.
response/destAccount			
proxyNumber	String{16}	Yes	Echoed back from the request.
productCode	String{6}	Yes	Echoed back from the request.
accountCcy	String{3}	Yes	Currency of the destination account where the fund to be transferred
amount	String{12}	Yes	Credited Amount.
feeAmount	String{12}	Yes	Fee Amount
responseCode	String{2}	Yes	Code should be 00
responseText	String{100}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/fundtransfer	
Request	POST	
	Fund Transfer	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "APFDTR0dffgd98d5Td3", "exchangeRate": "1.00", "sourceAccount": { "proxyNumber": "000000012787", "productCode": "MCCAED", "accountCcy": "AED" }, "destAccount": {</pre>

		<pre> "proxyNumber": "000000012845", "productCode": "MCCAED", "accountCcy": "AED", "amount": "10" } </pre>
Response		<pre> { "txnRefNo": null, "exchangeRate": "1.0000", "transRefNumber": null, "sourceAccount": { "proxyNumber": "000000012787", "productCode": "MCCAED", "accountCcy": "AED", "amount": "10.00", "feeAmount": "0" }, "destAccount": { "proxyNumber": "000000012845", "productCode": null, "accountCcy": "AED", "amount": "10.00", "feeAmount": "0" }, "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.15 Exchange Rate

This API can be used to update the exchange rates maintained in the Yalamanchili Platform. The buying and selling rates can be updated for a combination of Source and Destination currency.

- Check performed if the rates for the „Source“ and „Destination“ currencies are already available for the requested date.
- If the rates for the requested date are available then the values received in the request are updated, else the values are maintained in the System.
- Currency should be three digit ISO format. Ex for US dollars as USD. [Exchange Rate](#)

Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				

msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
buyCurrency	String {3}	Yes	Currency code of the buying currency.
sellCurrency	String {3}	Yes	Currency code of the selling currency.
exRate	String{12}	Yes	Exchange rate used for buying and selling.
bankRate	String{12}	Yes	Bank Rate

Exchange Rate Response

Once the exchange is updated successful, transaction reference no is echoed back in the response along with response code.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
responseCode	String{2}	Yes	Code should be 00
responseText	String{100}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/exchangerate	
Request	POST	
	Exchange Rate	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" } }</pre>

		<pre> }, "txnRefNo": "0000000000000000EX02", "buyCurrency": "AED", "sellCurrency": "USD", "exRate": "01.2551", "bankRate": "01.2551" } </pre>
Response	<pre> { "txnRefNo": "0000000000000000EX02", "responseCode": "00", "responseText": "Transaction Success" } </pre>	

4.16 Card Order

This API can be used to place the Card Order for non-personalized card type. The process for placing Card order as below

1. Card Order should place against the Branch in the System. So that Stock Inventory can be maintained.
2. In the request, if the branch id is not mentioned, then as default card order will be placed under the branch of API User.
3. As default, cards will be delivered to the Card Ordered branch. If Requester wants to deliver to different address, then specify the address in the Address filed.
4. Before placing the Order, the system will validate whether the product is available for the branch, Card design is available for the product. If those condition matched, then the order will be placed and invoice number will be generated and send in the response.
5. Use the invoice number for tracking the Order status.

Once the Card Order places then following process are involved with the entity Yalamanchili's, Card Bureau and service Requester are

1. Yalamanchili will create the embossing file and send to the Card Bureau for Card Creation.
2. Only card has been created then Card Bureau will delivered the cards to the branch address or to the address mentioned in the card order request.
3. service Requester should receipt the card via "Card Receipt API-APSTRC" so that stock will get updated in the Narada.

Card Order Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	

channelType	String	App ID of the source from where the transaction is initiated	Y	
-------------	--------	--	---	--

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by service Requester.
Request/Order			
branchId	String {8}	Optional	Branch ID of the Branch used for Card Order.
productCode	String {6}	Yes	Product code for the Card Order to be placed.
cardDesign	String{6}	Yes	Card Design for the order.
quantity	String{10}	Yes	Number of cards to be ordered.
Request/Order/Delivery - This field can be optional, if not specified then card will be delivered to branch address of the order Requester. i.e branch of the api user.			
name	String{50}	Yes	Name of the Branch
address1	String{35}	Yes	Branch Address Line No1
address2	String{35}	Yes	Branch Address Line No2
address3	String{35}	Optional	Branch Address Line No3
address4	String{35}	Optional	Branch Address Line No4
city	String {20}	Yes	Branch address City Name
state	String {20}	Yes	Branch address State Name
country	String {20}	Yes	Branch address Country Name
postalCode	String {15}	Yes	Branch address Postal Code

Card Order Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
invoiceNo	String{20}	Yes	Invoice Number for the Card Order Placed. Use this Invoice number for order Tracking
orderRefNo	String{10}	Yes	Reference for the Order. Use this reference number for Receipt the order /to report card damage
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardorder
-----	---

Request	POST	
	Card Order	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "00000000000000CA04", "order": { "branchId": null, "productCode": "INRPAY", "cardDesign": "BASEPL", "quantity": "1", "delivery": { "name": "Accord Communications", "address1": "Ferry House", "address2": "Geet Apartment", "address3": null, "address4": null, "city": "Nagpur", "state": "Maharashtra", "country": "India", "postalCode": "354598784546546" } } }</pre>
Response		<pre>{ "txnRefNo": "00000000000000CA04", "invoiceNo": "2507248239681377", "orderRefNo": "016906", "responseCode": "00", "responseText": "Transaction Success" }</pre>

4.17 Card Receipt

Once the Card delivered to branch, then branch should acknowledge the delivery of the card by calling this API. So that in the Narada system cards will be marked as receipt and now it's ready for sale. Order reference number and pack reference is mandate to receipt the card. If there is any damage in the card then use the update stock API to report the damage and update the inventory too. Every card/Item is dispatched with pack

reference no. Use this pack reference number in the request to confirm the receipt.

Card Receipt Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
request/receipt			
orderRefNo	String {10}	Yes	Order Reference Number.
quantity	String {10}	Yes	No of Cards Received.
fromPackNo	String {12}	Yes	From pack Reference Number.
toPackNo	String {12}	Yes	To Pack Reference Number.

Card Receipt Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the response.
orderRefNo	String {12}	Yes	Echoed back from the response.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardreceipt	
	POST	

Request	Card Receipt	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "00000055s000000CA07", "receipt": { "orderRefNo": "016199", "quantity": "1", "fromPackNo": "12786", "toPackNo": "12786" } }</pre>
Response	<pre>{ "txnRefNo": "00000000000000CA04", "orderRefNo": "016906", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.18 Update Stock Details

This API is used to update the stock if there is any damage in the card.

Update Stock Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			

txnRefNo	String {32}	Yes	Unique Transaction Reference generated by service Requester.
orderRefNo	String {12}	Yes	Order Reference number for damage to be reported
quantity	String {10}	Yes	Number of Cards damaged.
Request/refNumbers - Pack No field will be multiple depends no of Quantity get damaged.			
packNo	String {12}	Yes	Pack Reference of the damaged Card.

Update Stock Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
responseXml - Root Node of the of XML			
txnRefNo	String {32}	Yes	Echoed back from the request
orderRefNo	String {12}	Yes	Echoed back from the request
quantity	String {10}	Yes	Echoed back from the request
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/updatestockdetails	
Request	POST	
	Update Stock	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "APyDFKdd7grtrtrm3", "orderRefNo": "016045", "quantity": "1", "refNumbers": { "packNo": ["000000012740", "000000012740"] } }</pre>

Response	<pre>{ "txnRefNo": "APyDFKdd7grtrtrm3", "orderRefNo": "016045", "quantity": "1", "responseCode": "00", "responseText": "Transaction Success" }</pre>
----------	--

4.19 Get Stock Details

This API is used to get the current stock status belong to branch requested. In the response cards ordered, card Activated, card with the branch (yet to activated).

Get Stock request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
RequestXml			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by service Requester.
branchId	String {8}	Yes	Get the stock details of the branch requested.

Get Stock response

The following table list the fields are returned in the response.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
branchId	String {8}	Yes	Echoed back from the request.
Response/stockInfo - This node will be based on the product mapped to the branch.			

productCode	String {6}	Yes	Short code of the product
cardOrdered	String {10}	Yes	Numbers of ordered by the branch up to now for that product
cardActivated	String {10}	Yes	Number of activated till now.
cardWithBranch	String {10}	Yes	Number of cards yet to activate.
cardDamaged	String {10}	Yes	Number of cards will be damaged.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/stockdetails	
Request	GET	
	Get Stock Details	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "APCTSDPrtr2dT73", "branchId": "BRCORPID09880" }</pre>
Response	<pre>{ "txnRefNo": "APCTSDPrtr2dT73", "branchId": "BRCORPID09880", "stockInfo": [{ "productCode": "AED Multicurrency", "cardOrdered": "0", "cardActivated": "0", "cardWithBranch": "0" }], "responseCode": "00", "responseText": "Transaction Success" }</pre>	

	}
--	---

4.20 Status Request

When the service Requester have not received the response from the Narada-API interface for initiated transaction, then this API will be helpful to know the status of transaction using original transaction reference Number.

Status Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Original Transaction reference Number

Status Response

Based on the response code returned in the response, service Requester will know whether transaction is received at the Narada-API Interface and processed. If the response code is "00" then transaction is processed successful. If the transaction not received by Narada-API then system will return the response code as "TXNNRV" - Transaction not received. If the transaction received and processed unsuccessful then relevant response, code and description of the original will be returned in the response.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/statusrequest	
Request	GET	
	API Status Request	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "APcF34654645fr55T3" }</pre>
Response	<pre>{ "txnRefNo": "APcF34654645fr55T3", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.21 Change Password

This API is used to change the password. API should validate new password and retype new password after that call the API with old and new password.

Change password Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			

txnRefNo	String {12}	Yes	Unique Transaction Reference generated by Service Requester.
oldPassword	String	Yes	Password should be minimum of 8 and maximum of 16 Characters. Hash the password with SHA-256 and encode to BASE64 format then send to
newPassword	String	Yes	Password should be minimum of 8 and maximum of 16 Characters. Hash the password with SHA-256 and encode to BASE64 format then send to NaradaPPH-API.

Change password Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {12}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/changepassword	
Request	POST	
	Change Password	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "APcF34654645fr55T3", "oldPassword": "APcF34654645fr55T3", "newPassword": "APcF34654645fr55T3" }</pre>
Response	<pre>{ "txnRefNo": "APcF34654645fr55T3", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.22 Access Rights

This API is used to provide the list of functions which are allowed for User Profile. Note this API is applicable to retrieve only registered Card Holder Profile Information.

Access Rights Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
userId	String {8}	Yes	User Id for the profile rights to be returned.

Access Rights Response

The following table list the fields are returned in the response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
userName	String {100}	Yes	Name of the Card Holder
lastLogin	String {25}	Yes	Last Login time of the Customer with the system. Format DD-MON-YYYY HH:MI:SS AM/PM
Response/menuList - This Node will have the list of Menu/Rights for the requested User			
tMenu	String {50 }	Yes	Name of the Menu
sMenu	String {50}	Yes	Sub Menu of the Main Menu
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/accessrights
-----	---

Request	GET	
	Access Rights	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "tusharhhhfyubvdsyr3", "userId": "CUSTOMER1" }</pre>
Response		<pre>{ "txnRefNo": "APcF34654645fr55T3", "userName": "pritam fulbandhe", "lastLogin": "12-03-2024 09:40:12", "menuList": { "tMenu": "Reports", "sMenu": "Daily Activity" }, "responseCode": "00", "responseText": "Transaction Success" }</pre>

4.23 PIN Retrieval

This API is used to retrieve ATM pin from the System. The ATM PIN would have already got generated in our system during the card data generation and also stored in the Chip.

PIN Retrieval Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			

txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
expiryDate	String {4}	Yes	Expiry Date of the Card Front panel. In MMY format
cvv2	String {3}	Yes	CVV2 of the Card Back Panel.
dob	String { 8 }	Yes	Customer's Date of Birth. Format : DDMMYYYY

PIN Retrieval Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
epinBlock	String {16}	Yes	Encrypted PINBLOCK <u>Note1:</u> - It will always be a 4 digit numeric PIN. - The PINBLOCK will be in ISO FORMAT-0 - T-DES encryption would be applied on the PINBLOCK - We will use a static Zone Pin Key for encryption of the PINBLOCK. <u>Note2:-</u> The Key Management for this Zone Pin Key would have to be carried out for both Test and Production between the two parties (YALAMANCHILI and client) as per Standard Information Security Policies.

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/pinretrieval	
	GET	

Request	PIN Retrieval	<pre> { "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "pinretrievalTushar1234c9", "proxyNumber": "000000012788", "expiryDate": "0629", "dob": "14061998", "cvv2": "182" } </pre>
---------	---------------	---

4.24 ATM PIN Verification

This API is used to verify ATM pin from the System.

ATM PIN verification Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
epinBlock	String {16}	Yes	Encrypted PINBLOCK Note1: - It will always be a 4 digit numeric PIN. - The PINBLOCK will be in ISO FORMAT-0 - T-DES encryption would be applied on the PINBLOCK - We will use a static Zone Pin Key for encryption of the PINBLOCK.

			<u>Note2:-</u> The Key Management for this Zone Pin Key would have to be carried out for both Test and Production between the two parties (YALAMANCHILI and client) as per Standard Information Security Policies.
dob	String { 8 }	Yes	Customer's Date of Birth. Format : DDMMYYYY

ATM PIN verification Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/atmpinverification	
Request	POST	
	ATM Pin Verification	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "00000000000000PV06", "epinBlock": "BD5B52E8F55B3002", "proxyNumber": "000000012748", "dob": "14061998" }</pre>
Response	<pre>{ "txnRefNo": "00000000000000PV06", "proxyNumber": "000000012748", "responseCode": "00", "responseText": "Transcation Success" }</pre>	

	}
--	---

4.25 ATM PIN Change

This API is used to change the ATM pin from the System.

ATM PIN change Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.

eoldPinBlock	String {16}	Yes	Encrypted PINBLOCK <u>Note1:</u> It will always be a 4 digit numeric PIN. The PINBLOCK will be in ISO FORMAT-0 T-DES encryption would be applied on the PINBLOCK • We will use a static Zone Pin Key for encryption of the PINBLOCK. <u>Note2:-</u> The Key Management for this Zone Pin Key would
--------------	-------------	-----	---

			have to be carried out for both Test and Production between the two parties (YALAMANCHILI and client) as per Standard Information Security Policies.
enewPinBlock	String {16}	Yes	Encrypted PINBLOCK <u>Note1:</u> It will always be a 4 digit numeric PIN. • The PINBLOCK will be in ISO FORMAT-0 • T-DES encryption would be applied on the PINBLOCK • We will use a static Zone Pin Key for encryption of the PINBLOCK. <u>Note2:-</u> The Key Management for this Zone Pin Key would have to be carried out for both Test and Production between the two parties (YALAMANCHILI and client) as per Standard Information Security Policies.

ATM PIN change Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/atmpinchange	
Request	POST	
	ATM Pin Change	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, ... }</pre>

		<pre> "txnRefNo": "pinertg6d5gf", "proxyNumber": "000000012748", "epinBlockOld": "BD5B52E8F55B3002", "epinBlockNew": "AFA1E2B9A23B7376" </pre>
Response		<pre> { "txnRefNo": "00000000000000PV06", "proxyNumber": "000000012748", "responseCode": "00", "responseText": "Transcation Success" } </pre>

4.26 Assign override settings

This API is used to campaign code mapped in the System. Campaign Code is a code used to identify a group of limits and fees. An example of Campaign Code would be special or differential fee conditions and limits to be applied for a VIP Personnel. The Campaign Code will be an over-ride to the product settings on limits and fees. The Campaign Code is assigned to one product mapped to the card number.

Pre-Requisite:

- Please be informed that the Campaign Code should already be pre-defined in the system using the Product Settings feature of the NARADA Prepaid Portal using the over-ride settings options.

Assign override settings Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
campaignCode	String {10}	Yes	Campaign Code

productCode	String {6}	Yes	Short code of the product
flag	String {1}	Yes	Campaign Code flag Enable/Disable [Y/N]

Assign override settings Response

All the Campaign Codes have an effective date(Start-Date and End-Date) and if the current date is within the Start-Date and End-date range only then the transaction is considered successful.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/assignoverridesettings	
Request	GET	
	Assign Override Settings	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "000000000000000001", "proxyNumber": "000000012845", "campaignCode": "CHGNEW", "productCode": "MCCAED", "flag": "N" }</pre>
Response	<pre>{ "txnRefNo": "000000000000000001", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.27 Alert Settings - set/unset

The following API is used to configure the SMS or Text Message alert settings for a specific set of transactions to a given cardholder.

Alert settings Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
productCode	String {6}	Yes	Short code of the product
alertType	String {6}	Yes	This is a string to represent the scenario or business transaction and can be any one of the following values 1. ATMCWD - This is for ATM Cash Withdrawal 2. PURCSE - This is for Purchases. 3. LOWBAL - This is when the cardholders account goes below the configured value by the cardholder. 4. TOPACC - This is sent when the card account is topped up.

frequency	String {3}	Yes	It can be either of the following values 1. DLY - <i>Applicable only for LOWBAL</i> 2. WLY - <i>Applicable only for LOWBAL</i> 3. MLY - <i>Reserved for Future Use</i> 4. YLY - <i>Reserved for Future Use</i> 5. TXN - <i>Applicable for ATMCWD, PURCSE, TOPACC</i> . Also this is a transaction triggered message if the transaction was successful.
alertData	String{12}	Optional	This will contain the amount for a LOW BALANCE ALERT in the format 000000000200 if the LOW BALANCE value is set as 2 units of the cardholder currency
channel	String{5}	Yes	Alert Type [SMS/EMAIL/BOTH]
alertSet	String{1}	Yes	Alert set or unset [Y/N]

Alert settings Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/alertsettings	
Request	POST	
	Alert Settings	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "1234566TXNREF12", "proxyNumber": "000000000012", "productCode": "PAYPRD", "alertType": "aLTSET", }</pre>

		<pre> "frequency": "DLY", >alertData": "000000000200", "channel": "SMS", >alertSet": "Y" </pre>
Response		<pre> { "txnRefNo": "000000000000000001", "proxyNumber": "000000000012", "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.28 Get Card number

This API can be called to retrieve the card number of the card holder.

Get Card number Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
refext1	String	Conditional	Future Use, This is based on client specific.
refext2	String	Optional	Future Use
refext3	String	Optional	Future Use

Get Card number Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
cardNumber	String {16}	Yes	Card number will be present linked to ProxyNumber.
expiryDate	String {8}	Yes	Expiry Date of Customer's Identification Proof Format :DDMMYYYY
nameOnCard	String {25}	Optional	Customer Preferred Name on the Card. This filed is applicable for Purchasing a personalized Card.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardnumberdetail	
Request	GET	
	Get Card Details	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "APIGCN45erdetail", "proxyNumber": "000000012845", "refText1": null, "refText2": null, "refText3": null }</pre>

Response	<pre> { "txnRefNo": "APIGCN45erdetail", "proxyNumber": "000000012845", "cardNumber": "3948076424178787", "expiryDate": "31-JUL-29", "nameOnCard": "SDFSDFSASF", "responseCode": "00", "responseText": "Transaction Success" } </pre>
----------	--

4.29 Get CSC Enquiry

This API can be called to retrieve the 4CSC. This functionality is only applicable for American Express Card Scheme - Virtual Cards.

Get CSC Enquiry Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
expiryDate	String {4}	Yes	Expiry Date of Customer's Identification Proof Format :YYMM

Get CSC enquiry Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
csc	String {4}	Yes	4CSC value will be set in the Response for the linked Card.

responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cscenquiry		
Request	GET		
	4CSC	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "pppUHIAdghgIHUHGdIU", "proxyNumber": "000000000401", "expiryDate": "0011463544318" }</pre>	
Response	<pre>{ "txnRefNo": "1234566TXNREF12", "proxyNumber": "000000000012", "csc": "1234", "responseCode": "00", "responseText": "Transaction Success" }</pre>		

4.30 Card Order Status

This API can be called to retrieve the status of card order.

Card Order Status Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceId which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	

timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
invoiceNo	String {13}	Yes	Either Invoice Number or Order Reference Number can be given in this field.

Card Order Status Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
invoiceNo	String {13}	Yes	Echoed back from the request.
invoiceDate	String {8}	Yes	Invoice Date. Format :DDMMYYYY
orderedBy	String {100}	Yes	Who is the initiate card order
productCode	String {6}	Yes	Short code of the product
plasticName	String {100}	Yes	Plastic name of the card order
cardOrdered	String {10}	Yes	Numbers of ordered by the branch up to now for that product
orderStatus	String {25}	Yes	Current Status of the card order
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/cardorderstatus	
Request	GET	
	Card Order Status	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "cardOrderStatus": { "txnRefNo": "WIZ202302171684895539768", "invoiceNo": "WIZ202302171684895539768", "invoiceDate": "2023-04-04", "orderedBy": "WIZ202302171684895539768", "productCode": "WIZ202302171684895539768", "plasticName": "WIZ202302171684895539768", "cardOrdered": "WIZ202302171684895539768", "orderStatus": "WIZ202302171684895539768", "responseCode": "00", "responseText": "Transaction Success" } }</pre>

		<pre> "txnRefNo": "APACB56d367rt4531", "invoiceNo": "016080" } </pre>
Response		<pre> { "txnRefNo": "APACB56d367rt4531", "invoiceNo": "016080", "cardOrderInfo": { "details": [{ "txnRefNo": "APACB56d367rt4531", "invoiceNo": "016080", "invoiceDate": "05-JUL-24", "orderedBy": "APIUSER", "productCode": "MCCAED", "plasticName": "BASEPL", "cardOrdered": "1", "orderStatus": "IA" }] }, "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.31 IVR PIN Set

This API is used to set the IVR pin. The IVR PIN would have already got generated in our system during the card data generation.

IVR PIN Set Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	

channelType	String	App ID of the source from where the transaction is initiated	Y	
-------------	--------	--	---	--

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
ivrPin	String	Yes	IvrPin should be 6 characters. Hash the password with SHA-256 and encode to BASE64 format then send to NaradaPPH-API.
dob	String { 8 }	Yes	Customer's Date of Birth. Format : DDMMYYYY

IVR PIN Set Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/ivrpinsset	
Request	POST	
	IVR PIN set	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "000000000000PIS001",</pre>

		<pre> "proxyNumber": "000000012748", "ivrPin": "0629", "dob": "14061998" </pre>
Response	<pre> { "txnRefNo": "1234566TXNREF12", "proxyNumber": "000000000012", "responseCode": "00", "responseText": "Transaction Success" } </pre>	

4.32 IVR PIN Change

This API is used to change the IVR pin from the system.

IVR PIN change Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
oldIvrPin	String {16}	Yes	IvrPin should be 6 characters. Hash the password with SHA-256 and encode to BASE64 format then send to NaradaPPH-API.
newIvrPin	String {16}	Yes	Pin should be 6 characters. Hash the password with SHA-256 and encode to BASE64 format then send to NaradaPPH-API.

IVR PIN change Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/ivrpinchange	
Request	POST	
	IVR PIN Change	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "000000000000PIS001", "proxyNumber": "000000012748", "oldIvrPin": "0629", "newIvrPin": "64753", "dob": "14061998" }</pre>
Response	<pre>{ "txnRefNo": "1234566TXNREF12", "proxyNumber": "000000000012", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.34 IVR PIN Validation

This API is used to validate the IVR PIN from the System.

IVR PIN Validation Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				

msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
ivrPin	String {16}	Yes	IvrPin should be 6 characters. Hash the password with SHA-256 and encode to BASE64 format then send to NaradaPPH-API.
dob	String { 8 }	Optional	Customer's Date of Birth. Format : DDMMYYYY

IVR PIN Validation Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/ivrpinvalidation	
Request	POST	
	VALIDATE IVR PIN	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" } }</pre>

		<pre> }, "txnRefNo": "000000000000PIS001", "proxyNumber": "000000012748", "ivrPin": "0629", "dob": "14061998" } </pre>
Response		<pre> { "txnRefNo": "1234566TXNREF12", "proxyNumber": "000000000012", "responseCode": "00", "responseText": "Transaction Success" } </pre>

4.35 Reset Web Password

This API is used to reset web password. It is used to web portal only and not supported in API login credentials

Reset Web Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
refext1	String {100}	Optional	Future Use
refext2	String {100}	Optional	Future Use
refext3	String {100}	Optional	Future Use
newPassword	String	Yes	Password should be minimum of 8 and maximum of 16 characters. Hash the password with SHA-256 and encode to BASE64 format then send to Narada-API.
confirmPassword	String	Yes	Password should be minimum of 8 and maximum of 16 characters. Hash the password with SHA-256 and encode to BASE64 format then send to Narada-API.

Reset Web Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/resetwebpassword	
Request	POST	
	Reset Web Usage	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "1234566TXNREF12", "refext1": "", "refext2": "", "refext3": "", "newPassword": "WWDJDJSSNNSSW222DS", "confirmPassword": "WWDJDJSSNNSSW222DS" }</pre>
Response	<pre>{ "txnRefNo": "1234566TXNREF12", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.36 Retrieve Web Profile

This API is used to retrieve web profile like user id, mobile no, email. User Id is used to web portal only and not supported API login credentials

Retrieve Web Profile Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
refext1	String {100}	Optional	Future Use
refext2	String {100}	Optional	Future Use
refext3	String {100}	Optional	Future Use

Retrieve Web Profile Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
userId	String {8}	Yes	User Id for the profile access.
emailId	String { 50 }	Optional	Email ID of the Card Holder
mobileNumber	String { 15 }	Optional	Customer's Mobile Number Format: (+) with Country Code.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/retrievewebprofile
-----	---

Request	POST	
	Retrieve Web Profile	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "1234566TXNREF12", "proxyNumber": "00000000012", "refext1": "", "refext2": "", "refext3": "" }</pre>
Response		<pre>{ "txnRefNo": "1234566TXNREF12", "userId": "YAL3237", "emailId": "pritam@yalamanchili.in", "mobileNumber": "9187786755", "responseCode": "00", "responseText": "Transaction Success" }</pre>

4.37 ATM PIN Set

This API is used to reset the ATM pin from the System.

ATM PIN change Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			

txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
expiryDate	String {4}	Optional	Expiry Date of the Card Front panel. In MMYY format
cvv2	String {3}	Optional	CVV2 of the Card Back Panel.
dob	String { 8 }	Optional	Customer's Date of Birth. Format : DDMMYYYY
epinBlock	String {16}	Yes	Encrypted PINBLOCK <u>Note1:</u> - It will always be a 4 digit numeric PIN. - The PINBLOCK will be in ISO FORMAT-0 - T-DES encryption would be applied on the PINBLOCK - We will use a static Zone Pin Key for encryption of the PINBLOCK. <u>Note2:-</u> The Key Management for this Zone Pin Key would have to be carried out for both Test and Production between the two parties (YALAMANCHILI and client) as per Standard Information Security Policies.

ATM PIN Set Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the request.
proxyNumber	String {16}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/atmpinset	
Request	POST	
	ATM PIN SET	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, }</pre>

		<pre> "txnRefNo": "pinsetTushar1d24d5cd", "proxyNumber": "000000012748", "expiryDate": "0629", "dob": "14061998", "epinBlock": "EE606A40795F4346" </pre>
Response	<pre> { "txnRefNo": "1234566TXNREF12", "proxyNumber": "000000012748", "responseCode": "00", "responseText": "Transaction Success" } </pre>	

4.38 New OTP Request

This API is used to new OTP generation.

New OTP Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {12}	Yes	Unique Transaction Reference generated by Service Requester.
proxyNumber	String {16}	Yes	Either Source Card Number or Proxy Number. Card Number will be 16 digits and Proxy Number will be 12 digits.
expiryDate	String {4}	Yes	Expiry Date of the Card Front panel. In MMY format

New OTP Response

If the requested new OTP is sends to SMS. The following table list the fields are returned in the API response.

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {12}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/newotprequest	
Request	POST	
	New OTP Request	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "1234566TXNREF12", "proxyNumber": "00000000012", "expiryDate": "0525" }</pre>
Response	<pre>{ "txnRefNo": "1234566TXNREF12", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.39 OTP Validation

This API is used to OTP validation.

OTP validation Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				

msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {12}	Yes	Unique Transaction Reference generated by Service Requester.
otp	String {6}	Yes	OTP Value

OTP validation Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {12}	Yes	Echoed back from the request.
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/otpvalidation	
Request	POST	
	OTP Validation	<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, , }</pre>

		<pre> "txnRefNo": "1234566TXNREF12", "otp": "123456" </pre>
Response	<pre> { "txnRefNo": "1234566TXNREF12", "responseCode": "00", "responseText": "Transaction Success" } </pre>	

4.41 Set Limit Details

This API can be used to set/modify the existing Limits which are set by the individual Card holders for their Cards.

Set Limit Request

The following table lists and describes each field which need to pass in the Request.

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TracelD which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {32}	Yes	Unique Transaction Reference generated by Service Requestor. Minimum 12 character length and allowed up to 32 character length.
proxyNumber	String {12}	Yes	Proxy Number(mapped to each customer)
spendPOSLife	String{15}	NO	POS transaction spend limit amount for lifetime. This limits set by the customer on card level

spendPOSTYear	String{10}	NO	POS transaction spend limit amount for a year
spendPOSTMonth	String{10}	NO	POS transaction spend limit amount for a Month
spendPOSTWeek	String{10}	NO	POS transaction spend limit amount for a Week
spendPOSTDaily	String{10}	NO	POS transaction spend limit amount for Daily
txnPOSTLife	String{10}	NO	POS transaction spend limit count for life-time.
txnPOSTYear	String {10}	NO	POS transaction spend limit count for year.
txnPOSTMonth	String {10}	NO	POS transaction spend limit count for Month.
txnPOSTWeek	String {10}	NO	POS transaction spend limit count for Week.
txnPOSTDaily	String {10}	NO	POS transaction spend limit count for Daily.
spendATMLife	String {10}	NO	ATM transaction spend limit amount for life-time. This limits set by the customer on card level
spendATMYear	String {10}	NO	ATM transaction spend limit amount for a year
spendATMMonth	String {10}	NO	ATM transaction spend limit amount for a Month
spendATMWeek	String {10}	NO	ATM transaction spend limit amount for a Week
spendATMDaily	String {10}	NO	ATM transaction spend limit amount for Daily
txnATMLife	String {10}	NO	ATM transaction spend limit count for life-time.
txnATMYear	String {10}	NO	ATM transaction spend limit count for year.

txnATMMonth	String {10}	NO	ATM transaction spend limit count for year.
txnATMWeek	String {10}		ATM transaction spend limit count for Week.
txnATMDaily	String {10}		ATM transaction spend limit count for Daily
spendEcomLife	String {10}		ECOM transaction spend limit amount for lifetime. This limits set by the customer on card level
spendEcomYear	String {10}		ECOM transaction spend limit amount for a year
spendEcomMonth	String {10}		ECOM transaction spend limit amount for a Month
spendEcomWeek	String {10}		ECOM transaction spend limit amount for a Week
spendEcomDaily	String {10}		ECOM transaction spend limit amount for Daily
txnEcomLife	String {10}		ECOM transaction spend limit count for lifetime.
txnEcomYear	String {10}		ECOM transaction spend limit count for year.
txnEcomMonth	String {10}		ECOM transaction spend limit count for Month.
txnEcomWeek	String {10}		ECOM transaction spend limit count for Week.
txnEcomDaily	String {10}		ECOM transaction spend limit count for Daily
spendContactless-Life	String {10}		Contactless transaction spend limit amount for life-time. This limits set by the customer on card level
spendContactlessYear	String {10}		Contactless transaction spend limit amount for a year
spendContactless-Month	String {10}		Contactless transaction spend limit amount for a Month

spendContact-lessWeek	String {10}		Contactless transaction spend limit amount for a Week
spendContact-lessDaily	String {10}		Contactless transaction spend limit amount for Daily
txnContactlessLife	String {10}		Contactless transaction spend limit count for lifetime.
txnContactlessYear	String {10}		Contactless transaction spend limit count for year.
txnContactless-Month	String {10}		Contactless transaction spend limit count for Month.
txnContactlessWeek	String {10}		Contactless transaction spend limit count for Week.
txnContactlessDaily	String {10}		Contactless transaction spend limit count for Daily

Set Limit Response

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Response			
txnRefNo	String {32}	Yes	Echoed back from the Request
proxyNumber	String{100}	Yes	Echoed back from the Request
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/setlimit		
	POST		

Request		<pre> { "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "CSTRwe343cggct021", "proxyNumber": "000000012935", "spendPOSLife": "1", "spendPOSYear": "", "spendPOSMonth": "40", "spendPOSWeek": "", "spendPOSDaily": "", "txnPOSLife": "", "txnPOSYear": "", "txnPOSMonth": "", "txnPOSWeek": "", "txnPOSDaily": "", "spendATMLife": "", "spendATMYear": "", "spendATMMonth": "", "spendATMWeek": "", "spendATMDaily": "", "txnATMLife": "", "txnATMYear": "", "txnATMMonth": "", "txnATMWeek": "", "txnATMDaily": "", "spendEcomLife": "", "spendEcomYear": "", "spendEcomMonth": "", "spendEcomWeek": "", "spendEcomDaily": "", "txnEcomLife": "", "txnEcomYear": "", "txnEcomMonth": "", "txnEcomWeek": "", "txnEcomDaily": "", "spendContactlessLife": "", "spendContactlessYear": "", "spendContactlessMonth": "", "spendContactlessWeek": "", "spendContactlessDaily": "", "txnContactlessLife": "", "txnContactlessYear": "", "txnContactlessMonth": "", "txnContactlessWeek": "" } </pre>
---------	--	--

		<code>"txnContactlessDaily": ""</code>
Response	<pre>{ "txnRefNo": "CSTRwe3ghgcfut021", "proxyNumber": "000000012872", "responseCode": "00", "responseText": "Transaction Success" }</pre>	

4.42 Get Limit Details

This API can be used to get the existing Limits which are set by the individual Card holders based on card.

Get Limit Request

The following table lists and describes each field which need to pass in the Request

Parameter	Type	Description	Mandatory	Sample Values
Request Header				
msgHdr				
msgId	String	TraceID which is unique across the transaction across services. Can be used to do reverse payment process. This won't be modified in any scenario for entire transaction	Y	
timestamp	String	Timestamp of the transaction	Y	
channelType	String	App ID of the source from where the transaction is initiated	Y	

ELEMENT	DATA TYPE	REQUIRED	DESCRIPTION
Request			
txnRefNo	String {12}	Yes	Unique Transaction Reference generated by Service-Requestor
proxyNumber	String{16}	Yes	Proxy Number(mapped to each customer)
Response			
txnRefNo	String {32}	YES	Echoed back from the Request
proxyNumber	String{16}	YES	Echoed back from the Request

spendPOSLife	String {10}	NO	POS transaction spend limit amount for lifetime. This limits set by the customer on card level
spendPOSYear	String {10}	NO	POS transaction spend limit amount for a year
spendPOSMonth	String {10}	NO	POS transaction spend limit amount for a Month
spendPOSWeek	String {10}	NO	POS transaction spend limit amount for a Week
spendPOSDaily	String {10}	NO	POS transaction spend limit amount for Daily
txnPOSLife	String {10}	NO	POS transaction spend limit count for lifetime.
txnPOSYear	String {10}	NO	POS transaction spend limit count for year.
txnPOSMonth	String {10}		POS transaction spend limit count for Month.
txnPOSWeek	String {10}		POS transaction spend limit count for Week.
txnPOSDaily	String {10}		POS transaction spend limit count for Daily.
availSpend-POSLife	String {10}		Available POS transaction spend limit amount for lifetime. This limits set by the customer on card level
availSpendPO-SYear	String {10}		Available POS transaction spend limit amount for a year
availSpend-POSMonth	String {10}		Available POS transaction spend limit amount for a Month
availSpend-POSWeek	String {10}		Available POS transaction spend limit amount for a Week
availSpend-POSDaily	String {10}		Available Daily POS transaction spend limit amount
availTxnPOSLife	String {10}		Available POS transaction spend limit count for lifetime. This limits set by the customer on card level

availTxnPO- SYear	String {10}		Available POS transaction spend limit count for a year
avail- TxnPOSMonth	String {10}		Available POS transaction spend limit count for a Month
avail- TxnPOSWeek	String {10}		Available POS transaction spend limit count for a Week
avail- TxnPOSDaily	String {10}		Available Daily POS transaction spend limit count
prdSpend- POSLife	String {10}		Product level POS transaction spend limit amount for Life
prdSpendPO- SYear	String {10}		Product level POS transaction spend limit amount for Year
prdSpend- POSMonth	String {10}		Product level POS transaction spend limit amount for Month
prdSpend- POSWeek	String {10}		Product level POS transaction spend limit amount for Week
prdSpend- POSDaily	String {10}		Product level POS transaction spend limit amount for Daily
prdTxnPOSLife	String {10}		Product level POS transaction spend limit count for Life
prdTxnPOSTh	String {10}		Product level POS transaction spend limit count for Year
prdTxnPOSWeek	String {10}		Product level POS transaction spend limit count for Month
prdTxnPOSDaily	String {10}		Product level POS transaction spend limit count for Week
spendATMLife	String {10}		ATM transaction spend limit amount for lifetime. This limits set by the customer on card level
spendATMYear	String {10}		ATM transaction spend limit amount for a year
spendATMMonth	String {10}		ATM transaction spend limit amount for a Month
spendATMWeek	String {10}		ATM transaction spend limit amount for a Week
spendATMDaily	String {10}		ATM transaction spend limit amount for Daily
txnATMLife	String {10}		ATM transaction spend limit count for lifetime.
txnATMYear	String {10}		ATM transaction spend limit count for year.
txnATMMonth	String {10}	NA	ATM transaction spend limit count for Month.
txnATMWeek	String {10}		ATM transaction spend limit count for Week.
txnATMDaily	String {10}		ATM transaction spend limit count for Daily.
avail- SpendATMLife	String {10}		Available ATM transaction spend limit amount for lifetime. This limits set by the customer on card level
avail- SpendATMYear	String {10}		Available ATM transaction spend limit amount for a year

avail-SpendATMMonth	String {10}		Available ATM transaction spend limit amount for a Month
avail-SpendATMWeek	String {10}		Available ATM transaction spend limit amount for a Week
avail-SpendATMDaily	String {10}		Available Daily ATM transaction spend limit amount
availTxnATMLife	String {10}		Available ATM transaction spend limit count for lifetime. This limits set by the customer on card level
availTxnATMYear	String {10}		Available ATM transaction spend limit count for a year
avail-TxnATMMonth	String {10}		Available ATM transaction spend limit count for a Month
avail-TxnATMWeek	String {10}		Available ATM transaction spend limit count for a Week
avail-TxnATMDaily	String {10}		Available Daily ATM transaction spend limit count
prd-SpendATMLife	String {10}		Product level ATM transaction spend limit amount for Life
prd-SpendATMYear	String {10}		Product level ATM transaction spend limit amount for Year
prd-SpendATMMonth	String {10}		Product level ATM transaction spend limit amount for Month
prd-SpendATMWeek	String {10}		Product level ATM transaction spend limit amount for Week
prd-SpendATMDaily	String {10}		Product level ATM transaction spend limit amount for Daily
prdTxnATMLife	String {10}		Product level ATM transaction spend limit count for Life
prdTxnATMYear	String {10}		Product level ATM transaction spend limit count for Year
prdTxnATMMonth	String {10}		Product level ATM transaction spend limit count for Month
prdTxnATMWeek	String {10}		Product level ATM transaction spend limit count for Week
prdTxnATMDaily	String {10}		Product level ATM transaction spend limit count for Daily
spendEcomLife	String {10}		ECOM transaction spend limit amount for lifetime. This limits set by the customer on card level
spendEcomYear	String {10}		ECOM transaction spend limit amount for a year
spendEcom-Month	String {10}		ECOM transaction spend limit amount for a Month
spendEcomWeek	String {10}		ECOM transaction spend limit amount for a Week
spendEcomDaily	String {10}		ECOM transaction spend limit amount for Daily
txnEcomLife	String {10}		ECOM transaction spend limit count for lifetime.
txnEcomYear	String {10}		ECOM transaction spend limit count for year.
txnEcomMonth	String {10}		ECOM transaction spend limit count for Month.

txnEcomWeek	String {10}		ECOM transaction spend limit count for Week.
txnEcomDaily	String {10}		ECOM transaction spend limit count for Daily.
availSpendEcom-Life	String {10}		Available ECOM transaction spend limit amount for lifetime. This limits set by the customer on card level
availSpendEcom-Year	String {10}		Available ECOM transaction spend limit amount for a year
availSpendEcom-Month	String {10}		Available ECOM transaction spend limit amount for a Month
availSpendEcom-Week	String {10}		Available ECOM transaction spend limit amount for a Week
availSpendEcomDaily	String {10}		Available Daily ECOM transaction spend limit amount
availTxnEcomLife	String {10}		Available ECOM transaction spend limit count for lifetime. This limits set by the customer on card level
availTxnEcomYear	String {10}		Available ECOM transaction spend limit count for a year
availTxnEcom-Month	String {10}		Available ECOM transaction spend limit count for a Month
availTxnEcom-Week	String {10}		Available ECOM transaction spend limit count for a Week
avail-TxnEcomDaily	String {10}		Available Daily ECOM transaction spend limit count
prdSpendEcom-Life	String {10}		Product level ECOM transaction spend limit amount for Life
prdSpendEcom-Year	String {10}		Product level ECOM transaction spend limit amount for Year
prdSpendEcom-Month	String {10}		Product level ECOM transaction spend limit amount for Month
prdSpendEcom-Week	String {10}		Product level ECOM transaction spend limit amount for Week
prdSpendEcomDaily	String {10}		Product level ECOM transaction spend limit amount for Daily
prdTxnEcomLife	String {10}		Product level ECOM transaction spend limit count for Life
prdTxnEcomYear	String {10}		Product level ECOM transaction spend limit count for Year
prdTxnEcom-Month	String {10}		Product level ECOM transaction spend limit count for Month
prdTxnEcom-Week	String {10}		Product level ECOM transaction spend limit count for Week
prdTxnEcomDaily	String {10}		Product level ECOM transaction spend limit count for Daily
spendContactlessLife	String {10}		Contactless transaction spend limit amount for lifetime. This limits set by the customer on card level
spendContactlessYear	String {10}		Contactless transaction spend limit amount for a year
spendContactlessMonth	String {10}		Contactless transaction spend limit amount for a Month
SpendContactlessWeek	String {10}		Contactless transaction spend limit amount for a Week

spendContactlessDaily	String {10}		Contactless transaction spend limit amount for Daily
txnContactlessLife	String {10}		Contactless transaction spend limit count for lifetime.
txnContactlessYear	String {10}		Contactless transaction spend limit count for year.
txnContactlessMonth	String {10}		Contactless transaction spend limit count for Month.
txnContactlessWeek	String {10}		Contactless transaction spend limit count for Week.
txnContactlessDaily	String {10}		Contactless transaction spend limit count for Daily.
availSpendContactlessLife	String {10}		Available Contactless transaction spend limit amount for lifetime. This limits set by the customer on card level
availSpendContactlessYear	String {10}		Available Contactless transaction spend limit amount for a year
availSpendContactlessMonth	String {10}		Available Contactless transaction spend limit amount for a Month
availSpendContactlessWeek	String {10}		Available Contactless transaction spend limit amount for a Week
availSpendContactlessDaily	String {10}		Available Daily Contactless transaction spend limit amount
availTxnContactlessLife	String {10}		Available Contactless transaction spend limit count for lifetime. This limits set by the customer on card level
availTxnContactlessYear	String {10}		Available Contactless transaction spend limit count for a year
availTxnContactlessMonth	String {10}		Available Contactless transaction spend limit count for a Month
availTxnContactlessWeek	String {10}		Available Contactless transaction spend limit count for a Week
availTxnContactlessDaily	String {10}		Available Daily Contactless transaction spend limit count
prdSpendContactlessLife	String {10}		Product level Contactless transaction spend limit amount for Life
prdSpendContactlessYear	String {10}		Product level Contactless transaction spend limit amount for Year
prdSpendContactlessMonth	String {10}		Product level Contactless transaction spend limit amount for Month
prdSpendContactlessWeek	String {10}		Product level Contactless transaction spend limit amount for Week
prdSpendContactlessDaily	String {10}		Product level Contactless transaction spend limit amount for Daily
prdTxnContactlessLife	String {10}		Product level Contactless transaction spend limit count for Life
prdTxnContactlessYear	String {10}		Product level Contactless transaction spend limit count for Year
prdTxnContactlessMonth	String {10}		Product level Contactless transaction spend limit count for Month
prdTxnContactlessWeek	String {10}		Product level Contactless transaction spend limit count for Week

prdTxnContactlessDaily	String {10}		Product level Contactless transaction spend limit count for Daily
responseCode	String {2}	Yes	Success code should be 00
responseText	String {500}	Yes	Description Transaction Success

Sample JSON Format:

API	https://uat2.yalamanchili.in/naradaapiservices/api/v1/getlimit	
Request	POST	
		<pre>{ "msgHdr": { "msgId": "WIZ202302171684895539768", "timestamp": "2023-04-04T04:54:08.956Z", "channelType": "web" }, "txnRefNo": "TstGetlirtpi0002a", "proxyNumber": "000000012872" }</pre>
Response	<pre>{ "txnRefNo": "TstGetlirtpi0002a", "proxyNumber": "000000012872", "spendPOSLife": "60", "spendPOSYear": null, "spendPOSMonth": "40", "spendPOSWeek": null, "spendPOSDaily": null, "txnPOSLife": "60", "txnPOSYear": null, "txnPOSMonth": null, "txnPOSWeek": null, "txnPOSDaily": null, "availSpendPOSLife": null, "availSpendPOSYear": "40", "availSpendPOSMonth": null,</pre>	

	<pre> "availSpendPOSWeek": null, "availSpendPOSDaily": null, "availTxnPOSLife": null, "availTxnPOSYear": null, "availTxnPOSMonth": null, "availTxnPOSWeek": null, "availTxnPOSDaily": null, "prdSpendPOSLife": null, "prdSpendPOSYear": null, "prdSpendPOSMonth": null, "prdSpendPOSWeek": null, "prdSpendPOSDaily": null, "prdTxnPOSLife": null, "prdTxnPOSYear": null, "prdTxnPOSMonth": null, "prdTxnPOSWeek": null, "prdTxnPOSDaily": null, "spendATMLife": null, "spendATMYear": null, "spendATMMonth": null, "spendATMWeek": null, "spendATMDaily": "99999999", "txnATMLife": null, "responseCode": "00", "responseText": "Transaction Success" } </pre>
--	--

4. IMPORTANT NOTIFICATIONS

1. All API request element TxnRefNo - Unique Transaction Reference generated by Service Requester (12 character length) / external vendor (MASTER/VISA) 32 character lengths.
2. Request should be maintaining the sequence order as per API specification request element column.
3. Service Requester will send API request should be HTTP - POST method only (YMC support only HTTP - POST).
4. Encryption/Decryption is mandatory for all API transaction. After implementation of encryption, we can start the UAT.

5. SECURITY IMPLEMENTATION

5.1 Certificates Management

1. Service Requestor should generate 2 certificates.
 - a. Signing Certificate
 - b. Encryption Certificate
2. The Certificates must be a X509 digital cert in .pem format
3. Yalamanchili will designate a certificate custodian for receiving the certificates from the client. The Service Requestor should send the certificates only to the designated certificate custodian at Yalamanchili.
4. The Service certificate expiry period must not exceed 2 years.
5. Yalamanchili will also generate 2 certificates
 - a. Signing Certificate
 - b. Encryption Certificate
6. The certificates will be shared in .pem format
7. Client needs to designate a certificate custodian and Yalamanchili will send its certificates only to the certificate custodian at client end.

5.2 Keys & Certificates Usage

Following table depicts the usage of various keys and certificates

S. No	Owner	Stored At/Generated By	Key/Certificate	Usage
1	Yalamanchili	Client	Encryption Certificate	Encrypt the API request (payload) being sent to Yalamanchili
2	Client	Client	Private Key(Signing)	Sign the encrypted payload to be sent to Yalamanchili.
3	Yalamanchili	Client	Signing Certificate	Verify the signed response received from Yalamanchili
4	Client	Client	Private Key(Encryption)	Decrypt the encrypted API Response received from Yalamanchili
5	Client	Yalamanchili	Signing Certificate	Verify the signed payload received from Client
6	Yalamanchili	Yalamanchili	Private Key(Encryption)	Decrypt the encrypted API Request received from Client
7	Client	Yalamanchili	Encryption Certificate	Encrypt the API response to be sent to Client
8	Yalamanchili	Yalamanchili	Private Key (Signing)	Sign the encrypted response to be sent to the Client

5.3 HTTPS Headers

Name	Description
Accept	application/json; charset=UTF-8
Accept-Language	en-US
Content-Language	en-US
Content-Type	application/json
API_USERID	Unique User ID assigned to the ServiceRequestor
API_PASSWORD	Password set to the API User ID
CLIENTID	ID Specific to the Client initiating the transaction

5.4 JWE Header

Name	Description	Value
alg	(Required) Algorithm to randomly encrypt CEK	RSA-OAEP-256
typ	(Required) Media type of the JWE. JavaScript Object Signing and Encryption (JOSE) indicates that JWE is using JWE Compact Serialization scheme.	JOSE
enc	(Required) Type of encryption used by the CEK to encrypt sensitive payload elements.	A256GCM
iat	(Required) Time when JWE was issued. Expressed in UNIX epoch time (seconds since 1 January, 1970) and issued at timestamp in UTC when the transaction was created and signed.	Sample : 1429837145

5.5 JWS Header

Name	Description	Value
alg	(Required) A description of the algorithm that is used to sign the JWS payload.	PS256
typ	(Required) Media type of the JWE. JavaScript Object Signing and Encryption (JOSE) indicates that JWE is using JWE Compact Serialization scheme.	JOSE
enc	(Required) Type of encryption used by the CEK to encrypt sensitive payload elements.	A256GCM

cty	(Required) The content type of the JWS payload.	JWE
-----	---	-----

5.6 Other Security Considerations

1. Service Requestor will send API request should be HTTPS - JSON API request.
2. Payload Encryption is mandatory for JSON API request.
3. Public IP validation is mandatory if the API is accessed via internet.
4. Yalamanchili advises the client to access APIs via IPSec VPNs or MPLS for enhanced security.
5. The payload fields in the APIs contain sensitive information and hence the payload must be encrypted and signed using JWE (JSON Web Encryption) and JWS (JSON Web Signature). A compact serialization scheme is followed for both JWE and JWS with Base64URLencoded elements separated by a "." (period).

5.7 Sample Code Snippet:

5.7.1 Java Code snippet for generating JWE Header

```
private static JWEHeader generateJWEHeader() {
    Map<String, Object> jwsHeaders = new HashMap<>();
    long iat = System.currentTimeMillis() / 1000;
    jwsHeaders.put("iat", iat);
    return new JWEHeader.Builder(JWEAlgorithm.RSA_OAEP_256, EncryptionMethod.A256GCM)
        .type(JOSEObjectType.JOSE).contentType(JOSEObjectType.JOSE.getType()).cus-
        tomParams(jwsHeaders).build();
}
```

5.7.2 Java Code snippet for Payload Encryption:

```
public static String encryptJwe(RSAPublicKey publicKey, String payload) throws Exception
{
    JWEHeader jweHeader = generateJWEHeader();
    log.info("[SecurityUtils][encryptJwe] Payload for JWE Construction {}" + payload);
    JWEObj jweObj = new JWEObj(jweHeader, new Payload(payload));
    try {
        jweObj.encrypt(new RSAEncrypter(publicKey));
        return jweObj.serialize();
    } catch (JOSEException je) {
        log.error("[SecurityUtils][encryptJwe]JOSEException Exception while JWE Con-
        struction" + je);
        throw new Exception(je.getMessage(), je);
    } catch (Exception e) {
        log.error("[SecurityUtils][encryptJwe] Generic Exception while JWE Construction"
        + e);
        throw new Exception(e.getMessage(), e);
    }
}
```

5.7.3 Java Code snippet for generating JWS Header:

```
private static JWSHeader generateJWSHeader() {
    Map<String, Object> jwsHeaders = new HashMap<>();
    jwsHeaders.put("typ", "JOSE");
    jwsHeaders.put("cty", "JWE");
    // Unique value
    JWSAlgorithm algorithm = JWSAlgorithm.PS256;
    long iat = System.currentTimeMillis() / 1000;
    jwsHeaders.put("iat", iat);
    return new JWSHeader.Builder(algorithm).type(JOSEObjectType.JOSE).contentType("JWE").customParams(jwsHeaders)
        .build();
}
```

5.7.4 Java Code snippet for Signing the Encrypted payload:

```
public static String createJws(String jwe, PrivateKey privateKey) throws Exception {
    log.info("[SecurityUtils][createJws] Ready for JWS Construction");
    try {
        JWSHeader jwsHeader = generateJWSHeader();
        JWSSigner signer = new RSASSASigner(privateKey);
        JWSObject jwsObject = new JWSObject(jwsHeader, new Payload(jwe));
        jwsObject.sign(signer);
        return jwsObject.serialize();
    } catch (JOSEException e) {
        log.error("[SecurityUtils][createJws] Exception while JWS Construction" + e);
        throw new Exception(e.getMessage(), e);
    }
}
```

5.7.5 Java Code snippet for Verifying the Signed payload:

```
public static String verifyAndExtractJweFromJWS(String jws, RSAPublicKey publicKey) {
    try {
        JWSObject jwsObject = JWSObject.parse(jws);
        if (!jwsObject.verify(new RSASSAVerifier(publicKey))) {
            log.error(
                "[SecurityUtils][verifyAndExtractJweFromJWS] Encountered Exception while verifying signature");
        }
        return jwsObject.getPayload().toString();
    } catch (ParseException e) {
        log.error("[SecurityUtils][verifyAndExtractJweFromJWS] Invalid JWS Message" + e);
        return null;
    } catch (JOSEException e) {
        log.error(
```



```

        "[SecurityUtils][verifyAndExtractJweFromJWS] Encounterd JOSEException
while verifying signature"
        + e);
    return null;
}
}

```

5.7.6 Java Code snippet for Decrypting the encrypted payload:

```

public static String decryptJwe(String jweString, RSAPrivateKey rsaPrivateKey) throws
Exception {
    try {
        log.info("[SecurityUtils][decryptJwe]Extracted jwe ***** {}",jweString);
        JWEObjcet jweObject = JWEObjcet.parse(jweString);
        JWEObjcet.Header header = jweObject.getHeader();
        JWEObjcet.Algorithm jweAlgorithm = header.getAlgorithm();
        if (JWEObjcet.Algorithm.RSA_OAEP_256.equals(jweAlgorithm)) {
            jweObject.decrypt(new RSADecrypter(rsaPrivateKey));
            log.info("[SecurityUtils][decryptJwe]Extracted jwe" + jweObject.getPay-
load().toString());
            return jweObject.getPayload().toString();
        } else {
            throw new Exception("Unsupported JWE Algorithm: " + jweAlgorithm);
        }
    } catch (JOSEException e) {
        throw new Exception(e.getMessage(), e);
    } catch (ParseException e) {
        throw new Exception("Invalid JWE String: " + jweString);
    }
}

```

5.8 HTTPS Headers

Name	Description
Accept	application/json; charset=UTF-8
Accept-Language	en-US
Content-Language	en-US
Content-Type	application/json
API_USERID	Unique User ID assigned to the ServiceRequestor
API_PASSWORD	Password set to the API User ID
CLIENTID	ID Specific to the Client initiating the transaction
APIKEY	API Key specific to the API. API Keys are given at the end of the document

7 APPENDIX

7.1 Transaction Summary - APIkey

Sr .No	API Name	API Key
1	Purchase a Card/Register the customer	APNCRD
2	Update Customer Details	APUPCR
3	Get Card Details	APCHDT
4	Block /UnBlock the Card	ACDSTS
5	Card Activation	APCDAC
6	Card Replacement	APCDRP
7	Account Addition	APACAD
8	Load Card / Funding an Account	APLCRD
9	Query Balance	APACBL
10	Amount Refund	APCRND
11	Account closure	APACCL
12	Get X Transactions	APXTXN
13	Debit/Credit the Account	APCRDR
14	Fund Transfer	APFDTR
15	Exchange Rate	APFREX
16	Card Order	APCROR
17	Card Receipt	APSTRC
18	Update Stock Details	APSKUP
19	Get Stock Details	APGTSD
20	Status Request	APSTRQ
21	Change Password	ACHPSS
22	Profile Creation	APRFCR
23	Access Rights	APACRT
24	PIN Retrieval	APIPIR
25	ATM PIN Verification	APIVER
26	ATM PIN Change	APICHG
27	Assign Override settings	AOVRST
28	Alert settings - set/unset	APALTS
29	Get card number	APIGCN
30	Get CSC Enquiry	ACSENQ
31	Card Order Status	APCOST
32	IVR PIN Set	APIIVR
33	IVR PIN Change	APIIVC
34	IVR PIN Validation	APIPNV

35	Reset Web Password	APFORP
36	Retrieve Web Profile	APUSPF
37	ATM PIN Set	APINST
38	New OTP Request	AFPOTP
39	OTP Validation	AVPOTP

7.2 Card Status

Card Status	Description
I	Active
CN	Card Returned
M	Card Issued
C	Closed
L	Locked
B	Blocked
HL	Hot List Lock
HS	Hot List Stolen
HD	Hot List Damaged
D	Delivered
CL	Cancelled
Q/K	Pin Regeneration requested
E	Expired
FL	Fraud lock

7.3 List of Error Codes

Response Code	Response Text
00	Transaction Success
03	Unable to process the request
09	Transaction amount is greater than card account balance
10	Invalid Card No
11	Error While Extracting Message Format
17	No records found
20	Unable to process the request
45	Card is in Closed status/TXN AMOUNT should not be in negative
47	Card is Not Active
103	Invalid CVV/expire Date/DOB
104	Invalid EPinBlock
147	Card Balance is Negative
177	Unable to process the request
213	Not enough Records for Refund Request
214	Not enough Records for Top UP Request

217	Invalid Customer Id
412	This operations is not allowed on Suspended card
1777	Unable to process the request
TXNNRV	Transaction not received
ACCCLS	All Accounts Closed For the Card
ACCEXT	Account Already Existed With the Currency.
ACTCRD	Active Cards Cannot Be Replaced
AGNRST	This is not valid customer for this agency
ALRCLD	Card is Already Closed or Cancelled
AMTEXE	Transfer Amounts Exceeded more than Block Amount.
BALNT0	Balance must be Equal to Zero
CACBLK	Card account is in Blocked status
CACINA	Card account is not in active status
CACLCK	Card account is in Locked status
CAPCHA	Checking Limit for Card
CARDBL	Card is Blocked
CARDLC	Card is in Locked State
CARDLC	Card is Closed
CAREXD	Card is Expired
CBELIM	Card Balance exceed the Limit
CBNTCG	Card Balance Limit Configuration Is Not Done
CCDNOT	Campaign Code Does Not Exist
CIDEXT	Customer Already Exist
CIDEXT	Customer Id Already Exists
CLACCT	This Operation cannot be performed
CRDBLP	Permanent Blocked, Card Status Cannot Be Changed
CRDBLO	Card is Blocked
CRDCLD	Card is Closed
CRDEXP	Card Expired
CRDINA	Invalid Card Number/Card is Inactive
CRDLKD	Card is Locked
CRDLOK	Card is in Blocked status
CRDNCP	Card is not belonging to the Corporate
CRPDWG	Current Password is Wrong
DENY	Error While Extracting Message Format
DMLERR	Error in DML Operations
ENTBLK	Entity is blocked
ENTCDE	Error In Entity Credit Days Check
EXEAMT	Refund Amount is Greater than Balance
FINERR	Error in financial Block

INACRD	Inactive Card
INCRCD	Card No Does not belong to this Corporate Id
INNCRD	Card is In Active
INTERR	Unable to process the request
INVACC	Access Denied - Rights not Assigned
INVADR	Invalid Address Format
INVCID	Invalid Customer ID
INVCRD	Invalid Card Number/Proxy Number
INVCST	Invalid Customer
INVOPR	This operations is not allowed on Cancelled cards
INVPLA	Invalid Card Design
INVREF	Invalid Reference Number for the Card and Amount Blocked.
INVTRN	Invalid Transaction Code
INVTXN	Transaction code is not configured
INVUSR	Invalid User
IVRNEQ	Both IVRPIN are not equal
LMAMDL	Per day limit exceeded.
LMAMTE	Per transaction limit exceeded.
LMANEX	Annual limit Exceeded
LMDLEX	Daily limit Exceeded
LMHFEX	Half yearly limit Exceeded
LMLTEX	Lifetime limit Exceeded
LMMTEX	Monthly limit Exceeded
LMQUEX	Quarterly limit Exceeded
LMTNOT	None of the Limit Codes are configured for that Product.
LMWKEX	Weekly limit Exceeded
LSSBAL	Available Card Balance is Less than the Amount
MATCRD	Card Status is Same. So, Cannot Be Changed
NEGBAL	Card is in Negative Balance
NOCHRY	No Records found for the Inputs Card No and Currency
NOCLET	No Client
NOCUST	Customer is not Registered.
NORCRA	No records available for the requested card number
NORCRB	No Records Found
NORCRC	No Records Found
NOTACT	Card is In Active
NOTAUT	Not Authorized
NOTINV	Card is not part of inventory
NOTRVP	New Wallet for the Currency Not available - Cannot Assign Product
ORDEXT	Replacement Card Order already exists on this card

PIDNXT	No Products Exists
PSDCNT	Password cannot be changed within seven days
PSTHIS	Password should not be in last 13 passwords.
REFDAT	Data Exists within the 10 Days in MAS_CHRGTBH_HISTORY
RPLFLD	Both The cards Must be Blocked
SPLERR	Error in splitting Input Data
SUPLER	This Operation is Not Allowed In Presence of Supplementary Card one
SYSERR	System Error
TASRMA	Transaction Amount should be more than or equal to Min. Amount
TIDEXT	Transaction Reference Already Existed
TXNALT	Transaction Reference Number is already exists
TXNBLK	Channel is Restricted
USMPSD	New Password should not be the part of user id
INVAPI	Invalid apiKey
INVALIDPASSWORD	Invalid login credential
INVDSG	Invalid Digital Signature
INVBRN	Invalid Branch User
INVUSR	Invalid login credential
USRBLK	User is blocked
USRSUS	User is suspended
USRCLO	User is closed
EXPPWD	Password is expired
NOCVV2	No CVV found for this card
XTRACT	Invalid Branch User
NOPRDC	No Product Count
NOZERO	Card Balance is greater than Zero
NGTBAL	Card Balance is Negative
INVEXR	Invalid Exchange Rate
INVPRD	Invalid Wallet
NOEXRT	Exchange Rate is not Defined
INMAAD	Invalid mailing address
INRSAD	Invalid Residence address
ERRTOP	Error During TopUp
INPDID	Invalid product mapping
CRDACT	Card is Already Activated
REQENC	Required session key and encryption request
REQTOK	Required token
INVDAT	Invalid input for From Date/To Date
USREXT	User ID Is Already Existed

INBRID	Invalid Branch ID
CRDCLO	Card is Closed
ACCCLD	Account is Closed
IACTNO	Invalid Activation Number
NTBLCD	Only Blocked Card can be Replaced
NTGAMT	Amount should not be in Negative
CRDHTL	Card is Hot Listed
NOTSAM	Source and Destination Card Number should not be same
SRCACC	Source Card Account should be Active
CBLZRO	Card Balance should not be ZERO
ZETRAM	Transfer Amount should not be Negative or Zero
DESACC	Destination Card Account should be Active
TXNINA	Channel has been restricted
INCDUS	Invalid Card User
INVCTR	User should be Customer
DCCNER	Invalid identification type request
AGELMT	Customer Age should be greater than 18
INVCCY	Bill Ccy should be equal to Product Ccy
NOTFRT	Already user profile created
INACFL	Activation Flag should not be empty for this request
INVDAT	Invalid Date
INPDID	Invalid Product Mapping
VITPRD	Virtual Product should not be allow here
INVQTY	Invalid Card Quantity
INVFNO	Invalid FromPackNo
INVTNO	Invalid ToPackNo
INVETY	Invalid Entries
INVEXR	Invalid Exchange Rate
BUYNOT	Buy Currency Code Not Exists
SELNOT	Sell Currency Code Not Exists
INVCMP	Invalid Campaign Code
INCPDT	Campaign Code Effective Date is Greater than Current_Date
INVFRQ	Invalid Frequency
IVALDA	Alert Data is Must For LOW BALANCE ALERT
ACTEXT	Account Already Exist for the Card
DATERR	Invalid Data
CRDTMB	Card is Temporarily Blocked
INVFCY	Invalid Source account currency
INVFPD	Invalid Source card account
INVTPD	Invalid Destination card account

INVTCTY	Invalid Destination account currency
INVEXP	Invalid exchange rate for card account
DATER1	From_date Should not be Greater than To_date
DATER2	From_date Should not be Greater than Current_date
DATER3	From_date Should not be 6 Months older than Current_date
DATER4	To_date Should not be Greater than Current_date
DATER5	Date Difference between from_date and to_date should not be greater than 90
CRATMB	Card is Already Temporarily Blocked
CRABLP	Card is Already Permanently Blocked

7.4 List of Transaction Codes

These are generalized transaction types for common API specification. It is changed through client based.

Transaction Code	Transaction Name+
000000	Purchase - Non - WEB [Domestic Same Currency]
000001	Purchase Fee- Non - WEB
000002	Purchase- Non - WEB [Domestic Cross Currency]
000003	Purchase- Non - WEB [International Same Currency]
000004	Purchase- Non - WEB [International Cross Currency]
000005	Purchase- Non - WEB[Domestic Cross Currency based on
000006	Purchase- Non - WEB[International Cross currency based on Billing ccy
000020	Decline Purchase- Non - WEB
000021	Decline Purchase Fee- Non - WEB
010000	ATM Cash Withdrawal- Non - WEB [Domestic Same Currency]
010002	ATM Cash Withdrawal- Non - WEB[Domestic Cross Currency]
010003	ATM Cash Withdrawal- Non - WEB[International Same Currency]
010004	ATM Cash Withdrawal- Non - WEB[International Cross Currency]
010005	ATM Cash Withdrawal- Non - WEB[Domestic Cross Currency based
010006	ATM Cash Withdrawal- Non - WEB[International Cross currency based
010010	ATM Cash Withdrawal- Non - WEB [Not In Use]
010020	Decline CWD- Non - WEB
010021	Decline CWD Fee- Non - WEB
011101	Declined ATM Transaction- Non - WEB [Not Used in PPH]
011102	Declined ATM Transaction- Non - WEB[Not Used in PPH]
013000	Cash Advance- Non - WEB
020000	Adjustment Debit- Non - WEB
020001	Adjustment Debit- Non - WEB
070000	ATM Cash Withdrawal- Non - WEB [SMS Domestic Same Currency]
070002	ATM Cash Withdrawal- Non - WEB[SMS Domestic Cross Currency]

070003	ATM Cash Withdrawal- Non - WEB[SMS International Same Currency]
070004	ATM Cash Withdrawal- Non - WEB[SMS International Cross Currency]
070005	ATM Cash Withdrawal- Non - WEB[SMS Domestic Cross Currency based on Billing ccv authorization]
070006	ATM Cash Withdrawal- Non - WEB[SMS International Cross currency based on Billing ccv authorization]
070011	Branch Fund Transfer - WEB
080000	Purchase- Non - WEB[SMS Domestic Same Currency]
080002	Purchase- Non - WEB[SMS Domestic Cross Currency]
080003	Purchase- Non - WEB[SMS International Same Currency]
080004	Purchase- Non - WEB[SMS International Cross Currency]
080005	Purchase- Non - WEB[SMS Domestic Cross Currency based on Billing ccv authorization]
080006	Purchase- Non - WEB[SMS International Cross currency based on Billing ccv authorization]
090000	Balance Inquiry- Non - WEB [SMS Balance Inquiry]
100000	Pin Verification- Non - WEB
100001	Customer Registration- WEB
100003	Customer Registration FeeWEB
100004	Subscription Fee
100005	Customer Registration Fee
100006	ATM Cash Withdrawal Fee-- Non - WEB
100007	ATM Declined Fee-- Non - WEB
100008	ATM Declined Fee- Non - WEB
100009	Agency Registration- WEB
100010	Council Registration - WEB
100011	Lost Card - WEB
100012	Lost Card Fee - WEB
100013	Card Suspend/Unsuspend - WEB
100014	Card Suspend/Unsuspend Fee- WEB
100015	Employee Registration- WEB
100016	Customer Registration-WEB
100017	IPIN Request-WEB
100018	IPIN Request Fee-WEB
100020	Personalised Cus Registration-WEB
100021	Product Settings-WEB
100022	Card Statement-WEB
100023	Card Statement Fee-WEB
100024	Delivery Fee-WEB
100025	Branch Card Issuance-WEB
100026	Branch Card Issuance Fee-WEB
100027	Card Order - Payment-WEB
100028	Card Replacement Request-WEB

100029	Card Replacement Fee-WEB
100030	CallCenter Replacement (Due to Damanged Card)-WEB
100031	CallCenter Replacement (Due to Damanged Card) Fee-WEB
100032	CallCenter Card Cancellation-WEB
100033	Customer Details-WEB
100034	Customer Refund Request-WEB
100035	SMS Balance Enquiry-WEB
100036	SMS Balance Enquiry Fee-WEB
100037	Call Center Request PAC-WEB
100038	CallCenter Replacement-Instant-WEB
100039	CallCenter Replacement-Instant-Fee-WEB
100041	Lost Card Blocking-WEB
100042	Customer Lost Card Blocking Fee-WEB
100043	Customer Refund Request Process-WEB
100044	Online Card Registration-WEB
100045	New Card Account-WEB
100046	New Card Account Fee-WEB
100048	New Card Account Subscription Fee-WEB
100049	Branch Refund Maker-WEB
100050	Branch Refund-WEB
100051	Branch Refund Fee-WEB
100052	Refund-WEB
100053	Refund Fee-WEB
100054	Topup-WEB
100055	TopUp Fee-WEB
100056	Customer Locking/Unlocking-WEB
100057	Online Purchase Fee-WEB
100058	Registered Post-WEB
100059	Registered Post Fee-WEB
100060	Online Purchase-WEB
100061	Council Registration-WEB
100062	Card Statement Request-WEB
100064	Card Statement Transaction Fee-WEB
100067	Web Access PIN-WEB
100068	International Transaction Fee-- Non - WEB [Cross Border Conversion Fee]
100069	Customer Dispute-WEB
100070	Customer Dispute Fee-WEB
100071	International Transaction Fee- Non - WEB [Cross Border Fee]
100072	International Transaction Fee- Non - WEB [Conversion Fee]
100073	Conversion Fee- Non - WEB [Not used in PPH]

100074	CallCenter Card Not Received Fee-WEB
100075	CallCenter Transactions-WEB
100076	CallCenter Audit Trail-WEB
100077	CallCenter Lost/Stolen Card-WEB
100078	CallCenter Transactions Fee-WEB
100079	CallCenter Notepad-WEB
100080	CallCenter Email-WEB
100081	CallCenter Damaged Card-WEB
100082	CallCenter Customer Details-WEB
100083	CallCenter Found Card-WEB
100084	CallCenter Found Card Fee-WEB
100085	CallCenter Damaged Card Fee-WEB
100086	Customer Card Replacement Request Fee-WEB
100087	Customer Account Summary-WEB
100089	Transaction History-WEB
100090	Dispute Logging-WEB
100091	Update My Details-WEB
100092	Change Password-WEB
100093	Call Center Card History-WEB
100094	Card Reissue Request-WEB
100095	Entity Payment-WEB
100098	Customer - New Card Account-WEB
100099	Customer - New Card Account Fee-WEB
100100	Product Settings-WEB
100101	WEB Reset PIN-WEB
100102	WEB Reset PIN Fee-WEB
100103	Monthly Fee Transaction-Non - WEB
100104	Monthly Fee- Non - WEB
100105	Deactivation through Merchant- Non - WEB
100106	Deactivation through Merchant- Non - WEB
100116	Branch TopUp-WEB
100117	Branch TopUp-WEB
100118	Branch TopUp Fee-WEB
100119	Fund Transfer Debit Transaction-WEB
100120	Fund Transfer Credit Transaction-WEB
100123	Activation through Merchant Fee Non - WEB
100124	Activation through Merchant Fee Non - WEB
100125	Refund Reversed Non - WEB
100128	Customer Card Replacement Request
100129	Customer Card Replacement Fee

100130	Supplimentary Card
100131	Supplimentary Card Fee
100132	Account Authorization
100134	Branch TopUp Maker
100135	Account Delink Authorization
100201	Call Center Change PIN IMG
100203	Call Center New Card Account IMG
100204	Call Center Fund Transfer IMG
100205	Call Center Auth Order Settings IMG - WEB
100206	Call Center Auth Order Settings View IMG - WEB
100207	Call Center Lost / Stolen Card IMG-WEB
100208	Call Center Card Not Received IMG-WEB
100209	Call Center Transactions IMG-WEB
100210	Call Center Request PAC IMG-WEB
100211	Call Center Card Activation IMG-WEB
100212	Call Center Lost / Stolen / Damaged Card IMG-WEB
100213	Call Center Change PAC IMG-WEB
100239	FeeRuler Filter Adjustment-Credit-WEB
100240	FeeRuler Filter Adjustment Fee-Credit-WEB
100241	FeeRuler Filter Adjustment-Debit-WEB
100242	FeeRuler Filter Adjustment Fee-Debit-WEB
100243	CallCenter Card Replacement-WEB
100244	CallCenter Card Replacement Fee-WEB
100245	CallCenter Customer Balance-WEB
100246	CallCenter Customer Balance Fee-WEB
100247	CallCenter Locking/Unlocking-WEB
100248	CallCenter Locking/Unlocking Fee-WEB
100249	CallCenter Lost/Stolen/Damaged Card-WEB
100250	CallCenter Lost/Stolen/Damaged Card Fee-WEB
100261	Online Card Issuance-WEB
100262	Online Card Issuance Fee-WEB
100290	Purchaser Registration-WEB
100292	Net Card Issuance-WEB
100293	Net Card Issuance Fee-WEB
100294	NET New Card Account-WEB
100295	NET New Card Account Fee-WEB
100296	Branch Card issuance-WEB
100297	Branch Card issuance Fee-WEB
100328	Customer Card Replacement Request1-WEB
100329	Customer Card Replacement Fee1-WEB

100555	Customer Locking/Unlocking Fee-WEB
100901	Call Center Customer Balance Fee-WEB
100903	Agency Match Off-WEB
100911	Block Swap Amount-Non - WEB
100912	Swap Transfer Debit Transaction- Non - WEB
100913	Swap Transfer Debit Transaction Fee - Non - WEB
100914	Swap Transfer Credit Transaction - Non - WEB
100915	Swap Transfer Credit Transaction Fee- Non - WEB
100916	Release Swap Amount- Non - WEB
101011	Chargeback Details- WEB & NON-WEB
101012	Outstanding- WEB & NON - WEB
101025	Technical Chargeback- WEB
101100	Charge Fees-WEB
101150	Fee Collection-Non - WEB
101160	Fee Disbursement - Non - WEB
101170	Fee Collection- Non - WEB
101180	Fee Disbursement- Non - WEB
108042	Chargeback Request-WEB
109001	Fund Transfer Third party-WEB
109002	Fund Transfer Third party Fee-WEB
110001	Peso Fund Transfer with in EastWest Bank
110002	Peso Fund Transfer with in EastWest Bank Fee
110003	Peso Fund Transfer with in EastWest Bank Same Customer
110004	Peso Fund Transfer with in EastWest Bank same customer Fee
110005	Dollar Fund Transfer with in EastWest Bank
110006	Dollar Fund Transfer with in EastWest Bank Fee
110007	Dollar Fund Transfer with in EastWest Bank Same customer
110008	Dollar Fund Transfer with in EastWest Bank Same customer Fee
110009	Peso Fund Transfer Intra Bank
110010	Peso Fund Transfer Intra Bank Fee
110011	Dollar Fund Transfer Intra Bank
110012	Dollar Fund Transfer Intra Bank Fee
110013	International Fund Transfer-Non - WEB
110014	International Fund Transfer Fee- Non - WEB
110015	Bills Payment Debit
110016	Bills Payment Debit Fee
110017	Bills Payment Credit
110018	Bills Payment Credit Fee
110019	Cheque Book Re-Order
110020	Cheque Book Re-Order Fee

110021	Statement of Account Fee for Debit
110022	Statement of Account Fee for Credit
110023	Online Cheque Viewing Fee
110024	Cheque Stop Payment Order Fee
110025	Statement Request Fee-WEB
110026	Lost Card Blocking Limit-WEB
110027	Lost Card Blocking Fee-WEB
110028	Card Locking Fee-WEB
110030	Online Foreign Exchange Fee
110031	Open a Savings Account
111111	Card Balance- Non - WEB
111112	SMS Alert- Non - WEB
111113	SMS Alert Fee- Non - WEB
200000	Refund- Non - WEB
200003	Balance Inquiry- Non - WEB [Not used in PPH]
200005	POS Cash Advance- Non - WEB
200006	Cash Advance- Non - WEB [Domestic Cross Currency based on Billing ccy for authorization]
200007	Cash Advance- Non - WEB [International Cross currency based on Billing ccy for authorization]
200008	Cash Advance Fee- Non - WEB
200009	Cash Advance- Non - WEB[Domestic Cross Currency]
200074	Forex- Non - WEB
200079	Forex- Non - WEB
201000	Merchant Credit Return
210000	IBFT Deposit
211128	Financial Adjustment- Non - WEB
230007	Cash Advance- Non - WEB [SMS Cash Advance]
230008	Cash Advance- Non - WEB [SMS Domestic Cross Currency based on Billing ccy authorization]
230009	Cash Advance- Non - WEB[SMS International Cross currency based on Billing ccy authorization]
230010	Cash Advance- Non - WEB [Domestic Cross Currency]
250000	Language Change-WEB
250001	LangChange Fee-WEB
260000	VMT amount
260001	VMT Fee
270000	Account Verification Service
280000	Cash Payment
290000	Funds Disbursement Credit
300000	POS Balance Inquiry-- Non - WEB
300001	Balance Inquiry Fee- Non - WEB
300006	Sale Fee- Non - WEB
300007	Cash Back- Non - WEB
300008	Cash Back Fee- Non - WEB

300020	Decline POS Balance Inquiry- Non - WEB
300021	Decline POS Balance Inquiry Fee- Non - WEB
302551	Balance Adjustment Debit- Non - WEB
302552	Balance Adjustment Credit- Non - WEB
310000	ATM Balance Inquiry- Non - WEB
310001	ATM Balance Inquiry Fee - Non - WEB
310020	Decline ATM Balance Inquiry- Non - WEB
310021	Decline ATM Balance Inquiry Fee- Non - WEB
320000	Oar
320001	Oar Fee
322239	Card Adjustment-WEB
400000	ATM Fund Transfer- Non - WEB
400001	Transaction Settlement- Non - WEB [Used in Dispute for FA]
400002	Transaction Settlement- Non - WEB [Used in Dispute for FA]
400003	Transaction Settlement- Non - WEB [Used in Dispute for FA]
400004	Transaction Settlement- Non - WEB [Used in Dispute for FA]
400005	Transaction Settlement- Non - WEB [Used in Dispute for FA]
400006	Transaction Settlement- Non - WEB [Used in Dispute for FA]
400007	Transaction Settlement- Non - WEB [Used in Dispute for FA]
400008	Copy Request-WEB [Used in Dispute for FA]
400010	ATM Fund Transfer Credit Transaction- Non - WEB [Not Used in PPH]
400011	ATM Fund Transfer Fee- Non - WEB [Not Used in PPH]
402021	FUND TRANSFER INTERBANK Credit Transaction
440000	FUND TRANSFER INTER
460000	IBFT WITHDRAWAL
460001	IBFT Withdrawal Fee
500001	Purchase Reversal- Non - WEB[Domestic Same Currency]
500002	Purchase Reversal- Non - WEB[Domestic Cross Currency]
500003	Purchase Reversal- Non - WEB[International Same Currency]
500004	Purchase Reversal- Non - WEB[International Cross Currency]
500005	Cash Withdrawal Reversal- Non - WEB[Domestic Same Currency]
500006	Cash Withdrawal Reversal- Non - WEB[Domestic Cross Currency]
500007	Cash Withdrawal Reversal- Non - WEB[International Same Currency]
500008	Cash Withdrawal Reversal- Non - WEB[International Cross Currency]
500009	Cash Disbursement Reversal- Non - WEB
500010	IBFT Withdrawal
500011	Bill Payment- Non - WEB
500012	Purchase Release- Non - WEB
500013	Cash Withdrawal Reversal- Non - WEB
500014	Purchase Reversal- Non - WEB[SMS Domestic Same Currency]
500015	Cash Disbursement Reversal- Non - WEB[SMS Cash Disbursement]
500016	Cash Disbursement Reversal- Non - WEB
500017	Merchant Return Reversal- Non - WEB

500018	Cash Withdrawal Reversal- Non - WEB[Domestic Cross Currency based on Billing ccy authorization]
500019	Cash Withdrawal Reversal- Non - WEB[International Cross currency based on Billing ccy authorization]
500020	Purchase Reversal- Non - WEB[Domestic Cross Currency based on Billing ccy authorization]
500021	Purchase Reversal- Non - WEB[International Cross currency based on Billing ccy authorization]
500022	Cash Disbursement Reversal- Non - WEB[SMS Domestic Cross Currency based on Billing ccy authorization]
500023	Cash Disbursement Reversal- Non - WEB[SMS International Cross currency based on Billing ccy authorization]
500024	Cash Disbursement Reversal- Non - WEB[SMS Domestic Cross Currency]
500025	Cash Disbursement Reversal- Non - WEB[Domestic Cross Currency]
500026	Purchase Release- Non - WEB
500027	Merchant Return Reversal- Non - WEB
500028	Cash Advance Release- Non - WEB[Domestic Cross Currency based
500029	Cash Advance Release- Non - WEB[International Cross
500030	Cash Advance Release- Non - WEB[Domestic Same Currency]
500031	Cash Advance Release- Non - WEB[Domestic Cross Currency]
500032	Cash Withdrawal Reversal- Non - WEB[Domestic Cross Currency]
500033	Purchase Reversal-Non-WEB[Domestic Cross Currency]
500034	Cash Advance Reversal- Non - WEB[Domestic Cross Currency]
500035	Cash Withdrawal Reversal- Non - WEB[Domestic Same Currency]
500036	Purchase Reversal-Non-WEB [Domestic Same Currency]
500037	Cash Advance Reversal- Non - WEB[Domestic Same Currency]
500038	Cash Withdrawal Reversal- Non - WEB [International Same Currency]
500039	Purchase Reversal- Non - WEB[International Same Currency]
500040	Cash Withdrawal Reversal- Non - WEB [International Cross Currency]
500041	Purchase Reversal- Non - WEB[International Cross Currency]
500074	Forex Reversal
500075	Forex Reversal
500076	Forex Reversal
570006	Cash Withdrawal Reversal- Non - WEB[SMS Domestic Cross Currency]
570007	Cash Withdrawal Reversal- Non - WEB[SMS International Same Currency]
570008	Cash Withdrawal Reversal- Non - WEB[SMS International Cross Currency]
580002	Purchase Reversal- Non - WEB[SMS Domestic Cross Currency]
580003	Purchase Reversal- Non - WEB[SMS International Same Currency]
580004	Purchase Reversal- Non - WEB[SMS International Cross Currency]
600000	Transaction Settlement [Used in EOD and Dispute for FA entries]
600001	Chargeback-WEB[Used in EOD and Dispute for FA entries]
600002	Transaction Settlement- Non - WEB[Used in EOD and Dispute for FA entries]
600003	Chargeback Reconciliation-WEB[Used in EOD and Dispute for FA entries]
600004	Chargeback- Non - WEB & WEB[Used in EOD and Dispute for FA entries]

600005	Chargeback- Non - WEB & WEB[Used in EOD and Dispute for FA entries]
600008	Customer Credit Queue-WEB[Used in EOD and Dispute for FA entries]
600009	Transaction Settlement - Non - WEB[Used in EOD and Dispute for FA entries]
600011	Chargeback Re-presentment-WEB[Used in Dispute for FA entries]
600012	Technical Chargeback-WEB[Used in Dispute for FA entries]
600013	Chargeback Representment-WEB[Used in Dispute for FA entries]
700000	Manual Load/UnLoad-WEB
700001	Balance Transfer-WEB
700002	Fee Reversal-WEB
700003	Reversal Chargeback-[Used in Dispute for FA entries]
700004	Close Account
700005	Fraud
700006	Service Enquiry Fee
700007	Dispute- WEB[Used in Dispute for FA entries]
700008	Other-WEB[Used in Dispute for FA entries]
800000	Refund - Non WEB[Used in Dispute for FA entries]
800001	Refund Settlement - Non WEB[Used in Dispute for FA entries]
800002	Release-WEB[Used in Dispute for FA entries]
800003	Reversal Settlement-Non WEB[Used in Dispute for FA entries]
800004	Refund Reversal Settlement-Non WEB[Used in Dispute for FA entries]
800005	Outstanding-WEB[Used in EOD for FA entries]
800006	Refund-WEB[Used in Dispute for FA entries]
800008	Outstanding-WEB[Used in Dispute for FA entries]
800009	Refund Settlement[Used in EOD for FA entries]
800010	Refund[Used in EOD for FA entries]
800011	Reversal Settlement[Used in Dispute for FA entries]
800012	Representment- WEB[Used in Dispute for FA entries]
800013	Chargeback Representment-WEB[Used in Dispute]
800014	Chargeback Representment-WEB[Used in Dispute]
800015	Chargeback Representment-WEB[Used in Dispute]
800016	Chargeback Representment-WEB[Used in Dispute]
800017	Chargeback Representment-WEB[Used in Dispute]
800018	Chargeback Representment-WEB[Used in Dispute]
800020	Chargeback Reconciliation-WEB[Used in Dispute]
800021	Reissue Fee-WEB[Used in Dispute]
800022	Maintenance Fee-WEB[Used in Dispute]
840000	BILL PAYMENT- WEB
900100	IVR Balance Inquiry- Non WEB
900101	IVR Balance Inquiry Fee Non WEB
900102	IVR Last n Transactions Non WEB
900103	IVR Last n Transactions Fee - Non WEB
900104	IVR Enquiry- Non WEB
900105	IVR Enquiry Fee-Non - WEB

900106	IVR Reset PIN- Non - WEB
900107	IVR Reset PIN Fee - Non - WEB
900108	Council Maker-WEB
900110	Reorder Maker-WEB
900111	Fee Maker-WEB
900112	Assign Products-WEB
900113	Card Activation-WEB
900114	Pin Regeneration-WEB
900115	Card Replacement Authorization-WEB
900116	Service User Registration-WEB
900117	Service User Registration Fee-WEB
910000	Check Book Reorder-WEB
940000	Pin Change-Non - WEB
940001	Pin Change Fee Non - WEB
950000	Mini Statement-WEB
950001	MST Fee-WEB
950002	Business Client Top up Debit FileUpload-WEB
950003	Business Client Top up Credit FileUpload-WEB
950004	Business Client/Consumer Top up-WEB
950005	Business Client Top up Debit WEB
950006	Business Client Top up Credit WEB
950007	Business Client Top up Fee FileUpload
950008	Business Client Top up Fee WEB
950009	Consumer Top up Fee
950010	Business Client Refund Debit WEB
950011	Business Client Refund Fee WEB
950012	Business Client Refund Credit WEB
950013	Business Client Registration- WEB
950014	Consumer Registration-WEB
950016	Basic Due Diligence-WEB
950017	Customer FundTransfer Debit Transaction-WEB
950018	Customer FundTransfer Credit Transaction-WEB
950019	Customer FundTransfer Fee-WEB
950020	Customer Card Closure Refund-WEB
950021	Customer Card Closure Refund Fee-WEB
950022	Customer Card Closure Refund Unsettle-WEB
950023	Customer Card Closure Refund Unsettle Fee-WEB
950024	Microsite Customer Topup-WEB
950025	Microsite Customer Topup Fee-WEB
950026	Product Upgrade-WEB
950027	Council Refund Debit FileUpload-WEB
950028	Council Refund Credit FileUpload-WEB
950029	Council Refund Fee FileUpload-WEB
950031	Council/Service User Refund-WEB

950032	Service User Refund Fee-WEB
CRPFUP	Council Registration - File Upload-WEB
CRPTOP	Reload - Manual-WEB
EMPFUP	Employee Registration - File Upload-WEB
EPAYPC	Entity Payment- WEB

7.5 List of Transaction Types

These are generalized transaction types for common API specification. It is changed through client based.

Transaction Type	Meaning
T	Approved [Web Transactions]
T	Pending
F	Pending [Fee Record]
R	Reversed
RF	Fee Reversed
S	Settled
TR	Transaction Reversed
TF	Fee Reversed
BR	Reversed [Base2 Reversal]
FBR	Fee Reversed [Base2 Reversal record Fee]
RL	Released
FRL	Fee Released
CB	Chargeback Raised
DC	Dispute Closed
CR	Copy Request Raised
DP	ChargeBack Pending