

▼ 19660_Mahmud_Omer

Week4_Hw2

1. Classification on Colab using MNIST dataset Process Study the course material of this chapter. Run all the cells described in the notebook Chapter 3 – Classification on Colab and try to understand the code along the way. Adding notebooks to your portfolio

- Machine Learning
 - Supervised Learning
 - Classification on Colab using MNIST dataset

Run the code on Colab

- References
 - Get Start with Colab

First, let's import a few common modules, ensure Matplotlib plots figures inline and prepare a function to save the figures. We also check that Python 3.5 or later is installed (although Python 2.x may work, it is deprecated so we strongly recommend you use Python 3 instead), as well as Scikit-Learn ≥0.20.

```
# Python ≥3.5 is required
import sys
assert sys.version_info >= (3, 5)

# Is this notebook running on Colab or Kaggle?
IS_COLAB = "google.colab" in sys.modules
IS_KAGGLE = "kaggle_secrets" in sys.modules

# Scikit-Learn ≥0.20 is required
import sklearn
assert sklearn.__version__ >= "0.20"

# Common imports
import numpy as np
import os

# to make this notebook's output stable across runs
np.random.seed(42)

# To plot pretty figures
%matplotlib inline
import matplotlib as mpl
import matplotlib.pyplot as plt
mpl.rc('axes', labelsize=14)
mpl.rc('xtick', labelsize=12)
mpl.rc('ytick', labelsize=12)

# Where to save the figures
PROJECT_ROOT_DIR = "."
CHAPTER_ID = "classification"
IMAGES_PATH = os.path.join(PROJECT_ROOT_DIR, "images", CHAPTER_ID)
os.makedirs(IMAGES_PATH, exist_ok=True)

def save_fig(fig_id, tight_layout=True, fig_extension="png", resolution=300):
    path = os.path.join(IMAGES_PATH, fig_id + "." + fig_extension)
    print("Saving figure", fig_id)
    if tight_layout:
        plt.tight_layout()
    plt.savefig(path, format=fig_extension, dpi=resolution)
```

▼ MNIST

Warning: since Scikit-Learn 0.24, `fetch_openml()` returns a Pandas DataFrame by default. To avoid this and keep the same code as in the book, we use `as_frame=False`.

```

from sklearn.datasets import fetch_openml
mnist = fetch_openml('mnist_784', version=1, as_frame=False)
mnist.keys()

dict_keys(['data', 'target', 'frame', 'categories', 'feature_names', 'target_names', 'DESCR', 'details', 'url'])

X, y = mnist["data"], mnist["target"]
X.shape

(70000, 784)

y.shape

(70000,)

28 * 28

784

%matplotlib inline
import matplotlib as mpl
import matplotlib.pyplot as plt

some_digit = X[0]
some_digit_image = some_digit.reshape(28, 28)
plt.imshow(some_digit_image, cmap=mpl.cm.binary)
plt.axis("off")

save_fig("some_digit_plot")
plt.show()

Saving figure some_digit_plot

```



```

y[0]

'5'

y = y.astype(np.uint8)

def plot_digit(data):
    image = data.reshape(28, 28)
    plt.imshow(image, cmap = mpl.cm.binary,
                interpolation="nearest")
    plt.axis("off")

# EXTRA
def plot_digits(instances, images_per_row=10, **options):
    size = 28
    images_per_row = min(len(instances), images_per_row)
    # This is equivalent to n_rows = ceil(len(instances) / images_per_row):
    n_rows = (len(instances) - 1) // images_per_row + 1

    # Append empty images to fill the end of the grid, if needed:
    n_empty = n_rows * images_per_row - len(instances)
    padded_instances = np.concatenate([instances, np.zeros((n_empty, size * size))], axis=0)

    # Reshape the array so it's organized as a grid containing 28x28 images:

```

```

image_grid = padded_instances.reshape((n_rows, images_per_row, size, size))

# Combine axes 0 and 2 (vertical image grid axis, and vertical image axis),
# and axes 1 and 3 (horizontal axes). We first need to move the axes that we
# want to combine next to each other, using transpose(), and only then we
# can reshape:
big_image = image_grid.transpose(0, 2, 1, 3).reshape(n_rows * size,
                                                    images_per_row * size)

# Now that we have a big image, we just need to show it:
plt.imshow(big_image, cmap = mpl.cm.binary, **options)
plt.axis("off")

plt.figure(figsize=(9,9))
example_images = X[:100]
plot_digits(example_images, images_per_row=10)
save_fig("more_digits_plot")
plt.show()

```

Saving figure more_digits_plot



```
y[0]
```

5

```
X_train, X_test, y_train, y_test = X[:60000], X[60000:], y[:60000], y[60000:]
```

▼ Training a Binary Classifier

```
y_train_5 = (y_train == 5)
y_test_5 = (y_test == 5)
```

Note: some hyperparameters will have a different default value in future versions of Scikit-Learn, such as `max_iter` and `tol`. To be future-proof, we explicitly set these hyperparameters to their future default values. For simplicity, this is not shown in the book.

```
from sklearn.linear_model import SGDClassifier
```

```
sgd_clf = SGDClassifier(max_iter=1000, tol=1e-3, random_state=42)
sgd_clf.fit(X_train, y_train_5)

sgd_clf.predict([some_digit])

array([ True])

from sklearn.model_selection import cross_val_score
cross_val_score(sgd_clf, X_train, y_train_5, cv=3, scoring="accuracy")

array([0.95035, 0.96035, 0.9604 ])
```

▼ Performance Measures

▼ Measuring Accuracy Using Cross-Validation

```
from sklearn.model_selection import StratifiedKFold
from sklearn.base import clone

skfolds = StratifiedKFold(n_splits=3, shuffle=True, random_state=42)

for train_index, test_index in skfolds.split(X_train, y_train_5):
    clone_clf = clone(sgd_clf)
    X_train_folds = X_train[train_index]
    y_train_folds = y_train_5[train_index]
    X_test_fold = X_train[test_index]
    y_test_fold = y_train_5[test_index]

    clone_clf.fit(X_train_folds, y_train_folds)
    y_pred = clone_clf.predict(X_test_fold)
    n_correct = sum(y_pred == y_test_fold)
    print(n_correct / len(y_pred))

0.9669
0.91625
0.96785
```

Note: `shuffle=True` was omitted by mistake in previous releases of the book.

```
from sklearn.base import BaseEstimator
class Never5Classifier(BaseEstimator):
    def fit(self, X, y=None):
        pass
    def predict(self, X):
        return np.zeros((len(X), 1), dtype=bool)

never_5_clf = Never5Classifier()
cross_val_score(never_5_clf, X_train, y_train_5, cv=3, scoring="accuracy")

array([0.91125, 0.90855, 0.90915])
```

Warning: this output (and many others in this notebook and other notebooks) may differ slightly from those in the book. Don't worry, that's okay! There are several reasons for this:

- first, Scikit-Learn and other libraries evolve, and algorithms get tweaked a bit, which may change the exact result you get. If you use the latest Scikit-Learn version (and in general, you really should), you probably won't be using the exact same version I used when I wrote the book or this notebook, hence the difference. I try to keep this notebook reasonably up to date, but I can't change the numbers on the pages in your copy of the book.
- second, many training algorithms are stochastic, meaning they rely on randomness. In principle, it's possible to get consistent outputs from a random number generator by setting the seed from which it generates the pseudo-random numbers (which is why you will see `random_state=42` or `np.random.seed(42)` pretty often). However, sometimes this does not suffice due to the other factors listed here.
- third, if the training algorithm runs across multiple threads (as do some algorithms implemented in C) or across multiple processes (e.g., when using the `n_jobs` argument), then the precise order in which operations will run is not always guaranteed, and thus the exact result may vary slightly.

- lastly, other things may prevent perfect reproducibility, such as Python dicts and sets whose order is not guaranteed to be stable across sessions, or the order of files in a directory which is also not guaranteed.

▼ Confusion Matrix

```
from sklearn.model_selection import cross_val_predict

y_train_pred = cross_val_predict(sgd_clf, X_train, y_train_5, cv=3)

from sklearn.metrics import confusion_matrix

confusion_matrix(y_train_5, y_train_pred)

array([[53892,   687],
       [ 1891,  3530]])

y_train_perfect_predictions = y_train_5 # pretend we reached perfection
confusion_matrix(y_train_5, y_train_perfect_predictions)

array([[54579,    0],
       [    0,  5421]])
```

▼ Precision and Recall

```
from sklearn.metrics import precision_score, recall_score

precision_score(y_train_5, y_train_pred)

0.8370879772350012

cm = confusion_matrix(y_train_5, y_train_pred)
cm[1, 1] / (cm[0, 1] + cm[1, 1])

0.8370879772350012

recall_score(y_train_5, y_train_pred)

0.6511713705958311

cm[1, 1] / (cm[1, 0] + cm[1, 1])

0.6511713705958311

from sklearn.metrics import f1_score

f1_score(y_train_5, y_train_pred)

0.7325171197343846

cm[1, 1] / (cm[1, 1] + (cm[1, 0] + cm[0, 1]) / 2)

0.7325171197343847
```

▼ Precision/Recall Trade-off

```
y_scores = sgd_clf.decision_function([some_digit])
y_scores

array([2164.22030239])

threshold = 0
y_some_digit_pred = (y_scores > threshold)
```

```

y_some_digit_pred

array([ True])

threshold = 8000
y_some_digit_pred = (y_scores > threshold)
y_some_digit_pred

array([False])

y_scores = cross_val_predict(sgd_clf, X_train, y_train_5, cv=3,
                             method="decision_function")

from sklearn.metrics import precision_recall_curve


precisions, recalls, thresholds = precision_recall_curve(y_train_5, y_scores)

def plot_precision_recall_vs_threshold(precisions, recalls, thresholds):
    plt.plot(thresholds, precisions[:-1], "b--", label="Precision", linewidth=2)
    plt.plot(thresholds, recalls[:-1], "g-", label="Recall", linewidth=2)
    plt.legend(loc="center right", fontsize=16) # Not shown in the book
    plt.xlabel("Threshold", fontsize=16)       # Not shown
    plt.grid(True)                             # Not shown
    plt.axis([-50000, 50000, 0, 1])           # Not shown

recall_90_precision = recalls[np.argmax(precisions >= 0.90)]
threshold_90_precision = thresholds[np.argmax(precisions >= 0.90)]

plt.figure(figsize=(8, 4)) # Not shown
plot_precision_recall_vs_threshold(precisions, recalls, thresholds) # Not shown
plt.plot([threshold_90_precision, threshold_90_precision], [0., 0.9], "r:") # Not shown
plt.plot([-50000, threshold_90_precision], [0.9, 0.9], "r:") # Not shown
plt.plot([-50000, threshold_90_precision], [recall_90_precision, recall_90_precision], "r:") # Not shown
plt.plot([threshold_90_precision, [0.9], "ro") # Not shown
plt.plot([threshold_90_precision, [recall_90_precision], "ro") # Not shown
save_fig("precision_recall_vs_threshold_plot") # Not shown
plt.show()

```



```

(y_train_pred == (y_scores > 0)).all()


True

def plot_precision_vs_recall(precisions, recalls):
    plt.plot(recalls, precisions, "b-", linewidth=2)
    plt.xlabel("Recall", fontsize=16)
    plt.ylabel("Precision", fontsize=16)
    plt.axis([0, 1, 0, 1])
    plt.grid(True)

plt.figure(figsize=(8, 6))
plot_precision_vs_recall(precisions, recalls)
plt.plot([recall_90_precision, recall_90_precision], [0., 0.9], "r:")
plt.plot([0.0, recall_90_precision], [0.9, 0.9], "r:")
plt.plot([recall_90_precision, [0.9], "ro")

```

```
save_fig("precision_vs_recall_plot")
plt.show()
```



```
threshold_90_precision = thresholds[np.argmax(precisions >= 0.90)]
```

```
threshold_90_precision
```

```
3370.0194991439557
```

```
y_train_pred_90 = (y_scores >= threshold_90_precision)
```

```
precision_score(y_train_5, y_train_pred_90)
```

```
0.9000345901072293
```

```
recall_score(y_train_5, y_train_pred_90)
```

```
0.4799852425751706
```

▼ The ROC Curve


```
from sklearn.metrics import roc_curve
```

```
fpr, tpr, thresholds = roc_curve(y_train_5, y_scores)
```

```
def plot_roc_curve(fpr, tpr, label=None):
    plt.plot(fpr, tpr, linewidth=2, label=label)
    plt.plot([0, 1], [0, 1], 'k--') # dashed diagonal
    plt.axis([0, 1, 0, 1])          # Not shown in the book
    plt.xlabel('False Positive Rate (Fall-Out)', fontsize=16) # Not shown
    plt.ylabel('True Positive Rate (Recall)', fontsize=16)    # Not shown
    plt.grid(True)                 # Not shown

plt.figure(figsize=(8, 6))          # Not shown
plot_roc_curve(fpr, tpr)
fpr_90 = fpr[np.argmax(tpr >= recall_90_precision)] # Not shown
plt.plot([fpr_90, fpr_90], [0., recall_90_precision], "r:") # Not shown
plt.plot([0, fpr_90], [recall_90_precision, recall_90_precision], "r:") # Not shown
plt.plot([fpr_90], [recall_90_precision], "ro")          # Not shown
save_fig("roc_curve_plot")          # Not shown
plt.show()
```

Saving figure roc_curve_plot



```
from sklearn.metrics import roc_auc_score
```

```
roc_auc_score(y_train_5, y_scores)
```

```
0.9604938554008616
```

Note: we set `n_estimators=100` to be future-proof since this will be the default value in Scikit-Learn 0.22.

```
from sklearn.ensemble import RandomForestClassifier
forest_clf = RandomForestClassifier(n_estimators=100, random_state=42)
y_probas_forest = cross_val_predict(forest_clf, X_train, y_train_5, cv=3,
                                   method="predict_proba")
```

```
y_scores_forest = y_probas_forest[:, 1] # score = proba of positive class
fpr_forest, tpr_forest, thresholds_forest = roc_curve(y_train_5, y_scores_forest)
```

```
recall_for_forest = tpr_forest[np.argmax(fpr_forest >= fpr_90)]
```

```
plt.figure(figsize=(8, 6))
plt.plot(fpr, tpr, "b:", linewidth=2, label="SGD")
plot_roc_curve(fpr_forest, tpr_forest, "Random Forest")
plt.plot([fpr_90, fpr_90], [0., recall_90_precision], "r:")
plt.plot([0.0, fpr_90], [recall_90_precision, recall_90_precision], "r:")
plt.plot([fpr_90], [recall_90_precision], "ro")
plt.plot([fpr_90, fpr_90], [0., recall_for_forest], "r:")
plt.plot([fpr_90], [recall_for_forest], "ro")
plt.grid(True)
plt.legend(loc="lower right", fontsize=16)
save_fig("roc_curve_comparison_plot")
plt.show()
```



```

roc_auc_score(y_train_5, y_scores_forest)

0.9983436731328145

y_train_pred_forest = cross_val_predict(forest_clf, X_train, y_train_5, cv=3)
precision_score(y_train_5, y_train_pred_forest)

0.9905083315756169

recall_score(y_train_5, y_train_pred_forest)

0.8662608374838591

```

▾ Multiclass Classification

```

from sklearn.svm import SVC

svm_clf = SVC(gamma="auto", random_state=42)
svm_clf.fit(X_train[:1000], y_train[:1000]) # y_train, not y_train_5
svm_clf.predict([some_digit])

array([5], dtype=uint8)

some_digit_scores = svm_clf.decision_function([some_digit])
some_digit_scores

array([[ 2.81585438,  7.09167958,  3.82972099,  0.79365551,  5.8885703 ,
         9.29718395,  1.79862509,  8.10392157, -0.228207 ,  4.83753243]])

np.argmax(some_digit_scores)

5

svm_clf.classes_

array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9], dtype=uint8)

svm_clf.classes_[5]

5

from sklearn.multiclass import OneVsRestClassifier
ovr_clf = OneVsRestClassifier(SVC(gamma="auto", random_state=42))
ovr_clf.fit(X_train[:1000], y_train[:1000])
ovr_clf.predict([some_digit])

array([5], dtype=uint8)

len(ovr_clf.estimators_)

10

sgd_clf.fit(X_train, y_train)
sgd_clf.predict([some_digit])

array([3], dtype=uint8)

sgd_clf.decision_function([some_digit])

array([[ -31893.03095419, -34419.69069632, -9530.63950739,
         1823.73154031, -22320.14822878, -1385.80478895,
        -26188.91070951, -16147.51323997, -4604.35491274,
        -12050.767298   ]])

```

Warning: the following two cells may take close to 30 minutes to run, or more depending on your hardware.

```

cross_val_score(sgd_clf, X_train, y_train, cv=3, scoring="accuracy")

array([0.87365, 0.85835, 0.8689 ])

from sklearn.preprocessing import StandardScaler
scaler = StandardScaler()
X_train_scaled = scaler.fit_transform(X_train.astype(np.float64))
cross_val_score(sgd_clf, X_train_scaled, y_train, cv=3, scoring="accuracy")

array([0.8983, 0.891 , 0.9018])

```

▼ Error Analysis

```

y_train_pred = cross_val_predict(sgd_clf, X_train_scaled, y_train, cv=3)
conf_mx = confusion_matrix(y_train, y_train_pred)
conf_mx

array([[5577,  0, 22,  5,  8, 43, 36,  6, 225,  1],
       [ 0, 6400, 37, 24,  4, 44,  4,  7, 212, 10],
       [ 27, 27, 5220, 92, 73, 27, 67, 36, 378, 11],
       [ 22, 17, 117, 5227,  2, 203, 27, 40, 403, 73],
       [ 12, 14, 41,  9, 5182, 12, 34, 27, 347, 164],
       [ 27, 15, 30, 168, 53, 4444, 75, 14, 535, 60],
       [ 30, 15, 42,  3, 44, 97, 5552,  3, 131,  1],
       [ 21, 10, 51, 30, 49, 12,  3, 5684, 195, 210],
       [ 17, 63, 48, 86,  3, 126, 25, 10, 5429, 44],
       [ 25, 18, 30, 64, 118, 36,  1, 179, 371, 5107]])

```

```

# since sklearn 0.22, you can use sklearn.metrics.plot_confusion_matrix()
def plot_confusion_matrix(matrix):
    """If you prefer color and a colorbar"""
    fig = plt.figure(figsize=(8,8))
    ax = fig.add_subplot(111)
    cax = ax.matshow(matrix)
    fig.colorbar(cax)


```

```

plt.matshow(conf_mx, cmap=plt.cm.gray)
save_fig("confusion_matrix_plot", tight_layout=False)
plt.show()

```

Saving figure confusion_matrix_plot




```

row_sums = conf_mx.sum(axis=1, keepdims=True)
norm_conf_mx = conf_mx / row_sums

np.fill_diagonal(norm_conf_mx, 0)
plt.matshow(norm_conf_mx, cmap=plt.cm.gray)
save_fig("confusion_matrix_errors_plot", tight_layout=False)
plt.show()

```

Saving figure confusion_matrix_errors_plot



```
cl_a, cl_b = 3, 5
```

```
X_aa = X_train[(y_train == cl_a) & (y_train_pred == cl_a)]
```

```
X_ab = X_train[(y_train == cl_a) & (y_train_pred == cl_b)]
```

```
X_ba = X_train[(y_train == cl_b) & (y_train_pred == cl_a)]
```

```
X_bb = X_train[(y_train == cl_b) & (y_train_pred == cl_b)]
```

```
plt.figure(figsize=(8,8))
```

```
plt.subplot(221); plot_digits(X_aa[:25], images_per_row=5)
```

```
plt.subplot(222); plot_digits(X_ab[:25], images_per_row=5)
```


```
plt.subplot(223); plot_digits(X_ba[:25], images_per_row=5)
```

```
plt.subplot(224); plot_digits(X_bb[:25], images_per_row=5)
```

```
save_fig("error_analysis_digits_plot")
```

```
plt.show()
```

Saving figure error_analysis_digits_plot



▼ Multilabel Classification

```
from sklearn.neighbors import KNeighborsClassifier
```

```
y_train_large = (y_train >= 7)
```

```
y_train_odd = (y_train % 2 == 1)
```

```
y_multilabel = np.c_[y_train_large, y_train_odd]
```

```
knn_clf = KNeighborsClassifier()
```

```
knn_clf.fit(X_train, y_multilabel)
```

```
KNeighborsClassifier()
```

```
knn_clf.predict([some_digit])
```

```
array([[False,  True]])
```

Warning: the following cell may take a very long time (possibly hours depending on your hardware).

```
y_train_knn_pred = cross_val_predict(knn_clf, X_train, y_multilabel, cv=3)
f1_score(y_multilabel, y_train_knn_pred, average="macro")
```

0.976410265560605

▼ Multioutput Classification

```
noise = np.random.randint(0, 100, (len(X_train), 784))
X_train_mod = X_train + noise
noise = np.random.randint(0, 100, (len(X_test), 784))
X_test_mod = X_test + noise
y_train_mod = X_train
y_test_mod = X_test
```


```
some_index = 0
plt.subplot(121); plot_digit(X_test_mod[some_index])
plt.subplot(122); plot_digit(y_test_mod[some_index])
save_fig("noisy_digit_example_plot")
plt.show()
```

Saving figure noisy_digit_example_plot



```
knn_clf.fit(X_train_mod, y_train_mod)
clean_digit = knn_clf.predict([X_test_mod[some_index]])
plot_digit(clean_digit)
save_fig("cleaned_digit_example_plot")
```

Saving figure cleaned_digit_example_plot




▼ Extra material

▼ Dummy (ie. random) classifier

```
from sklearn.dummy import DummyClassifier
dmy_clf = DummyClassifier(strategy="prior")
y_probas_dmy = cross_val_predict(dmy_clf, X_train, y_train_5, cv=3, method="predict_proba")
y_scores_dmy = y_probas_dmy[:, 1]
```

```
fpr, tpr, thresholdsr = roc_curve(y_train_5, y_scores_dmy)
plot_roc_curve(fpr, tpr)
```



▼ KNN classifier

```
from sklearn.neighbors import KNeighborsClassifier
knn_clf = KNeighborsClassifier(weights='distance', n_neighbors=4)
knn_clf.fit(X_train, y_train)
```

```
KNeighborsClassifier(n_neighbors=4, weights='distance')
```

```
y_knn_pred = knn_clf.predict(X_test)
```

```
from sklearn.metrics import accuracy_score
accuracy_score(y_test, y_knn_pred)
```

```
0.9714
```

```
from scipy.ndimage.interpolation import shift
def shift_digit(digit_array, dx, dy, new=0):
    return shift(digit_array.reshape(28, 28), [dy, dx], cval=new).reshape(784)
```

```
plot_digit(shift_digit(some_digit, 5, 1, new=100))
```



```
X_train_expanded = [X_train]
y_train_expanded = [y_train]
for dx, dy in ((1, 0), (-1, 0), (0, 1), (0, -1)):
    shifted_images = np.apply_along_axis(shift_digit, axis=1, arr=X_train, dx=dx, dy=dy)
    X_train_expanded.append(shifted_images)
    y_train_expanded.append(y_train)
```

```
X_train_expanded = np.concatenate(X_train_expanded)
y_train_expanded = np.concatenate(y_train_expanded)
X_train_expanded.shape, y_train_expanded.shape
```

```
((300000, 784), (300000,))
```

```
knn_clf.fit(X_train_expanded, y_train_expanded)
```

```
KNeighborsClassifier(n_neighbors=4, weights='distance')
```

```
y_knn_expanded_pred = knn_clf.predict(X_test)
```

```
accuracy_score(y_test, y_knn_expanded_pred)
```

0.9763

```

ambiguous_digit = X_test[2589]
knn_clf.predict_proba([ambiguous_digit])

array([[0.24579675, 0.        , 0.        , 0.        , 0.        ,
        0.        , 0.        , 0.        , 0.        , 0.75420325]])

plot_digit(ambiguous_digit)

```



▼ Exercise solutions

▼ 1. An MNIST Classifier With Over 97% Accuracy

Warning: the next cell may take close to 16 hours to run, or more depending on your hardware.

```

from sklearn.model_selection import GridSearchCV

param_grid = [{'weights': ["uniform", "distance"], 'n_neighbors': [3, 4, 5]}]

knn_clf = KNeighborsClassifier()
grid_search = GridSearchCV(knn_clf, param_grid, cv=5, verbose=3)
grid_search.fit(X_train, y_train)

Fitting 5 folds for each of 6 candidates, totalling 30 fits
[CV] n_neighbors=3, weights=uniform .....
[Parallel(n_jobs=1)]: Using backend SequentialBackend with 1 concurrent workers.
[CV] ..... n_neighbors=3, weights=uniform, score=0.972, total=168.0min
[CV] n_neighbors=3, weights=uniform .....
[Parallel(n_jobs=1)]: Done 1 out of 1 | elapsed: 168.0min remaining: 0.0s
[CV] ..... n_neighbors=3, weights=uniform, score=0.971, total=12.3min
[CV] n_neighbors=3, weights=uniform .....
[Parallel(n_jobs=1)]: Done 2 out of 2 | elapsed: 180.3min remaining: 0.0s
[CV] ..... n_neighbors=3, weights=uniform, score=0.969, total=11.9min
[CV] n_neighbors=3, weights=uniform .....
[CV] ..... n_neighbors=3, weights=uniform, score=0.969, total=12.5min
[CV] n_neighbors=3, weights=uniform .....
[CV] ..... n_neighbors=3, weights=uniform, score=0.970, total=12.7min
[CV] n_neighbors=3, weights=distance .....
[CV] ..... n_neighbors=3, weights=distance, score=0.972, total=12.5min
[CV] n_neighbors=3, weights=distance .....
[CV] ..... n_neighbors=3, weights=distance, score=0.972, total=12.8min
[CV] n_neighbors=3, weights=distance .....
[CV] ..... n_neighbors=3, weights=distance, score=0.970, total=12.6min
[CV] n_neighbors=3, weights=distance .....
[CV] ..... n_neighbors=3, weights=distance, score=0.970, total=12.9min
[CV] n_neighbors=3, weights=distance .....
[CV] ..... n_neighbors=3, weights=distance, score=0.971, total=11.3min
[CV] n_neighbors=4, weights=uniform .....
[CV] ..... n_neighbors=4, weights=uniform, score=0.969, total=11.0min
[CV] n_neighbors=4, weights=uniform .....
[CV] ..... n_neighbors=4, weights=uniform, score=0.968, total=11.0min
[CV] n_neighbors=4, weights=uniform .....
[CV] ..... n_neighbors=4, weights=uniform, score=0.968, total=11.0min
[CV] n_neighbors=4, weights=uniform .....
[CV] ..... n_neighbors=4, weights=uniform, score=0.967, total=11.0min
[CV] n_neighbors=4, weights=uniform .....
[CV] ..... n_neighbors=4, weights=uniform, score=0.970, total=11.0min
[CV] n_neighbors=4, weights=distance .....
[CV] ..... n_neighbors=4, weights=distance, score=0.973, total=11.0min

```

```
[CV] n_neighbors=4, weights=distance .....
[CV] ..... n_neighbors=4, weights=distance, score=0.972, total=11.0min
[CV] n_neighbors=4, weights=distance .....
[CV] ..... n_neighbors=4, weights=distance, score=0.970, total=11.0min
[CV] n_neighbors=4, weights=distance .....
[CV] ..... n_neighbors=4, weights=distance, score=0.971, total=11.0min
[CV] n_neighbors=4, weights=distance .....
[CV] ..... n_neighbors=4, weights=distance, score=0.972, total=11.3min
[CV] n_neighbors=5, weights=uniform .....
[CV] ..... n_neighbors=5, weights=uniform, score=0.970, total=10.9min
[CV] n_neighbors=5, weights=uniform .....
[CV] ..... n_neighbors=5, weights=uniform, score=0.970, total=11.0min
[CV] n_neighbors=5, weights=uniform .....
[CV] ..... n_neighbors=5, weights=uniform, score=0.969, total=11.0min
[CV] n_neighbors=5, weights=uniform .....
[CV] ..... n_neighbors=5, weights=uniform, score=0.968, total=11.1min
[CV] n_neighbors=5, weights=uniform .....
[CV] ..... n_neighbors=5, weights=uniform, score=0.969, total=11.0min
[CV] n_neighbors=5, weights=distance .....
[CV] ..... n_neighbors=5, weights=distance, score=0.970, total=93.6min
[CV] n_neighbors=5, weights=distance .....
[CV] ..... n_neighbors=5, weights=distance, score=0.971, total=11.0min
```

```
grid_search.best_params_
```

```
{'n_neighbors': 4, 'weights': 'distance'}
```

```
grid_search.best_score_
```

```
0.9716166666666666
```

```
from sklearn.metrics import accuracy_score
```

```
y_pred = grid_search.predict(X_test)
accuracy_score(y_test, y_pred)
```

```
0.9714
```

▼ 2. Data Augmentation

```
from scipy.ndimage.interpolation import shift
```

```
def shift_image(image, dx, dy):
    image = image.reshape((28, 28))
    shifted_image = shift(image, [dy, dx], cval=0, mode="constant")
    return shifted_image.reshape([-1])
```

```
image = X_train[1000]
shifted_image_down = shift_image(image, 0, 5)
shifted_image_left = shift_image(image, -5, 0)
```

```
plt.figure(figsize=(12,3))
plt.subplot(131)
plt.title("Original", fontsize=14)
plt.imshow(image.reshape(28, 28), interpolation="nearest", cmap="Greys")
plt.subplot(132)
plt.title("Shifted down", fontsize=14)
plt.imshow(shifted_image_down.reshape(28, 28), interpolation="nearest", cmap="Greys")
plt.subplot(133)
plt.title("Shifted left", fontsize=14)
plt.imshow(shifted_image_left.reshape(28, 28), interpolation="nearest", cmap="Greys")
plt.show()
```

```

    ^      Original      ^      Shifted down      ^      Shifted left
X_train_augmented = [image for image in X_train]
y_train_augmented = [label for label in y_train]

for dx, dy in ((1, 0), (-1, 0), (0, 1), (0, -1)):
    for image, label in zip(X_train, y_train):
        X_train_augmented.append(shift_image(image, dx, dy))
        y_train_augmented.append(label)

X_train_augmented = np.array(X_train_augmented)
y_train_augmented = np.array(y_train_augmented)

shuffle_idx = np.random.permutation(len(X_train_augmented))
X_train_augmented = X_train_augmented[shuffle_idx]
y_train_augmented = y_train_augmented[shuffle_idx]

knn_clf = KNeighborsClassifier(**grid_search.best_params_)

knn_clf.fit(X_train_augmented, y_train_augmented)

KNeighborsClassifier(n_neighbors=4, weights='distance')

```

Warning: the following cell may take close to an hour to run, depending on your hardware.

```

y_pred = knn_clf.predict(X_test)
accuracy_score(y_test, y_pred)

0.9763

```

By simply augmenting the data, we got a 0.5% accuracy boost. :)

3. Tackle the Titanic dataset

The goal is to predict whether or not a passenger survived based on attributes such as their age, sex, passenger class, where they embarked and so on.

Let's fetch the data and load it:

```

import os
import urllib.request

TITANIC_PATH = os.path.join("datasets", "titanic")
DOWNLOAD_URL = "https://raw.githubusercontent.com/ageron/handson-ml2/master/datasets/titanic/"

def fetch_titanic_data(url=DOWNLOAD_URL, path=TITANIC_PATH):
    if not os.path.isdir(path):
        os.makedirs(path)
    for filename in ("train.csv", "test.csv"):
        filepath = os.path.join(path, filename)
        if not os.path.isfile(filepath):
            print("Downloading", filename)
            urllib.request.urlretrieve(url + filename, filepath)

fetch_titanic_data()

import pandas as pd

def load_titanic_data(filename, titanic_path=TITANIC_PATH):
    csv_path = os.path.join(titanic_path, filename)
    return pd.read_csv(csv_path)

train_data = load_titanic_data("train.csv")
test_data = load_titanic_data("test.csv")

```


The data is already split into a training set and a test set. However, the test data does *not* contain the labels: your goal is to train the best model you can using the training data, then make your predictions on the test data and upload them to Kaggle to see your final score.

Let's take a peek at the top few rows of the training set:

```
train_data.head()
```

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parc
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	
				Cumings, Mrs. John				

The attributes have the following meaning:

- **PassengerId**: a unique identifier for each passenger
- **Survived**: that's the target, 0 means the passenger did not survive, while 1 means he/she survived.
- **Pclass**: passenger class.
- **Name, Sex, Age**: self-explanatory
- **SibSp**: how many siblings & spouses of the passenger aboard the Titanic.
- **Parch**: how many children & parents of the passenger aboard the Titanic.
- **Ticket**: ticket id
- **Fare**: price paid (in pounds)
- **Cabin**: passenger's cabin number
- **Embarked**: where the passenger embarked the Titanic

Let's explicitly set the `PassengerId` column as the index column:

```
train_data = train_data.set_index("PassengerId")
test_data = test_data.set_index("PassengerId")
```

Let's get more info to see how much data is missing:

```
train_data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 891 entries, 1 to 891
Data columns (total 11 columns):
#   Column      Non-Null Count  Dtype
---  -
0   Survived    891 non-null    int64
1   Pclass      891 non-null    int64
2   Name        891 non-null    object
3   Sex         891 non-null    object
4   Age         714 non-null    float64
5   SibSp       891 non-null    int64
6   Parch       891 non-null    int64
7   Ticket      891 non-null    object
8   Fare        891 non-null    float64
9   Cabin       204 non-null    object
10  Embarked    889 non-null    object
dtypes: float64(2), int64(4), object(5)
memory usage: 83.5+ KB
```

```
train_data[train_data["Sex"]=="female"]["Age"].median()
```

```
27.0
```

Okay, the **Age**, **Cabin** and **Embarked** attributes are sometimes null (less than 891 non-null), especially the **Cabin** (77% are null). We will ignore the **Cabin** for now and focus on the rest. The **Age** attribute has about 19% null values, so we will need to decide what to do with them. Replacing

null values with the median age seems reasonable. We could be a bit smarter by predicting the age based on the other columns (for example, the median age is 37 in 1st class, 29 in 2nd class and 24 in 3rd class), but we'll keep things simple and just use the overall median age.

The **Name** and **Ticket** attributes may have some value, but they will be a bit tricky to convert into useful numbers that a model can consume. So for now, we will ignore them.

Let's take a look at the numerical attributes:

```
train_data.describe()
```

	Survived	Pclass	Age	SibSp	Parch	
count	891.000000	891.000000	714.000000	891.000000	891.000000	891
mean	0.383838	2.308642	29.699113	0.523008	0.381594	32
std	0.486592	0.836071	14.526507	1.102743	0.806057	49
min	0.000000	1.000000	0.416700	0.000000	0.000000	0
25%	0.000000	2.000000	20.125000	0.000000	0.000000	7
50%	0.000000	3.000000	28.000000	0.000000	0.000000	14

- Yikes, only 38% **Survived!** 🤖 That's close enough to 40%, so accuracy will be a reasonable metric to evaluate our model.
- The mean **Fare** was £32.20, which does not seem so expensive (but it was probably a lot of money back then).
- The mean **Age** was less than 30 years old.

Let's check that the target is indeed 0 or 1:

```
train_data["Survived"].value_counts()
```

```
0    549
1    342
Name: Survived, dtype: int64
```

Now let's take a quick look at all the categorical attributes:

```
train_data["Pclass"].value_counts()
```

```
3    491
1    216
2    184
Name: Pclass, dtype: int64
```

```
train_data["Sex"].value_counts()
```

```
male    577
female  314
Name: Sex, dtype: int64
```

```
train_data["Embarked"].value_counts()
```

```
S    644
C    168
Q     77
Name: Embarked, dtype: int64
```

The Embarked attribute tells us where the passenger embarked: C=Cherbourg, Q=Queenstown, S=Southampton.

Now let's build our preprocessing pipelines, starting with the pipeline for numerical attributes:

```
from sklearn.pipeline import Pipeline
from sklearn.impute import SimpleImputer
```

```
from sklearn.preprocessing import StandardScaler

num_pipeline = Pipeline([
    ("imputer", SimpleImputer(strategy="median")),
    ("scaler", StandardScaler())
])
```

Now we can build the pipeline for the categorical attributes:

```
from sklearn.preprocessing import OneHotEncoder

cat_pipeline = Pipeline([
    ("imputer", SimpleImputer(strategy="most_frequent")),
    ("cat_encoder", OneHotEncoder(sparse=False)),
])
```

Finally, let's join the numerical and categorical pipelines:

```
from sklearn.compose import ColumnTransformer

num_attribs = ["Age", "SibSp", "Parch", "Fare"]
cat_attribs = ["Pclass", "Sex", "Embarked"]

preprocess_pipeline = ColumnTransformer([
    ("num", num_pipeline, num_attribs),
    ("cat", cat_pipeline, cat_attribs),
])
```

Cool! Now we have a nice preprocessing pipeline that takes the raw data and outputs numerical input features that we can feed to any Machine Learning model we want.

```
X_train = preprocess_pipeline.fit_transform(
    train_data[num_attribs + cat_attribs])
X_train

array([[ -0.56573582,  0.43279337, -0.47367361, ...,  0.         ,
         0.         ,  1.         ],
       [  0.6638609 ,  0.43279337, -0.47367361, ...,  1.         ,
         0.         ,  0.         ],
       [ -0.25833664, -0.4745452 , -0.47367361, ...,  0.         ,
         0.         ,  1.         ],
       ...,
       [ -0.10463705,  0.43279337,  2.00893337, ...,  0.         ,
         0.         ,  1.         ],
       [ -0.25833664, -0.4745452 , -0.47367361, ...,  1.         ,
         0.         ,  0.         ],
       [  0.20276213, -0.4745452 , -0.47367361, ...,  0.         ,
         1.         ,  0.         ]])
```

Let's not forget to get the labels:

```
y_train = train_data["Survived"]
```

We are now ready to train a classifier. Let's start with a `RandomForestClassifier`:

```
from sklearn.ensemble import RandomForestClassifier

forest_clf = RandomForestClassifier(n_estimators=100, random_state=42)
forest_clf.fit(X_train, y_train)

RandomForestClassifier(random_state=42)
```

Great, our model is trained, let's use it to make predictions on the test set:

```
X_test = preprocess_pipeline.transform(test_data[num_attribs + cat_attribs])
y_pred = forest_clf.predict(X_test)
```

And now we could just build a CSV file with these predictions (respecting the format expected by Kaggle), then upload it and hope for the best. But wait! We can do better than hope. Why don't we use cross-validation to have an idea of how good our model is?

```
from sklearn.model_selection import cross_val_score

forest_scores = cross_val_score(forest_clf, X_train, y_train, cv=10)
forest_scores.mean()

0.8137578027465668
```

Okay, not too bad! Looking at the [leaderboard](#) for the Titanic competition on Kaggle, you can see that our score is in the top 2%, woohoo! Some Kagglers reached 100% accuracy, but since you can easily find the [list of victims](#) of the Titanic, it seems likely that there was little Machine Learning involved in their performance! 😞

Let's try an SVC:

```
from sklearn.svm import SVC

svm_clf = SVC(gamma="auto")
svm_scores = cross_val_score(svm_clf, X_train, y_train, cv=10)
svm_scores.mean()


0.8249313358302123
```

Great! This model looks better.

But instead of just looking at the mean accuracy across the 10 cross-validation folds, let's plot all 10 scores for each model, along with a box plot highlighting the lower and upper quartiles, and "whiskers" showing the extent of the scores (thanks to Nevin Yilmaz for suggesting this visualization). Note that the `boxplot()` function detects outliers (called "fliers") and does not include them within the whiskers. Specifically, if the lower quartile is Q_1 and the upper quartile is Q_3 , then the interquartile range $IQR = Q_3 - Q_1$ (this is the box's height), and any score lower than $Q_1 - 1.5 \times IQR$ is a flier, and so is any score greater than $Q_3 + 1.5 \times IQR$.

```
import matplotlib.pyplot as plt

plt.figure(figsize=(8, 4))
plt.plot([1]*10, svm_scores, ".")
plt.plot([2]*10, forest_scores, ".")
plt.boxplot([svm_scores, forest_scores], labels=("SVM", "Random Forest"))
plt.ylabel("Accuracy", fontsize=14)
plt.show()
```



The random forest classifier got a very high score on one of the 10 folds, but overall it had a lower mean score, as well as a bigger spread, so it looks like the SVM classifier is more likely to generalize well.

To improve this result further, you could:

- Compare many more models and tune hyperparameters using cross validation and grid search,
- Do more feature engineering, for example:
 - Try to convert numerical attributes to categorical attributes: for example, different age groups had very different survival rates (see below), so it may help to create an age bucket category and use it instead of the age. Similarly, it may be useful to have a special

category for people traveling alone since only 30% of them survived (see below).

- Replace **SibSp** and **Parch** with their sum.
- Try to identify parts of names that correlate well with the **Survived** attribute.
- Use the **Cabin** column, for example take its first letter and treat it as a categorical attribute.

```
train_data["AgeBucket"] = train_data["Age"] // 15 * 15
train_data[["AgeBucket", "Survived"]].groupby(['AgeBucket']).mean()
```

Survived	
AgeBucket	
0.0	0.576923
15.0	0.362745
30.0	0.423256
45.0	0.404494
60.0	0.240000

```
train_data["RelativesOnboard"] = train_data["SibSp"] + train_data["Parch"]
train_data[["RelativesOnboard", "Survived"]].groupby(['RelativesOnboard']).mean()
```

Survived	
RelativesOnboard	
0	0.303538
1	0.552795
2	0.578431
3	0.724138
4	0.200000
5	0.136364
6	0.333333
7	0.000000

▼ 4. Spam classifier

First, let's fetch the data:

```
import os
import tarfile
import urllib.request

DOWNLOAD_ROOT = "http://spamassassin.apache.org/old/publiccorpus/"
HAM_URL = DOWNLOAD_ROOT + "20030228_easy_ham.tar.bz2"
SPAM_URL = DOWNLOAD_ROOT + "20030228_spam.tar.bz2"
SPAM_PATH = os.path.join("datasets", "spam")

def fetch_spam_data(ham_url=HAM_URL, spam_url=SPAM_URL, spam_path=SPAM_PATH):
    if not os.path.isdir(spam_path):
        os.makedirs(spam_path)
    for filename, url in (("ham.tar.bz2", ham_url), ("spam.tar.bz2", spam_url)):
        path = os.path.join(spam_path, filename)
        if not os.path.isfile(path):
            urllib.request.urlretrieve(url, path)
        tar_bz2_file = tarfile.open(path)
        tar_bz2_file.extractall(path=spam_path)
        tar_bz2_file.close()

fetch_spam_data()
```

Next, let's load all the emails:

```
HAM_DIR = os.path.join(SPAM_PATH, "easy_ham")
SPAM_DIR = os.path.join(SPAM_PATH, "spam")
ham_filenames = [name for name in sorted(os.listdir(HAM_DIR)) if len(name) > 20]
spam_filenames = [name for name in sorted(os.listdir(SPAM_DIR)) if len(name) > 20]
```

```
len(ham_filenames)
```

```
2500
```

```
len(spam_filenames)
```

```
500
```

We can use Python's `email` module to parse these emails (this handles headers, encoding, and so on):

```
import email
import email.policy

def load_email(is_spam, filename, spam_path=SPAM_PATH):
    directory = "spam" if is_spam else "easy_ham"
    with open(os.path.join(spam_path, directory, filename), "rb") as f:
        return email.parser.BytesParser(policy=email.policy.default).parse(f)

ham_emails = [load_email(is_spam=False, filename=name) for name in ham_filenames]
spam_emails = [load_email(is_spam=True, filename=name) for name in spam_filenames]
```

Let's look at one example of ham and one example of spam, to get a feel of what the data looks like:

```
print(ham_emails[1].get_content().strip())
```

```
Martin A posted:
Tassos Papadopoulos, the Greek sculptor behind the plan, judged that the
limestone of Mount Kerdyllo, 70 miles east of Salonika and not far from the
Mount Athos monastic community, was ideal for the patriotic sculpture.
```

```
As well as Alexander's granite features, 240 ft high and 170 ft wide, a
museum, a restored amphitheatre and car park for admiring crowds are
planned
```

```
-----
So is this mountain limestone or granite?
If it's limestone, it'll weather pretty fast.
```

```
----- Yahoo! Groups Sponsor -----~>
4 DVDs Free +s&p Join Now
http://us.click.yahoo.com/pt6YBB/NXiEAA/mG3HAA/7gSolB/TM
-----~>
```

```
To unsubscribe from this group, send an email to:
forteana-unsubscribe@groups.com
```

```
Your use of Yahoo! Groups is subject to http://docs.yahoo.com/info/terms/
```

```
print(spam_emails[6].get_content().strip())
```

```
Help wanted. We are a 14 year old fortune 500 company, that is
growing at a tremendous rate. We are looking for individuals who
want to work from home.
```

```
This is an opportunity to make an excellent income. No experience
is required. We will train you.
```

```
So if you are looking to be employed from home with a career that has
vast opportunities, then go:
```

```
http://www.basetel.com/wealthnow
```

```
We are looking for energetic and self motivated people. If that is you
than click on the link and fill out the form, and one of our
employment specialist will contact you.
```

To be removed from our link simple go to:

<http://www.basetel.com/remove.html>

4139v0LW7-758DoDY1425FRhM1-764SMFc8513fCsL140

Some emails are actually multipart, with images and attachments (which can have their own attachments). Let's look at the various types of structures we have:

```
def get_email_structure(email):
    if isinstance(email, str):
        return email
    payload = email.get_payload()
    if isinstance(payload, list):
        return "multipart({})".format(", ".join([
            get_email_structure(sub_email)
            for sub_email in payload
        ]))
    else:
        return email.get_content_type()

from collections import Counter

def structures_counter(emails):
    structures = Counter()
    for email in emails:
        structure = get_email_structure(email)
        structures[structure] += 1
    return structures

structures_counter(ham_emails).most_common()

[('text/plain', 2408),
 ('multipart(text/plain, application/pgp-signature)', 66),
 ('multipart(text/plain, text/html)', 8),
 ('multipart(text/plain, text/plain)', 4),
 ('multipart(text/plain)', 3),
 ('multipart(text/plain, application/octet-stream)', 2),
 ('multipart(text/plain, text/enriched)', 1),
 ('multipart(text/plain, application/ms-tnef, text/plain)', 1),
 ('multipart(multipart(text/plain, text/plain, text/plain), application/pgp-signature)',
 1),
 ('multipart(text/plain, video/mng)', 1),
 ('multipart(text/plain, multipart(text/plain))', 1),
 ('multipart(text/plain, application/x-pkcs7-signature)', 1),
 ('multipart(text/plain, multipart(text/plain, text/plain), text/rfc822-headers)',
 1),
 ('multipart(text/plain, multipart(text/plain, text/plain), multipart(multipart(text/plain, application/x-pkcs7-signature)))',
 1),
 ('multipart(text/plain, application/x-java-applet)', 1)]

structures_counter(spam_emails).most_common()

[('text/plain', 218),
 ('text/html', 183),
 ('multipart(text/plain, text/html)', 45),
 ('multipart(text/html)', 20),
 ('multipart(text/plain)', 19),
 ('multipart(multipart(text/html))', 5),
 ('multipart(text/plain, image/jpeg)', 3),
 ('multipart(text/html, application/octet-stream)', 2),
 ('multipart(text/plain, application/octet-stream)', 1),
 ('multipart(text/html, text/plain)', 1),
 ('multipart(multipart(text/html), application/octet-stream, image/jpeg)', 1),
 ('multipart(multipart(text/plain, text/html), image/gif)', 1),
 ('multipart/alternative', 1)]
```

It seems that the ham emails are more often plain text, while spam has quite a lot of HTML. Moreover, quite a few ham emails are signed using PGP, while no spam is. In short, it seems that the email structure is useful information to have.

Now let's take a look at the email headers:

```
for header, value in spam_emails[0].items():
    print(header,":",value)

Return-Path : <12a1mailbot1@web.de>
Delivered-To : zzzz@localhost.spamassassin.taint.org
Received : from localhost (localhost [127.0.0.1]) by phobos.labs.spamassassin.taint.org (Postfix) with ESMTD id 136B943C32
Received : from mail.webnote.net [193.120.211.219] by localhost with POP3 (fetchmail-5.9.0) for zzzz@localhost (single-drop);
Received : from dd_it7 ([210.97.77.167]) by webnote.net (8.9.3/8.9.3) with ESMTD id NAA04623 for <zzzz@spamassassin.taint.org>
From : 12a1mailbot1@web.de
Received : from r-smtp4.korea.com - 203.122.2.197 by dd_it7 with Microsoft SMTPSVC(5.5.1775.675.6); Sat, 24 Aug 2002 09:42:10 +0900
To : dcek1a1@netsgo.com
Subject : Life Insurance - Why Pay More?
Date : Wed, 21 Aug 2002 20:31:57 -1600
MIME-Version : 1.0
Message-ID : <0103c1042001882DD_IT7@dd_it7>
Content-Type : text/html; charset="iso-8859-1"
Content-Transfer-Encoding : quoted-printable
```

There's probably a lot of useful information in there, such as the sender's email address (12a1mailbot1@web.de looks fishy), but we will just focus on the `Subject` header:

```
spam_emails[0]["Subject"]
```

```
'Life Insurance - Why Pay More?'
```

Okay, before we learn too much about the data, let's not forget to split it into a training set and a test set:

```
import numpy as np
from sklearn.model_selection import train_test_split

X = np.array(ham_emails + spam_emails, dtype=object)
y = np.array([0] * len(ham_emails) + [1] * len(spam_emails))

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
```

Okay, let's start writing the preprocessing functions. First, we will need a function to convert HTML to plain text. Arguably the best way to do this would be to use the great [BeautifulSoup](#) library, but I would like to avoid adding another dependency to this project, so let's hack a quick & dirty solution using regular expressions (at the risk of [unholy radiance destroying all enlightenment](#)). The following function first drops the `<head>` section, then converts all `<a>` tags to the word HYPERLINK, then it gets rid of all HTML tags, leaving only the plain text. For readability, it also replaces multiple newlines with single newlines, and finally it unescapes html entities (such as `>` or ` `):

```
import re
from html import unescape

def html_to_plain_text(html):
    text = re.sub('<head.*?>.*?</head>', '', html, flags=re.M | re.S | re.I)
    text = re.sub('<a.*?>', ' HYPERLINK ', text, flags=re.M | re.S | re.I)
    text = re.sub('<.*?>', '', text, flags=re.M | re.S)
    text = re.sub(r'(\s*\n)+', '\n', text, flags=re.M | re.S)
    return unescape(text)
```

Let's see if it works. This is HTML spam:

```
html_spam_emails = [email for email in X_train[y_train==1]
                    if get_email_structure(email) == "text/html"]
sample_html_spam = html_spam_emails[7]
print(sample_html_spam.get_content().strip()[:100], "...")
```

```
<HTML><HEAD><TITLE></TITLE><META http-equiv="Content-Type" content="text/html; charset=windows-1252"><STYLE>A:link {TEX-DECORATION: none}
<BODY text="#000000" vLink="#0033ff" link="#0033ff" bgColor="#CCCC99"><TABLE borderColor="#660000" cellSpacing="0" cellPadding="0" border="1">
|  |
| --- |
| OTC |
| Newsletter |
| Discover Tomorrow's Winners |

```

And this is the resulting plain text:


```
print(html_to_plain_text(sample_html_spam.get_content())[:1000], "...")
```

OTC
 Newsletter
 Discover Tomorrow's Winners
 For Immediate Release
 Cal-Bay (Stock Symbol: CBYI)
 Watch for analyst "Strong Buy Recommendations" and several advisory newsletters picking CBYI. CBYI has filed to be traded on the OTCBB,
 Put CBYI on your watch list, acquire a position TODAY.
 REASONS TO INVEST IN CBYI
 A profitable company and is on track to beat ALL earnings estimates!
 One of the FASTEST growing distributors in environmental & safety equipment instruments.
 Excellent management team, several EXCLUSIVE contracts. IMPRESSIVE client list including the U.S. Air Force, Anheuser-Busch, Chevron Re
 RAPIDLY GROWING INDUSTRY
 Industry revenues exceed \$900 million, estimates indicate that there could be as much as \$25 billi ...

Great! Now let's write a function that takes an email as input and returns its content as plain text, whatever its format is:

```
def email_to_text(email):
    html = None
    for part in email.walk():
        ctype = part.get_content_type()
        if not ctype in ("text/plain", "text/html"):
            continue
        try:
            content = part.get_content()
        except: # in case of encoding issues
            content = str(part.get_payload())
        if ctype == "text/plain":
            return content
        else:
            html = content
    if html:
        return html_to_plain_text(html)

print(email_to_text(sample_html_spam)[:100], "...")
```

OTC
 Newsletter
 Discover Tomorrow's Winners
 For Immediate Release
 Cal-Bay (Stock Symbol: CBYI)
 Wat ...

Let's throw in some stemming! For this to work, you need to install the Natural Language Toolkit ([NLTK](#)). It's as simple as running the following command (don't forget to activate your virtualenv first; if you don't have one, you will likely need administrator rights, or use the `--user` option):

```
$ pip3 install nltk
```

```
try:
    import nltk

    stemmer = nltk.PorterStemmer()
    for word in ("Computations", "Computation", "Computing", "Computed", "Compute", "Compulsive"):
        print(word, "=>", stemmer.stem(word))
except ImportError:
    print("Error: stemming requires the NLTK module.")
    stemmer = None

Computations => comput
Computation => comput
Computing => comput
Computed => comput
Compute => comput
Compulsive => compuls
```

We will also need a way to replace URLs with the word "URL". For this, we could use hard core [regular expressions](#) but we will just use the [urlextract](#) library. You can install it with the following command (don't forget to activate your virtualenv first; if you don't have one, you will likely need administrator rights, or use the `--user` option):

```
$ pip3 install urlextract
```

```
# if running this notebook on Colab or Kaggle, we just pip install urlextract
if IS_COLAB or IS_KAGGLE:
    %pip install -q -U urlextract
```

Note: inside a Jupyter notebook, always use `%pip` instead of `!pip`, as `!pip` may install the library inside the wrong environment, while `%pip` makes sure it's installed inside the currently running environment.

```
try:
    import urlextract # may require an Internet connection to download root domain names

    url_extractor = urlextract.URLExtract()
    print(url_extractor.find_urls("Will it detect github.com and https://youtu.be/7Pq-S557XQU?t=3m32s"))
except ImportError:
    print("Error: replacing URLs requires the urlextract module.")
    url_extractor = None

['github.com', 'https://youtu.be/7Pq-S557XQU?t=3m32s']
```

We are ready to put all this together into a transformer that we will use to convert emails to word counters. Note that we split sentences into words using Python's `split()` method, which uses whitespaces for word boundaries. This works for many written languages, but not all. For example, Chinese and Japanese scripts generally don't use spaces between words, and Vietnamese often uses spaces even between syllables. It's okay in this exercise, because the dataset is (mostly) in English.

```
from sklearn.base import BaseEstimator, TransformerMixin

class EmailToWordCounterTransformer(BaseEstimator, TransformerMixin):
    def __init__(self, strip_headers=True, lower_case=True, remove_punctuation=True,
                 replace_urls=True, replace_numbers=True, stemming=True):
        self.strip_headers = strip_headers
        self.lower_case = lower_case
        self.remove_punctuation = remove_punctuation
        self.replace_urls = replace_urls
        self.replace_numbers = replace_numbers
        self.stemming = stemming
    def fit(self, X, y=None):
        return self
    def transform(self, X, y=None):
        X_transformed = []
        for email in X:
            text = email_to_text(email) or ""
            if self.lower_case:
                text = text.lower()
            if self.replace_urls and url_extractor is not None:
                urls = list(set(url_extractor.find_urls(text)))
                urls.sort(key=lambda url: len(url), reverse=True)
                for url in urls:
                    text = text.replace(url, " URL ")
            if self.replace_numbers:
                text = re.sub(r'\d+(?:\.\d*)?(?:[eE][+-]?[d+])?', 'NUMBER', text)
            if self.remove_punctuation:
                text = re.sub(r'\W+', ' ', text, flags=re.M)
            word_counts = Counter(text.split())
            if self.stemming and stemmer is not None:
                stemmed_word_counts = Counter()
                for word, count in word_counts.items():
                    stemmed_word = stemmer.stem(word)
                    stemmed_word_counts[stemmed_word] += count
                word_counts = stemmed_word_counts
            X_transformed.append(word_counts)
        return np.array(X_transformed)
```

Let's try this transformer on a few emails:

```
X_few = X_train[:3]
X_few_wordcounts = EmailToWordCounterTransformer().fit_transform(X_few)
X_few_wordcounts
```

```
array([Counter({'chuck': 1, 'murcko': 1, 'wrote': 1, 'stuff': 1, 'yawn': 1, 'r': 1}),
      Counter({'the': 11, 'of': 9, 'and': 8, 'all': 3, 'christian': 3, 'to': 3, 'by': 3, 'jefferson': 2, 'i': 2, 'have': 2,
'superstit': 2, 'one': 2, 'on': 2, 'been': 2, 'ha': 2, 'half': 2, 'rogueri': 2, 'teach': 2, 'jesu': 2, 'some': 1, 'interest': 1,
'quot': 1, 'url': 1, 'thoma': 1, 'examin': 1, 'known': 1, 'word': 1, 'do': 1, 'not': 1, 'find': 1, 'in': 1, 'our': 1, 'particular': 1,
'redeem': 1, 'featur': 1, 'they': 1, 'are': 1, 'alik': 1, 'found': 1, 'fabl': 1, 'mytholog': 1, 'million': 1, 'innoc': 1, 'men': 1,
'women': 1, 'children': 1, 'sinc': 1, 'introduc': 1, 'burnt': 1, 'tortur': 1, 'fine': 1, 'imprison': 1, 'what': 1, 'effect': 1, 'thi':
1, 'coercion': 1, 'make': 1, 'world': 1, 'fool': 1, 'other': 1, 'hypocrit': 1, 'support': 1, 'error': 1, 'over': 1, 'earth': 1, 'six':
1, 'histor': 1, 'american': 1, 'john': 1, 'e': 1, 'remsburg': 1, 'letter': 1, 'william': 1, 'short': 1, 'again': 1, 'becom': 1, 'most':
1, 'pervert': 1, 'system': 1, 'that': 1, 'ever': 1, 'shone': 1, 'man': 1, 'absurd': 1, 'untruth': 1, 'were': 1, 'perpetr': 1, 'upon':
1, 'a': 1, 'larg': 1, 'band': 1, 'dupe': 1, 'import': 1, 'led': 1, 'paul': 1, 'first': 1, 'great': 1, 'corrupt': 1}),
      Counter({'url': 4, 's': 3, 'group': 3, 'to': 3, 'in': 2, 'fortean': 2, 'martin': 2, 'an': 2, 'and': 2, 'we': 2, 'is': 2,
'yahoo': 2, 'unsubscribe': 2, 'y': 1, 'adamson': 1, 'wrote': 1, 'for': 1, 'altern': 1, 'rather': 1, 'more': 1, 'factual': 1, 'base': 1,
'rundown': 1, 'on': 1, 'hamza': 1, 'career': 1, 'includ': 1, 'hi': 1, 'belief': 1, 'that': 1, 'all': 1, 'non': 1, 'muslim': 1, 'yemen':
1, 'should': 1, 'be': 1, 'murder': 1, 'outright': 1, 'know': 1, 'how': 1, 'unbias': 1, 'memri': 1, 'don': 1, 't': 1, 'html': 1, 'rob':
1, 'sponsor': 1, 'number': 1, 'dvd': 1, 'free': 1, 'p': 1, 'join': 1, 'now': 1, 'from': 1, 'thi': 1, 'send': 1, 'email': 1, 'egroup':
1, 'com': 1, 'your': 1, 'use': 1, 'of': 1, 'subject': 1})]),
      dtype=object)
```

This looks about right!

Now we have the word counts, and we need to convert them to vectors. For this, we will build another transformer whose `fit()` method will build the vocabulary (an ordered list of the most common words) and whose `transform()` method will use the vocabulary to convert word counts to vectors. The output is a sparse matrix.

```
from scipy.sparse import csr_matrix

class WordCounterToVectorTransformer(BaseEstimator, TransformerMixin):
    def __init__(self, vocabulary_size=1000):
        self.vocabulary_size = vocabulary_size
    def fit(self, X, y=None):
        total_count = Counter()
        for word_count in X:
            for word, count in word_count.items():
                total_count[word] += min(count, 10)
        most_common = total_count.most_common()[self.vocabulary_size:]
        self.vocabulary_ = {word: index + 1 for index, (word, count) in enumerate(most_common)}
        return self
    def transform(self, X, y=None):
        rows = []
        cols = []
        data = []
        for row, word_count in enumerate(X):
            for word, count in word_count.items():
                rows.append(row)
                cols.append(self.vocabulary_.get(word, 0))
                data.append(count)
        return csr_matrix((data, (rows, cols)), shape=(len(X), self.vocabulary_size + 1))

vocab_transformer = WordCounterToVectorTransformer(vocabulary_size=10)
X_few_vectors = vocab_transformer.fit_transform(X_few_wordcounts)
X_few_vectors
```

```
<3x11 sparse matrix of type '<class 'numpy.longlong'>'
with 20 stored elements in Compressed Sparse Row format>
```

```
X_few_vectors.toarray()

array([[ 6,  0,  0,  0,  0,  0,  0,  0,  0,  0,  0],
       [99, 11,  9,  8,  3,  1,  3,  1,  3,  2,  3],
       [67,  0,  1,  2,  3,  4,  1,  2,  0,  1,  0]], dtype=int64)
```

What does this matrix mean? Well, the 99 in the second row, first column, means that the second email contains 99 words that are not part of the vocabulary. The 11 next to it means that the first word in the vocabulary is present 11 times in this email. The 9 next to it means that the second word is present 9 times, and so on. You can look at the vocabulary to know which words we are talking about. The first word is "the", the second word is "of", etc.

```
vocab_transformer.vocabulary_

{'the': 1,
 'of': 2,
 'and': 3,
 'to': 4,
```

```
'url': 5,
'all': 6,
'in': 7,
'christian': 8,
'on': 9,
'by': 10}
```

We are now ready to train our first spam classifier! Let's transform the whole dataset:

```
from sklearn.pipeline import Pipeline

preprocess_pipeline = Pipeline([
    ("email_to_wordcount", EmailToWordCounterTransformer()),
    ("wordcount_to_vector", WordCounterToVectorTransformer()),
])

X_train_transformed = preprocess_pipeline.fit_transform(X_train)
```

Note: to be future-proof, we set `solver="lbfgs"` since this will be the default value in Scikit-Learn 0.22.

```
from sklearn.linear_model import LogisticRegression
from sklearn.model_selection import cross_val_score

log_clf = LogisticRegression(solver="lbfgs", max_iter=1000, random_state=42)
score = cross_val_score(log_clf, X_train_transformed, y_train, cv=3, verbose=3)
score.mean()

[Parallel(n_jobs=1)]: Using backend SequentialBackend with 1 concurrent workers.
[Parallel(n_jobs=1)]: Done 1 out of 1 | elapsed: 0.1s remaining: 0.0s
[CV] .....
[CV] ..... , score=0.981, total= 0.1s
[CV] .....
[CV] ..... , score=0.985, total= 0.2s
[CV] .....
[CV] ..... , score=0.991, total= 0.2s
[Parallel(n_jobs=1)]: Done 2 out of 2 | elapsed: 0.3s remaining: 0.0s
[Parallel(n_jobs=1)]: Done 3 out of 3 | elapsed: 0.5s finished
0.9858333333333333
```

Over 98.5%, not bad for a first try! :) However, remember that we are using the "easy" dataset. You can try with the harder datasets, the results won't be so amazing. You would have to try multiple models, select the best ones and fine-tune them using cross-validation, and so on.

But you get the picture, so let's stop now, and just print out the precision/recall we get on the test set:

```
from sklearn.metrics import precision_score, recall_score

X_test_transformed = preprocess_pipeline.transform(X_test)

log_clf = LogisticRegression(solver="lbfgs", max_iter=1000, random_state=42)
log_clf.fit(X_train_transformed, y_train)

y_pred = log_clf.predict(X_test_transformed)

print("Precision: {:.2f}%".format(100 * precision_score(y_test, y_pred)))
print("Recall: {:.2f}%".format(100 * recall_score(y_test, y_pred)))

Precision: 95.88%
Recall: 97.89%
```