



Singleton Pattern

Shin-Jie Lee (李信杰)

Associate Professor

Computer and Network Center

Department of CSIE

National Cheng Kung University



Design Aspect of Facade

the sole instance of a class



Outline

- ☐ Chocolate Boiler Requirements Statements
- ☐ Initial Design
- ☐ Recurrent Problems
- ☐ Intent
- ☐ Singleton Pattern Structure
- ☐ Singleton with Multi-threading Issues



Chocolate Boiler

Shin-Jie Lee (李信杰)

Assistant Professor

Computer and Network Center

Department of CSIE

National Cheng Kung University



Requirements Statements

- ☐ A chocolate boiler is used to boil chocolate.
- ☐ Before boiling chocolate with the boiler, you have to make sure that the boiler is now empty and then fill chocolate in. Besides, you can't boil chocolate again while the chocolate has already been boiled.
- ☐ After boiling, it is time to drain out the boiled chocolate and make the boiler empty again.
- ☐ In order to prevent some unexpected situation, it is not allowed to have multiple instances of the chocolate boiler in the system.



Requirements Statements₁


- ❑ A chocolate boiler is used to boil chocolate.

ChocolateBoiler
+ChocolateBoiler() +boil()



Requirements Statements₂


- ❑ Before boiling chocolate with the boiler, you have to make sure that the boiler is now empty and then fill chocolate in. Besides, you can't boil chocolate again while the chocolate has already been boiled.





Requirements Statements₃


- ❑ After boiling, it is time to drain out the boiled chocolate and make the boiler empty again.






Requirements Statements₄

- ❑ In order to prevent some unexpected situation, it is not allowed to have multiple instances of the chocolate boiler in the system.





Initial Design





Recurrent Problem

- ❑ It's important for some classes to have exactly one instance and ensure that the instance is easily accessible.
- ❑ A global variable makes an object accessible, but it doesn't keep you from instantiating multiple objects.




Intent

- ❑ Ensure a class only has one instance, and provide a global point of access to it.




Singleton Structure₁





Singleton Structure₂






Singleton Structure₃

	Instantiation	Use	Termination
Singleton	Singleton creates itself and make sure there is only one instance.	Client gets the unique instance of Singleton from Singleton, and performs its operation(s).	Don't Care



Singleton with Multi-threading Issues₁

❑ **Issue:** In a multi-threading situation, if more than one thread request Singleton's instance, it may result in multiple instances which violates Singleton's intent.





Singleton with Multi-threading Issues₂

❑ Solution 1: Synchronizing the getInstance() method

This keyword in Java permits only one thread to enter the method at a time.

```
public static synchronized ChocolateBoiler getInstance() {  
    if (instance == null) {  
        instance = new ChocolateBoiler();  
    }  
    return instance;  
}
```

However, if the instance has been created already, it doesn't make sense to allow only one thread to obtain the existing instance at the a time.

ChocolateBoiler
-empty: boolean -boiled: boolean <u>-instance: ChocolateBoiler</u>
-ChocolateBoiler() <u>+getInstance(): ChocolateBoiler</u> +boil() +fill() +drain() +isEmpty() +isBoiled()




Singleton with Multi-threading Issues₃

❑ Solution 2: Eager creation

The instance is created when loading the ChocolateBoiler class, so the getInstance() method just return the early created instance to client.

```
public static ChocolateBoiler getInstance() {  
    return instance;  
}
```

It is a tradeoff to apply this approach if a Singleton instance occupies a huge amount of memory and is not needed so often.





Singleton with Multi-threading Issues₄

❑ Solution 3: Synchronizing the getInstance() method with double-checked locking

This statement in Java permits only one thread to enter this block at a time. If the instance is not created yet, the critical creation block allows only one thread to enter.

If the instance has been created, just return the existing instance without any synchronization.

Check nullity again in order to prevent creating instance more than once.

```
public static ChocolateBoiler getInstance() {  
    if (instance == null) {  
        synchronized (ChocolateBoiler.class) {  
            if (instance == null) {  
                instance = new ChocolateBoiler();  
            }  
        }  
    }  
    return instance;  
}
```

ChocolateBoiler
-empty: boolean -boiled: boolean <u>-instance: ChocolateBoiler</u>
-ChocolateBoiler() <u>+getInstance(): ChocolateBoiler</u> +boil() +fill() +drain() +isEmpty() +isBoiled()