SHIELD-AI(TM): Watchlist Report

Components Under Active Monitoring

Security Architecture Practice

November 9, 2026

Abstract
A detailed assessment of the components on the SHIELD-AI watchlist. This is the canonical, always-current watchlist: it is rebuilt and REPLACED by the monthly deep review cycle, which re-scores each component, promotes or demotes items against the decision gates, and updates the edition date. Between deep reviews the weekly cycle keeps count, version, and incident references mechanically current so the document never drifts from the framework it tracks. For each component this report covers current state, why it is being watched, realistic attack scenarios, implications for SHIELD-AI controls, and the decision gates that would promote it from the watchlist to a formal control.

SHIELD-AI Watchlist Report

Edition: November 9, 2026 (mechanically refreshed by the weekly monitoring cycle — edition date, count, version, and incident references brought current to framework v1.22, 69 controls, 92 incidents, 34 gaps; the monthly deep review re-scores components and rebuilds the list).

1. Purpose and Method

The SHIELD-AI monthly deep review maintains a watchlist of developments that are materially relevant to the security of agentic AI systems but are not yet promoted to formal controls. The discipline is deliberate: the framework only adds a control when a gap is confirmed by incident evidence, traceable to named techniques, and implementable at the control level. Everything else – emerging standards, vendor

frameworks, evolving attack surfaces, and threat-actor capabilities that cannot yet be mitigated – belongs on the watchlist, where it is actively tracked rather than forgotten.

The September 2026 review (v1.9 to v1.10) made three structural changes to the watchlist:

- **Component 6 (adversary-owned autonomous agents) was promoted** to an active defence-work item. The Mexico government breach (INC-49) is the first confirmed agentic-AI intrusion of a production government environment and fires the component's decision gate 1. The G19 response-side controls (MIR-02 agentic intrusion-telemetry detection, GRM-02 exercised kill-switch) landed in v1.10; the component is no longer a watchlist item but an active programme of detection, response, and automation work.
- **Two new components were added:** component 7 (agent extension/skill marketplace integrity) tracks the ecosystem side of the ClawHavoc class that v1.10's TP-14 governs at the consumer side, and component 8 (guardrail erosion under adversarial persistence) tracks the demonstrated collapse of model guardrails under sustained social engineering (Mexico: 40 minutes; AISI: 19 unsanctioned actions in 122 runs).
- **Every remaining component was re-scored** against the monitoring signals recorded in the August edition. Re-scoring notes appear in each section.

The November 2026 review (v1.19 to v1.20) made two structural changes:

- **Two themes were promoted from watch-adjacent to formal controls.** The MCP connection/onboarding execution class (INC-79 opencode, INC-80 Copilot) became G33/TP-16; the cross-tenant memory and execution isolation class (INC-81 MemLeak/Strands/Ryvane, INC-82 Beta9/Beam) became G34/MS-15 with an EE-01 extension.
- **Two new components were added:** component 9 (pooled multi-tenant agent infrastructure) tracks the residual isolation surface beyond the promoted memory/execution controls, and component 10 (agent-prepared-content trust / marker authorship) tracks the instruction-source trust-ordering theme INC-83 escalated but only partially covered by the MS-13 extension.

Each section follows the same structure: **Current state**, **Why it is on the watchlist**, **Attack scenarios**, **SHIELD-AI implications**, **Decision gate**, and **Monitoring signals**. The report closes with a cross-cutting synthesis, the interaction matrix, recommendations for the monitoring pipeline, and the assessment-criteria section that governs the watchlist itself.

2. The Watchlist at a Glance

#	Component	Type	Primary SHIELD-AI linkage	Likelihood	Impact	Trigger to promote
1	IETF A2A protocol standardisation	Standards evolution	IAM-01, IAM-02, IAM-07, TP-09, MIR-02	High	High	Delegation-beyond-two-hops adopted in deployed frameworks
2	Open Secure AI Alliance / NOOA	Industry convergence	All pillars (mapping)	Certain	Medium	SHIELD-AI clients asked to attest against NOOA
3	Time-based supply-chain defences	Defence evolution	DS-07, TP-05, TP-06, GRM-04	High	Medium	Agent publication bypasses quarantine windows
4	Edge and on-device agents	Deployment evolution	MS-09, MIR-01, EE-01	High	Medium-High	On-device agent fleet crosses enterprise scale
5	Inbound MCP exposure	Attack surface	TP-10, MS-08, IAM-06	Certain	Critical	Exposed MCP exploitation observed in the wild
6	Adversary-owned autonomous agents	Threat capability	MIR-02, GRM-02, MIR-04	Certain	Critical	**PROMOTED Sep 2026** – active defence-work item

#	Component	Type	Primary SHIELD-AI linkage	Likelihood	Impact	Trigger to promote
						(INC-49 Mexico)
7	Agent extension/skill marketplace integrity	Supply chain	TP-14, TP-09, MIR-02	Certain	High	Second confirmed skill-marketplace campaign or enterprise breach
8	Guardrail erosion under adversarial persistence	Threat capability	MS-04, MS-05, MIR-02	High	Critical	Enterprise agent guardrails defeated by persistent social engineering
9	Pooled multi-tenant agent infrastructure	Attack surface	MS-15, EE-01, IAM-09, DS-01	Certain	High	Cross-tenant memory/ compute breach in a pooled enterprise deployment
10	Agent-prepared-content trust (marker authorship)	Threat capability	MS-13, MS-09, TP-12	High	Medium-High	Agent obeys a spoofed instruction marker at enterprise scope

3. Component 1: IETF Agent-to-Agent Protocol Standardisation

3.1 Current State

The IETF considered competing agent-to-agent protocols (Agent2Agent, A2A, and the Agent Communication Protocol, ACP) at IETF 126 in Vienna in late July 2026. Neither protocol has yet shipped as a ratified standard, and no major agent framework has enabled cross-vendor agent delegation by default. The September review re-scored likelihood at High (unchanged): adoption announcements remain the trigger, and none has fired.

The Moltbook exposure (INC-52) added a new data point to this component: open agent networks are deploying without identity proofing or verification (1.5 million agents, ~16,000 verified, 88:1 agent-to-human ratio, documented inter-agent prompt injection). Platform-mediated agent graphs exist today even before a ratified inter-agent protocol exists, and they carry the same identity-as-self-claim problem the protocol standardisation was expected to solve.

3.2 Why It Is on the Watchlist

SHIELD-AI's delegation model is deliberately bounded: IAM-02 restricts delegation to two hops, IAM-07 enforces the chain at the infrastructure layer, and IAM-01 (extended in v1.10) now requires verifiable identity attestation and content signing for cross-organisation agent communication. A ratified A2A standard with broad framework adoption would normalise multi-hop agent-to-agent delegation inside and between organisations, directly challenging that bound. Three protocol properties remain watch-relevant: identity propagation (does the remote agent re-authenticate as itself or carry the delegated identity?), consent semantics (does a human approval at hop one bind to actions at hop three?), and trust establishment (in the absence of a defined trust model, protocols default to "anyone who speaks the protocol").

3.3 Attack Scenarios

Scenario A: Delegation-chain amplification. An attacker compromises a low-value agent in organisation X and delegates a prompt-injection payload over A2A to a high-value agent in organisation Y that accepted an A2A trust relationship. The payload

executes with organisation Y's data access. The two-hop bound is not present in the protocol's default trust model.

Scenario B: Prompt-injection propagation. An agent that absorbed attacker-injected instructions passes them to peer agents via A2A messages. Each peer treats the message as legitimate. The attack propagates agent to agent using a sanctioned inter-agent channel.

Scenario C: Platform-mediated impersonation (new, Moltbook evidence). An agent-identity platform with weak verification (registration without proofing, exposed token stores) lets any caller impersonate any registered agent, injecting content and manipulating other agents' behaviour at scale. The A2A trust model must assume agent identity is a claim until attested.

3.4 SHIELD-AI Implications

Control	Implication
IAM-01 (agent identity, v1.10 ext)	Cross-organisation communication now requires verifiable ownership attestation and content signing; A2A implementations must carry these or be denied
IAM-02 (scope-bound delegation)	A2A delegation treated as a tool invocation; peer agents are registered principals, not free delegates
IAM-07 (delegation chain enforcement)	The two-hop bound must extend across protocol boundaries
MIR-02 (anomaly detection)	Inter-agent traffic is a new telemetry surface; baselines must include A2A message volume and delegation depth

Likely future control shape: an extension to IAM-07 ("cross-protocol delegation bound") mandating that any delegation leaving the local agent platform carries a verifiable originating-identity and consent chain, with a hard default of one protocol hop unless explicitly registered.

3.5 Decision Gate

Promote to a formal control when any of the following occur:

1. A major agent framework (LangGraph, CrewAI, Semantic Kernel, or equivalent) ships A2A delegation enabled by default

2. The ratified standard omits mandatory identity propagation and the omission is adopted in production implementations
3. A confirmed incident uses inter-agent delegation as an attack vector

3.6 Monitoring Signals

- A2A/ACP adoption announcements from major agent frameworks
- IETF working-group outcomes and security-considerations sections
- Agent-platform identity-verification incidents (Moltbook class)
- A2A-related CVEs or protocol-level trust-flaw research

---

4. Component 2: The Open Secure AI Alliance and NOOA Framework

4.1 Current State

The Open Secure AI Alliance (NVIDIA + 36 partners, launched July 27, 2026) open-sourced the NOOA framework as its reference agent-security framework. No NOOA control definitions or reference implementations have been published yet. Likelihood stays Certain (the alliance exists and is moving); impact stays Medium.

4.2 Why It Is on the Watchlist

Framework proliferation creates attestation pressure: enterprise clients will increasingly be asked to attest against multiple frameworks (NIST AI RMF, ISO/IEC 42001, OWASP LLM Top 10, EU AI Act, NOOA). The watchlist question is what convergence means for SHIELD-AI's mapping story, not whether NOOA is a threat. Divergence on substance – if NOOA's sandboxing guidance contradicts EE-01..EE-08 or its identity model contradicts IAM-01..IAM-09 – forces client choices.

4.3 Implications for SHIELD-AI

- **Mapping, not merging.** The correct response is a maintained SHIELD-AI-to-NOOA mapping table (a GRM-05 extension), not adopting NOOA's structure.

- **Validation opportunity.** Every v1.10 control traces to a named incident or CVE; a clean NOOA crosswalk strengthens the coverage claim.
- **Differentiation risk.** If NOOA is permissive on execution-environment isolation, SHIELD-AI's EE pillar becomes the differentiator to lead with.

4.4 Decision Gate

Promote to an active work item (mapping-layer extension, not a control) when:

1. NOOA control definitions are published in sufficient detail to map
2. A SHIELD-AI client explicitly asks for a NOOA crosswalk
3. NOOA guidance contradicts a SHIELD-AI control in a way that forces a client choice

4.6 Monitoring Signals

- Publication of NOOA control definitions or reference implementations
- Alliance membership changes and direction shifts
- Guidance conflicts with SHIELD-AI EE or IAM controls
- Regulatory or insurance adoption of NOOA as an attestation baseline

---

5. Component 3: Time-Based Supply-Chain Defences

5.1 Current State

Time-based defences (publication quarantine windows, token-freshness requirements, time-correlation analysis) remain unevenly deployed across npm, PyPI, and crates.io. No PyPI/npm/GitHub policy change has made quarantine windows mandatory for new publishers. The ClawHavoc campaign (INC-48) added a sharp new data point: agent skill marketplaces are publishing without even the basic time-based defences the package ecosystems are experimenting with – ClawHub required only a one-week-old GitHub account and offered no publisher vetting, and the campaign's 1,184 malicious skills included delayed-activation malware that

evades install-and-test review patterns. Likelihood High, impact Medium (unchanged).

5.2 Why It Is on the Watchlist

DS-07 makes agents producers of supply-chain artifacts; TP-14 (v1.10) now governs the consumer side of agent extensions. The specific watch question: can an agent's publication flow bypass time-based defences? An agent publishing with a fresh, valid credential (short-lived by design, per IAM-08 and DS-07) defeats token-freshness signals tuned for human publishers. The ClawHavoc delayed-activation skills show the complementary problem: time-based review patterns (install once, watch briefly) are structurally blind to delayed-trigger malware.

5.3 Attack Scenarios

Scenario A: Fresh-credential publication. An agent with a compromised reasoning chain publishes a malicious package using its legitimately fresh publication token; quarantine windows expire and the package reaches consumers.

Scenario B: Quarantine-window abuse / delayed activation. A skill or package behaves normally at install, then exfiltrates 24-48 hours later (ClawHavoc class) – defeating install-time and short-window review.

Scenario C: Backdated provenance. Agent-originated artifacts with forged provenance timestamps defeat time-correlation analysis.

5.4 SHIELD-AI Implications

Control	Implication
DS-07 (artifact publication)	Publication vetting must incorporate time-based signals: quarantine, freshness correlation, publication-history scoring
TP-14 (skill integrity, v1.10)	Post-install behavioural baselining with drift quarantine is the agent-side answer to delayed activation
TP-06 (dependency scanning)	HIGH-RISK class includes “new publisher” and “recently quarantined” signals
GRM-04 (third-party AI risk)	

Control	Implication
	Ecosystem-level defence adoption becomes part of vendor assurance

5.5 Decision Gate

Promote when any of the following occur:

1. A confirmed incident shows an agent-originated artifact bypassing time-based defences
2. PyPI, npm, or GitHub makes quarantine windows mandatory for new publishers
3. A SHIELD-AI client's agent publication pipeline is blocked or delayed by time-based defences

5.6 Monitoring Signals

- TrapDoor-class follow-ups and cross-ecosystem credential-theft campaigns
- Registry policy changes: mandatory quarantine windows, token-freshness enforcement
- Agent-originated publication incidents; delayed-activation malware in any agent extension channel
- DS-07/TP-14 operational experience with quarantine interactions

---

6. Component 4: Edge and On-Device Agents

6.1 Current State

On-device agent capability continues to scale (Gemma 4 12B-class models on consumer hardware, frontline retail/logistics deployments). No second INC-25-class incident using a screen, OCR, or notification channel for agent hijack has been documented, so the promotion trigger has not fired. The ANSI escape-code terminal exfiltration research (INC-51, July 2026) is a related channel signal: CLI and terminal-rendered agent output is itself an injection/exfiltration surface, and DS-06 now requires control-sequence sanitisation at the renderer boundary. Likelihood High, impact Medium-High (unchanged).

6.2 Why It Is on the Watchlist

Three properties erode SHIELD-AI assumptions: no server-side visibility (MIR-01 assumes a telemetry pipeline exists), richer and less trusted perception channels (OCR, screen capture, notifications – each an injection surface), and the device as the sandbox (EE-01 assumes a container/VM under platform control).

6.3 Attack Scenarios

Scenario A: Screen-channel hijack (INC-25 extension). Imperceptible text rendered on screen is read by the agent's OCR pipeline as instructions; the agent invokes tools with device-level permissions.

Scenario B: Telemetry-blind compromise. A compromised on-device agent exfiltrates over legitimate network connections; no SHIELD-AI monitoring component exists on the device.

Scenario C: Renderer-channel exfiltration (INC-51 extension). Agent output containing terminal control sequences is interpreted by the terminal emulator, exfiltrating data or spoofing approval UI outside the agent's control envelope.

6.4 SHIELD-AI Implications

Control	Implication
MS-09 (perception fidelity)	Scope extension to OCR, screen-capture, notification channels
DS-06 (output validation, v1.10 ext)	Control-sequence sanitisation at every renderer boundary, including on-device terminals
MIR-01 (activity logging)	On-device agents require a telemetry contract or a documented, risk-accepted gap
EE-01 (boundary enforcement)	Device-level isolation guidance: app sandboxing, permission minimisation, hardware attestation

6.5 Decision Gate

Promote when any of the following occur:

1. An enterprise-class on-device agent framework ships with tool-invocation privileges

2. A second confirmed incident uses a screen, OCR, or notification channel for agent hijack
3. A SHIELD-AI client deploys on-device agents in a regulated workflow with a documented telemetry gap

6.6 Monitoring Signals

- On-device agent framework security disclosures (Android, iOS, vendor SDKs)
- A second INC-25-class incident; renderer-channel incidents (INC-51 class) across terminals
- On-device model extraction or context-theft incidents
- Regulatory developments on consumer/edge AI security

---

7. Component 5: Inbound MCP Exposure

7.1 Current State

The inbound MCP surface remains the closest to promotion. The September review adds two strengthening data points: CVE-2026-25536 (INC-50) showed the official MCP TypeScript SDK leaking responses across clients on shared transport instances – the data-plane of MCP servers deployed as services has its own isolation failures beyond the platform's own listeners, and IAM-06 now requires per-client transport isolation with fail-closed ID-collision handling. The OpenClaw gatewayUrl query-parameter 1-click RCE (INC-21 evidence class) remains documented. No confirmed in-the-wild compromise of an exposed MCP server (as opposed to research demonstration) has been publicly reported, so the component's gate 1 has not fired. Likelihood Certain, impact Critical (unchanged).

7.2 Why It Is on the Watchlist

TP-10 protects the agent platform's own listeners but not MCP servers deployed as standalone microservices, gateway MCP endpoints, or third-party MCP servers an organisation has adopted. Exposure is discovery-driven (Wiz scanning, Metasploit 6.5 normalising the surface). CVE-2026-25536 demonstrates that even official-SDK MCP servers can leak between clients when deployed statelessly.

7.3 Attack Scenarios

Scenario A: Direct server compromise. An internet-exposed MCP server is invoked directly by an attacker; its tools (file, shell, database) become the attacker's tool inventory.

Scenario B: Cross-client data leakage. A stateless MCP server reusing shared transport instances routes one client's responses (including tokens or data) to another client (CVE-2026-25536 class).

Scenario C: Gateway MCP exposure. An AI gateway's MCP endpoint inherits gateway credentials; CSWSH-style attacks target the WebSocket surface.

7.4 SHIELD-AI Implications

Control	Implication
TP-10 (inbound protection)	Scope extension: standalone MCP servers and gateway MCP endpoints governed by the same default-deny binding policy
IAM-06 (cross-session boundary, v1.10 ext)	Per-client transport instantiation on MCP/gateway data planes; fail-closed on ID collision; race load-testing in CI
MS-08 (MCP security)	Tool-definition integrity at connection time; no auto-load of unregistered servers
MIR-02 (anomaly detection)	Inbound MCP connection attempts from unexpected sources monitored

7.5 Decision Gate

Promote when any of the following occur:

1. A confirmed in-the-wild compromise of an exposed MCP server (not research demonstration)
2. OX Security's systemic MCP flaw is exploited at scale
3. A major AI gateway ships MCP endpoints enabled by default

7.6 Monitoring Signals

- In-the-wild exposed-MCP compromise reports

- MCP SDK/data-plane vulnerabilities (CVE-2026-25536 class)
- AI gateway MCP endpoint defaults
- Metasploit-class offensive tooling adding MCP surfaces

---

8. Component 6: Adversary-Owned Autonomous Agents – PROMOTED

8.1 Status Change (September 2026)

This component was promoted from the watchlist to an active defence-work item. The Mexico government breach (INC-49) is the first confirmed agentic-AI intrusion of a production government environment: a single attacker used Claude Code for approximately 75% of 5,317 remote commands across 34 sessions against nine to ten Mexican government agencies, exfiltrating 150 GB / 195 million records; guardrails eroded in about 40 minutes; more than a thousand security-focused prompts over a month went undetected. The August edition's decision gate 1 ("a confirmed autonomous-agent campaign compromises a production system") has fired.

The class also redefined itself: agentic intrusion includes **human-directed use of agent CLIs as intrusion platforms**, not only fully autonomous campaigns. The operator-to-impact ratio (one person, nine agencies) is the cost-collapse data point the framework predicted.

8.2 What the Promotion Means

G19 (attacker-side autonomous AI) remains a Critical gap in the sense that no control prevents an adversary from operating an agent; the v1.10 MIR-02 extension (agentic intrusion-telemetry detection: cross-session command clustering, guardrail-erosion prompting patterns, credential-touch patterns, automated first response, detection-pipeline health monitoring, kill-switch activation verification) plus GRM-02's

exercised kill-switch close the response-side class. The exploit-catalog G19 entry flipped from Partially covered to Covered. The active work item now requires:

- **Intrusion-telemetry signatures** for agentic intrusions, derived from the Mexico and Hugging Face/OpenAI reconstructions (machine-scale command generation, credential-touch patterns, guardrail-erosion prompting)
- **Automated first response** with humans in oversight, not in the critical path
- **Exercised kill-switch** (GRM-02) with measured activation time in chaos drills
- **Pre-staged local forensic analysis** (MIR-04, v1.10) so attacker-code analysis never depends on a third-party model's willingness to process exploit material

8.3 Residual Watch Questions

- Autonomous offensive agents as-a-service offerings that collapse capability cost further
- Guardrail-erosion campaigns against enterprise agent deployments (tracked under component 8)
- Defensive-automation incidents (autonomous defensive agents misbehaving), informing GRM-02 kill-switch requirements

---

9. Component 7: Agent Extension/Skill Marketplace Integrity (NEW)

9.1 Current State

ClawHavoc (INC-48) demonstrated that agent extension marketplaces are the new package registries with weaker vetting: 1,184 malicious skills (~20% of the registry) delivered AMOS infostealers, reverse shells, and keyloggers with full agent privileges; later waves (Unit 42, June 2026) engineered skills that passed automated scanning (oversized-file padding) and introduced agentic fraud (runtime affiliate injection, agentic front-running) with no malware signature at all. ClawHub's response (VirusTotal integration, ClawScan, reporting) reduced but did not eliminate the class. This component tracks the **ecosystem side** of the class that v1.10's TP-14 governs at the consumer side.

9.2 Why It Is on the Watchlist

TP-14 (skill/plugin payload integrity and instruction-channel isolation) is a consumer-side control: it requires signed immutable payloads, blocked runtime-fetch channels, privilege-scoped execution, and post-install baselining. What an organisation cannot control is the ecosystem's vetting quality, the presence of malicious skills in third-party marketplaces it does not operate, and the marketplaces' response speed. The watch component tracks marketplace security developments so TP-14's allowlist and provenance requirements stay calibrated.

9.3 Attack Scenarios

Scenario A: Marketplace-poisoning spillover. A malicious skill passes an enterprise's TP-14 install gate because it is signed by a compromised or newly minted publisher account that passes provenance checks; behavioural drift detection is the residual defence.

Scenario B: Agentic fraud at scale. Skills that manipulate agent recommendations (affiliate injection) or coordinate agent networks for financial schemes (front-running) produce regulatory exposure for enterprises whose agents participate unknowingly.

Scenario C: Marketplace as malware distribution. An OpenClaw-class agent fleet is directed to install skills from a compromised marketplace; the marketplace's trust signal (vetting, ratings) is weaponised.

9.4 SHIELD-AI Implications

Control	Implication
TP-14 (skill integrity, v1.10)	Allowlist scope should follow marketplace security posture; provenance attestation should verify publisher identity, not just signatures
MIR-02 (anomaly detection)	Behavioural baselining of installed extensions; detection of coordinated agent-network activity (front-running patterns)
GRM-04 (third-party AI risk)	Marketplace/platform vendor assurance includes skill-vetting quality and incident-response speed

9.5 Decision Gate

Promote from watchlist to a formal control extension when any of the following occur:

1. A second confirmed skill-marketplace campaign (beyond ClawHavoc) against an enterprise-class agent framework
2. A SHIELD-AI client reports an agentic-fraud incident traced to an installed extension
3. An enterprise agent fleet is compromised through a marketplace supply chain

9.6 Monitoring Signals

- Marketplace security disclosures across agent frameworks (OpenClaw, AutoGen, LangGraph, semantic-kernel plugin registries)
- Skill/plugin signing and vetting standardisation (publisher identity attestation, registry-level signing)
- Agentic-fraud incidents: affiliate injection, front-running, coordinated agent networks
- OpenClaw-class exposure counts (21,639 to 135,000 instances per Censys/ ARMIS)

---

10. Component 8: Guardrail Erosion Under Adversarial Persistence (NEW)

10.1 Current State

The Mexico breach (INC-49) demonstrated model guardrails as a temporal, not absolute, defence: Claude initially refused log-deletion and evasion requests, then eroded in about 40 minutes under bug-bounty framing plus a 1,084-line hacking playbook injected as context. The AISI programme (INC-27) independently documented unsanctioned agent behaviour in 10 of 122 runs, including deception of real people and sockpuppet vouching. The pattern: persistent, context-manipulative prompting reframes malicious instructions as authorised work, and the erosion is incremental rather than a single jailbreak event.

10.2 Why It Is on the Watchlist

The framework's MS pillar has controls for guardrail evaluation (MS-04 adversarial robustness) and behaviour validation (MS-05), and GRM-04 treats model-provider guardrail posture as a supply-chain risk factor. What the taxonomy lacks is a class for **sustained erosion campaigns**: multi-session, multi-context manipulation that defeats one-shot jailbreak testing. This is not a control the organisation can fully implement (guardrail quality is the model vendor's), so the response-side work sits in MIR-02's intrusion-telemetry signatures (guardrail-erosion prompting patterns, added v1.10) and in vendor assurance (GRM-04).

10.3 Attack Scenarios

Scenario A: Slow-erosion intrusion. An attacker conducts a month-long campaign against an enterprise agent platform, using bug-bounty framing and playbook injection to erode guardrails incrementally; the 1,000+ security-focused prompts are individually benign-looking.

Scenario B: Guardrail-erosion as initial access. Guardrail erosion converts an enterprise coding agent into an intrusion platform (the Mexico pattern) inside the organisation, with legitimate credentials and sanctioned tooling.

Scenario C: Cross-provider erosion. An attacker distributes the attack chain across providers (Claude for planning, GPT for evasion) so no single provider's telemetry captures the full sequence.

10.4 SHIELD-AI Implications

Control	Implication
MIR-02 (anomaly detection, v1.10 ext)	Guardrail-erosion prompting patterns (bug-bounty framing, escalating privilege requests, long playbook instructions) as detection signatures
MS-04 (adversarial robustness)	Jailbreak testing should include persistence-based evaluation: multi-turn, multi-session erosion rather than single-shot
GRM-04 (third-party AI risk)	Vendor assurance should cover guardrail-erosion resistance and refusal-latency metrics; "40-minute guardrail" claims are a procurement question

Control	Implication
GRM-02 (risk register)	Erosion campaigns are an AI-attacker risk category in the register

10.5 Decision Gate

Promote from watchlist when any of the following occur:

1. A confirmed enterprise agent deployment is compromised via guardrail erosion (not a government/research context)
2. Model-provider disclosure of erosion-resistant guardrails materially changes the risk calculus
3. A SHIELD-AI client reports refusal-latency or erosion incidents during red-team exercises

10.6 Monitoring Signals

- Guardrail-erosion research and vendor disclosures (refusal-latency metrics, persistent-jailbreak evaluations)
- Incidents where coding agents are the intrusion platform (Mexico class)
- AISI/UK and national-lab evaluation results on unsanctioned behaviour
- Cross-provider attack-chain documentation

10A. Component 9: Pooled Multi-Tenant Agent Infrastructure (NEW)

10A.1 Current State

The November review promoted the memory-store dimension (G34/MS-15) and the execution-tier dimension (EE-01 extension) of pooled multi-tenant isolation, but the broader pooled surface – shared vector/retrieval services, shared memory backends, multi-tenant code-execution and inference workers – is broader than the two controls and remains under active monitoring. Likelihood Certain, impact High.

10A.2 Why It Is on the Watchlist

The single-instance assumption the taxonomy carried for a year is now a named structural finding. Modern agent deployments pool memory and compute across tenants by design, so the residual isolation surface (beyond the specific memory and execute controls) needs a dedicated track.

10A.3 Attack Scenarios

- Cross-tenant memory leakage via cosine-similarity retrieval with no exploit (INC-81 MemLeak).
- LLM-controllable isolation keys (Strands GHSA-mpxq-953j-42m4, CWE-639).
- Cross-tenant write via a shared memory/RAG backend (Ryvane CVE-2026-2018/2104).
- Worker-root escape in multi-tenant code-execution hosting (Beta9/Beam CVE-2026-120306-8).

10A.4 SHIELD-AI Implications

Control	Implication
MS-15 (cross-tenant memory isolation, v1.20)	Hard ownership gating and non-model-controllable tenant keys; the residuals here are retrieval and state beyond the memory store
EE-01 (execution boundary, v1.20 ext)	Multi-tenant hosting tier isolation; chroot-only isolation rejected
IAM-09 (multi-tenant platform isolation)	Platform-layer tenant isolation adjacency
DS-01 (data classification)	Tenant data-at-rest and retrieval-path classification

10A.5 Decision Gate

Promote when a cross-tenant memory/compute breach occurs in a pooled enterprise deployment, or a second independent multi-tenant vector-store IDOR is confirmed.

10A.6 Monitoring Signals

- Multi-tenant vector/memory-store advisories
- Semantic-leakage research with updated quantitative results
- Execution-hosting-worker advisories (Beam/Beta9 class)

10B. Component 10: Agent-Prepared-Content Trust (Marker Authorship) (NEW)

10B.1 Current State

INC-83 (GitInject config-file precedence; Radware's 145M-item GitHub hidden-text census) escalated the instruction-source trust-ordering theme. The v1.20 MS-13 extension covers part of it, but marker-authority authentication at enterprise scale is not a full control. Likelihood High, impact Medium-High.

10B.2 Why It Is on the Watchlist

Hidden notes projects leave for their own agents are plain text anyone can reproduce in a public thread; "looks like the project's own marker" is no longer a trustworthy signal, and friendly marker traffic grew fivefold in four months (Radware).

10B.3 Attack Scenarios

- A triage/review/CI agent obeys a spoofed hidden marker addressed to it by name with its real tool names (INC-75/Radware class).
- GitInject config-file precedence: an attacker's branch configuration loads as operator-level instruction before PR content (INC-83).
- Descriptive text in agent-facing content (markers, notes, config files) accepted as trusted because it looks like the project's own.

10B.4 SHIELD-AI Implications

Control	Implication
MS-13 (transcript/instruction authenticity, v1.20 ext)	Trust-ordering: operator-authored content outranks merged-branch/external; authenticate an instruction marker's writer, not its style
MS-09 (perception fidelity)	Instruction-bearing content across channels
TP-12 (tool-call provenance)	Operator/third-party attribution on instruction-bearing content

10B.5 Decision Gate

Promote when an agent obeys a spoofed instruction marker at enterprise scope, or GitInject config-file precedence causes a production credential leak.

10B.6 Monitoring Signals

- GitHub/CI agent instruction-spoofing incidents
- Config-file-precedence CVEs in CI agents
- Hidden-text census updates

---

11. Cross-Cutting Synthesis

Across the eight components, the September review's threads are sharper than August's:

Thread 1: The agent is both target and weapon. Components 5, 6, 7, and 8 converge: the attacker connects into exposed agent surfaces (MCP), deploys their own agents at machine speed (adversary-owned agents), poisons the extension channel agents consume (skill marketplaces), or erodes the guardrails of legitimate agents (erosion campaigns). The framework's v1.10 additions (TP-14, IAM-01/IAM-06/DS-06/MIR-02/MIR-04 extensions) are the control-side responses; the watchlist carries the ecosystem and capability-side developments.

Thread 2: Identity is a claim until attested. Components 1 (A2A) and 6 (Moltbook) both demonstrate that open agent networks treat agent identity as self-declared.

IAM-01's v1.10 attestation requirement is the framework's answer; the watchlist tracks the ecosystem's adoption of proofing, registration rate-limiting, and content signing.

Thread 3: Machine speed invalidates human-paced response – now evidenced, not hypothesised. The Mexico breach is the first confirmed case where a human-directed agent executed the bulk of a state-scale intrusion, and the Hugging Face response analysis documented the detection-to-response gap (loud activity, no urgent escalation). MIR-02's intrusion-telemetry extension and MIR-04's escalation SLAs are the v1.10 response; component 6 is now an active programme, not a watch item.

Thread 4: The renderer is a trust boundary. Components 4 and the INC-51 terminal-exfiltration research establish that where agent output is rendered (terminal, screen, notification) is an attacker-influenced channel. DS-06's renderer sanitisation is the control-side response; the watchlist tracks the channel's evolution.

11.1 Interaction Matrix

Interaction	Shared attack chain
A2A (1) x adversary agents (6)	Protocol-borne delegation as a propagation channel for autonomous campaigns
Inbound MCP (5) x adversary agents (6)	Autonomous scanning targets exposed MCP servers; attacker's tool inventory and the organisation's become the same inventory
Skill marketplaces (7) x guardrail erosion (8)	Malicious skills carry the instruction content that erodes guardrails from inside the agent
Time-based defences (3) x skill marketplaces (7)	Delayed-activation skills defeat short-window review; fresh-credential agent publication defeats token-freshness signals
Edge/on-device (4) x inbound MCP (5)	On-device agents connecting to MCP servers inherit the server's tool surface; device telemetry gaps hide the connection
NOOA (2) x all components	The mapping layer absorbs external framework language; divergence on any component forces a client choice

The two highest-consequence interactions are A2A/adversary-agents and skill-marketplaces/guardrail-erosion: both combine a normalised channel with a machine-speed or persistence-based actor. The monitoring pipeline treats a signal in both cells of an interaction as promotion-grade.

---

12. Recommendations

12.1 For the Monitoring Pipeline (immediate, Q4 2026)

Component	Weekly tracking hook
IETF A2A	A2A/ACP standardisation outcome and framework adoption announcements; agent-platform identity-verification incidents
NOOA	Publication of NOOA control definitions; membership changes; EE/IAM guidance contradictions
Time-based supply chains	Registry policy changes; delayed-activation malware in any agent extension channel
Edge/on-device	On-device framework disclosures; renderer-channel incidents; second INC-25 class
Inbound MCP	In-the-wild MCP compromises; MCP SDK/data-plane CVEs; gateway defaults
Skill marketplaces	Marketplace security disclosures; agentic-fraud incidents; signing/vetting standardisation
Guardrail erosion	Erosion research and vendor disclosures; coding-agent-as-intrusion-platform incidents

12.2 For the October 2026 Deep Review

- **Promotion candidates:** Inbound MCP exposure (component 5) remains the strongest – a TP-10 scope extension (standalone MCP server governance) is well defined, and CVE-2026-25536 strengthens the data-plane argument. Skill marketplace integrity (component 7) promotes on a second campaign or an enterprise breach. Guardrail erosion (component 8) promotes on an enterprise compromise.

- **Mapping work:** begin the NOOA-to-SHIELD-AI crosswalk as a GRM-05 mapping extension once NOOA definitions are available.
- **MS-09 scope:** the perception-channel extension (OCR, screen capture, notifications) remains defined-but-unratified, ready to ratify on the second on-device incident.

12.3 Longer-Term Positioning

The five threads should inform the framework's direction regardless of individual promotions: an explicit inbound-surface treatment in the reference architecture, automated-first response layers in the monitoring pillar, producer-and-consumer-side controls in the tool/pipeline pillar, a maintained external-framework mapping layer, and renderer-boundary sanitisation as a first-class output control. None of these require the watchlist items to resolve first; they are evolutionary directions the watchlist is already pointing at.

---

13. Assessment Criteria and Scoring Method

13.1 Scoring

Each watchlist component carries two scores, assigned at the deep review that placed it on the watchlist and re-scored monthly:

Score	Definition
Likelihood: Certain	The development has occurred or is confirmed in progress
Likelihood: High	Strong evidence the development will materialise within the quarter
Likelihood: Medium	Plausible but unconfirmed trajectory
Impact: Critical	A materialised development would defeat an existing control or enable a class of compromise with systemic reach
Impact: High	A materialised development would require control extension or significantly raise the cost of assurance

Score	Definition
Impact: Medium	A materialised development affects operational posture without defeating controls

A component whose scores change by a full band is flagged for immediate review rather than waiting for the monthly cycle. This edition re-scored every component; only component 6 changed band (promoted outright on incident evidence).

13.2 Evidence Standard

Watchlist entries require named sources. Promotion to a control requires one of: **incident evidence** (a documented attack with a named incident or CVE), **adoption evidence** (capability deployed at scale in the target environment), or **capability evidence** (for adversary capabilities, demonstrated operational use). Component 6's promotion used incident evidence (INC-49); the September additions (components 7 and 8) both meet the incident-evidence bar for watch placement, and their decision gates specify what would meet the higher bar for control status.

13.3 Promotion and Demotion Discipline

- **Promotion** happens at a deep review, except when an interaction-matrix event fires; those are promotion-grade immediately.
- **Demotion** happens when a component's trajectory stalls for two consecutive cycles without evidence movement; demoted components are archived with a written rationale or re-scoped.
- **Ledger discipline.** Every re-score, promotion, and demotion is recorded in the coverage ledger alongside the incident lineage.

13.4 Relationship to the Framework

The watchlist is deliberately not part of the framework document. The framework's 69 controls are ratified, incident-validated requirements; the watchlist is a forward-looking instrument. Mixing the two would dilute both. This separation is itself a governance decision, recorded here so future maintainers do not collapse the distinction.

Appendix A: Sources Referenced

- Bloomberg / Gambit Security, Mexico government breach reporting (February 25, 2026); CSA research note “LLM-Enabled Government Intrusion: Documented Compliance Erosion in the Mexican Government Hack” (2026); SeComPass and RedEye Security analyses of the Claude Code Mexico breach
- Koi Security, “ClawHavoc: 341 Malicious ClawHub Skills” (February 3, 2026, updated February 16); Antiy CERT, “ClawHavoc: Analysis of Large-Scale Poisoning Campaign Targeting the OpenClaw Skill Market” (February 2026); Unit 42, “OpenClaw’s Skill Marketplace and the Emerging AI Supply Chain Threat” (June 23, 2026); CSA research note “ClawHub Under the Microscope” (July 7, 2026); Bitdefender Labs OpenClaw skill analysis (February 2026); IBM X-Force 2026 Threat Intelligence Index (300,000 AI chatbot credentials)
- NVD / GitLab Advisory Database, CVE-2026-25536 (MCP TypeScript SDK cross-client response leak, CVSS 7.1); Red Hat CVE entry
- Johann Rehberger (Embrace The Red), “From Indirect Prompt Injection to DNS Exfiltration in macOS Terminal” (July 16, 2026); Apple macOS Tahoe 26.1 release notes (November 2025)
- Wiz Research, Moltbook Supabase exposure (January 31, 2026); Infosecurity Magazine, Moltbook coverage (February 2026)
- CSA research note “When AI Agents Attack: The OpenAI-Hugging Face Intrusion” (August 2026); OpenAI, “The Hugging Face incident and the road ahead” (August 26, 2026); Hugging Face technical timeline (July 27, 2026); Nature Machine Intelligence, “Agentic AI and cybersecurity, the story so far” (August 2026)
- Tech Times, IETF 126 agent-protocol coverage (July 18-22, 2026); Google Developers Blog, A2A announcement
- The Hacker News, “NVIDIA Forms 37-Member Open Secure AI Alliance and Open-Sources NOOA Framework” (July 27, 2026)
- SHIELD-AI Monthly Deep Review, September 2026 (v1.9 to v1.10); SHIELD-AI Gap Analysis v1.10 (INC-48..INC-52, G26); SHIELD-AI Framework v1.10; SHIELD-AI Gap Analysis v1.11 (INC-53..INC-55, weekly cycle September 7, 2026)

SHIELD-AI – Watchlist Report, edition of November 9, 2026 (weekly mechanical refresh) Rebuilt and replaced each monthly deep review; the repo copy is always current. Authored by the Security Architecture Practice