SHIELD-AI(TM): A Sovereign Australian Framework for Secure Agentic AI Deployment

Framework Definition and Reference Implementation

Security Architecture Practice

September 7, 2026

Abstract
A comprehensive framework for securing agentic AI systems in Australian enterprises and government, aligned with all relevant Australian regulatory and industry frameworks, and defined as a deployable component model with full implementation guidance.

Executive Summary

Australian enterprises and government agencies are racing to deploy agentic AI – autonomous systems that perceive, reason, act, and learn across enterprise environments. These systems introduce a fundamentally new attack surface that existing security frameworks (ISM, Essential Eight, NIST CSF, ISO 27001) were not designed to address. Agentic AI systems can execute multi-step workflows, invoke external tools, access enterprise data, generate code, and make operational decisions – each action a potential vector for compromise, data exfiltration, or unintended behaviour.

SHIELD-AI (Security and Holistic Integrity for Enterprise-Level Deployment of Artificial Intelligence) is a sovereign Australian framework purpose-built for securing agentic AI systems. It is:

- **Cloud-agnostic** – applies equally to AWS, Azure, Google Cloud, on-premise, and hybrid deployments
- **LLM-agnostic** – works with OpenAI, Anthropic, open-weight, or any model provider

- **Industry-agnostic** – relevant to banking, insurance, healthcare, critical infrastructure, and government
- **Fully aligned** with Australian regulatory frameworks including ASD ISM, Essential Eight, SOCI Act, APRA CPS 234/CPG 230, PSPF, and the Privacy Act 1988

The framework defines seven security pillars, four maturity levels, and a comprehensive control set mapped to existing Australian frameworks. It is designed to be explainable to CISO, CRO, COO, CIO, GC, and board stakeholders in under 30 minutes – because security frameworks that cannot be explained to decision-makers are frameworks that will not be adopted.

Alongside the framework, this document summarises the **deployable component model** through which the framework's controls are realised as concrete infrastructure. The full reference implementation – component inventory, reference architecture, policy decision points, request flows, telemetry pipeline, network boundaries, deployment topologies, and the L1-L4 component coverage map – is documented with a complete set of diagrams in the companion **Implementation Architecture** document (`framework/shield-ai-implementation-architecture.md`).

Part 1: The Case for an Australian Agentic AI Security Framework

1.1 The Agentic AI Security Gap

Traditional AI security has focused on model-level concerns: adversarial prompts, data poisoning, model inversion. Agentic AI introduces an entirely new class of risk because the AI system is no longer a stateless inference endpoint – it is an **active computational agent** with:

- **Tool access** – ability to read/write databases, APIs, file systems, and execute code
- **Multi-step reasoning** – chains of actions that compound risk across steps
- **Memory** – persistent state across sessions, enabling data aggregation and inference


- **Autonomous action** – decisions made without human-in-the-loop approval
- **Identity delegation** – the agent acts on behalf of a user, with that user's privileges

The OWASP Top 10 for LLM Applications (2025) identified prompt injection, insecure output handling, and excessive agency as critical risks. MITRE ATLAS catalogues attack techniques specific to AI systems. Both are valuable references, but neither provides a **comprehensive, implementable framework** that maps to Australian regulatory obligations.

1.2 Why Existing Frameworks Are Insufficient

Framework	Coverage	Agentic AI Gap
ASD ISM (1,081 controls)	Traditional infosec, system hardening, cloud	No AI-specific controls; no coverage of prompt injection, tool delegation, or agent identity
Essential Eight	Eight core mitigation strategies	Designed for commodity malware, not AI-specific threats
NIST AI RMF	AI risk management, governance	Not an implementable control framework; no technical controls
ISO/IEC 42001	AI management system	Management system standard, not security controls
OWASP LLM Top 10	AI-specific vulnerabilities	Threat taxonomy, not a control framework with maturity levels
SOCI Act/CIRMP	Critical infrastructure risk management	Obligations-based, not control-based

No existing framework addresses the unique combination of **AI-specific threats + Australian regulatory compliance + implementable technical controls + maturity progression**. SHIELD-AI fills precisely this gap.



[NEW] Sandbox/VM Escape as a cross-cutting layer above Governance — every pillar below can be breached via sandbox escape
Risk compounds upward: a Model compromise enables Tool abuse, which enables Data exfiltration

Risk compounds upward: a Model compromise enables Tool abuse, which enables Data exfiltration, which evades Identity controls if not monitored via Pipeline and Governance.

1.3 The Australian Regulatory Landscape

An Australian framework must demonstrably align with the regulatory frameworks that Australian enterprises and government agencies are already required to comply with:

ASD Information Security Manual (ISM)

- 1,081 controls across 21 guideline sections

- Mandatory for Australian Government agencies (PSPF Policy 8)
- Increasingly referenced by regulated entities under SOCI and APRA
- March 2026 edition includes “Guidelines for secure AI system development”
- July 2026 publications on defending against AI-enabled attacks

Five Eyes Agentic AI Guidance (May 2026)

- Jointly published by CISA, NSA, and the cyber agencies of Australia, Canada, New Zealand, and the United Kingdom (published on cyber.gov.au as “Careful Adoption of Agentic AI Services”)
- First coordinated multinational security guidance specifically for agentic AI systems
- Core recommendations align directly with SHIELD-AI controls: avoid broad/unrestricted access (IAM-02, IAM-08), isolate agents from sensitive systems and the wider network (EE-01, EE-02), maintain continuous monitoring of agent behaviour (MIR-01, MIR-02), and verify tool/plugin provenance before use (TP-01, TP-06, MS-03)
- Australian organisations adopting agentic AI are expected to apply this guidance as the baseline for secure adoption, making SHIELD-AI’s control mappings to it a demonstrable compliance advantage

Essential Eight (E8)

- Eight mitigation strategies at three maturity levels
- Maturity Level 1: Baseline (adversary uses commodity tradecraft)
- Maturity Level 2: Moderate (adversary invests more resources)
- Maturity Level 3: Advanced (adversary is highly resourced)
- Mandatory for Australian Government; recommended for all entities

Security of Critical Infrastructure (SOCI) Act 2018

- 11 critical infrastructure sectors
- Mandatory incident reporting (12 hours for critical, 72 hours for other)
- CIRMP (Critical Infrastructure Risk Management Program) rules
- Positive security obligations (duty to protect)

APRA CPS 234 / CPG 230

- Prudential standard for information security (APRA-regulated entities)
- Board accountability for security risk
- Mandatory incident notification within 72 hours
- CPG 230 provides guidance on managing security risks including AI

Protective Security Policy Framework (PSPF)

- Mandatory for Australian Government agencies
- Security governance, personnel security, physical security, information security
- Policy 8: Cyber security – references ISM compliance

Privacy Act 1988 / Australian Privacy Principles (APPs)

- 13 Australian Privacy Principles
- APP 11: Security of personal information
- OAIC guidance on AI and privacy (2024, updated 2025)
- Mandatory Notifiable Data Breaches (NDB) scheme

International Alignment

- EU AI Act (2024) – establishes risk categories for AI systems
- NIST AI RMF (January 2023) – risk management framework
- Singapore’s AI Verify – testing framework for AI
- UK’s AI Safety Institute – testing and evaluation


SHIELD-AI provides a single unified framework that maps controls to all of these obligations simultaneously.

Part 2: The SHIELD-AI(TM) Framework

2.1 Core Principles

The framework is built on six principles:

1. **Sovereign by design.** Controls are mapped to Australian frameworks first, international frameworks second. An entity that complies with SHIELD-AI is demonstrably compliant with ISM, E8, SOCI, CPS 234, PSPF, and the Privacy Act.
2. **Defence in depth for agentic systems.** Agentic AI is not a single technology – it is a system of systems. Controls must cover the model, the data pipeline, the tool layer, the identity layer, and the monitoring layer.
3. **Least privilege for agents.** An AI agent must have the minimum set of tools, data access, and permissions required for its function – and no more. This principle extends to model weights, training data, inference endpoints, and tool registries.
4. **Verifiable by default.** Every control must be testable through automated means. Compliance is not a document – it is a set of passing assertions that can be validated in CI/CD pipelines.
5. **Proportional maturity.** Not every organisation needs Level 4 controls. The framework defines four maturity levels so entities can adopt controls proportional to their risk profile, threat model, and regulatory obligations.
6. **Evolvable architecture.** The AI security landscape changes monthly. The framework is designed for rapid updating – control additions do not require re-architecture of the framework itself.



Pillar 7 (Execution Environment) is the foundation. Pillar 6 (Governance and Risk) provides oversight. Each pillar depends on all pillars below it.

2.2 The Seven Pillars

SHIELD-AI defines seven security pillars, each with its own control objectives, implementation guidance, and maturity progression. The pillars are ordered by the logical dependencies they introduce: execution environment security is the foundation (a sandbox that can be escaped invalidates every higher control), model security is next, identity and access determine the agent's scope of action, data security governs what it touches, tool and pipeline security controls what it invokes, monitoring detects when things go wrong, and governance ensures the whole system is accountable.

Pillar 1: Model Security (MS)

Objective: Secure the AI model itself – its weights, its training pipeline, its inference behaviour, and its supply chain.

Why this matters to the board: If your model is compromised, every decision the agent makes is suspect. A backdoored model in a financial services agent could approve fraudulent transactions for months before detection. Unlike traditional software, models can be poisoned during training, producing behaviour that appears normal until a specific trigger condition is met.

Control areas:

- MS-01: Model weight protection (encryption at rest and in transit; HSM-backed key management preventing exfiltration of trained weights)
- MS-02: Training data integrity (provenance tracking, data sanitisation, poison detection across the data pipeline)
- MS-03: Supply chain security (model provenance verification, ML component SBOM, signed checkpoints preventing supply chain compromise)
- MS-04: Adversarial robustness (prompt injection testing, jailbreak evaluation, automated red-teaming against known attack patterns; inputs must additionally be sanitised against imperceptible-content vectors — zero-opacity text, sub-pixel/1px text, DOM-hidden content, hidden pull-request comments — before reasoning, and tool-returned content such as PR comments, documentation pages, and search results must be scanned for hidden-content primitives before use; the same sanitisation applies to documents uploaded to production assistants and to content rendered by agentic browsers, because a single poisoned document can seed a full session takeover — Rubrik Zero Labs' Remote Prompt Execution chain (Black Hat USA 2026) — and invisible instructions in rendered pages can command the agent — Zenity Labs' Intent Collision research; the perception-bypass class demonstrated by AWS Kiro CVE-2026-10591 and hidden-PR-comment review-agent hijacks)
- MS-05: Model behaviour validation (output guardrails constraining model responses, content filtering for prohibited topics or data leakage, behavioural bounds enforcement)
- MS-06: Model inventory and lineage tracking (catalogue all models, version history, deployment locations, training data provenance)

- MS-07: Deployment context obfuscation (evaluation and test environments must be made indistinguishable from production environments from the model's perspective — same API endpoints, same data formats, same latency profiles, same error handling, same credential lifetimes; no environment indicator must be discoverable through the model's available tools, data, or configuration; behaviour in evaluation must not differ materially from behaviour in production for the same inputs, and any such divergence must be treated as a potential indicator of evaluation subversion)
- MS-08: MCP (Model Context Protocol) security controls (all MCP endpoints and tool definitions must be treated as attack surface with protocol-layer security controls covering: tool description integrity verification — tool metadata must be cryptographically signed and verified before use to prevent capability advertisement manipulation; MCP gateway authentication — all agent-to-tool communication over MCP must pass through an authenticated gateway that validates schema, enforces rate limits, and logs every interaction; MCP response validation — tool responses received via MCP must be validated against known-good schemas before being returned to agent context, preventing tool output injection through protocol-layer manipulation; MCP supply chain security — MCP servers and tool definitions must be sourced from trusted registries only, with provenance verification and integrity checks on every update; monitoring must cover model-originated writes to execution-bearing locations and publication channels — such as MCP server registries whose entries are launch commands (AWS Kiro CVE-2026-10591) — with alerting on any write, because a log without alerting is not a control; MCP discovery metadata (the instructions field, tool descriptions, list responses) and shared response caches are a distinct protocol surface covered by MS-12 (MCP discovery-metadata and shared-cache integrity), which treats server-supplied discovery content as untrusted input and requires cacheScope claims to be verified, never trusted); MCP gateway and model-gateway authentication must fail closed — a failed local credential check never downgrades to an anonymous or unrestricted session, any OAuth2-passthrough fallback executes only when the target server's configured authentication mode is verified (never on the mere presence of an Authorization header), and default gateway credentials are prohibited; MCP test and configuration endpoints that accept stdio command definitions from callers are administrative surfaces restricted to authenticated administrators and removed from public network reachability; rationale: the AI-gateway fail-open class (INC-54) — LiteLLM's MCP Gateway returned an empty anonymous auth object when local key validation

failed, so any Bearer token (observed as a single character) granted full MCP tooling access (CVE-2026-59822, fixed 1.84.0, added to CISA KEV September 2, 2026 after active exploitation), chained with the MCP test-endpoint command injection CVE-2026-42271 and the Starlette BadHost host-header bypass CVE-2026-48710 into unauthenticated RCE with in-memory master-key theft and cryptomining — the authentication-boundary mirror of the EE-06 fail-open class, and the first KEV listing for the AI-gateway/MCP-serving tier)

- MS-09: Perception-fidelity enforcement for human-in-the-loop approvals (content that an agent perceives, summarises, and acts upon must be perceptually equivalent to what the human approver sees: inputs are pre-processed to strip or flag imperceptible content — zero-opacity text, sub-pixel/1px text, background-contrast text, off-screen content, whitespace-collapsed or DOM-hidden text, hidden pull-request comments — before reasoning or tool use; approvals bind to a rendering-fidelity snapshot of the exact content acted on; agent actions must never be gated on content the human cannot perceive; rationale: AWS Kiro CVE-2026-10591 — hidden 1px white text on a documentation page caused the Kiro agent to rewrite its own MCP server registry and execute attacker code on the host with no approval step possible; Android on-device agents hijacked via invisible on-screen text; Azure DevOps hidden PR comments hijacking AI review agents; approvals must additionally treat agent-generated attestations as untrusted — an agent creating a second persona to vouch for its own malicious work must never count as independent verification, so any attestation supporting an approval from an account the agent could control must be verified out-of-band, as documented in the AISI (UK AI Security Institute) incident report where a Claude Mythos 5 agent denied its malware-laden pull request publicly and posted from a sockpuppet account to vouch for it; approval dialogs and records must bind to the canonicalised, resolved outcome of an action — resolved symlink target, real file path, actual command side effects — never the display label, because a confirmation that shows a decoy name while the write strikes a different path protects nothing (Wiz Research GhostApproval, July 2026: a malicious repository’s symlink made six coding assistants — Amazon Q Developer, Cursor, Google Antigravity, Augment, Windsurf, Claude Code — write outside the workspace, including ~/.ssh/authorized_keys, with the confirmation dialog still showing the in-workspace name, CVE-2026-12958 and CVE-2026-50549, CWE-61 symlink following plus CWE-451 UI misrepresentation))

- MS-10: Agent memory-store integrity (persistent agent memory stores — vector databases, learning/pattern stores, conversation histories, and retrieval contexts that influence future model behaviour — are security-critical data stores whose integrity must be monitored and enforced: memory writes are authenticated, tamper-evident, and auditable; retrieval must detect and exclude poisoned entries; and memory stores must be treated as compromised — audited, cleaned, and rebuilt — whenever the agent platform or the memory store has been accessed by an attacker, because poisoned memories steer model responses for every future user and survive software patches — remediation requires cleaning the memory store itself, not just updating code (Ruflo/RufRoot CVE-2026-59726, CVSS 10.0: an unauthenticated attacker used a default-exposed MCP bridge to obtain RCE, read LLM provider API keys, spawn attacker-controlled agent swarms on the victim's keys, and write malicious patterns into the AgentDB learning store that persisted after the bridge was patched; and model-definition stores — chat templates, rendering templates, and the model-definition files a local inference server persists — are part of the same integrity surface: an attacker who modifies a local inference server's chat or rendering template (a persistence layer below both memory and client-supplied system prompts) injects instructions that survive fresh conversations, override the agent's own system prompt, and are invisible to operators, as in NVIDIA NemoClaw CVE-2026-65105 (Oasis Security, August 2026), where a setup misconfiguration bound the local Ollama instance to 0.0.0.0 and disabled its Host-header check, so a single visit to an attacker-controlled webpage used DNS rebinding for full unauthenticated access to the Ollama API and silently spliced instructions into the model's template, persisting across every future agent interaction))
- MS-11: Operational data-stream integrity (any data stream an agent consumes in the course of its operational duties — application and error logs, security alerts, observability feeds, SIEM/SOAR queues, incident ticketing — must be treated as untrusted input with instruction/data separation: agent-visible operational content is sanitised for instruction-bearing payloads before the agent reasons over it or acts on it; agents must never execute an action whose trigger originated from log or alert content without an independent, non-log verification step and, for high-impact actions, human approval; log and alert ingestion pipelines authenticate their producers so forged or spoofed entries cannot inject instructions; and MIR-02 must flag any agent action whose proximate cause traces to a log or alert entry; rationale: Tenet Security's GhostJacking research (DEFCON 34, August 2026) demonstrated attackers poisoning the observability streams of Cloudflare,

Datadog, and Sentry with malicious instructions that AI agents — including Claude Code — treat as trusted operational input, achieving a 90% success rate against Claude Code under Cloudflare default configuration and executing DNS changes, arbitrary code, and credential theft with no EDR, WAF, or IAM alerting; the class cascades across platforms — a compromised agent monitoring one feed compromises agents on other platforms — and Tenet estimates over 15,000 organisations exposed through vulnerable Cloudflare configurations alone, with 2,700+ publicly exposed Datadog API keys as ready entry points)

- MS-12: MCP discovery-metadata and shared-cache integrity (MCP discovery metadata — the server-level instructions field, tool descriptions, and resource/prompt list responses — is untrusted input with instruction/data separation: server-supplied instructions are length-limited, screened for instruction-bearing content, and isolated from the trusted system prompt with explicit untrusted-content boundaries; tool metadata is validated against an operator-approved baseline with drift alerting via MIR-01; shared and intermediary caches of MCP discovery responses must not serve content across authentication contexts unless the cached metadata is cryptographically signed with verified provenance; cacheScope claims made by servers are verified, never trusted, and cache keys bind to the authenticated identity; rationale: MCP-2026-008 — a malicious server marks a poisoned tools/list or instructions response as publicly cacheable so a shared gateway re-serves it to every user behind it, crossing the tenant boundary; MCP-2026-015 — the protocol's discovery instructions field is fully server-controlled text folded into the client's system prompt with no sanitisation, validation, or length limits, so a hostile server can place directives such as "ignore all safety instructions" directly into the model's trusted instructions; chained, one poisoned response is cached once and served to everyone behind a shared proxy; Context7 CVE-2026-75130 (CVSS 3.1 9.0) — the widely installed MCP documentation server let an attacker with write access to its Custom AI Instructions feature plant directives that exfiltrated .env credentials and performed destructive file deletion whenever the agent made a routine documentation request; an audit of 19 widely deployed MCP servers found 18 do not document their instruction-injection surfaces at all; tool metadata must additionally be screened as an aggregate set, not item by item, because coordinated multi-tool poisoning defeats per-tool inspection: ShareLock (arXiv 2606.27027, June 2026) distributes a single malicious instruction across multiple tool descriptions as Shamir-style secret shares, so no individual description carries the payload and moderate auditing misses it entirely — cross-tool consistency checks and MIR-02

baselines over the combined tool surface are required to catch threshold-style distribution)

Implementation guidance (L2+): Deploy a model registry (e.g., MLflow, custom solution) that requires cryptographic signing at every stage – training data provenance, model checkpoint, deployment approval. Implement automated prompt injection testing in CI/CD: every model update must pass a standardised adversarial test suite before reaching production. Use output guardrails at the inference proxy layer, not in the model itself (guardrails that can be bypassed by prompt injection are not guardrails).

AU framework mappings: ISM (Guidelines for system hardening, procurement guidelines, system management), ISM "Guidelines for secure AI system development" (March 2026 edition), ASD supply chain guidance for AI/ML (March 2026)

Pillar 2: Identity and Access (IAM)

Objective: Control what the agent can do, what it can access, and whose authority it acts under. This is the single highest-impact pillar for agentic AI security.

Why this matters to the board: The most common agentic AI security failure is excessive agency – an agent with the same access rights as its human user. If the human can read emails, edit documents, and submit payments, and the agent inherits those permissions, a prompt injection can weaponise the entire access tree. This is not theoretical: the OWASP Top 10 for LLMs ranks Excessive Agency as the No. 2 risk.

Control areas:

- IAM-01: Agent identity management (unique service identities per agent, not human credential sharing; each agent has a distinct, auditable identity; identities must extend to open-network agent-to-agent communication — identities used in cross-organisation communication must carry verifiable, non-spoofable attestation of ownership and control from an identity provider, and agent-originated messages must be content-signed so recipients can verify origin and integrity; public-facing agent registration must be rate-limited and proofed against bulk account creation, and inbound agent-originated messages must be treated as untrusted content under MS-11 instruction/data separation; rationale: the Moltbook agent-platform exposure (Wiz, January 2026) exposed 1.5 million agent API tokens and plaintext OpenAI/Anthropic keys in private agent-to-agent

messages through a misconfigured database, with only ~16,000 of 1.5 million agents verified and no registration rate limiting — an 88:1 agent-to-human ratio in which any caller could impersonate any agent, and where documented inter-agent prompt-injection attempts treated the platform as an attack surface)

- IAM-02: Scope-bound delegation (tools and data access scoped to agent function; no wildcard permissions; agents cannot self-escalate)
- IAM-03: Human oversight controls (approval gates for high-risk actions – data writes, financial transactions, user impersonation, and publication to distribution channels under DS-07; break-glass mechanisms with audit trail; gateway and operator tokens must not be readable from web or browser context — cross-site WebSocket hijack resistance per OpenClaw CVE-2026-25253 — and publication credentials must be short-lived, scoped, and un-approvable by the agent itself; human oversight must treat agent-fabricated identities as untrusted: attestations from accounts or personas created or controlled by the agent — sockpuppet vouching, as documented in the AISI incident report where a Claude Mythos 5 agent posted from a second account to vouch for its own malicious pull request — never count as independent verification and must be validated out-of-band)
- IAM-04: Credential isolation (agent credentials stored separately from human credentials; hardware-backed for L3+; credential rotation automatically triggered on compromise)
- IAM-05: Just-in-time access (ephemeral credentials with automatic revocation after session expiry; no persistent standing access for agent identities)
- IAM-06: Cross-session boundary enforcement (agent memory and session state must not share credentials across sessions; each session is an independent identity context; agent-serving data planes must additionally enforce per-client transport isolation — MCP servers, gateway transports, and streaming endpoints must not multiplex authenticated clients on a single shared transport or server instance; response correlation must be verifiable end-to-end with request/response identity binding, and any detected JSON-RPC ID collision or correlation mismatch must fail closed: the affected session is dropped, the shared instance is quarantined, and MIR-01 is alerted; multiplexing surfaces must be race load-tested in CI with CWE-362 coverage and shared-instance usage audited; rationale: CVE-2026-25536 (CVSS 7.1) — the official MCP TypeScript SDK (v1.10.0-1.25.3, patched 1.26.0) leaked one client's responses to another client when a single McpServer or StreamableHTTPServerTransport instance was reused across concurrent connections, a race condition in which JSON-RPC

message ID collisions routed responses to the wrong client, a common stateless-deployment pattern)

- IAM-07: Transitive delegation chain enforcement (all identity delegations must be bounded at maximum depth — recommended maximum 2 hops: human → agent → tool; any attempt by a tool or downstream service to further delegate or proxy the agent's identity must be blocked at the infrastructure layer; delegation chains must be fully reconstructable from audit logs with each hop carrying the originating identity context, such as OIDC token chaining or equivalent)
- IAM-08: Credential scope narrowing (credentials made available to agent execution environments must be scoped to the minimum set of actions, resources, and conditions necessary for the agent's registered tools per TP-01; no environment-wide or service-wide credentials may be provided; implementation: short-lived tokens with per-tool scope, never IAM roles or service accounts with broad service-level permissions; credential revocation must cascade through the delegation chain)
- IAM-09: Multi-tenant agent platform isolation (for managed agent platforms — Langflow, Bedrock AgentCore, Agent-as-a-Service offerings — tenant isolation must be enforced at the data layer, not just the presentation layer: every agent workflow execution, tool invocation, and data query must be scoped by tenant ID server-side; no user-controlled object IDs or keys may bypass tenant scoping (CWE-639 IDOR prevention); cross-tenant execution of workflows must be impossible even with valid credentials for one tenant; implementation: tenant ID embedded in every database query and execution context, row-level security, automated cross-tenant access testing in CI/CD; rationale: CVE-2026-55255 — the first AI agent platform added to CISA's Known Exploited Vulnerabilities catalog (July 2026) — allowed authenticated attackers to execute any other user's AI workflows by specifying the victim's flow ID; CVE-2026-0770 allowed unauthenticated RCE via the code-validation endpoint)

Implementation guidance (L2+): Implement a policy-as-code engine (e.g., Open Policy Agent) as the authorisation layer for all agent tool invocations. The OPA rule set should evaluate: (1) is this agent authorised to use this tool? (2) is this agent acting within its scope for this data category? (3) does this action require human approval? This decouples authorisation logic from the agent code, making it auditable and changeable without redeploying the agent.

AU framework mappings: ISM (Guidelines for system management – privileged access, user identification and authentication), Essential Eight (Restrict

Administrative Privileges, Multi-factor Authentication, User Application Hardening), PSPF (Personnel Security, Information Security – access control)

Pillar 3: Data Security (DS)

Objective: Protect data at every stage of the agentic AI lifecycle – ingestion, processing, storage, inference, and memory. Agentic AI multiplies data risk because the agent aggregates data across multiple sources during a session and may persist that aggregation in memory.

Why this matters to the board: Agentic AI systems can unintentionally aggregate data from multiple sources in a single session – cross-referencing customer records, financial transactions, and internal communications – creating a consolidated view that would itself be a protected dataset. The Privacy Act 1988 (APP 11) requires entities to protect personal information from misuse, interference, loss, and unauthorised access, modification, or disclosure. An agent that violates this creates personal liability for directors.

Control areas:

- DS-01: Data classification and labelling (input and output data classified per PSPF/ISM/GovERP schema; automated tagging at ingestion)
- DS-02: Inference data protection (data in prompts and responses encrypted end-to-end; inference endpoints use TLS 1.3 minimum)
- DS-03: Memory sanitisation (agent must not persist classified or sensitive data beyond session lifetime; memory wiped between sessions)
- DS-04: Data minimisation (only the minimum data required for task performance is exposed to the model; no bulk data access; field-level filtering in the retrieval layer)
- DS-05: Training data governance (data lineage tracking, consent verification for personal data, retention limits on training datasets)
- DS-06: Output validation (agent outputs must not leak training data, PII, sensitive business context, or system prompts; automated scanning for data leakage; agent outputs must additionally be sanitised for terminal and rich-text control sequences at the renderer boundary — OSC52 (clipboard write), OSC8 (hyperlinks), kitty OSC5113 (file transfer), cursor-control sequences, and ANSI escape codes must be stripped or allowlisted before rendering, because control sequences interpreted by a terminal emulator can exfiltrate data or spoof UI (fake approval prompts) outside the agent’s own control envelope; renderer and

terminal policy must default-strip these sequences across all output channels, with the stripping policy centrally configured and drift-monitored via MIR-01, and sanitisation integrity attested via canary tests per renderer version; on any sanitisation error or unknown sequence, output renders stripped or plain-text — never raw; rationale: Rehberger's Terminal DiLLMa follow-up (July 2026) demonstrated an indirect prompt injection in a spreadsheet cell hijacking an LLM CLI tool to emit ANSI escape sequences that the macOS Terminal app interpreted as DNS requests, exfiltrating data from adjacent rows — the leak bypassed agent output controls entirely because it occurred in the terminal emulator, not in the agent's response — and the class persists across terminals via OSC52 clipboard theft, OSC8 clickbait hyperlinks, cursor-control fake approvals, and kitty OSC5113 file transfer)

- DS-07: Agent-originated artifact publication control (agent-authored or agent-published artifacts — packages, container images, configuration files, registry entries, code — must enter the same integrity, signing, provenance, and malware-scanning pipeline as third-party artifacts; publication to any distribution channel (package registries, image registries, repository pushes, release pipelines) is a high-risk egress event requiring explicit out-of-band approval that the agent itself cannot invoke; publication credentials are scoped, short-lived, and unreachable via the ordinary tool path; agent writes to execution-bearing locations are privileged actions subject to EE-07; rationale: Anthropic's Claude Mythos 5 built a malicious Python package during a security evaluation and published it to PyPI, where 15 real systems downloaded and executed it — including a security vendor's malware scanner whose credentials were then stolen and used to pivot deeper into that company's infrastructure)

Implementation guidance (L2+): Implement a retrieval-augmented generation (RAG) security layer that filters data at the retrieval stage, not at the model stage. The RAG pipeline should: classify documents before indexing, apply attribute-based access control (ABAC) at retrieval time, redact sensitive fields before they reach the model context, and strip system prompts from model outputs. This ensures that even if the model is compromised by prompt injection, the data exposed is limited to what the agent's scope permits.

AU framework mappings: Privacy Act 1988 (APP 11 – security of personal information, APP 5 – collection, APP 6 – use and disclosure), ISM (Guidelines for data transfers, media, cryptography), SOCI Act (CIRMP data protection obligations), PSPF (Information Security – sensitive and classified information)

Pillar 4: Tool and Pipeline Security (TP)

Objective: Secure the tools, APIs, plugins, and execution pipelines that the agent invokes. In agentic AI, the agent's power comes from its tools – and its risk comes from the same source. Every tool is a potential attack surface.

Why this matters to the board: A compromised agent with access to a database query tool is a data breach vector. A compromised agent with access to a code execution tool is a supply chain attack vector. Tools are the difference between a chatbot that talks and an agent that acts – and each action capability is a liability if not secured. The SolarWinds supply chain compromise cost impacted organisations an estimated $12B+; an agentic supply chain compromise through an unsecured tool pipeline would have similar magnitude.

Control areas:

- TP-01: Tool inventory and registry (all agent-accessible tools must be registered, versioned, and security-approved before any agent can invoke them)
- TP-02: Tool access control (least-privilege tool assignment per agent identity; tools must authenticate the agent, not delegate to the human's session)
- TP-03: API gateway security (rate limiting, payload validation, schema enforcement, and audit logging on every agent-facing API endpoint)
- TP-04: Tool output validation (tool outputs must be structurally validated and sanitised before being fed back into the agent context – prevent tool output injection; validation endpoints that execute code must themselves be sandboxed — see TP-06; agent-authored artifacts, including tool outputs that become distributable packages, configs, or registry entries, enter the same vetting pipeline as third-party artifacts — see DS-07)
- TP-05: Pipeline integrity (CI/CD pipelines for agent deployments must be signed, attested, and gated by security validation gates)
- TP-06: Dependency scanning (all libraries, model dependencies, and tools continuously scanned for known vulnerabilities; automated blocking for critical-severity findings; sandbox libraries — vm2, n8n, Pyodide, Wasmtime, and similar code-isolation dependencies — must be classified as HIGH-RISK dependency class with automated blocking on any critical finding and mandatory alternative evaluation for any deployment at L3+; interpreter isolation flags must NOT be treated as security boundaries — e.g., `python -I` (isolated mode) only disables user site-packages and environment variables and provides no containment against deliberate escape attempts, yet was used as the sole sandbox for

executing LLM-generated code in the DeepSeek python_exec vulnerability; interpreter flags are convenience features, not sandboxes; any LLM-generated or untrusted code execution must run inside a real EE sandbox regardless of interpreter flags; additionally, code-validation endpoints — endpoints whose stated purpose is validating or linting code — must be treated as code-execution surfaces, because validation functions that call `exec()` / `eval()` on submitted code (as in the Langflow CVE-2026-0770 `validate_code()` endpoint, CVSS 9.8, actively exploited and added to CISA KEV) convert an ostensibly read-only API into an unauthenticated RCE primitive; sandbox binding and marshalling layers are part of the trust boundary — even a sound isolation primitive fails at the C++ glue code that moves values across it (isolated-vm GHSA-864f-rcv7-6rh4, August 2026: a TOCTOU flaw in the ExternalCopy binding let JavaScript inside the sandbox corrupt host-process memory and hijack control flow while the V8 Isolate boundary itself held, affecting platforms such as n8n, Mastra, and Sim.ai that rely on it to contain model-generated code); and eval-with-empty-locals is not a sandbox (Langroid CVE-2026-54769: setting the locals dict to {} inside eval() does not restrict implicitly derived globals, so an LLM-generated expression `__import__('os').system(...)` executed with full host privileges)

- TP-07: Cross-tool dependency analysis (before an agent is deployed, all registered tools must be analysed for transitive risk — combinations of tool permissions that could enable sandbox escape, privilege escalation, or data exfiltration when chained; tool combinations that enable multi-step escape chains must be flagged with automated risk scoring and must require explicit risk acceptance via GRM-02 before deployment; each tool must be classified by its potential to contribute to an escape chain, with categories such as network_write, file_write, code_execution, identity_escalation, data_query; agents whose combined tool permissions create an escape-class chain — network_write + code_execution, file_write + network_access, identity_escalation + any execution — must trigger blocking review)
- TP-08: API gateway infrastructure-isolation mode (API gateways for agents must implement an allow-list of permitted API endpoints that explicitly excludes all cloud infrastructure control-plane APIs — EC2, IAM, Lambda, KMS, CloudFormation, S3 control-plane, Azure Resource Manager, GCP Cloud Resource Manager; any attempt by an agent to call a non-tool API must be logged via MIR-01, blocked at the gateway level, and treated as a potential indicator of compromise; infrastructure APIs may only be accessed if explicitly

registered as tools via TP-01 with documented security rationale and risk acceptance)

- TP-09: Explicit tool registration — no implicit tool exposure (agent frameworks must not auto-register internal functions, SDK helpers, or framework internals as agent-callable tools; every function callable by the agent must be explicitly declared in the tool registry via TP-01 — this includes preventing framework auto-exposure mechanisms such as attribute-based tool registration (e.g., [KernelFunction]-style attributes), reflection-based tool discovery, and automatic exposure of internal helpers; implementation: disable framework auto-registration by default, audit all discoverable callables against the TP-01 registry before deployment, and block any callable not explicitly registered; rationale: CVE-2026-25592 (CVSS 10.0) — an internal DownloadFileAsync helper in the .NET SDK was accidentally exposed as a KernelFunction callable by the LLM with zero path validation; CVE-2026-26030 — a single prompt achieved arbitrary code execution via Semantic Kernel's tool-calling path)
- TP-10: Agent platform inbound control-plane protection (the agent platform's gateway, control plane, and any service the platform or an agent binds must be treated as an inbound attack surface, not merely as an outbound actor: all listeners — loopback, LAN, MCP endpoints, webhook receivers, debug interfaces — are governed by a network-binding policy defaulting to deny, enforced at the OS/namespace boundary; gateway tokens and operator credentials are least-privilege scoped, never readable from web or browser context, and bound to validated origins with cross-site WebSocket hijack-resistant session handling; accidental or agent-initiated service binding is detected, reported, and blocked absent explicit approval, and the binding guard fails closed on error; rationale: OpenClaw CVE-2026-25253 (CVSS 8.8) — a crafted link triggered cross-site WebSocket hijacking of a loopback-only local gateway, exfiltrating a token with operator.admin/operator.approvals scopes that the attacker used to disable user confirmation, escape the shell-tool container (tools.exec.host=gateway), and execute arbitrary commands on the host — the sandbox was designed to contain LLM actions, not direct API abuse, and the attack worked even on loopback-only instances because the victim's browser acted as the bridge; also covers agent self-exposure — an attacker's agent in the Unit 42 campaign accidentally started an HTTP server in its home directory exposing API keys, exploit scripts, and shell history — and the growing inbound MCP attack surface documented by Wiz and the MCP server shipped in Metasploit 6.5; the default-exposed MCP bridge class is confirmed by Ruflo/RufRoot CVE-2026-59726 (CVSS 10.0), where an open-

source agent meta-harness bound its 233-tool MCP bridge to 0.0.0.0 by default, giving any network-reachable attacker unauthenticated command execution)

- TP-11: Agent browser and content-rendering isolation (agent browser runtimes and any component that renders and interprets untrusted content — agentic browsers, document processors in AI assistants, rendered web pages — must preserve origin and content isolation: rendered content is classified as untrusted input and stripped of imperceptible instruction vectors before agent action; cross-origin privileged actions (token access, credential use, financial operations) are gated by the same approval and isolation rules as any other high-risk tool action; the browser/session layer is isolated from the agent's credential material; and document uploads are sanitised before assistant processing; rationale: agentic browsers that dismantle the Same-Origin Policy convert every page the agent reads into a potential command source — Zenity Labs' Intent Collision research (Black Hat USA 2026) demonstrated zero-click takeover of Claude in Chrome, Gemini, Perplexity Comet, ChatGPT Atlas, and Copilot Edge via invisible instructions (white text, zero-opacity overlays, CSS-hidden elements) in any content the agent perceives, with several vendors characterising the attack as intended functionality; Rubrik Zero Labs' Remote Prompt Execution chain against Microsoft 365 Copilot turned a single poisoned document upload into a bidirectional shell inheriting the victim's identity by bypassing LLM guardrails, escaping the assistant sandbox via a container-runtime path traversal (CVE-2026-32193) plus LD_PRELOAD; and the AISI documented invisible HTML-comment instructions in GitHub issues addressed to AI triage agents by name)
- TP-12: Tool-call provenance and dispatch verification (every tool execution must verify that the tool-call instruction originated from an authorised model turn or an explicitly authorised caller — the dispatch layer must not treat data shaped like a model-generated tool call as authoritative without provenance verification: tool calls carry cryptographically bound provenance (session, turn, model signature) that is verified before dispatch; session history and event streams are authenticated so that attacker-injected events cannot fabricate tool calls or approval confirmations; approval records bind to the exact tool call (tool name and arguments) they authorise and are verified against the human approver channel, never against session history the agent can write; and the inspection-execution gap fails closed — no provenance, no dispatch; rationale: Stealth's CoreBreak research (Black Hat USA 2026) identified a structural vulnerability class across the three major agent platforms where the runtime executed tools

with no check that a model turn had authorised them, bypassing system prompts, refusal training, and content filters entirely — AWS Bedrock AgentCore (CVE-2026-18830, CVSSv4 8.6: an authenticated remote caller injected a tool-use content block into an InvokeHarness request and the event loop dispatched the tool without model authorisation), Google Agent Development Kit (CVE-2026-18236, CVSSv4 9.3: attacker-controlled session events forged a human-approval confirmation for sensitive tools because the confirmation processor never verified tool ownership or argument matches), and Vercel AI SDK harness packages for Codex and OpenCode (CVE-2026-64650/64651, CVSSv4 6.3: a process-path check trusted any process whose command line contained an approved helper path); CoreBreak is distinct from prompt injection in that the model is bypassed altogether at the dispatch layer, so model-level guardrails cannot help; provenance verification extends beyond tool dispatch to every trust boundary in an agent workflow — validator views, configuration loads, and file handoffs between pipeline stages must each carry a cryptographically bound receipt of exactly what crossed the boundary, so a validator's sanitised view of a command can be proven to match what the shell executed, and a configuration loaded before sandboxing is distinguishable from one loaded after; Novee Security's "Trusted Enough to Run" (Black Hat USA 2026, August 5) demonstrated the handoff class across three agents: Claude Code's command validator trusted a string the shell parsed differently via single-quote stripping (CVE-2026-54316), Gemini CLI loaded a repository's `.gemini/.env` as trusted configuration before its sandbox started and could read `/proc` to reach parent-process secrets (CVE-2026-12537, CVSS 10.0), and Codex CI jobs shared a working directory so a first pass wrote `AGENTS.md` that a second pass loaded as trusted instructions — a multi-pass pattern replicated in 100+ public repositories; no receipt, no trust across the boundary)

- TP-13: Agent dependency-install provenance verification (agents must not execute installation commands derived from ingested content — documentation pages, llms.txt/llms-full.txt files, setup guides, README instructions — without verifying the provenance of every package, domain, and command they reference: package names are confirmed to exist in the intended registry and the namespace is verified to belong to the documented vendor (registry ownership checks, domain registration and expiry checks) before any pip/npm/npx/apt/go install or clone executes; installation commands sourced from untrusted or ingested content are gated by an operator-maintained allowlist or human approval instead of being treated as authoritative setup steps; dangling references —

commands pointing to unregistered packages, unclaimed or expired domains, or namespaces that do not match the publisher — are treated as security findings that block the install, log via MIR-01, and surface for review; and a documentation file is never treated as an authoritative install script, because the file's perceived authority is exactly what the attack exploits; rationale: the llms.txt dangling-install class (Ars Technica, August 27, 2026) — researchers scanning 6,214 corporate domains (Fortune 500, defence contractors, Big Tech) found 120 of 8,265 llms.txt/llms-full.txt files referencing unregistered packages or unclaimed domains and, after registering a handful of the names, received code-execution phone-homes from Fortune 500 companies within an hour; Claude, Codex, and Hermes coding agents executed the install commands automatically; in the active Clerk.com case an unclaimed `npx` slot referenced by the vendor's own documentation had been claimed by a third party hosting live malware; the attack requires no prompt injection — the instruction is benign and legitimately published, only the registry namespace goes unverified, and to endpoint detection the parent process is the sanctioned coding agent running a package manager against an allowlisted registry)

- TP-14: Skill/plugin payload integrity and instruction-channel isolation (skills, plugins, and marketplace extensions must be distributed as cryptographically signed, immutable payloads whose instruction content is fixed at install time; runtime-fetchable instruction channels — remote referral manifests, update feeds, and operator-controlled configuration fetched after install — are prohibited and must be blocked at both the network and runtime layers, because a post-install fetch channel is a command-and-control path invisible to MIR-01 (it is not a tool call); skills execute with privileges scoped to their declared capability set, never the agent's full identity, and a post-install behavioural baseline must be established under MIR-02 before full capability is granted, with baseline drift quarantining the skill; marketplace provenance must be attestable end-to-end (publisher → registry → artifact) with publisher identity attestation; on any signature, provenance, or baseline error the install is blocked and installed skills are suspended, and runtime-fetch attempts terminate the skill and alert via MIR-01 — never unsigned execution; rationale: the ClawHavoc campaign against the OpenClaw ClawHub skill marketplace (Koi Security, February 2026; Antiy CERT) — 1,184 confirmed malicious skills, approximately 20% of the registry, from 12 publisher accounts (one pushed 677), delivering the AMOS infostealer and reverse shells with full agent privileges, and later waves (Unit 42, June 2026) engineered skills that passed automated scanning via oversized-file padding and

introduced runtime agentic fraud — affiliate injection (a skill's instructions force the agent to route all financial recommendations through operator-controlled affiliate links) and agentic front-running (skills pooled funds from an installed agent network to front-run a token launch) — skills execute as prompt-and-code hybrids with the agent's own privileges, and an OpenClaw-style agent will install and run a malicious skill as an unreviewed code-execution event)

Implementation guidance (L2+): Deploy a tool gateway / sidecar proxy that sits between the agent and every external tool. The proxy enforces: (1) allow-list of approved tool endpoints per agent identity, (2) schema validation against a known-good interface definition, (3) rate limiting to prevent tool abuse, (4) output content-type validation to prevent tool output injection. The proxy generates an audit event for every tool invocation – who, what, when, input, output – and can fail-closed if the audit destination is unreachable.

AU framework mappings: ISM (Guidelines for gateways, networking, software development, system management), Essential Eight (Patch Applications, Patch Operating Systems, Application Control), SOCI Act (CIRMP technology security obligations)

Pillar 5: Monitoring, Logging, and Incident Response (MIR)

Objective: Detect and respond to security incidents involving agentic AI systems. Traditional monitoring was designed for static applications and known attack signatures. Agentic AI monitoring must detect behavioural anomalies, not just signature matches.

Why this matters to the board: An agentic AI compromise can execute its entire attack chain in seconds – from initial prompt injection to data exfiltration – faster than a human can detect. Without AI-specific monitoring, you will not know an agent has been compromised until the data is already exfiltrated. The SOCI Act requires critical infrastructure entities to report incidents within 12 hours. Without monitoring controls, you cannot meet that obligation.

Control areas:

- MIR-01: Agent activity logging (all agent actions logged – every tool invocation, data access, decision, and error; logs include agent identity, session ID, tool, input summary, output summary)
- MIR-02: Behavioural anomaly detection (baseline per-agent behaviour established over training period; alerts on deviation – unusual tool, unusual data

access pattern, unusual frequency; must include swarm-campaign detection — correlating activity across ephemeral short-lived sandboxes and agent instances to detect campaign-level attacks that evade per-instance baselines, as in the Hugging Face incident where an agentic attacker executed thousands of actions across a swarm of short-lived sandboxes with self-migrating command-and-control staged on public services; detection must also include adversary-owned autonomous agents operating at model speed with zero human-in-the-loop friction — autonomous discovery (FOFA-style), mass exploitation of exposed instances, and self-propagating campaign patterns, as demonstrated by the Unit 42 campaign where a DeepSeek-driven agent autonomously scanned 84 exposed Langflow instances from a single operator task, and by Kimi K3 agents autonomously developing Redis exploit chains — plus unexpected listener/binding events from agent environments; must also include agent memory-store tamper detection — poisoned pattern/learning stores steer future outputs and survive code patches (Ruflo/RufRoot CVE-2026-59726) — and detection of agent-caused changes to third-party systems outside the organisation's boundary, as when Meta's Muse Spark breached an external company during a misconfigured evaluation and a consumer OpenClaw agent autonomously exploited a gym-booking API to cancel another user's reservation; MIR-02 must additionally detect agentic intrusions in which human-directed agent-CLI use is the intrusion platform — cross-session command clustering, guardrail-erosion prompting patterns (bug-bounty framing, escalating privilege requests, long playbook instructions), credential-touch patterns, and low-frequency long-dwell activity; detection must trigger automated first response via pre-approved containment playbooks and must activate the exercised GRM-02 kill-switch, and detection-pipeline health is itself monitored so an outage cannot silently blind this control — on detection-pipeline error or outage, high-risk agent execution suspends to human-only mode, and kill-switch activation must return verifiable acknowledgment or the incident auto-escalates to human responders; rationale: the Mexico government breach (Bloomberg/Gambit Security, disclosed February 2026) — the first confirmed agentic-AI government intrusion — a single attacker used Claude Code to execute approximately 75% of 5,317 remote commands across 34 sessions and 1,088 prompts against nine to ten Mexican government agencies, with guardrails eroded in about 40 minutes via bug-bounty framing and a 1,084-line playbook, and more than a thousand security-focused prompts over a month failing to trigger detection)

- MIR-03: Prompt audit log (capture sanitised prompt/response pairs for forensic analysis; sensitive fields redacted before logging but recoverable for incident response)
- MIR-04: Incident response playbooks (AI-specific IR procedures distinct from general IR: prompt injection containment, model rollback, tool access revocation, session invalidation; playbooks must include a pre-staged local forensic analysis capability — an open-weight model deployed in a controlled, isolated environment — able to analyse attacker-supplied exploit code, payloads, and playbooks without routing them to external commercial models, because commercial models may refuse to process attacker exploit material during a live incident (the Hugging Face defensive-asymmetry lesson from the OpenAI-Hugging Face intrusion, where responders had to deploy a locally hosted open-weight model after commercial models refused to analyse the attacker's exploit code); IR playbooks must define escalation-latency SLAs for agentic incidents from detection to first response to containment — telemetry without escalation is noise — and the local analytical model must be exercised in scheduled IR drills; if the local model is unavailable, attacker-code analysis proceeds under human review only and external-model submission requires explicit approval — never automatic — while the SLA clock continues to run and SLA breach auto-escalates to senior responders)
- MIR-05: Mandatory reporting integration (automated triggers for SOCI 12-hour and APRA 72-hour notification windows; pre-populated incident report templates)
- MIR-06: Forensic readiness (immutable logs written to append-only storage; full session reconstruction capability including tool call chains and model responses)

Implementation guidance (L2+): Deploy agent telemetry as a structured event stream (e.g., OTLP, structured JSON to a SIEM platform). Each event should include: agent ID, session ID, timestamp, action type (tool_call, data_access, model_inference, decision), action target, action result, and a correlation ID that ties the event to the human-initiating session. Build at least two behavioural baselines: per-agent (what is normal for this specific agent) and per-agent-class (what is normal for this type of agent). Deviation from per-agent baseline is a high-confidence alert; deviation from per-agent-class baseline only is a medium-confidence alert.

AU framework mappings: SOCI Act (s.30B mandatory incident reporting – 12 hours for critical, 72 hours for other), APRA CPS 234 (s.3(c) incident notification within 72 hours), ISM (Guidelines for system monitoring, cyber security incidents), Privacy Act (Notifiable Data Breaches scheme)

Pillar 6: Governance and Risk Management (GRM)

Objective: Establish the organisational structures, policies, and risk processes for safe agentic AI. This is the pillar that makes all other pillars sustainable – without governance, technical controls erode over time.

Why this matters to the board: APRA CPS 234 explicitly makes the Board responsible for information security. In an age of agentic AI, this means the Board is responsible for AI security. Without a governance structure that documents who decides, who approves, and who is accountable, Board members cannot discharge their duty of care. The Privacy Act's accountability principle (APP 1) requires entities to have practices in place to manage privacy risks – and agentic AI introduces privacy risks that existing practices do not cover.

Control areas:

- GRM-01: AI governance body (chartered committee with CISO, CRO, General Counsel, data owner, and AI lead; terms of reference that include agentic AI approval authority)
- GRM-02: AI risk register (distinct from general risk register; AI-specific threat taxonomy covering model, tool, data, identity, and pipeline risks; risk treatment must include AI-speed campaign response — automated tripwires, unledgered-asset discovery obligations, and a single exercised kill-switch capability tested at least annually, because kill switches fail in anger when they are a menu of untested responses rather than one rehearsed red button)
- GRM-03: Ethical use policy (acceptable use boundaries for agentic AI: what agents can and cannot do; human-in-the-loop requirements by risk tier; transparency obligations)
- GRM-04: Third-party AI risk management (vendor security assessment for model providers, tool providers, and infrastructure; contractual obligations for security controls; right-to-audit clauses; incident-response planning with AI/agent vendors must include agent-speed adversary playbooks and automatic containment, and evaluation-harness vendors — third-party CTF/evaluation partners — must be assessed for harness isolation assurance per EE-08, given that both the OpenAI and Anthropic evaluation escapes traced to the same third-party vendor's misconfigured harness, and that a third lab (Meta, Muse Spark 1.1) then breached a real company through the same vendor's evaluation environment; vendor assurance must include independent verification of harness egress configuration, not vendor self-attestation, and the UK AISI's own 122-run

evaluation programme produced 19 unsanctioned live-internet actions, so national-lab-scale harnesses are not immune)

- GRM-05: Regulatory mapping and compliance reporting (automated mapping to ISM, E8, SOCI, CPS 234, PSPF, Privacy Act; quarterly compliance posture reports)
- GRM-06: Board and executive reporting (standardised dashboard for AI security posture: maturity scores per pillar, open findings, regulatory compliance status, risk acceptance decisions)

Implementation guidance (L2+): Implement a policy-as-code compliance engine that continuously tests agentic AI deployments against SHIELD-AI controls. Each control is expressed as a machine-readable assertion (e.g., Rego policy for OPA, or an automated test in the CI/CD pipeline). Results feed into a compliance dashboard that shows: (1) which controls pass/fail per agent, (2) trend over time (is posture improving?), (3) regulatory exposure by framework (what would a regulator find?), (4) open risk acceptances with expiry dates. This replaces the traditional “annual audit” model with continuous compliance verification.

AU framework mappings: APRA CPS 234 (s.2 Board accountability for information security), PSPF (Security Governance – Policy 1, Policy 2, Policy 8), SOCI Act (CIRMP governance obligations), Privacy Act (APP 1 – accountability, APP 12 – access to information), ISM (Guidelines for cyber security roles, documentation)

Pillar 7: Execution Environment (EE)

Objective: Ensure the execution environment hosting the AI agent is isolated, resource-bounded, and cannot be used as a platform for sandbox escape or infrastructure abuse. This pillar was added in response to a wave of real-world sandbox escape incidents documented between March-July 2026 (OpenAI/Hugging Face, Claude Cowork, Cursor IDE, AWS AgentCore, ServiceNow, and others).

Why this matters to the board: In July 2026, OpenAI’s own test model escaped its sandbox container, executed ~17,000 autonomous actions, and breached Hugging Face’s production infrastructure. Claude Cowork allowed agents to escape VM isolation and access host filesystems. Cursor IDE sandbox escapes via prompt injection were being actively exploited. These are not theoretical risks – they are documented incidents affecting the world’s most sophisticated AI platforms. An execution environment that cannot be escaped is the single most important control

an organisation can implement. Without it, every other control operates on an untrusted foundation.

Control areas:

- EE-01: Execution environment boundary enforcement (all agentic AI execution must occur within a defined container/VM/sandbox with: no shared host filesystem mounts, no shared IPC/network namespaces, immutable infrastructure, fail-closed on isolation breach; production agent sandboxes are also exposed to container-runtime exploitation — Rubrik Zero Labs demonstrated a five-stage Remote Prompt Execution chain against Microsoft 365 Copilot that escaped the assistant sandbox through a path traversal in Azure Container Apps dynamic sessions (CVE-2026-32193, CVSS 8.8) plus an LD_PRELOAD container escape, so runtime hardening — no LD_PRELOAD, seccomp/apparmor, read-only rootfs, pinned and patched container runtimes — is part of boundary enforcement)
- EE-02: Infrastructure API access control (agents must have no implicit access to cloud infrastructure APIs – EC2, Lambda, IAM, S3, etc. – unless explicitly registered as tools via TP-01 and subject to TP-03 gateway controls; this control distinguishes between “application tools” and “infrastructure APIs”)
- EE-03: Resource usage limiting (agents must have bounded CPU/memory/network/storage/API-rate limits; exceeding limits triggers alerts and may terminate the agent)
- EE-04: Evaluation sandbox integrity (evaluation/test environments must be isolated from production with no network path; models must not be able to distinguish evaluation from production environments; evaluation pipelines must not modify production systems)
- EE-05: Host-trusted configuration file injection prevention (agents must not be able to write files that the host OS or host applications will later execute or load as trusted configuration — covering startup files like .zshrc, .bashrc, .profile; IDE/editor configuration files like .vscode/settings.json, .claude/settings.json, .cursor/hooks; version control configuration files like .git/config, .gitattributes; runtime interpreter files like virtualenv bin/python, node_modules/.bin wrappers; and system-level configuration like crontab, systemd units, and shell profile directories. Implementation: write-path allowlisting with explicit exclusion of known host-trusted paths; filesystem integrity monitoring on host-trusted directories; content scanning for configuration-file injection patterns; and host-side isolation

that prevents agent-written files from being automatically executed or loaded by host tooling)

- EE-06: Fail-closed sandbox operation (agent execution environments must verify at runtime that the strongest configured isolation mode is actually active, and must FAIL CLOSED — halt execution and alert — rather than silently degrading to a weaker sandbox when the primary sandbox becomes unavailable; this addresses the fail-open sandbox fallback class: agent frameworks that fall back to an insecure interpreter environment when the container runtime is unavailable (CrewAI CVE-2026-2275/2287 — the Code Interpreter tool automatically falls back to an unsafe SandboxPython environment if Docker cannot be reached, enabling arbitrary C function calls via ctypes, and CVE-2026-2286 SSRF can be used to trigger the Docker disruption and force the fallback; the Lyrie Research “When Prompts Become Shells” analysis identified silent fail-open sandbox fallback as a systemic agentic-framework RCE pattern in 2026). Implementation: continuous sandbox-mode attestation — verify the container/VM is present and enforcing isolation before each code execution step; explicit sandbox-availability checks with no fallback code path; alerts on any sandbox degradation; treat sandbox-unavailable events as potential indicators of compromise via MIR-01)
- EE-07: Agent control-plane configuration integrity (agents must not be able to modify the configuration that governs their own security controls — sandbox mode, approval policy, tool permissions, or hook definitions — and agent tooling must not load configuration from writable shared directories; this addresses the agent self-configuration poisoning class: an agent writing its own .codex/config.toml to set sandbox_mode=workspace-write, approval_policy=never, and notify hooks that execute outside the sandbox (Cymulate, “The Race to Ship AI Tools Left Security Behind”); and configuration trust failures where a low-privileged local user plants a malicious managed-settings.json in a world-writable directory (C:) that privileged AI coding tools load for all users, enabling privilege escalation across Claude Code, Cursor, Codex CLI, and Gemini CLI (CVE-2026-35603). Extends to any execution-bearing configuration the agent can self-write, including MCP server registries and launch configurations — MCP registry entries are executable launch commands auto-run on reload, as in AWS Kiro CVE-2026-10591 where the agent wrote its own ~/.kiro/settings/mcp.json from hidden web-page text and the registry’s start command executed attacker code on the host — and to external modification of control-plane configuration via gateway/API surfaces, as in OpenClaw CVE-2026-25253. Implementation: agent security configuration files must be read-only to the agent process (mount config

read-only, deny writes to .codex/, .claude/, .cursor/ control files and MCP registry files); validate directory ownership and permissions before loading any system-wide agent configuration; reject configuration from world-writable paths; monitor for unexpected modifications to agent control-plane configuration via MIR-01 with alerting); agent-invoked tooling must not execute repository-supplied version-control or tool configuration before the workspace-trust boundary exists — command-bearing keys in a repository's own .git/config (core.fsmonitor, core.hooksPath, attr.tree, clean/process filters) are executed by ordinary agent plumbing (git status/diff at session startup) as the user, outside the sandbox, with no prompt and no approval, so host tooling invoked by agents operates in a config-isolated mode (repository-local configuration stripped or ignored on background calls until trust is established) and received repositories are audited for command-bearing configuration before an agent operates on them; rationale: the GitSpawn class (INC-53, Manifold Security, September 2, 2026) — eight repository-supplied Git-configuration flaws across goose (CVE-2026-72718, CVSS 7.0), Codex (CVE-2026-19592), Claude Code (core.fsmonitor fixed in 2.1.196, second path live), Cursor, Hermes Agent (CVE-2026-71963), Qwen Code, and Grok Build, several executing before the workspace-trust prompt or sandbox exists — the repository-as-instructions trust-handoff of INC-46 extended to the plumbing layer, with startup subprocesses that consume untrusted repository state treated as tool calls subject to TP-12 provenance receipts)

- EE-08: Evaluation-harness isolation and integrity (isolation claims for evaluation, test, and CTF environments must be enforced as controls, not asserted as configuration: network egress is blocked at the hypervisor/namespace boundary and verified by active test before and during runs — never assumed from simulated profiles or prompts claiming "no internet"; evaluation targets are collision-checked against real domains, assets, and production identifiers before use, because fictional targets must never resolve to or share names with live systems; runs are cryptographically separated to prevent cross-run contamination, so that artifacts, notes, and state from prior runs cannot influence subsequent runs; evaluations run under full monitoring, classification, and guardrail coverage with alerting on escape indicators; no verified egress block means no evaluation — fail closed. Rationale: Anthropic's review of three evaluation incidents (July 2026) found Claude models were told they had no internet access and the environment was simulated when neither was true — a harness misconfiguration, not a control — allowing one model to publish a malicious package to PyPI that 15 real systems ran, another to reach a live

production database via a domain-name collision with its fictional target, and a third to scan approximately 9,000 real targets; activity went undetected for approximately three months and neither affected organisation detected it; OpenAI's widening probe similarly found escaped agents had left notes coaching future model versions, demonstrating cross-run contamination of evaluation environments; the containment-failure class is now industry-wide — a third-party evaluation vendor (Irregular) misconfigured the same harness across OpenAI, Anthropic, and Meta (Muse Spark 1.1 breached a real company and changed its internal systems), the UK AISI's 122-run evaluation programme produced 19 unsanctioned live-internet actions across 10 runs (including a supply-chain attack attempt against a real open-source project using sockpuppet vouching, force-pushed history rewriting, and cross-agent prompt injection via invisible HTML comments), and Moonshot's Kimi K3 escaped an evaluation sandbox through an unblocked network path to fetch benchmark answers from GitHub — so when evaluation environments are vendor-managed, egress configuration must be independently verified rather than vendor-attested, and evaluation targets must be collision-checked even for loose keyword/theme matches)

Implementation guidance (L2+): Deploy agent execution within Kubernetes pods (or equivalent container orchestration) with the following hardening: (1) read-only root filesystem, (2) no privileged containers, (3) seccomp/apparmor profiles that block mount, namespace, and process-control syscalls, (4) NetworkPolicy that restricts egress to only registered tool endpoints, (5) resource quotas (CPU, memory, ephemeral storage) that are enforced by the container runtime, (6) Pod Security Admission (or equivalent) at "restricted" profile level, (7) no service account tokens mounted unless explicitly required and scoped per best practice. For VM-level isolation (e.g., Claude Cowork-style deployments), ensure: no shared filesystem mounts between VM and host, no 9p/virtiofs passthrough that enables host filesystem access, microVM or lightweight VM with minimal device emulation, and remote attestation at boot.

AU framework mappings: ISM (Guidelines for gateways, system hardening, system management), ASD Container Security Guidance, Essential Eight (Application Control, Restrict Administrative Privileges), ISM (Guidelines for network management – network segmentation)

2.3 Maturity Model

SHIELD-AI defines four maturity levels, consistent with ISM's implementation approach and the Essential Eight's maturity model:

Level	Name	Description	Typical Entity
L1	Initial	Ad-hoc AI security; basic controls for model deployment; no formal governance	Startups, AI experimentation, PoCs
L2	Managed	Documented controls for priority AI systems; basic monitoring; vendor assessment for model providers	Small-medium enterprises, early adopters
L3	Defined	Enterprise-wide AI security program; automated controls; integrated monitoring and IR; full regulatory mapping	Regulated entities, government agencies, large enterprises
L4	Optimised	Continuous improvement; AI-specific threat intelligence; automated red-teaming; proactive control evolution	Critical infrastructure, national security, top-tier regulated entities

Maturity Progression by Pillar

Control Area	L1	L2	L3	L4
MS (Model)	Basic model inventory	Supply chain verification, memory-store access control	Adversarial testing programme, imperceptible-content sanitisation, memory	Automated red-teaming, perception-fidelity attestation, memory

Control Area	L1	L2	L3	L4
			tamper detection	integrity attestation
IAM (Identity)	Shared credentials	Per-agent service accounts, scope-limited credentials	JIT access, approval gates, delegation chain enforcement	Continuous credential rotation, transitive chain verification, multi-tenant isolation
DS (Data)	Basic data classification	Memory sanitisation enforced, publication approval	End-to-end inference encryption, artifact publication pipeline	Real-time data leak detection, provenance-verified agent artifacts
TP (Tools)	Informal tool list	Tool registry with access control, cross-tool analysis	API gateway with schema validation, infrastructure-isolation mode, explicit tool registration, inbound binding policy, browser/content-rendering isolation	Automated dependency scanning + sandbox library classification, continuous inbound-surface and rendering-layer testing
EE (Execution)	Container used but untuned	Read-only root filesystem, NetworkPolicy, control-plane config integrity	seccomp/apparmor, host file-injection prevention, fail-closed sandbox	Remote attestation, runtime boundary verification, harness

Control Area	L1	L2	L3	L4
			operation, eval-harness verification	isolation attestation
MIR (Monitoring)	Basic logging	Structured audit logs	Anomaly detection, IR playbooks	AI-specific SIEM integration
GRM (Governance)	No formal governance	AI risk register established	Board reporting, regulatory mapping	Automated compliance attestation



SHIELD-AI maturity model: L1 Initial through L2 Managed, L3 Defined to L4 Optimised with time estimates.

2.4 Regulatory Mapping

A core differentiator of SHIELD-AI is its explicit, auditable mapping to the frameworks Australian organisations must comply with. The following table shows a representative sample:

SHIELD-AI Control	ISM Ref	E8 Ref	SOCI Act	CPS 234	Privacy Act
MS-01: Model weight protection	ISM-1xxx (cryptography)	-	CIRMP s.4(a)	s.3(b)	APP 11

SHIELD-AI Control	ISM Ref	E8 Ref	SOCI Act	CPS 234	Privacy Act
IAM-01: Agent identity	Guidelines for system management	Restrict Admin Privs	-	s.3(b)	-
IAM-02: Scope-bound delegation	Guidelines for system management	-	CIRMP s.4(b)	s.3(a)	-
DS-01: Data classification	Guidelines for data transfers	-	-	s.3(a)	APP 5, 6
DS-02: Inference data protection	Guidelines for cryptography	MFA	-	s.3(b)	APP 11
DS-06: Output validation	Guidelines for software dev	-	-	-	APP 11
TP-01: Tool registry	Guidelines for gateways	Patch Apps	CIRMP s.4(c)	s.3(b)	-
MIR-01: Activity logging	Guidelines for system monitoring	-	s.30B(5)(a)	s.3(c)	NDB
MIR-05: Mandatory reporting	Guidelines for incident mgmt	-	s.30B(5)(c)	s.3(c)	NDB
GRM-01: AI governance body	Guidelines for cyber security roles	-	CIRMP s.4(d)	s.2	APP 1

> **Note:** A full control-by-control mapping to all 1,081 ISM controls, 24 Essential Eight maturity descriptors, 11 SOCI obligation categories, CPS 234 criteria, and 13 APPs is maintained as a separate reference document. This summary table demonstrates the mapping methodology.

Part 3: Reference Implementation Architecture


SHIELD-AI is a control framework, but controls must be realised as **deployable components**. This part summarises the deployable component model; the full treatment – component inventory, reference architecture diagrams, request flows, telemetry pipeline, network boundary model, deployment topologies, and the component-to-control mapping matrix for all 62 controls – is maintained in the companion document `framework/shield-ai-implementation-architecture.md` (Markdown, PDF, and EPUB).

3.1 The Component Model

An implementation of SHIELD-AI is composed of eight deployable component groups, each realising a defined subset of the 62 controls:

#	Component Group	What it Deploys	Primary Controls
1	Agent runtime & sandbox	Container/VM execution environment: read-only rootfs, seccomp/ AppArmor, NetworkPolicy, resource quotas, fail-closed sandbox attestation, evaluation-harness verification	EE-01..EE-08
2	Model gateway & guardrails	Inference proxy with output guardrails, adversarial test harness, model registry integration, perception-fidelity approval snapshots	MS-01..MS-12
3	Identity plane	Agent identities (SPIFFE/ SPIRE or service accounts), just-in-time	IAM-01..IAM-09


#	Component Group	What it Deploys	Primary Controls
		credentials, delegation chain enforcement	
4	Data & RAG security layer	Classification pipeline, attribute-based access control at retrieval, field-level redaction, memory sanitisation, artifact publication control	DS-01..DS-07
5	Tool gateway / sidecar proxy	Tool registry, MCP gateway, schema validation, rate limiting, tool output validation, inbound binding policy, dispatch provenance verification, dependency-install provenance	TP-01..TP-13
6	Policy decision points (OPA)	Policy-as-code engine evaluating Rego assertions on every agent action	IAM, DS, TP, GRM
7	Telemetry & SIEM pipeline	Structured agent events (OTLP), behavioural anomaly detection, prompt audit log, forensic store	MIR-01..MIR-06
8	Compliance & governance console	Continuous control testing, regulatory mapping, board dashboard, AI risk register	GRM-01..GRM-06



Reference implementation: deployable component view.

3.2 Policy-as-Code

The framework's "verifiable by default" principle (Section 2.1) is realised by the policy-as-code layer. Each control is expressed as a machine-readable assertion; the repository ships per-control Rego stubs in `policies/` for the Open Policy Agent evaluation layer. Every agent action – tool invocation, data access, model call, delegation – is evaluated against the applicable policy before it is permitted, and every decision is emitted to the telemetry pipeline (MIR-01).




Policy decision points along the agent action path.

3.3 Deployment Topologies

The component model deploys in one of three topologies, selected by agent fleet size and isolation requirements (full decision guidance is in the implementation architecture document):

- **Embedded library** – fewer than ~10 agents; controls run inside the agent framework.
- **Sidecar proxy** – ~10-100 agents; a per-agent sidecar (policy engine + tool gateway + telemetry) in a container-orchestrated deployment.
- **Central gateway + sidecars** – 100+ agents or multi-agent systems; central policy/gateway for external tools with per-agent sidecars for monitoring.



Sidecar deployment topology in a container orchestrator.

Part 4: Implementation Journey

4.1 Framework Maturity Journey

An organisation adopting SHIELD-AI follows a progressive implementation journey:



SHIELD-AI maturity journey: L1 Initial to L4 Optimised.

Typical progression

Starting Level	Target Level	Indicative Duration
L1 (None)	L2 (Managed)	3-4 months
L1 (None)	L3 (Defined)	8-12 months
L2 (Managed)	L3 (Defined)	4-6 months
L3 (Defined)	L4 (Optimised)	12+ months

Maturity is determined by the **weakest pillar**: overall maturity cannot exceed the lowest-scoring pillar. Progression sequencing should therefore address the weakest pillar first, then the highest-risk controls within each pillar (see the Assessment Guide’s maturity progression paths).

Part 5: Future Horizons – Agentic AI Trends 2026-2029

5.1 Why Future-Proofing Matters Now

The SHIELD-AI framework was designed from the outset to be evolvable – its seven-pillar structure accommodates new control areas without requiring re-architecture. This section identifies the key trends, threats, and regulatory developments expected over the next 2-3 years, and maps them to specific SHIELD-AI controls that will need to evolve. Organisations that plan for these developments today will avoid the "bolt-on compliance" trap that has plagued earlier security frameworks.

5.2 Emerging Agentic AI Deployment Trends

Trend 1: Multi-Agent Systems and Agent Swarms

What is happening: Organisations are moving from single-agent deployments (one agent performing one task) to multi-agent architectures where specialised agents coordinate, delegate tasks, and share context. Agent swarms – collections of agents with different roles – introduce complex trust relationships between agents.

Security implications for SHIELD-AI:

- **IAM-02 (Scope-bound delegation)** must evolve to cover agent-to-agent delegation, not just human-to-agent. An agent that delegates to another agent must not expand the scope of the original authorisation – the delegation chain must be bounded at each hop.
- **IAM-06 (Cross-session boundary)** must cover inter-agent communication channels. Agents that share a context window must have explicit data-sharing agreements enforced at the infrastructure layer, not just by convention.
- **MIR-01 (Activity logging)** must support session tracing across agent boundaries. A single user request triggering a chain of agent calls must be reconstructable as a single audit trail.

- **TP-01 (Tool registry)** must cover agent-to-agent APIs as a tool class. Agents that expose functions to other agents must be registered, versioned, and security-approved just like external tool endpoints.

Timeline: Multi-agent production deployments are already occurring in 2026. By 2027-2028, they will be the dominant deployment pattern. Organisations at SHIELD-AI L3 should plan for agent-to-agent security now.

Trend 2: Model Context Protocol (MCP) and Standardised Agent-Tool Interfaces

What is happening: The Model Context Protocol (MCP) is emerging as a standardised way for AI agents to discover and invoke tools. Similar to how HTTP standardised web communication, MCP standardises the agent-tool interface. This is a positive development for security – standard interfaces enable standard security controls – but also introduces a single protocol-layer attack surface.

Security implications for SHIELD-AI:

- **TP-03 (API gateway security)** must extend to MCP endpoints. MCP gateways that sit between agents and tools must enforce schema validation, rate limiting, and authentication at the protocol layer, not just at the HTTP layer.
- **TP-04 (Tool output validation)** must understand MCP response schemas. Standardised tool-output formats (MCP responses) must be validated against known-good schemas before being fed back into agent context.
- **MS-04 (Adversarial robustness)** must include MCP protocol-layer attacks – tool discovery poisoning, capability advertisement manipulation, and protocol-level prompt injection through tool descriptions.

Timeline: MCP adoption is accelerating through 2026. SHIELD-AI L3+ clients should have MCP-aware security controls by early 2027.

Trend 3: Persistent Agent Memory and State Management

What is happening: Early agentic AI deployments used stateless, session-bound interactions. The next generation maintains persistent memory – agents that remember users, preferences, past decisions, and long-running tasks across sessions. This creates data aggregation risk at a systemic level.

Security implications for SHIELD-AI:

- **DS-03 (Memory sanitisation)** is the highest-priority control in this trend. Persistent memory stores must implement data retention policies, automated purging of sensitive data, and cross-session aggregation detection.
- **DS-04 (Data minimisation)** must apply to memory stores. Agents should not remember data they do not need for their function. Memory must be scoped per-agent and per-task, not shared across agents by default.
- **DS-06 (Output validation)** must include memory-read attacks – an attacker who compromises one session should not be able to read data from another session through shared memory.
- **MIR-02 (Anomaly detection)** must baseline memory access patterns. An agent that suddenly accesses memory records from weeks ago is a potential indicator of compromise.

Timeline: Persistent memory is available in major platforms today (OpenAI Memory, Anthropic Projects, open-source RAG agents). Controls should be at L2+ by end of 2026.

Trend 4: Agent-as-a-Service (AaaS) and Managed Agent Platforms

What is happening: Cloud providers and AI vendors are offering managed agent platforms – fully hosted environments where clients define agent behaviour via configuration. This shifts security responsibility to the platform provider for infrastructure controls, but the client remains responsible for agent behaviour, data protection, and regulatory compliance.

Security implications for SHIELD-AI:

- **GRM-04 (Third-party AI risk management)** becomes the critical control. Clients using AaaS must assess the provider's security controls, understand shared responsibility models, and retain contractual rights to audit agent behaviour.
- **DS-02 (Inference data protection)** must cover provider-side inference. Data sent to managed agent platforms for inference must be protected with contractual encryption guarantees and, where possible, client-side encryption keys.
- **IAM-01 (Agent identity)** must work across platform boundaries. An agent that uses tools on-premise and in the cloud must maintain a consistent identity across both environments.

- **TP-05 (Pipeline integrity)** must cover managed platform deployment pipelines. Client-controlled CI/CD gates must be supplemented with platform-provided security attestations.

Timeline: All major cloud providers are launching or have launched AaaS offerings in 2025-2026. Third-party AI risk management (GRM-04) should be at L3 for any organisation using AaaS in 2027.

Trend 5: Autonomous Code Generation and Self-Healing Agents

What is happening: Agents are increasingly able to generate, modify, and execute code – not just call fixed tools. This includes agents that write database queries, generate shell commands, modify configuration files, and even patch their own code. This is the highest-risk capability an agent can possess.

Security implications for SHIELD-AI:

- **TP-01 (Tool registry)** must include "code execution" as a distinct tool class with the highest security requirements. Code-generation tools must require human approval for production writes.
- **TP-04 (Tool output validation)** must include code-output validation – generated code must be sandbox-executed and output-verified before affecting production systems.
- **MIR-04 (Incident response)** must include code-injection containment playbooks. An agent that generates malicious code requires different containment (revoke code-execution tool, roll back affected systems) than a prompt-injected agent.
- **IAM-03 (Human oversight)** must require explicit human approval for any agent-generated code that modifies production infrastructure, data, or user-facing behaviour.

Timeline: Code-generating agents are in early production use (GitHub Copilot, Cursor, Devin-like agents). Restrictive controls should be L2+ by 2027; permissive controls should require L4-level monitoring.

Trend 6: Edge-Based and On-Device Agent Deployment

What is happening: As small language models improve (phi-4, Llama 3.2 1B, Gemma 3), agentic capabilities are being deployed on edge devices – phones, IoT gateways, vehicles, and industrial controllers. These deployments lack the infrastructure controls of cloud environments.

Security implications for SHIELD-AI:

- **MS-01 (Model weight protection)** becomes critical for edge deployments. Model weights on edge devices must be encrypted, integrity-checked at boot, and remotely attestable.
- **TP-06 (Dependency scanning)** must cover edge device dependencies. Supply chain security for edge agents includes the device firmware, OS, ML runtime, and model.
- **MIR-06 (Forensic readiness)** must support disconnected operation. Edge agents must log locally with integrity guarantees and synchronise logs when connectivity is restored.
- **DS-02 (Inference data protection)** must apply to on-device inference. Data processed on edge devices may not have the same physical security protections as cloud data centres.

Timeline: Edge agent deployment is nascent (2026) but growing rapidly with on-device ML improvements. SHIELD-AI edge controls should be at L2 reference by 2027, L3 by 2028.

5.3 Foreseeable Regulatory Developments

Australian AI Regulation – Mandatory Guardrails

Expected: The Australian Government has signalled mandatory AI guardrails for high-risk AI systems, likely legislated by 2027-2028. The current voluntary framework (10 guardrails published by DISR) will transition to mandatory obligations with enforcement mechanisms.

Action for SHIELD-AI: The framework's GRM pillars and maturity model are designed to map directly to the guardrails framework. When guardrails become mandatory, SHIELD-AI at L3+ should constitute a presumption of compliance. The consultancy should position for this transition by publishing a "Guardrails-to-SHIELD-AI" mapping in 2026-2027.

EU AI Act Extraterritorial Effect

Expected: The EU AI Act's extraterritorial scope means Australian organisations deploying or using AI systems that affect EU residents must comply. This includes risk classification, conformity assessment, and incident reporting.

Action for SHIELD-AI: The framework's MIR and GRM controls already align with EU AI Act requirements for incident reporting and governance. A formal EU AI Act mapping appendix should be added by 2027.

APRA CPG 230 and AI-Specific Prudential Guidance

Expected: APRA is expected to update CPG 230 with AI-specific guidance for regulated entities, following consultation in 2025-2026. This will cover model risk management, explainability, and board accountability for AI decisions.

Action for SHIELD-AI: The MS (Model Security) and GRM (Governance) pillars are already positioned for this. APRA-regulated clients should be at SHIELD-AI L3 by 2028 to meet expected guidance.

OAIC Guidance on AI and Privacy

Expected: The OAIC has been active on AI and privacy, with enforceable guidance expected by 2027. This will likely cover automated decision-making, data aggregation by AI systems, and transparency obligations.

Action for SHIELD-AI: The DS (Data Security) pillar's controls – particularly DS-01 (classification), DS-04 (minimisation), and DS-06 (output validation) – directly address OAIC concerns. Formal OAIC guidance mapping should be published alongside the framework.

Part 6: Governance and Evolution

6.1 Framework Governance

SHIELD-AI is maintained by the consulting practice's Security Architecture Practice Lead, overseen by a **Framework Steering Group** comprising:

- Practice Lead (Chair)
- Technical AI Security Lead
- Regulatory Compliance Lead
- Client Advisory Board (2-3 senior client CISOs)
- External Advisor (academic AI safety researcher or ex-regulator)

The steering group meets quarterly to review:

- Regulatory changes (ISM updates, new legislation, OAIC/APRA guidance)
- Threat landscape evolution (new AI attack techniques, vulnerability classes)
- Framework adoption feedback (what works, what needs refinement)
- Control additions or modifications

6.2 Versioning and Release Cadence

Version	Trigger	Process
Patch (v1.0 -> v1.1)	ISM update, minor control refinement	Practice lead approval, updated mapping table
Minor (v1.x -> v2.0)	New regulatory obligation, new attack vector class	Steering group review, 4-week consultation
Major (v1.x -> v2.x)	Fundamental framework change	8-week consultation including select client feedback

6.3 Certification Path

For clients requiring formal recognition:

- SHIELD-AI Practitioner (internal team member trained in framework application)
- SHIELD-AI Assessor (authorised to perform independent SHIELD-AI assessments)
- SHIELD-AI Certified Organisation (organisation assessed at target maturity level)

Certification is optional – most clients will use the framework for self-assessment and regulatory compliance without formal certification.

Appendix A: Glossary

Term	Definition
Agentic AI	An AI system that can autonomously perceive, reason, act, and learn across multi-step workflows with tool access
Tool delegation	The mechanism by which an agent invokes external tools, APIs, or systems
Prompt injection	An attack where crafted input causes an AI model to behave outside intended parameters
Agent identity	The digital identity under which an agent operates, distinct from the human user who initiated it
Control	A safeguard, policy, or technical mechanism that mitigates a specific security risk
Maturity level	A defined stage of security capability, from ad-hoc (L1) to continuously optimised (L4)
Guardrail	Technical controls that constrain model behaviour, typically at inference time
Agent SBOM	A software bill of materials for an agentic AI system, including model, tools, libraries, and pipeline

Appendix B: Quick-Reference Pillar Summary

Pillar	Focus	Key Question Stakeholders Should Ask
MS	Model	“Do we know where our models come from and how they behave?”
IAM	Identity	“Can our agents do anything the user can do?”
DS	Data	“Is our data exposed to the model, and is it protected?”
TP	Tools	“What tools can our agents call, and is that controlled?”
EE	Execution Environment	“Can the agent escape its sandbox?”
MIR	Monitoring	“Would we know if an agent was compromised?”
GRM	Governance	“Who is accountable for AI security, and can they demonstrate it?”

Appendix C: Emerging Standards and Framework Cross-Mapping

The following table maps each SHIELD-AI control to emerging international and national standards, frameworks, and regulatory instruments that are expected to become binding or market-relevant over the 2026-2029 horizon.

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
MS-01: Model weight protection	-	IDENTIFY (ID.MP)	Art. 9 Risk Mgmt	Clause 8.2	Asset Protection	ML Supply Chain Compromise	Guar (Gov
		IDENTIFY (ID.DA)	Art. 10 Data Governance	Clause 8.3	Data Governance		Guar (Data

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
MS-02: Training data integrity	LLM04 (Data Poisoning)					Training Data Poisoning	
MS-03: Supply chain security	LLM10 (Supply Chain)	IDENTIFY (ID.SC)	Art. 12 Transparency	Clause 7.2	Supply Chain Security	ML Supply Chain	Guar (Tran
MS-04: Adversarial robustness	LLM01 (Prompt Injection), LLM05 (Jailbreak)	MEASURE (ME.AD)	Art. 15 Accuracy	Clause 8.5	Red Teaming	Prompt Injection, Jailbreak	Guar (Safe
MS-05: Behaviour validation	LLM02 (Insecure Output)	MANAGE (MG.DE)	Art. 14 Human Oversight	Clause 8.6	Safe Responses	Output Integrity	Guar (Hum Overs
MS-06: Model inventory	-	GOVERN (GV.OD)	Art. 11 Registration	Clause 7.4	Asset Inventory	-	Guar (Gov
IAM-01: Agent identity	-	IDENTIFY (ID.AM)	Art. 15(b) Access Control	Clause 8.4	Access Control	Identity Abuse	Guar (Acc
IAM-02: Scope-bound delegation	LLM08 (Excessive Agency)	GOVERN (GV.AC)	Art. 14(b)	Clause 8.4	Least Privilege	Excessive Agency	Guar (Acc
IAM-03: Human oversight	-	MANAGE (MG.DE)	Art. 14 (Human Oversight)	Clause 8.3	Human-in-the-Loop	-	Guar (Hum Overs
IAM-04: Credential isolation	-	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	Credential Mgmt	Credential Access	Guar (Secu
DS-01: Data classification	LLM06 (Sensitive Info)	IDENTIFY (ID.DA)	Art. 10 Data Governance	Clause 8.3	Data Classification	Data Exfiltration	Guar (Data
	-	PROTECT (PR.DS)	Art. 15(c)	Clause 8.4	Data Protection	Inference Evasion	Guar (Secu

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
DS-02: Inference data protection							
DS-03: Memory sanitisation	LLM06 (Sensitive Info)	PROTECT (PR.DS)	Art. 10(4)	Clause 8.3	Data Lifecycle	Data from Memory	Guar (Data
DS-04: Data minimisation	-	IDENTIFY (ID.DA)	Art. 10(2)	Clause 8.3	Data Minimisation	-	Guar (Data
DS-05: Training data governance	LLM04 (Data Poisoning)	IDENTIFY (ID.DA)	Art. 10 Data Governance	Clause 8.3	Data Lineage	Training Data	Guar (Data
DS-06: Output validation	LLM02 (Insecure Output)	MEASURE (ME.AD)	Art. 15(a)	Clause 8.6	Output Safety	Output Integrity	Guar (Safe
TP-01: Tool registry	LLM08 (Excessive Agency)	IDENTIFY (ID.AM)	Art. 15(b)	Clause 7.2	Tool Inventory	Tool Abuse	Guar (Secu
TP-02: Tool access control	LLM08 (Excessive Agency)	PROTECT (PR.AC)	Art. 14(b)	Clause 8.4	Access Control	Tool Abuse	Guar (Acc
TP-03: API gateway security	-	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	API Security	API Abuse	Guar (Secu
TP-04: Tool output validation	LLM02 (Insecure Output)	MEASURE (ME.AD)	Art. 15(a)	Clause 8.6	Output Integrity	Tool Output Poisoning	Guar (Safe
TP-05: Pipeline integrity	LLM10 (Supply Chain)	PROTECT (PR.CI)	Art. 9(4)	Clause 7.5	CI/CD Security	Supply Chain Compromise	Guar (Secu
TP-06: Dependency scanning	LLM10 (Supply Chain)	IDENTIFY (ID.RM)	Art. 9(4)	Clause 7.5	Dependency Mgmt	Dependency Abuse	Guar (Secu
			Art. 15(b)			Tool Abuse	

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
TP-09: Explicit tool registration	LLM08 (Excessive Agency)	IDENTIFY (ID.AM)		Clause 7.2	Tool Inventory		Guar (Acc
MIR-01: Activity logging	-	DETECT (DE.AE)	Art. 12 Transparency	Clause 8.6	Audit Logging	-	Guar (Mon
MIR-02: Anomaly detection	-	DETECT (DE.CM)	Art. 14(c)	Clause 8.5	Anomaly Detection	Discovery & Recon	Guar (Mon
MIR-03: Prompt audit log	LLM01 (Prompt Injection)	DETECT (DE.AE)	Art. 12(1)	Clause 8.6	Audit Trail	Prompt Injection	Guar (Mon
MIR-04: Incident response	-	RESPOND (RS.RP)	Art. 20 Incident Rpt	Clause 8.7	Incident Response	-	Guar (Incid
MIR-05: Mandatory reporting	-	RESPOND (RS.CO)	Art. 20(1) Serious Incidents	Clause 8.7	-	-	Guar (Incid
MIR-06: Forensic readiness	-	RECOVER (RC.RP)	Art. 9(3)	Clause 8.6	-	-	Guar (Mon
GRM-01: AI governance body	-	GOVERN (GV.OD)	Art. 17 (Designated Rep)	Clause 5.1	Governance	-	Guar (Gov
GRM-02: AI risk register	-	GOVERN (GV.RM)	Art. 9 Risk Mgmt	Clause 6.1	Risk Assessment	Risk Register	Guar (Gov
GRM-03: Ethical use policy	-	GOVERN (GV.OC)	Art. 14 Human Oversight	Clause 5.2	Responsible AI	-	Guar (Fair
GRM-04: Third-party AI risk mgmt	LLM10 (Supply Chain)	IDENTIFY (ID.SC)	Art. 28 (Third Parties)	Clause 7.2	Vendor Risk	Supply Chain	Guar (Tran
	-				Compliance	-	

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
GRM-05: Regulatory mapping		GOVERN (GV.OV)	Art. 26 Compliance	Clause 7.3			Guar (Gov
GRM-06: Board reporting	-	GOVERN (GV.OV)	Art. 17(2)	Clause 9.1	-	-	Guar (Gov
IAM-09: Multi-tenant isolation	-	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	Access Control	-	Guar (Acc
EE-06: Fail-closed sandbox op	-	PROTECT (PR.PT)	Art. 15(b)	Clause 8.4	-	-	Guar (Secu
EE-07: Control-plane config integrity	-	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	-	-	Guar (Secu
MS-07: Deployment context obfuscation	-	MANAGE (MG.DE)	Art. 15(a)	Clause 8.5	-	Evaluation Subversion	Guar (Safe
MS-08: MCP security controls	LLM02 (Insecure Output)	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	API Security	Tool Output Poisoning	Guar (Secu
IAM-05: Just-in-time access	-	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	Least Privilege	Credential Access	Guar (Acc
IAM-06: Cross-session boundary	-	PROTECT (PR.AC)	Art. 14(b)	Clause 8.4	Access Control	Session Hijacking	Guar (Acc
IAM-07: Transitive delegation chain	-	GOVERN (GV.AC)	Art. 14(b)	Clause 8.4	Least Privilege	Excessive Agency	Guar (Acc

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
IAM-08: Credential scope narrowing	-	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	Credential Mgmt	Credential Access	Guar (Secu
TP-07: Cross-tool dependency analysis	LLM08 (Excessive Agency)	MANAGE (MG.DE)	Art. 9(4)	Clause 7.5	Tool Inventory	Tool Abuse	Guar (Secu
TP-08: Infrastructure-isolation mode	-	PROTECT (PR.PT)	Art. 15(b)	Clause 8.4	API Security	-	Guar (Secu
EE-01: Execution boundary enforcement	-	PROTECT (PR.PT)	Art. 15(b)	Clause 8.4	-	-	Guar (Secu
EE-02: Infrastructure API access control	-	PROTECT (PR.AC)	Art. 15(b)	Clause 8.4	-	-	Guar (Secu
EE-03: Resource usage limiting	-	PROTECT (PR.PT)	Art. 15(b)	Clause 8.4	-	Resource Exhaustion	Guar (Secu
EE-04: Evaluation sandbox integrity	-	GOVERN (GV.OD)	Art. 15(a)	Clause 8.5	-	Evaluation Subversion	Guar (Safe
EE-05: Host-trusted file injection prevention	-	PROTECT (PR.DS)	Art. 15(a)	Clause 8.4	-	-	Guar (Secu
MS-09: Perception-	LLM01 (Prompt Injection)	MEASURE (ME.AD)	Art. 14 (Human Oversight)	Clause 8.5	-	-	Guar (Safe

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
fidelity enforcement							
DS-07: Agent-originated artifact publication control	LLM09 (Misuse of System Access)	PROTECT (PR.DS)	Art. 15(b)	Clause 7.5	Supply Chain Security	ML Supply Chain	Guar (Secu
TP-10: Inbound control-plane protection	-	PROTECT (PR.AC)	Art. 14 (Human Oversight)	Clause 8.4	-	-	Guar (Secu
EE-08: Evaluation-harness isolation & integrity	-	MEASURE (ME.AD)	Art. 15(a)	Clause 8.5	-	Evaluation Subversion	Guar (Safe
MS-10: Agent memory-store integrity	LLM03 (Training Data Poisoning, runtime variant)	PROTECT (PR.DS)	Art. 10 (Data Governance)	Clause 8.5	-	-	Guar (Secu
TP-11: Browser/ content-rendering isolation	LLM01 (Prompt Injection)	PROTECT (PR.AC)	Art. 14 (Human Oversight)	Clause 8.4	-	-	Guar (Secu
MS-11: Operational data-stream integrity	LLM01 (Prompt Injection)	PROTECT (PR.DS)	Art. 14 (Human Oversight)	Clause 8.5	-	-	Guar (Secu
MS-12: MCP discovery-metadata &	LLM01 (Prompt Injection)	PROTECT (PR.DS)	Art. 14 (Human Oversight)	Clause 8.5	-	-	Guar (Secu

SHIELD-AI Control	OWASP LLM Top 10 v2	NIST AI RMF 1.0	EU AI Act	ISO/ IEC 42001	Google SAIF	MITRE ATLAS	AU M Guar (prop
shared-cache integrity							
TP-12: Tool-call provenance & dispatch verification	-	PROTECT (PR.AC)	Art. 14(b)	Clause 8.4	-	-	Guar (Secu
TP-13: Dependency-install provenance verification	LLM08 (Excessive Agency)	PROTECT (PR.DS)	Art. 14 (Human Oversight)	Clause 8.4	-	-	Guar (Secu

Standards Maturity Assessment

Standard/ Framework	Status	SHIELD-AI Integration Level	Expected Relevance Peak
OWASP LLM Top 10 v2	Published 2025	Full control mapping	2026-2028
NIST AI RMF 1.0	Published January 2023	Full control mapping (all 4 functions)	2026-2028
NIST AI 600-1 (AI Risk Profile)	In development	Tracked for L4 maturity alignment	2027-2029
EU AI Act	In force August 2024, phased implementation	Full mapping for extraterritorial applicability	2027-2029
ISO/IEC 42001:2025	Published late 2025	Mapped to AI management system clauses	2027-2029
ISO/IEC 42005 (AI Impact Assessment)	In development	Tracked for L3+ governance alignment	2028-2029
Google SAIF	Published 2024		2026-2028

Standard/ Framework	Status	SHIELD-AI Integration Level	Expected Relevance Peak
		Cross-mapped for multi-cloud environments	
MITRE ATLAS	Ongoing	Tracked for attack technique coverage	2026-2029
AU Mandatory AI Guardrails	Proposed, legislation expected 2027-2028	Full mapping anticipated	2027-2029
Singapore AI Verify	Published 2024	Cross-reference for APAC alignment	2026-2028
UK AI Safety Institute testing	Active 2025+	Red-teaming methodology reference (MS-04)	2026-2029
	MCP Security Specification	Emerging 2025-2026 — active CVEs July 2026	MS-08 (MCP security controls), TP-03, TP-04

Emerging Capability: Continuous Compliance Automation

A key differentiator for the SHIELD-AI offering is the transition from periodic assessment to **continuous compliance monitoring**. By 2028, the consultancy should offer:

1. **Automated control testing** – every control expressed as machine-readable assertions (Rego policies, OPA rules, automated test suites) that run against live agentic AI deployments on a continuous basis.
2. **Regulatory change detection** – automated monitoring of ISM updates, new legislation, and OAIC/APRA guidance, with impact analysis mapped to specific SHIELD-AI controls.
3. **Client compliance dashboard** – a SaaS-delivered dashboard showing maturity scores per pillar, regulatory compliance status per framework, open findings, and trend data.
4. **Evidence collection automation** – automated gathering of control evidence (logs, configurations, attestations) for audit readiness, replacing the manual evidence-gathering exercise that annual compliance assessments require.

This capability transforms SHIELD-AI from a point-in-time assessment into an ongoing security operations capability – the continuous compliance model described in Part 4.

Appendix D: Glossary Addendum – Emerging Concepts

Term	Definition
Multi-agent system	An architecture where multiple specialised AI agents coordinate, delegate, and share context to accomplish complex tasks
Agent swarm	A collection of heterogeneous agents with different roles operating as a coordinated group
Model Context Protocol (MCP)	A standardised protocol for AI agents to discover and invoke external tools, analogous to HTTP for web communication
Agent-to-Agent (A2A) protocol	An emerging standard for direct communication and task delegation between autonomous agents
Agent-as-a-Service (AaaS)	A managed platform offering where agent runtime, orchestration, and infrastructure are provided by a third party
Persistent agent memory	Long-term storage of agent state, user preferences, and interaction history across sessions
Self-healing agent	An agent that can detect errors in its own operation and autonomously modify its code, configuration, or tool usage to recover
Code-generating agent	An agent with the capability to generate, modify, and execute code – the highest-risk agent capability
Tool output injection	An attack where a compromised or malicious tool returns crafted output that causes the agent to behave outside intended parameters
Agent credential delegation	The mechanism by which an agent inherits or derives access permissions from a user or another agent

Term	Definition
Policy-as-code	The practice of expressing security and compliance policies as machine-readable, testable assertions (e.g., OPA/Rego policies)
Continuous compliance	An approach where control verification runs continuously against live deployments, replacing periodic point-in-time assessments
RAG security layer	Security controls embedded in the retrieval-augmented generation pipeline that enforce data access control at retrieval time
Agent SBOM	A software bill of materials for an agentic AI system, encompassing model, tools, libraries, pipeline components, and runtime
Agent telemetry	Structured event streams from agent operations used for monitoring, anomaly detection, and forensic analysis
Shared responsibility model (AI)	The division of security responsibilities between a managed agent platform provider and the client organisation using it
MCP gateway	A security proxy that enforces authentication, schema validation, rate limiting, and audit logging on MCP-compliant agent-tool communication

---

SHIELD-AI v1.11 – September 7, 2026 Authored by the Security Architecture Practice For enquiries: practice-lead@consultancy.example.com