



SQL INDUSTRIAL PRACTICAL TASK
Employee Management System - DDL + Basic DML
60 Small Practical Tasks - Basic to Intermediate

Student Name: Neha Mondal

Mobile Number: 8001316777

Batch: 7.00pm-8.00pm Date: 11-10-2026

-----database and table creation-----

```
show databases;
create database company_db;
use company_db;
create table employees(employee_id int primary key ,employee_name
varchar(100),department varchar (50),salary decimal(10,2),city varchar
(50),joining_date date,status varchar(20));
show tables;
```

-- -----insert operations-----

```
insert into employees values(101, 'Rahul Patil', 'Development', 45000, 'Pune',
'2026-01-10', 'Active'),
                        (102,'Priya Sharma', 'Testing', 38000, 'Mumbai',
'2026-02-15', 'Active'),
                        (103, 'Amit Joshi', 'Development', 52000, 'Pune',
'2025-12-05', 'Active'),
                        (104, 'Sneha Kulkarni', 'HR', 35000, 'Nashik',
'2026-03-20', 'Active'),
                        (105, 'Rohan Deshmukh','Support', 30000,
'Mumbai', '2026-04-01', 'Inactive');
```

```
insert into employees values(106, 'Anjali More', 'Testing', 42000, 'Pune', '2026-
05-12', 'Active');
```

-- -----select queries-----

```
select*from employees;
select employee_name from employees;
select employee_name,salary from employees;
select employee_name,department,city from employees;
select*from employees where city='pune';
select*from employees where city='mumbai';
select*from employees where department='development';
select*from employees where status='active';
select*from employees where status='inactive';
select*from employees where employee_id=103;
select*from employees where employee_name='priya sharma';
select*from employees where salary>40000;
select*from employees where salary<40000;
select*from employees where salary=35000;
select*from employees where salary>=42000;
```

```
select city='pune' from employees where status='inactive';
select*from employees where department='development'and salary>=45000;
select*from employees where city='pune' or city='mumbai';
```

-- -----update operations-----

```
update employees set salary=48000 where salary=45000;
select*from employees;
update employees set status ='active' where employee_id=105;
update employees set city='pune' where employee_id=104;
update employees set department='development' where employee_id=102;
update employees set salary=45000 where employee_id=106 ;
update employees set salary= salary+3000 where employee_id=103;
update employees set salary=salary+2000 where department='testing';
update employees set city='mumbai branch' where city='mumbai' ;
```

-- -----delete operations-----

```
delete from employees where employee_id=105;
delete from employees where employee_name='rohan deshमुख';
delete from employees where status='inactive'
delete from employees where salary<30000;
delete from employees where employee_id=104;
```

-- -----alter table/ddl practice-----

```
-
alter table employees add email varchar(100);
alter table employees add mobile varchar(15);
alter table employees modify city varchar(100);
alter table employees rename column employee_name to name;
alter table employees drop column mobile;
alter table employees add experience int;
update employees set experience=2 where name='rahul patil';
```

-- -----table -level ddl practice-----

```
create table department (department_id int primary key, department_name
varchar(100),location varchar(100));
insert into department values(101, 'IT', 'Nagpur'),
```

```

(102, 'HR', 'Mumbai'),
(103, 'Finance', 'Pune');

select*from department;
update department set location ='nashik'where department_id=103;
delete from department where department_id=103;
alter table department rename to company_departments;
delete from company_departments;
drop table company_departments;
show tables;

```

SQL INDUSTRIAL PRACTICAL TASK
E-Commerce Product Inventory Management - DDL + DML + Operators
60 Small Practical Tasks - Basic to Intermediate

-----partA database and table creation-----

-

```

-- create database ecommerce_db;
-- use ecommerce_db;
-- create table products(product_id int primary key,product_name
varchar(100),category varchar(50),brand varchar(50),price decimal(10,2),
quantity int, city varchar(50),status varchar (20));
-- select*from products;
-- show tables;

```

-----PARTB insert operation-----

```

-- insert into products values(201, 'Galaxy M55', 'Mobile', 'Samsung', 32000, 15,
'Pune', 'Available'),

```

```
--          (202, 'iPhone 15', 'Mobile', 'Apple', 65000, 8,
'Mumbai', 'Available'),
--          (203, 'Moto Edge 50', 'Mobile', 'Motorola', 28000,
20, 'Pune', 'Available'),
--          (204, 'Inspiron 15', 'Laptop', 'Dell', 58000, 6, 'Nashik',
'Available'),
--          (205, 'IdeaPad Slim 3', 'Laptop', 'Lenovo', 45000, 12,
'Mumbai', 'Available'),
--          (206, 'Galaxy Watch 6', 'Watch', 'Samsung', 22000, 4, 'Pune',
'Out of Stock');
```

```
-- -----partB INSERT OPERATIONS (continued) -----
```

```
-- insert into products values(207, 'Apple Watch SE', 'Watch', 'Apple', 30000, 10,
'Mumbai', 'Available'),
--          (208, 'Redmi Pad', 'Tablet', 'Xiaomi', 24000, 18,
'Pune', 'Available'),
--          (209, 'OnePlus Pad', 'Tablet', 'OnePlus', 35000, 5,
'Nashik', 'Available'),
--          (210, 'Bluetooth Speaker', 'Accessories', 'JBL',
7000, 25, 'Mumbai', 'Available');
```

```
-- -----partc select & operators-----
-----
```

```
-- select*from products;
-- select product_name from products;
-- select product_name,price from products;
-- select product_name, category,brand,price from products;
-- select*from products where city='pune';
-- select*from products where category ='mobile';
-- select*from products where category ='laptop';
-- select*from products where price>30000;
-- select*from products where price<30000;
-- select*from products where price=30000;
-- select*from products where price>=45000;
-- select*from products where price<=30000;
-- select*from products where quantity>10;
-- select*from products where quantity<10;
```

-- -----part D logical operator-----

```
-- -- select*from products where city='pune' and category='mobile';
-- select*from products where city='pune' and category='mobile';
-- select*from products where price > 30000 and quantity > 5;
-- select*from products where price >= 30000 AND price <= 60000;
-- select*from products where city='pune' or city='mumbai';
```

-- -----part D logical operator (continued)-----

```
-- select*from products where category='laptop' or category='mobile';
-- select*from products where quantity<10 or price>50000;
-- select*from products where category = 'Mobile' and price > 30000;
-- select*from products where brand = 'Samsung' or brand = 'Apple';
-- select*from products where city = 'Pune' and status = 'Available' and
quantity > 10;
```

-- -----part E higher operator logic-----

```
-- select*from products where price between 25000 and 50000;
-- select*from products where quantity between 5 and 15;
-- select*from products where category in ('mobile','laptop','tablet');
-- select*from products where city in ('pune','mumbai');
-- select*from products where brand !='samsung';
-- select*from products where status !='out of stock';
-- select*from products where price != 30000;
-- select*from products where product_name like 'galaxy%';
-- select*from products where product_name like '%pad%';
-- select*from products where category ='mobile' and (price > 30000 or
quantity > 15);
```

-- -----part F update operation-----

```
-- update products set price=34000 where product_name ='Galaxy M55';
-- update products set quantity =12 where product_name='iphone 15';
-- update products set status='available' where product_name='Galaxy Watch
```

6';

-- update products set price= price + 2000 where category='mobile';

-- update products set quantity= quantity + 5 where city='pune';

-- update products set status='out of stock' where quantity<5;

-----part G delete operation-----

-- delete from products where product_id=210;

-- delete from products where price<8000;

-- delete from products where status='out of stock' and quantity<5;

-- delete from products where category='tablet' and price>30000;

TheKiranAcademy

Database Name : capgemini

Table Name : employee

id	name	profile	email	salary	age	experience
1	rani	dev	rani@gmail.com	11000	43	27
2	raj	test	raj@gmail.com	21000	33	17
3	radha	test	radha@gmail.com	26000	38	21
4	raj	dev	raj12@gmail.com	51000	32	12
5	john	dev	john@gmail.com	51000	39	27

Perform the following queries as per requirement.

-- create database capgimini;

-- use capgimini;

-- CREATE TABLE employee(id INT,name VARCHAR(50),profile
VARCHAR(50),email VARCHAR(100),salary INT,age INT,experience INT);

-- insert into employee(id, name, profile, email, salary, age,

```

experience)VALUES(1, 'rani', 'dev', 'rani@gmail.com', 11000, 43, 27),
--                                     (2, 'raj', 'test', 'raj@gmail.com',
21000, 33, 17),
--                                     (3, 'radha', 'test',
'radha@gmail.com', 26000, 38, 21),
--                                     (4, 'raj', 'dev', 'raj12@gmail.com',
51000, 32, 12),
--                                     (5, 'john', 'dev',
'john@gmail.com', 51000, 39, 27);
-- select*from employee;

-- alter table employee add column branch_location varchar(100);

-- select sum(salary) as total_salary from employee;

-- select max(salary) as max_salary from employee where profile='test';

-- select avg(experience) as avg_experience from employee;

-- select name, salary from employee where salary = (select max(salary) from
employee);

-- Select name from employee where experience = (select min(experience)
from employee);

-- select count(*) as total_employe from employee;

-- select name from employee where profile = 'test' and salary > 25000;

-- update employee set profile = 'support' where name = 'radha';

-- select max(salary) as second_highest_salary from employee where salary <
(select max(salary) from employee);

-- select min(salary) as second_lowest_salary from employee where salary >
(select min(salary) from employee);

-- select avg(salary) as average_salary from employee where profile = 'dev';

-- select name, salary from employee where experience = (select

```

min(experience) from employee);

-- select name, age, salary from employee where age = (select min(age) from
employee) and salary = (select max(salary)from employee

-- where age = (select min(age) from employee)

--);

-- delete from employee;

-- select*from employee;
