

Show query box

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0002 seconds.)

```
-- AHL EL KHEIR - Journal Integrity / Accounting History Audit -- READ-ONLY AUDIT SCRIPT -- Purpose: verify journal history, reference separation, reversal preservation, -- voucher linkage, duplicate/missing relationships, and balanced posted/voided entries. -- This script does NOT INSERT, UPDATE, DELETE, ALTER, or DROP anything. USE ahl_el_kheir;
```

Showing rows 0 - 12 (13 total, Query took 0.0015 seconds.) [reference_type: **DISBURSEMENT...** - **TRANSACTION_VOID...**] [status: **POSTED...** - **POSTED...**]

```
-- 1) Journal population by reference type and status. SELECT reference_type, status, COUNT(*) AS journal_count FROM journal_entries GROUP BY reference_type, status ORDER BY reference_type, status;
```

reference_type	1	status	2	journal_count
disbursement		posted		4
disbursement		voided		2
disbursement_void		posted		1
item_return		posted		1
manual		posted		1
manual		voided		1
opening_balance		posted		1
payroll		posted		3
payroll_reversal		posted		1
project		posted		2
transaction		posted		9
transaction		voided		1
transaction_void		posted		1

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0012 seconds.)

```
-- 2) Any journal entry without lines. SELECT je.id, je.entry_code, je.reference_type, je.reference_id, je.status FROM journal_entries je LEFT JOIN journal_lines jl ON jl.entry_id = je.id WHERE jl.id IS NULL ORDER BY je.id;
```

id	entry_code	reference_type	reference_id	status
----	------------	----------------	--------------	--------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0008 seconds.)

```
-- 3) Any journal entry with invalid line amounts: -- negative amount, or both debit and credit populated on one line. SELECT jl.id, jl.entry_id, jl.account_id, jl.debit, jl.credit FROM journal_lines jl WHERE jl.debit < 0 OR jl.credit < 0 OR (jl.debit > 0 AND jl.credit > 0) ORDER BY jl.entry_id, jl.id;
```

id	entry_id	account_id	debit	credit
----	----------	------------	-------	--------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0014 seconds.)

```
-- 4) Every journal must balance exactly to 2 decimals. SELECT je.id, je.entry_code, je.reference_type, je.reference_id, je.status, ROUND(COALESCE(SUM(jl.debit), 0), 2) AS total_debit, ROUND(COALESCE(SUM(jl.credit), 0), 2) AS total_credit, ROUND(COALESCE(SUM(jl.debit), 0) - COALESCE(SUM(jl.credit), 0), 2) AS difference FROM journal_entries je LEFT JOIN journal_lines jl ON jl.entry_id = je.id GROUP BY je.id, je.entry_code, je.reference_type, je.reference_id, je.status HAVING difference <> 0 ORDER BY je.id;
```

id	entry_code	reference_type	reference_id	status	total_debit	total_credit	difference
----	------------	----------------	--------------	--------	-------------	--------------	------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0005 seconds.)

```
-- 5) Duplicate automated transaction journals. SELECT reference_id AS transaction_id, COUNT(*) AS journal_count FROM journal_entries WHERE reference_type = 'transaction' GROUP BY reference_id HAVING COUNT(*) > 1 ORDER BY reference_id;
```

transaction_id	journal_count
----------------	---------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0005 seconds.)

```
-- 6) Duplicate transaction reversal journals. SELECT reference_id AS transaction_id, COUNT(*) AS reversal_count FROM journal_entries WHERE reference_type = 'transaction_void' GROUP BY reference_id HAVING COUNT(*) > 1 ORDER BY reference_id;
```

transaction_id	reversal_count
----------------	----------------

Current selection does not contain a unique column. Grid edit, checkbox, Edit, Copy and Delete features are not available.

Showing rows 0 - 2 (3 total, Query took 0.0019 seconds.)

```
-- 7) Transaction journal relationship integrity. -- A posted transaction should have exactly one posted journal. SELECT t.id AS transaction_id,
t.transaction_code, t.status AS transaction_status, COUNT(je.id) AS posted_journal_count FROM transactions t LEFT JOIN journal_entries je ON
je.reference_type = 'transaction' AND je.reference_id = t.id AND je.status = 'posted' WHERE t.status = 'posted' GROUP BY t.id, t.transaction_code, t.status
HAVING posted_journal_count <> 1 ORDER BY t.id;
```

transaction_id	transaction_code	transaction_status	posted_journal_count
8	NULL	posted	0
13	NULL	posted	0
16	NULL	posted	0

Current selection does not contain a unique column. Grid edit, checkbox, Edit, Copy and Delete features are not available.

Showing rows 0 - 2 (3 total, Query took 0.0009 seconds.)

```
-- 8) A voided transaction must preserve its original journal as voided -- and have exactly one transaction_void reversal. SELECT t.id AS transaction_id,
t.transaction_code, COUNT(CASE WHEN je.reference_type = 'transaction' AND je.status = 'voided' THEN 1 END) AS original_voided_count, COUNT(CASE WHEN
je.reference_type = 'transaction_void' THEN 1 END) AS reversal_count FROM transactions t LEFT JOIN journal_entries je ON (je.reference_type = 'transaction'
AND je.reference_id = t.id) OR (je.reference_type = 'transaction_void' AND je.reference_id = t.id) WHERE t.status = 'voided' GROUP BY t.id,
t.transaction_code HAVING original_voided_count <> 1 OR reversal_count <> 1 ORDER BY t.id;
```

transaction_id	transaction_code	original_voided_count	reversal_count
5	TXN-OUT-000005	0	0
14	NULL	0	0
15	NULL	0	0

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0004 seconds.)

```
-- 9) Orphan transaction journal references. SELECT je.id, je.entry_code, je.reference_type, je.reference_id FROM journal_entries je LEFT JOIN transactions
t ON t.id = je.reference_id WHERE je.reference_type IN ('transaction', 'transaction_void') AND t.id IS NULL ORDER BY je.id;
```

id	entry_code	reference_type	reference_id
----	------------	----------------	--------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0009 seconds.)

```
-- 10) Voucher * journal linkage integrity. -- Every voucher should point to an existing journal whose reference is voucher/id. SELECT v.id AS voucher_id,
v.voucher_no, v.status AS voucher_status, v.entry_id, je.id AS journal_id, je.reference_type, je.reference_id, je.status AS journal_status FROM vouchers v
LEFT JOIN journal_entries je ON je.id = v.entry_id WHERE v.entry_id IS NULL OR je.id IS NULL OR je.reference_type <> 'voucher' OR je.reference_id <> v.id
ORDER BY v.id;
```

voucher_id	voucher_no	voucher_status	entry_id	journal_id	reference_type	reference_id	journal_status
------------	------------	----------------	----------	------------	----------------	--------------	----------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0005 seconds.)

```
-- 11) Duplicate voucher journals. SELECT reference_id AS voucher_id, COUNT(*) AS journal_count FROM journal_entries WHERE reference_type = 'voucher' GROUP
BY reference_id HAVING COUNT(*) > 1 ORDER BY reference_id;
```

voucher_id	journal_count
------------	---------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0006 seconds.)

```
-- 12) Voucher status * journal status consistency for the current voucher model. -- Posted voucher => posted journal; voided voucher => original voucher
journal voided. SELECT v.id AS voucher_id, v.voucher_no, v.status AS voucher_status, je.status AS journal_status FROM vouchers v JOIN journal_entries je ON
je.id = v.entry_id WHERE (v.status = 'posted' AND je.status <> 'posted') OR (v.status = 'voided' AND je.status <> 'voided') ORDER BY v.id;
```

voucher_id	voucher_no	voucher_status	journal_status
------------	------------	----------------	----------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0005 seconds.)

```
-- 13) Voucher reversal audit: if a voucher has been voided, inspect any -- reversal entry explicitly. This does not assume a reversal type; it exposes -
- the actual history for review because the current voucher core may use its -- own reversal implementation. SELECT v.id AS voucher_id, v.voucher_no,
v.status AS voucher_status, original.id AS original_journal_id, original.entry_code AS original_entry_code, original.status AS original_journal_status,
reversal.id AS reversal_journal_id, reversal.entry_code AS reversal_entry_code, reversal.reference_type AS reversal_reference_type, reversal.status AS
reversal_status FROM vouchers v LEFT JOIN journal_entries original ON original.id = v.entry_id LEFT JOIN journal_entries reversal ON
reversal.reference_id = v.id AND reversal.id <> v.entry_id AND reversal.reference_type IN ('voucher_void', 'transaction_void', 'manual_void',
```

voucher_id	voucher_no	voucher_status	original_journal_id	original_entry_code	original_journal_status	reversal_journal_id
------------	------------	----------------	---------------------	---------------------	-------------------------	---------------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0013 seconds.)

```
-- 14) Journal lines pointing to missing accounts (should return zero rows). SELECT jl.id, jl.entry_id, jl.account_id FROM journal_lines jl LEFT JOIN
accounts a ON a.id = jl.account_id WHERE a.id IS NULL ORDER BY jl.entry_id, jl.id;
```

id	entry_id	account_id
----	----------	------------

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0006 seconds.)

```
-- 15) Voided journal history must retain its original lines.
SELECT je.id, je.entry_code, je.reference_type, je.reference_id, COUNT(jl.id) AS line_count
FROM journal_entries je LEFT JOIN journal_lines jl ON jl.entry_id = je.id WHERE je.status = 'voided' GROUP BY je.id, je.entry_code, je.reference_type,
je.reference_id HAVING line_count = 0 ORDER BY je.id;
```

id	entry_code	reference_type	reference_id	line_count
----	------------	----------------	--------------	------------

Current selection does not contain a unique column. Grid edit, checkbox, Edit, Copy and Delete features are not available.

Your SQL query has been executed successfully.

```
-- 16) Accounting-history net balance check across ALL journal statuses. -- Posted + reversal entries should balance globally; voided originals remain --
historical records and are intentionally included as historical debit/credit.
SELECT COUNT(DISTINCT je.id) AS journal_count, COUNT(jl.id) AS line_count,
ROUND(COALESCE(SUM(jl.debit), 0), 2) AS total_debit, ROUND(COALESCE(SUM(jl.credit), 0), 2) AS total_credit, ROUND(COALESCE(SUM(jl.debit), 0) -
COALESCE(SUM(jl.credit), 0), 2) AS difference FROM journal_entries je LEFT JOIN journal_lines jl ON jl.entry_id = je.id;
```

journal_count	line_count	total_debit	total_credit	difference
28	62	204945000.00	204945000.00	0.00

Current selection does not contain a unique column. Grid edit, checkbox, Edit, Copy and Delete features are not available.

Showing rows 0 - 9 (10 total, Query took 0.0005 seconds.)

```
-- 17) Reference types currently present in the database.
SELECT COALESCE(reference_type, '(NULL)') AS reference_type, COUNT(*) AS journal_count FROM
journal_entries GROUP BY reference_type ORDER BY reference_type;
```

reference_type	1	journal_count
disbursement		6
disbursement_void		1
item_return		1
manual		2
opening_balance		1
payroll		3
payroll_reversal		1
project		2
transaction		10
transaction_void		1

Warning: #1052 Column 'reference_type' in group statement is ambiguous