Data dictionary of `results/`

All result files are JSON (one file per benchmark problem unless stated otherwise). The field names and a few categorical labels were kept exactly as written by the analysis programs, which use Spanish names; this table gives their meaning. Fractions are given as numbers between 0 and 1 (e.g. `eajuste_med = 0.094` means 9.4 %) unless the name ends in `%`.

Common labels: `sistema` = problem; `segundos` = running time of that problem in seconds (on the machine that produced the file); `admisible` = admissible; `Stage 1` / `Stage 2` = stage of the selection; `Técnico` = technical failure (the nominal simulation fails); `salidas` = measured outputs; `estados` = state trajectories.

`selection/` and `settings/<variant>/` (analysis/selection.py)

Field	Meaning
`p`	number of estimated parameters of the PEtab problem
`S1`	subset returned by stage 1 (greedy selection by sensitivity energy)
`Rvar_S1_%`	R_var of the stage-1 subset (%)
`S1_cumple`	true if stage 1 reached R_var >= tau_R with at least 2 parameters
`cos_S1`, `erel_S1`	median cos(Delta) and e_rel of the stage-1 subset
`motivo_stage2`	why stage 2 was used ("stage 1 reaches R_var but is not admissible")
`etapa`	stage that produced the subset (`Stage 1`, `Stage 2`)
`S_antes_poda`	subset before backward elimination
`podados`	parameters removed by backward elimination
`S`	**final selected biological parameters**
`calibracion`	calibration parameters (scalings, offsets), always re-estimated with S
`Rvar_%`	R_var(S) (%)
`kappa`, `VIF`	condition number and largest VIF of the standardised columns of J for S
`cos_med`, `erel_med`	median over the scenarios of cos(Delta) and e_rel (no re-estimation)
`eajuste_med`	**median e_fit** (re-estimation of S and the calibration parameters)
`eajuste_cota`	upper bound e_rel used when e_fit was not computed (not used in the paper)
`eajuste_metodo`	present for the 8 problems where e_fit is computed to first order
`n_escenarios`	number of valid scenarios (of 15)
`admisible`	**admissible**:
`motivo`	reason when the problem could not be analysed
`T`, `etapa_paper`, `S_paper`	legacy fields of an earlier version of the analysis (state trajectories), not used

`external_validation/` (analysis/external_validation.py)

Field	Meaning
`division`	split: `condiciones nuevas` (held-out experimental conditions) or `extrapolación temporal (t ≥ c)` (later time points)

Field	Meaning
`n_condiciones`, `n_train`, `n_test`	number of conditions; training and test measurements
`S`, `	S
`p_y`	parameters that affect the outputs
`locales_prueba`, `S_locales_prueba`	parameters that only act in test conditions (excluded from the fits)
`no_evaluable`	why no training/test split was possible
`A_chi2_test_red`, `A_chi2_test_full`, `A_chi2_test_theta0`	real data: test chi2/n of the reduced model, of the full model (both re-fitted to the training data) and of the published theta0
`A_chi2_train_red`, `A_chi2_train_full`	real data: training chi2/n
`B_chi2_test_theta0`, `B_chi2_test_red`, `B_chi2_test_full`	synthetic data: test chi2/n (theta0 = signal-to-noise indicator)
`B_epred_red`, `B_epred_full`, `B_epred_theta0`	synthetic data: prediction error e_pred with respect to the known truth (1 for theta0)
`B_error`	failure of the synthetic experiment (simulation of the truth)
`etapas_reanudadas`	fits that were resumed from a checkpoint

`robustness/` (analysis/robustness.py)

Field	Meaning
`S`, `n_calibracion`	subset (fixed) and number of calibration parameters
`semilla`, `u`	seed and the 15 random directions u(k) (15 x p), the same at every size
`niveles`	results per perturbation size (`"1"`, `"5"`, ..., `"50"` = +-1 %, ..., +-50 %)
`niveles.*.n`	valid scenarios
`niveles.*.escenarios`	indices k of the valid scenarios
`niveles.*.eaj`, `erel`, `cos`	e_fit, e_rel and cos(Delta) of every valid scenario
`niveles.*.eaj_med`, `eaj_q25`, `eaj_q75`, `erel_med`, `cos_med`	median and quartiles
`patron`	robustness pattern A-D (Results)
`eajuste_metodo`	`linealizado` (first order) or `no lineal`

`single_parameter/` (analysis/single_parameter.py)

Field	Meaning
`candidatos`	number of candidates tested (up to 10 by energy and 10 by finite effect)
`un_parametro`	for each candidate: `parametro`, `e_rel`, `e_fit`, `admisible`
`algun_parametro_solo_basta`	true if some single parameter is admissible
`mejor`	best admissible single parameter j* (smallest e_fit)
`mejor_efit_10`, `S_efit_10`	median e_fit at +-10 % of {j*} and of the selected subset S
`mejor_validacion`	external validation of {j*} (same fields as external_validation)

Field	Meaning
`mejor_validacion_calibracion`	number of calibration parameters re-estimated with j* in that validation

`nested_validation/` (analysis/nested_validation.py)

Field	Meaning
`S,` `	S
`chi2_test_red_original`	test chi2/n of the reduced model with the non-selected parameters at theta0
`chi2_test_full_train`	test chi2/n of the full model re-estimated on the training data (theta_train)
`chi2_test_red_nested`	test chi2/n of the reduced model with the non-selected parameters at theta_train
`chi2_test_theta0`	test chi2/n of the published estimate theta0
`ratio_nested_vs_original`	`chi2_test_red_nested / chi2_test_red_original` (above 1: worse without the theta0 anchor)

`synthetic_seeds/<problem>/s<seed>.json` (analysis/synthetic_seeds.py)

One file per problem and seed (42-61). Fields as in `external_validation/` (keys `B_*`) for that seed: `semilla` = seed; `p_y` = free parameters; `B_chi2_test_theta0`, `B_chi2_test_red`, `B_chi2_test_full`; `B_epred_red`, `B_epred_full` (relative prediction error with respect to the truth; 1 = theta0); `nfev_red`, `nfev_full` = function evaluations of the fits; `seg_red` = seconds of the reduced fit; `B_error` = the simulation of the truth failed. `B_*_full` is absent for the four problems with more than 100 free parameters. `RESUMEN.json` and `RESUMEN.md` summarise all seeds (`por_semilla`: counts per seed; `por_sistema`: per problem, `con_senal` = seeds with signal, `red_ok_senal` = reduced e_pred <= tau_e among them, `red_le_full_senal` = reduced e_pred <= full).

`random_subsets/` and `calibration_only/` (analysis/baselines.py)

Field	Meaning
`k`	number of biological parameters of our subset (also used for the random subsets)
`chi2_ours`	test chi2/n of our subset (theta0 anchor), from `nested_validation/`
`chi2_rand_median`, `chi2_rand_q1`, `chi2_rand_q3`	median and quartiles of the test chi2/n over the random draws
`chi2_por_semilla`, `n_seeds`, `n_validas`	test chi2/n of each draw (seeds 0-19), number of draws, valid draws
`chi2_vacio`	test chi2/n with only the calibration parameters re-estimated (`n_cal` of them)
`ratio_rand_vs_ours`, `ratio_vacio_vs_ours`	baseline over ours (below 1: the baseline predicts better)
`nota`	`sin calibracion, th0 directo` = no calibration parameters: theta0 is evaluated directly

`qr_selection/` (analysis/qr_selection.py) and `brun_morris/` (analysis/brun_morris.py)

Field	Meaning
`S_ours`, `S_qr`, `S_brun`, `S_morris`	biological parameters selected by each criterion (same `k`)
`chi2_ours`, `chi2_qr`, `chi2_brun`, `chi2_morris`, `chi2_perfil`	test chi2/n of each subset (with the calibration parameters, theta0 anchor)

Field	Meaning
`overlap`, `overlap_brun_ours`, `overlap_morris_ours`	parameters shared with our subset
`ratio_qr_vs_ours`	`chi2_qr / chi2_ours`
`detalle_brun`	`gamma` = collinearity index of the selected subset, `cumple_gamma` = gamma <= 10, `dmsqr_top` = importance of the 15 candidates
`detalle_morris`	`mu_star_top` = mu* of the 10 most influential parameters, `fallos_simulacion` = failed elementary effects
`segundos_brun`, `segundos_morris`, `tipo`	seconds of each criterion (selection and fit); kind of split

`profile_likelihood/` (analysis/profile_likelihood.py)

`<problem>.json`:

Field	Meaning
`p_libres`, `n_bio`	free parameters of the training fit; biological parameters profiled
`n_identificables`, `n_no_identificables_practicos`, `n_planos`	parameters identifiable (profile above Delta chi2 = 3.84 on both sides), bounded on one side, flat
`S_perfil`	the `k` parameters with the narrowest profile confidence interval
`chi2_perfil`, `chi2_ours`, `chi2_qr`, `ratio_perfil_vs_ours`	test chi2/n of the profile subset, of ours and of pivoted QR
`overlap_perfil_ours`, `overlap_perfil_qr`	parameters shared with our subset and with the QR subset
`coste_min_train`	chi2 (sum of squares) of the full training fit used as the minimum
`rondas_reajuste`	times the full model was re-estimated because a profile point improved the minimum
`dchi2_minimo_perfiles`	smallest Delta chi2 among the profile points after the last re-estimation (below -1: residual improvement)
`puntos_fallidos`	profile points whose fit failed (Delta chi2 > 1e4), excluded
`perfiles`	per parameter: `clase` (`identificable`, `no identificable practico`, `plano`), `ancho_ic_log` (width of the 95 % interval in log units; infinite if open), `dchi2_max_izq`, `dchi2_max_der` (largest Delta chi2 on each side)
`no_evaluable`	not profiled: more than 60 free parameters (`PL_PMAX`), or no training/test split

`<problem>/perfil_<parameter>_<side>_<i>.json`: one profile point (`lado` = side, `despl` = displacement of log|theta_j|, `dchi2`, `nfev`, `theta` = re-estimated parameter vector); `<problem>/full_train.npz`: minimum (`theta`, `coste`, `rondas`). `logs/`: summary lines of the runs (`terminado` = problem finished with `seg_total` seconds; `reajuste` = re-estimation of the minimum).

`criteria_tests/` and `criteria_tests_20pc/` (analysis/criteria_tests.py)

File names `<problem>__<criterion>__adm.json` (admissibility) and `<problem>__<criterion>__sint_<seed>.json` (synthetic), with `<criterion>` = `ours`, `qr`, `brun`, `morris`, `perfil`. `criteria_tests/` uses perturbations of +-5 % (the level of the method); `criteria_tests_20pc/`, +-20 % (admissibility only).

Field	Meaning
`S`	biological parameters of the subset tested
`eajuste_med`, `erel_med`	median e_fit and median e_rel over the scenarios
`admisible`	min(`eajuste_med`, `erel_med`) <= 0.436 and at least 2 parameters (rule of the method)
`n_escenarios`, `lineal`	valid scenarios; true if e_fit was computed to first order (problems of `config.FIRST_ORDER`)
`B_chi2_test_theta0`, `B_chi2_test_red`, `B_epred_red`, `semilla`	synthetic experiment for that seed (as in `external_validation/`)
`no_evaluable`	`sin subconjunto` = the criterion has no subset for the problem; `falla la simulación de la verdad` = the truth could not be simulated

`identifiability/` (analysis/identifiability_*.py)

Profile likelihood of the selected parameters in the reduced problem (S and the calibration parameters free, the other parameters at theta0, all measurements).

`profiles/<problem>/minimo.npz`: optimum of the reduced problem (`theta`, `coste` = chi2, `rondas` = re-fits after a profile point improved the optimum). `profiles/<problem>/p_<parameter>_<+|->_<i>.json`: one profile point (`despl` = displacement in log|theta_j|, `log_theta`, `dchi2`, `theta` = all parameters after the re-fit). `profiles/<problem>.json`:

Field	Meaning
`chi2_por_gl`, `umbral_robusto`	chi2 per degree of freedom at the optimum; threshold of the robust variant, 3.84 max(1, chi2/d.f.)
`perfiles[].clase`, `clase_robusto`	`identificable` (profile above 3.84 on both sides within [theta0/10, 10 theta0]), `no identificable practico` (one side), `plano` (neither)
`perfiles[].ic_izq_log`, `ic_der_log`	distance (log) at which the profile crosses the threshold on each side (inf = no crossing)
`perfiles[].minimo_en_limite`, `puntos_fallidos`	sides without valid points (optimum at a bound); points whose simulation failed

`local/<problem>.json`: `kappa_SC_n`, `VIF_SC_n_S` (condition number and VIF of the unit-norm, uncentred columns of S and the calibration parameters at theta0), `par_mas_parecido_con_S` (most similar pair of columns and their cosine). `certificado*.csv`: one row per selected parameter with the quantities of the Lean theorem `ProfileIdentifiability.practically_identifiable_grad`: `I_j` (profiled information), `gamma` (norm of the projection of the residual onto the range of the sensitivity matrix), `eps_j` (largest nonlinear remainder at the profile points), `tstar`, `tstar_lineal` (Wald half-width), `d_menos`, `d_mas` (distances to the bounds), `certificado_lineal`, `certificado_local` (hypotheses satisfied with epsilon = 0, or with epsilon evaluated at the points up to the first crossing). `summary.md`: the counts quoted in the paper.

`timing_complete/` (analysis/selection.py run from scratch)

`parallel/`, `single_core/`: the complete result of `selection.py` (fields as in `selection/`) run without cached results, with the sensitivity computations on 16-64 cores or on one core; the run time is `segundos`. `parallel_corrected_code/`: the eight problems of `config.FIRST_ORDER` with the corrected program (version 1.1);

their subsets and `eajuste_med` are identical to `selection/`. The runs shared a 128-core server, so the times are upper bounds.

`robustness_independent/` (analysis/robustness.py with ROBUST_INDEP=1)

Same fields as `robustness/`, plus `direcciones` ("independent at every size") and, in every size of `niveles`, `semilla` (seed of the directions of that size: 42 at +-5 %, 42 + 1000 i at the i-th other size). The top-level `u` are the directions of seed 42; the scenarios of the other sizes are not the rows of `u`.

`synthetic_signal_a<amplitude>/` and `synthetic_seeds_a<amplitude>/` (analysis/synthetic_seeds.py)

One file per problem and seed (`<problem>/s<seed>.json`), as in `synthetic_seeds/`, with the amplitude `a` of the truth theta* = theta0 (1 + a u) in the folder name (005 = 0.05, 020 = 0.20, 050 = 0.50) and in `amplitud`. New fields (also in `synthetic_seeds_a005/`, `_a050/`):

Field	Meaning
`senal_rms_test`, `senal_rms_train`	root mean square of y(theta*) - y(theta0) per test / training measurement, in units of sigma
`senal_norma_test`, `ruido_norma_test`	norm of y(theta*) - y(theta0) on the test measurements, and sqrt(n_test) (norm of unit noise)

The `synthetic_signal_*` folders contain only these fields (no fits). `synthetic_seeds_a*` contain the same fields as `synthetic_seeds/` (`B_chi2_test_*`, `B_epred_red`, `B_epred_full`, ...).

`absolute_error/` (analysis/absolute_error.py)

Field	Meaning
`n`, `n_escenarios`	number of measurements; valid scenarios at +-5 %
`e_fit_med`	median e_fit over the scenarios (from `robustness/`, +-5 %)
`cambio_rms_sigma_med`	median of `|Delta y_full| / sqrt(n)`, the change of the full model per measurement in units of sigma
`error_rms_sigma_med`, `error_rms_sigma_max`	median and maximum of `e_fit * |Delta y_full| / sqrt(n)`, the error that remains after re-estimation, in units of sigma
`escenarios`	the same quantities for every scenario `k`

`settings_extra/` (analysis/selection.py --variant)

Same fields as `selection/`, for Lang and Raimundez, in folders named as in `settings/`; `README.md` lists the variants that did not finish.

Other files

File	Content
`simulator_check/simulator_check.jsonl`	one line per problem: `mediciones`, `condiciones`, `p`, `p_y`, `err_rel_mediana` and `err_rel_max_vs_simulations` (relative difference with the reference simulations of the benchmark), `nota` (why no comparison was possible)
`cost/simulation_times.json`	`p`, `t_sim` (seconds per simulation), `modo` (`salidas` or `estados`); Smith: `t_sim_medido` and `nota` (scaled from a second machine)
`crauste_blowup.json`	`nominal` and `un_parametro_1%` (24 one-at-a-time changes): `existe_en_[0,28]` (the solution exists on the measured horizon), `t_final` (time reached), `efectores_max`, `t_max`; `tolerancias`: number of failures (`fallos_*`) for each integrator tolerance
`sbml_to_lean/<problem>.json`	report of the translation to Lean: sizes (`n_estados`, `n_theta`, `reacciones`), checks done in Python before writing the Lean file, `lean` (file written), `teorema_final`, `traducido`
`sbml_to_lean/translation_fidelity.json`	for each model: `err_rel_max` (largest relative difference between the vector field of the Lean file and libRoadRunner), `err_theta`, `err_x0`, `err_por_punto`

Second review (version 1.5)

`selection_fixedscen/`, `selection_train_fixedscen/` (analysis/selection.py)

Same fields as `selection/`, plus:

Field	Meaning
`outputs`	`all` (all measured outputs) or `train` (rows of the training set only)
`fixed_scenarios`	`true`: a scenario in which the simulation with the subset fails counts as e_rel = inf; first-order e_fit = min(e_rel, projection) per scenario
`n_rows`	number of outputs used by the selection
`monotonia`	monotonicity log: `subsets_evaluated`, `nested_pairs` (pairs S < T of evaluated subsets), `violations` (S admissible and T not), `subsets` (each evaluated subset with its admissibility)

`qr_selection_gks/` (analysis/qr_selection.py with QR_VARIANT=gks)

Same fields as `qr_selection/` (`S_qr`, `chi2_qr`, `chi2_ours`, `overlap`, ...), plus `variant` = `gks`.

`efit_nonlinear/<problem>/s<k>.json` and `efit_nonlinear/<problem>.json` (analysis/efit_nonlinear.py)

Field	Meaning
`escenario`	scenario index (0-14)
`erel`, `efit`	relative error without and with nonlinear re-estimation of S and the calibration parameters
`arranques`	each starting point (`theta0`, `escenario`): error `e`, function evaluations `nfev`, optimiser `status`
`descartado`	why a scenario was discarded (full-model simulation failed, or change below the noise floor)
`eajuste_med_nolineal`, `eajuste_med_primer_orden`	median nonlinear e_fit and the first-order value of the selection

Field	Meaning
`tasa_paso_nolineal`, `admisible_nolineal`, `n_escenarios_validos`, `segundos_total`	pass rate, admissibility, valid scenarios, total CPU time

`criteria_tests_fixedscen/`, `criteria_tests_20pc_fixedscen/`, `criteria_tests_sint_<family>/` (analysis/criteria_tests.py)

One file per problem, criterion (`metodo`: `ours`, `train`, `brun`, `morris`, `perfil`, `qr`, `qr_gks`, `empty` = k = 0, `rand<i>` = random subset i) and test (`adm`, `real`, `sint_<seed>`):

Field	Meaning
`eajuste_med`, `erel_med`, `admisible`	admissibility test as in the selection (`admisible_sin_kmin`: without the rule |S| >= 2)
`tasa_paso`, `n_escenarios`, `escenarios_fijos`, `k`, `n_calibracion`	pass rate, valid scenarios, fixed scenario set, subset size, calibration parameters
`chi2_test`, `chi2_ours`, `ratio_vs_ours`	real data: test chi2/n of the subset, of our main subset, and their ratio
`familia`, `semilla`, `B_epred_red`, `B_chi2_test_theta0`, `senal_rms_test`	synthetic test: family of truths, seed, e_pred, chi2/n of theta0 on the synthetic test data (>= 2: signal), true signal in noise units
`calibracion_fija`	only in `criteria_tests_calfixed/`: the calibration parameters were kept at theta0 in the scenarios
`frac_cambio_calibracion`, `frac_cambio_calibracion_med`	only in `criteria_tests_calfixed/` for `ours`: per standard scenario, fraction of the squared output change produced by the calibration parameters alone, and its median

`criteria_tests_calfixed/` has the same files and fields for the admissibility test (`adm`) with the calibration parameters kept at theta0, for the 14 problems with calibration parameters. `calibration_fixed_summary.json` (analysis/calibration_fixed_summary.py) gives, per problem, `share_calibration` and, for the standard (`standard`) and the new (`calfixed`) test, the admissibility of every criterion, `efit_ours`, `random_fraction` and `discriminates` (calibration only not admissible and fewer than half of the random draws admissible); `counts` summarises them and `processor_hours` is the total time.

`conditioning_check.json` (analysis/conditioning_check.py)

`kappa_centred`, `VIF_centred` (as in the selection), `kappa_unit`, `VIF_unit` (unit-length columns without centring, as in the Lean least-squares statements), `kappa_unit_with_calibration`.

`identifiability/profiles_dense/`, `identifiability/profiles_selection_train_fixedscen/`

Same format as `identifiability/profiles/` (20 points per side, or the subsets selected on the training outputs).

`identifiability/audit2/certificado_box[_r<r>].csv` and `..._parametros.csv` (analysis/identifiability_box.py)

One row per selected parameter, side (`lado`) and condition (`condicion`: `abs` = absolute remainder on the tail, `rel` = relative remainder): `I_j`, `gamma`, `norma_r0`, `d_lado` (distance to the bound of the region), `pasa_muestra` (condition holds on the sample), `t` (tail start), `valor_final` (epsilon or eta after the adversarial search), `pasa_final`. `_parametros.csv`: `pf` = the hypotheses hold on both sides for parameter `parametro` in the region of radius r (10 if no suffix). `certificado_train.csv`: same columns as `identifiability/certificado.csv` for the training-output subsets.

Version 1.6

`subsets_<criterion>/<problem>.json` (analysis/prepare_criteria_subsets.py) and `subsets_single/` (analysis/prepare_single_subsets.py)

`S` (subset of the criterion, or the best single parameter), `calibracion` (calibration parameters, those of our selection), `admisible` (marks the problem for the profiling programs; not the admissibility of the subset), `origen` (source file and key) or `e_fit_5` and `S_ours` (single parameter).

`identifiability/profiles_subsets_<criterion>/` and `identifiability/profiles_subsets_single/`

Same format as `identifiability/profiles/`. Only the problems whose subset differs from ours were profiled; the others use our profiles. `identifiability/audit2/certificado_<criterion>.csv`: same columns as `identifiability/certificado.csv`.

`identifiability/criteria_identifiability.json` (figures_tables/identif_criteria_tables.py)

`common_problems` (the 27 problems compared) and, per criterion, `identifiable`/`selected` parameters, `all_identifiable`, `admissible_5`, `identifiable_and_admissible`, `identical_to_ours`, `cpu_h` and the exact McNemar tests against our subsets (`mcnemar_all_identifiable`, `mcnemar_both`: problems in which only ours or only the other criterion has the property, `p`, `p_holm`).

`robustness_subsets_single/`, `robustness_independent_subsets_single/`

Same format as `robustness/` for the best single parameter. `partial/<problem>__L<size>.json`: one perturbation size computed in its own process (`ROBUST_LEVEL`).

`kmin_comparison.json` (analysis/compare_single_vs_pair.py), `kmin_summary.json`, `kmin_times.json` (analysis/kmin_times.py)

Per problem: single parameter and pair; robustness (`pattern`, `admissible_up_to` = largest size with median e_fit <= tau_e, `pass_rate` = fraction of all scenarios with e_fit <= tau_e, `median_50`) with paired and independent directions; `adm20`; `synthetic` = (cases with e_pred <= tau_e, cases with signal); `identifiable` = (identifiable, selected). `summary`: sign tests over problems. `kmin_times.json`: elapsed time of the run and processor time per problem (seconds).