Data dictionary of `results/`

All result files are JSON (one file per benchmark problem unless stated otherwise). The field names and a few categorical labels were kept exactly as written by the analysis programs, which use Spanish names; this table gives their meaning. Fractions are given as numbers between 0 and 1 (e.g. `eajuste_med = 0.094` means 9.4 %) unless the name ends in %.

Common labels: `sistema` = problem; `segundos` = running time of that problem in seconds (on the machine that produced the file); `admisible` = admissible; `Stage 1` / `Stage 2` = stage of the selection; `Técnico` = technical failure (the nominal simulation fails); `salidas` = measured outputs; `estados` = state trajectories.

`selection/` and `settings/<variant>/` (analysis/selection.py)

Field	Meaning
`p`	number of estimated parameters of the PEtab problem
`S1`	subset returned by stage 1 (greedy selection by sensitivity energy)
`Rvar_S1_%`	R_var of the stage-1 subset (%)
`S1_cumple`	true if stage 1 reached R_var >= tau_R with at least 2 parameters
`cos_S1`, `erel_S1`	median cos(Delta) and e_rel of the stage-1 subset
`motivo_stage2`	why stage 2 was used ("stage 1 reaches R_var but is not admissible")
`etapa`	stage that produced the subset (`Stage 1`, `Stage 2`)
`S_antes_poda`	subset before backward elimination
`podados`	parameters removed by backward elimination
`S`	**final selected biological parameters**
`calibracion`	calibration parameters (scalings, offsets), always re-estimated with S
`Rvar_%`	R_var(S) (%)
`kappa`, `VIF`	condition number and largest VIF of the standardised columns of J for S
`cos_med`, `erel_med`	median over the scenarios of cos(Delta) and e_rel (no re-estimation)
`eajuste_med`	**median e_fit** (re-estimation of S and the calibration parameters)
`eajuste_cota`	upper bound e_rel used when e_fit was not computed (not used in the paper)
`eajuste_metodo`	present for the 8 problems where e_fit is computed to first order
`n_escenarios`	number of valid scenarios (of 15)
`admisible`	**admissible**:
`motivo`	reason when the problem could not be analysed
`T`, `etapa_paper`, `S_paper`	legacy fields of an earlier version of the analysis (state trajectories), not used

`external_validation/` (analysis/external_validation.py)

Field	Meaning
`division`	split: `condiciones nuevas` (held-out experimental conditions) or `extrapolación temporal (t ≥ c)` (later time points)
`n_condiciones`, `n_train`, `n_test`	number of conditions; training and test measurements
`S`, `|S|`, `n_calibracion`	subset validated, its size, number of calibration parameters
`p_y`	parameters that affect the outputs

Field	Meaning
locales_prueba, S_locales_prueba	parameters that only act in test conditions (excluded from the fits)
no_evaluable	why no training/test split was possible
A_chi2_test_red, A_chi2_test_full, A_chi2_test_theta0	real data: test chi2/n of the reduced model, of the full model (both re-fitted to the training data) and of the published theta0
A_chi2_train_red, A_chi2_train_full	real data: training chi2/n
B_chi2_test_theta0, B_chi2_test_red, B_chi2_test_full	synthetic data: test chi2/n (theta0 = signal-to-noise indicator)
B_epred_red, B_epred_full, B_epred_theta0	synthetic data: prediction error e_pred with respect to the known truth (1 for theta0)
B_error	failure of the synthetic experiment (simulation of the truth)
etapas_reanudadas	fits that were resumed from a checkpoint

robustness/ (analysis/robustness.py)

Field	Meaning
S, n_calibracion	subset (fixed) and number of calibration parameters
semilla, u	seed and the 15 random directions u(k) (15 x p), the same at every size
niveles	results per perturbation size ("1", "5", …, "50" = +-1 %, …, +-50 %)
niveles.*.n	valid scenarios
niveles.*.escenarios	indices k of the valid scenarios
niveles.*.eaj, erel, cos	e_fit, e_rel and cos(Delta) of every valid scenario
niveles.*.eaj_med, eaj_q25, eaj_q75, erel_med, cos_med	median and quartiles
patron	robustness pattern A-D (Results)
eajuste_metodo	linealizado (first order) or no lineal

single_parameter/ (analysis/single_parameter.py)

Field	Meaning
candidatos	number of candidates tested (up to 10 by energy and 10 by finite effect)
un_parametro	for each candidate: parametro, e_rel, e_fit, admisible
algun_parametro_solo_basta	true if some single parameter is admissible
mejor	best admissible single parameter j* (smallest e_fit)
mejor_efit_10, S_efit_10	median e_fit at +-10 % of {j*} and of the selected subset S
mejor_validacion	external validation of {j*} (same fields as external_validation)
mejor_validacion_calibracion	number of calibration parameters re-estimated with j* in that validation

nested_validation/ (analysis/nested_validation.py)

Field	Meaning
S, |S|, division, n_train, n_test	selected subset, its size, kind of split, number of training and test measurements

Field	Meaning
chi2_test_red_original	test chi2/n of the reduced model with the non-selected parameters at theta0
chi2_test_full_train	test chi2/n of the full model re-estimated on the training data (theta_train)
chi2_test_red_nested	test chi2/n of the reduced model with the non-selected parameters at theta_train
chi2_test_theta0	test chi2/n of the published estimate theta0
ratio_nested_vs_original	chi2_test_red_nested / chi2_test_red_original (above 1: worse without the theta0 anchor)

synthetic_seeds/<problem>/s<seed>.json (analysis/synthetic_seeds.py)

One file per problem and seed (42-61). Fields as in external_validation/ (keys B_*) for that seed: semilla = seed; p_y = free parameters; B_chi2_test_theta0, B_chi2_test_red, B_chi2_test_full; B_epred_red, B_epred_full (relative prediction error with respect to the truth; 1 = theta0); nfev_red, nfev_full = function evaluations of the fits; seg_red = seconds of the reduced fit; B_error = the simulation of the truth failed. B_*_full is absent for the four problems with more than 100 free parameters. RESUMEN.json and RESUMEN.md summarise all seeds (por_semilla: counts per seed; por_sistema: per problem, con_senal = seeds with signal, red_ok_senal = reduced e_pred <= tau_e among them, red_le_full_senal = reduced e_pred <= full).

random_subsets/ and calibration_only/ (analysis/baselines.py)

Field	Meaning
k	number of biological parameters of our subset (also used for the random subsets)
chi2_ours	test chi2/n of our subset (theta0 anchor), from nested_validation/
chi2_rand_median, chi2_rand_q1, chi2_rand_q3	median and quartiles of the test chi2/n over the random draws
chi2_por_semilla, n_seeds, n_validas	test chi2/n of each draw (seeds 0-19), number of draws, valid draws
chi2_vacio	test chi2/n with only the calibration parameters re-estimated (n_cal of them)
ratio_rand_vs_ours, ratio_vacio_vs_ours	baseline over ours (below 1: the baseline predicts better)
nota	sin calibracion, th0 directo = no calibration parameters: theta0 is evaluated directly

qr_selection/ (analysis/qr_selection.py) and brun_morris/ (analysis/brun_morris.py)

Field	Meaning
S_ours, S_qr, S_brun, S_morris	biological parameters selected by each criterion (same k)
chi2_ours, chi2_qr, chi2_brun, chi2_morris, chi2_perfil	test chi2/n of each subset (with the calibration parameters, theta0 anchor)
overlap, overlap_brun_ours, overlap_morris_ours	parameters shared with our subset
ratio_qr_vs_ours	chi2_qr / chi2_ours
detalle_brun	gamma = collinearity index of the selected subset, cumple_gamma = gamma <= 10, dmsqr_top = importance of the 15 candidates
detalle_morris	mu_star_top = mu* of the 10 most influential parameters, fallos_simulacion = failed elementary effects
segundos_brun, segundos_morris, tipo	seconds of each criterion (selection and fit); kind of split

profile_likelihood/ (analysis/profile_likelihood.py)

<problem>.json:

Field	Meaning
p_libres, n_bio	free parameters of the training fit; biological parameters profiled
n_identificables, n_no_identificables_practicos, n_planos	parameters identifiable (profile above Delta chi2 = 3.84 on both sides), bounded on one side, flat
S_perfil	the k parameters with the narrowest profile confidence interval
chi2_perfil, chi2_ours, chi2_qr, ratio_perfil_vs_ours	test chi2/n of the profile subset, of ours and of pivoted QR
overlap_perfil_ours, overlap_perfil_qr	parameters shared with our subset and with the QR subset
coste_min_train	chi2 (sum of squares) of the full training fit used as the minimum
rondas_reajuste	times the full model was re-estimated because a profile point improved the minimum
dchi2_minimo_perfiles	smallest Delta chi2 among the profile points after the last re-estimation (below -1: residual improvement)
puntos_fallidos	profile points whose fit failed (Delta chi2 > 1e4), excluded
perfiles	per parameter: clase (identificable, no identificable practico, plano), ancho_ic_log (width of the 95 % interval in log units; infinite if open), dchi2_max_izq, dchi2_max_der (largest Delta chi2 on each side)
no_evaluable	not profiled: more than 60 free parameters (PL_PMAX), or no training/test split

<problem>/perfil_<parameter>_<side>_<i>.json: one profile point (lado = side, despl = displacement of log|theta_j|, dchi2, nfev, theta = re-estimated parameter vector); <problem>/full_train.npz: minimum (theta, coste, rondas). logs/: summary lines of the runs (terminado = problem finished with seg_total seconds; reajuste = re-estimation of the minimum).

criteria_tests/ and criteria_tests_20pc/ (analysis/criteria_tests.py)

File names <problem>__<criterion>__adm.json (admissibility) and <problem>__<criterion>__sint_<seed>.json (synthetic), with <criterion> = ours, qr, brun, morris, perfil. criteria_tests/ uses perturbations of +-5 % (the level of the method); criteria_tests_20pc/, +-20 % (admissibility only).

Field	Meaning
S	biological parameters of the subset tested
eajuste_med, erel_med	median e_fit and median e_rel over the scenarios
admisible	min(eajuste_med, erel_med) <= 0.436 and at least 2 parameters (rule of the method)
n_escenarios, lineal	valid scenarios; true if e_fit was computed to first order (problems of config.FIRST_ORDER)
B_chi2_test_theta0, B_chi2_test_red, B_epred_red, semilla	synthetic experiment for that seed (as in external_validation/)
no_evaluable	sin subconjunto = the criterion has no subset for the problem; falla la simulación de la verdad = the truth could not be simulated

`timing_complete/` (analysis/selection.py run from scratch)

`parallel/`, `single_core/`: the complete result of `selection.py` (fields as in `selection/`) run without cached results, with the sensitivity computations on 16-64 cores or on one core; the run time is `segundos`. `parallel_corrected_code/`: the eight problems of `config.FIRST_ORDER` with the corrected program (version 1.1); their subsets and `ajuste_med` are identical to `selection/`. The runs shared a 128-core server, so the times are upper bounds.

Other files

File	Content
`simulator_check/simulator_check.jsonl`	one line per problem: `mediciones`, `condiciones`, `p`, `p_y`, `err_rel_mediana` and `err_rel_max_vs_simulations` (relative difference with the reference simulations of the benchmark), `nota` (why no comparison was possible)
`cost/simulation_times.json`	`p`, `t_sim` (seconds per simulation), `modo` (`salidas` or `estados`); Smith: `t_sim_medido` and `nota` (scaled from a second machine)
`crauste_blowup.json`	`nominal` and `un_parametro_1%` (24 one-at-a-time changes): `existe_en_[0,28]` (the solution exists on the measured horizon), `t_final` (time reached), `efectores_max`, `t_max`; `tolerancias`: number of failures (`fallos_*`) for each integrator tolerance
`sbml_to_lean/<problem>.json`	report of the translation to Lean: sizes (`n_estados`, `n_theta`, `reacciones`), checks done in Python before writing the Lean file, `lean` (file written), `teorema_final`, `traducido`
`sbml_to_lean/translation_fidelity.json`	for each model: `err_rel_max` (largest relative difference between the vector field of the Lean file and libRoadRunner), `err_theta`, `err_x0`, `err_por_punto`
`sct/sct_analysis.json`	SCT example: `theta0`, `R2_theta0`, `DE_100` (100 differential-evolution runs: seeds, R^2, parameter ranges, `cambia_signo` = changes sign), `sigma`, selection fields as above, `descartes` (rejected candidates and the parameter they are most collinear with), `niveles`/`patron` (robustness), `validacion` (chi2/n and R^2 on days 25-31; `red` = reduced, `full` = full, `_DE` = full model re-fitted by differential evolution; `estable_*` = stable)