HackerRank | Prepare Certify Compete

Search

2

Monil

@monilgautam187

Complete your profile

Add your missing details →

This data will be helpful to auto-fill your job applications

60%

Personal Information

monilgautam187@gmail.com

Add your mobile number

India

My Badges

C++

CPP

★★★

You have earned 15.00 points!

You are now 35 points away from the 4th star for your c++ badge.



56% 115/150

In this challenge, the task is to debug the existing code to successfully execute all provided test files.

The given code defines two classes `HotelRoom` and `HotelApartment` denoting respectively a standard hotel room and a hotel apartment. An instance of any of these classes has two parameters: `bedrooms` and `bathrooms` denoting respectively the number of bedrooms and the number of bathrooms in the room.

The prices of a standard hotel room and hotel apartment are given as:

- Hotel Room: $50 \cdot bedrooms + 100 \cdot bathrooms$.
- Hotel Apartment: The price of a standard room with the same number bedrooms and bathrooms plus 100.

For example, if a standard room costs 200, then an apartment with the same number of bedrooms and bathrooms costs 300.

In hotel's codebase, there is a piece of code reading the list of rooms booked for today and calculates the total profit for the hotel. However, sometimes calculated profits are lower than they should be.

Debug the existing `HotelRoom` and `HotelApartment` classes' implementations so that the existing code computing the total profit returns a correct profit.

Your function will be tested against several cases by the locked template code.

Input Format

The input is read by the provided locked code template.

In the first line, there is a single integer n denoting the number of rooms booked for today.

After that n lines follow. Each of these lines begins with a `room_type` which is either `standard` or `apartment`, and is followed by the number of bedrooms and the number of bathrooms in this room.

Constraints

- $1 \leq n \leq 100$
- There is at least 1 and at most 5 bedrooms in a room
- There is at least 1 and at most 5 bathrooms in a room

Output Format

The output is produced by the provided and locked code template. It calculates the total profit by iterating through the vector of all rooms read from the input.

Sample Input 0

```
2
standard 3 1
apartment 1 1
```

Sample Output 0

```
500
```

Explanation 0

In the sample we have one standard room with 3 bedrooms and 1 bathroom, and one apartment with one 1 bedrooms

```
    int get_price() {
        return HotelRoom::get_price() + 100;
    }
};

int main() {
    int n;
    cin >> n;
    vector<HotelRoom*> rooms;
    for (int i = 0; i < n; ++i) {
        string room_type;
        int bedrooms;
        int bathrooms;
        cin >> room_type >> bedrooms >> bathrooms;
        if (room_type == "standard") {
            rooms.push_back(new HotelRoom(bedrooms, bathrooms));
        } else {
            rooms.push_back(new HotelApartment(bedrooms, bathrooms));
        }
    }

    int total_profit = 0;
    for (auto room : rooms) {
        total_profit += room->get_price();
    }
    cout << total_profit << endl;

    for (auto room : rooms) {
        delete room;
    }
    rooms.clear();
```

Line: 54 Col: 12

Upload Code as File | Test against custom input | Run Code | Submit Code

You have earned 15.00 points!

You are now 35 points away from the 4th star for your c++ badge.

56% 115/150

Congratulations

You solved this challenge. Would you like to challenge your friends?

Next Challenge