

CC Logs API — Official API Documentation

1. Overview

The CC Logs API is a high-concurrency system designed for log ingestion, application version management, and client authentication. It utilizes a microservices-ready architecture with FastAPI, Celery, Redis, and Elasticsearch.

2. Global Response Formats

The API follows a standardized response structure for all endpoints to ensure consistent integration.

2.1 Success Response

Sent for all successful operations (200 OK, 201 Created).

```
{
  "status": true,
  "message": "Detailed success message",
  "data": {
    "key": "value"
  }
}
```

2.2 Error Response

Sent for client errors (4xx) or server errors (5xx).

```
{
  "status": false,
  "message": "Description of what went wrong",
  "error": "Internal error details or stack trace (if applicable)"
}
```

3. Administrative Endpoints (Admin)

3.1 Create New Client

`POST /admin/create-client` Used to register a new client and generate an initial access key.

Request Body:

Field	Type	Description
<code>client_id</code>	string	Unique identifier for the client
<code>access_key</code>	string	Secret key for the client
<code>expiry_date</code>	string	Expiry in <code>YYYY-MM-DD HH:MM:SS</code>
<code>status</code>	bool/str	<code>true</code> for active, <code>false</code> for suspended

3.2 Rotate Access Key

`POST /admin/rotate-key` Update the secret access key for an existing client.

Request Body:

Field	Type	Description
<code>client_id</code>	string	Target client ID
<code>new_key</code>	string	The new secret key

3.3 Upload Application Version

`POST /admin/upload-version` Upload a new build/package for a specific client.

Content-Type: `multipart/form-data`

Form Fields:

- `version` : (e.g., "2.1.0")
- `client_id` : (Target client)
- `release_notes` : (HTML or Text)
- `mandatory` : (0 or 1)
- `file` : (Binary file)

4. Logging & Monitoring

4.1 Push Log (High Concurrency)

`POST /push-log/` This endpoint offloads the processing to a Celery worker. It is highly optimized for performance.

Request Body: Accepts any JSON object containing log details (timestamp, level, message, agentId, etc.).

4.2 Search Logs

`GET /search-logs/` Query Elasticsearch for specific logs.

Query Parameters:

- `agentId` : Filter by agent
 - `level` : INFO, ERROR, WARNING, etc.
 - `start_date` : YYYY-MM-DD
 - `end_date` : YYYY-MM-DD
 - `page` : Pagination page number
 - `size` : Logs per page
-

5. Client Integration Endpoints

5.1 Validate Access Key

`POST /validate-key` Validates the key and returns a secure, time-limited S3 download URL for the latest app version.

Request Body:

```
{
  "access_key": "your_secret_key"
}
```

5.2 Check for Updates

`POST /check-version` Used by client applications to verify if a newer version is available.

Request Body:

```
{
  "client_id": "test_client",
  "current_version": "1.0.0"
}
```

6. HTTP Status Codes

Code	Meaning
200	OK - Request was successful
201	Created - Resource was successfully created
400	Bad Request - Invalid parameters
401	Unauthorized - Invalid or expired access key
404	Not Found - Resource does not exist
409	Conflict - Resource already exists (e.g., duplicate client_id)
500	Internal Server Error - Unexpected server issue

Document Version: 1.0.0

Copyright: © 2026 Czentrix Systems