Exp - 10 Internetworking with router in cisco packet tracer simulator

Aim: To design and configure different network using a router in cisco packet tracer.

Procedure: *) open cisco packet tracer and place one router, two switch and HPCs.

*) Connect two pcs to each switch using ethernet cable.

*) Connect both switche to the router.

*) Assign static IP address to all pcs and router interface.

Device	IP address	Subnet mask	Gateway
PC0	192.168.1.2	255.255.255.0	192.168.1.1
PC1	192.168.1.3	255.255.255.0	192.168.1.1
PC2	192.168.2.2	255.255.255.0	192.168.2.1
PC3	192.168.2.3	255.255.255.0	192.168.2.1

Router Configuration.

enable

configure terminal

interface gigabit Ethernet 0/0

ip address 192.168.1.1 255.255.0

no shut down

result

b) Design and configure an Internetwork using a wireless router, DHCP server, and Internet cloud

Aim: To configure a wireless network using a wireless router, DHCP and an Internet cloud

Procedure: *) place a wireless router, PCs or laptops and an Internet cloud in Cisco packet tracer.

*) Connect the Internet cloud the wireless router's Internet port.

*) Enable DHCP on the wireless router.

*) configure the wireless SSID and password

*) Connect laptop & the wireless network.

*) Test connectivity using the ping command.

Result; The wireless network is configured and device receive IP address automatically through DHCP.

c) Design and configure an Internetwork in your lab using a switch, router and ethernet cables

Aim: To establish communication between computer using a switch, router and ethernet cables.

Procedure: *) Place a router, one switch and 3-4 PCs in Cisco packet tracer.

*) Connect all PCs to the switch using ethernet cables.

*) Assign IP address to PCs in same subnet

*) Enable the router interface using the no shutdown command.

*) Test communication using ping command.

Result; The Internetwork is conf configured successfully and communication between connected device is verified using ping