```
#include <stdio.h>
 #include <conio.h>
 #include <stdlib.h>
 int i, j, k, a, b, u, v, n, ne = 1;
 int min, mincost = 0, cost[9][9], parent[9];
 int find(int);
 int uni(int, int);
 void main() {
 printf("\n\tImplementation of Kruskal's Algorithm\n");
 printf("\nEnter the no. of vertices:");
 scanf("%d", & n);
 printf("\nEnter the cost adjacency matrix:\n");
 for (i = 1; i <= n; i++) {
 for (j = 1; j <= n; j++) {
 scanf("%d", & cost[i][j]);
 if (cost[i][j] == 0)
 cost[i][j] = 999;
 }
 }
 printf("The edges of Minimum Cost Spanning Tree are\n");
 while (ne < n) { //edges < vertex - 1
 for (i = 1, min = 999; i <= n; i++) {
 for (j = 1; j <= n; j++) {
 if (cost[i][j] < min) {
 min = cost[i][j];
 a = u = i;
 b = v = j;
 }
 }
 }
 u = find(u);
 v = find(v);
 if (uni(u, v)) {
 printf("%d edge (%d,%d) =%d\n", ne++, a, b, min);
 mincost += min;
 }
 cost[a][b] = cost[b][a] = 999;
 }
 printf("\n\tMinimum cost = %d\n", mincost);
 getch();
 }
 int find(int i) {
 while (parent[i])
 i = parent[i];
```

```
return i;
}
int uni(int i, int j) {
if (i != j) {
parent[j] = i;
return 1;
}
return 0;
}
```