Home | Home | Week5_SimulatedAnnealing_8_Qu | HillClimbing_N_Queens

localhost:8889/notebooks/Week5_SimulatedAnnealing_8_Queens.ipynb

jupyter Week5_SimulatedAnnealing_8_Queens Last Checkpoint: 11 minutes ago

File Edit View Run Kernel Settings Help

Trusted

Code

JupyterLab Python 3 (ipykernel)

```
    print("\nChessboard:")

    for row in range(N):
        for col in range(N):
            if board[col] == row:
                print(" Q ", end="")
            else:
                print(" . ", end="")
        print()


# Main program
solution, cost = simulated_annealing()

if cost == 0:
    print("Solution found!")
else:
    print("No solution found within the iteration limit.")

print("Queen positions (row for each column):", solution)
print("Number of attacking pairs:", cost)

display_board(solution)
```

```
Solution found!
Queen positions (row for each column): [6, 1, 1, 6, 0, 2, 4, 1]
Number of attacking pairs: 0

Chessboard:
 .  .  .  .  Q  .  .  .
 .  Q  Q  .  .  .  .  Q
 .  .  .  .  .  Q  .  .
 .  .  .  .  .  .  .  .
 .  .  .  .  .  .  Q  .
 .  .  .  .  .  .  .  .
 Q  .  .  Q  .  .  .  .
 .  .  .  .  .  .  .  .
```

[ ]:

27°C Sunny

Search

ENG IN

10:32:15 31-10-2026