

update

14

Ques Update Lastname of Divya as chandru for emp-id 5.

SYNTAX:

UPDATE {TABLE-name}

SET {col-name} = {value}

WHERE id=5;

UPDATE employee
SET LastName = 'Chandru'
WHERE id=5;

↳ This is used to update a particular id (or) person.

INTERVIEW QUESTION:

Update salary of all employee by giving 8% from their current salary

Ans:

you should not use WHERE clause here

Query:

15

UPDATE employee

SET Salary = (Salary + (Salary * (8/100)));

Delete

Query Delete a particular record of employee where id is 6

SET SQL_SAFE_UPDATES = 0

SYNTAX:

DELETE FROM {table-name}

WHERE {key col-name} = { }

DELETE FROM employee

WHERE Emp-id = 6

[Same as Update, If where clause is not used, it will delete entire table records]

[9090]

DDL

(Data Definition Language)

[Defining the structure of
table] / db

* CREATE

* DROP

* { ALTER }

→ MODIFY
→ ADD
→ delete any
specific column
[DROP]

DML

(Data Manipulation
Language)

[trying to manipulate
the data on the top
of the table that we
have] (trying to make a
changes in already designed table)

* UPDATE

* DELETE

* INSERT

QUESTION:

(17)

Diff b/w ALTER command & UPDATE command.

Ans:

ALTER command is ^{change} used to the schema/structure of the table

UPDATE command is a part of DML, it is basically used to change the records available in the table.

Query:

Change the LastName varchar(20) to varchar(30).

* It is a DDL command because it is related to schema/definition of table. So use ALTER command.

SYNTAX:

(18)

ALTER TABLE {table_name}

{MODIFY} (already present column, modify)

{col_name} {datatype} {any constraints}

Ans

```
ALTER TABLE employee  
MODIFY LastName varchar(30) NOT NULL;
```

* If I want change something of the desc of the table / or that I written already at the creation part

* To Add a new column in table
{the description of the table will get change}

Instead of MODIFY → {ADD}

Q

ALTER TABLE employee {ADD} mobile varchar(10)

NOT NULL;

* to drop a particular column which is also related to the description of the table.

ALTER TABLE employee {DROP} mobile;

SYNTAX:

ADD ALTER TABLE {table-name} {ADD} {col-name} {d.Type} {con?}

Modify

" " "

MODIFY

"

"

drop

" " "

DROP

{col-name}

GROUP BY
HAVING

AGGREGATION

(20)

✓ COUNT(*) → count all the employee

SELECT COUNT(*) FROM employee

① COUNT(*)

counts all the rows in the result set, including rows with NULL values

② COUNT(col)

counts the num of non-null values in the specified column

✓ MAX()

✓ MIN()

✓ SUM()

{ GROUP BY } → Having