

# Scan Report

February 22, 2025

## Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Immediate scan of IP 6.87.153.254”. The scan started at Sat Feb 22 08:59:56 2025 UTC and ended at Sat Feb 22 09:41:06 2025 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

## Contents

<b>1</b>	<b>Result Overview</b>	<b>2</b>
<b>2</b>	<b>Results per Host</b>	<b>2</b>
2.1	6.87.153.254 . . . . .	2
2.1.1	Low general/tcp . . . . .	2

## 1 Result Overview

Host	High	Medium	Low	Log	False Positive
6.87.153.254	0	0	1	0	0
Total: 1	0	0	1	0	0

Vendor security updates are not trusted.

Overrides are on. When a result has an override, this report uses the threat of the override.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

It only lists hosts that produced issues.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains result 1 of the 1 results selected by the filtering above. Before filtering there were 26 results.

## 2 Results per Host

### 2.1 6.87.153.254

Host scan start Sat Feb 22 09:00:10 2025 UTC

Host scan end

Service (Port)	Threat Level
general/tcp	Low

#### 2.1.1 Low general/tcp

Low (CVSS: 2.6) NVT: TCP timestamps
<b>Summary</b> The remote host implements TCP timestamps and therefore allows to compute the uptime.
<b>Vulnerability Detection Result</b> It was detected that the host implements RFC1323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 4061953724 Packet 2: 683572438 ... continues on next page ...

...continued from previous page...

**Impact**

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

**Solution**

**Solution type:** Mitigation

To disable TCP timestamps on linux add the line 'net.ipv4.tcp\_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.

See the references for more information.

**Affected Software/OS**

TCP/IPv4 implementations that implement RFC1323.

**Vulnerability Insight**

The remote host implements TCP timestamps, as defined by RFC1323.

**Vulnerability Detection Method**

Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.

Details: TCP timestamps

OID:1.3.6.1.4.1.25623.1.0.80091

Version used: \$Revision: 14310 \$

**References**

Other:

URL:<http://www.ietf.org/rfc/rfc1323.txt>

URL:<http://www.microsoft.com/en-us/download/details.aspx?id=9152>

[ [return to 6.87.153.254](#) ]