


Image alignment



<http://www.wired.com/gadgetlab/2010/07/camera-software-lets-you-see-into-the-past/>


Computing transformations

- Given a set of matches between images A and B
 - How can we compute the transform T from A to B?



- Find transform T that best “agrees” with the matches


Simple case: translations



$(\mathbf{x}_t, \mathbf{y}_t)$

How do we solve for
 $(\mathbf{x}_t, \mathbf{y}_t)$?


Simple case: translations



Displacement of match $i = (\mathbf{x}'_i - \mathbf{x}_i, \mathbf{y}'_i - \mathbf{y}_i)$

$$(\mathbf{x}_t, \mathbf{y}_t) = \left(\frac{1}{n} \sum_{i=1}^n \mathbf{x}'_i - \mathbf{x}_i, \frac{1}{n} \sum_{i=1}^n \mathbf{y}'_i - \mathbf{y}_i \right)$$

Another view




$$\mathbf{x}_i + \mathbf{x}_t = \mathbf{x}'_i$$

$$\mathbf{y}_i + \mathbf{y}_t = \mathbf{y}'_i$$

- System of linear equations
 - What are the knowns? Unknowns?
 - How many unknowns? How many equations (per match)?

Another view



$$\mathbf{x}_i + \mathbf{x}_t = \mathbf{x}'_i$$

$$\mathbf{y}_i + \mathbf{y}_t = \mathbf{y}'_i$$

- Problem: more equations than unknowns
 - “Overdetermined” system of equations
 - We will find the *least squares* solution

Least squares formulation

- For each point $(\mathbf{x}_i, \mathbf{y}_i)$

$$\mathbf{x}_i + \mathbf{x}_t = \mathbf{x}'_i$$

$$\mathbf{y}_i + \mathbf{y}_t = \mathbf{y}'_i$$

- we define the *residuals* as

$$r_{\mathbf{x}_i}(\mathbf{x}_t) = (\mathbf{x}_i + \mathbf{x}_t) - \mathbf{x}'_i$$

$$r_{\mathbf{y}_i}(\mathbf{y}_t) = (\mathbf{y}_i + \mathbf{y}_t) - \mathbf{y}'_i$$

Least squares formulation

- Goal: minimize sum of squared residuals

$$C(\mathbf{x}_t, \mathbf{y}_t) = \sum_{i=1}^n \left(r_{\mathbf{x}_i}(\mathbf{x}_t)^2 + r_{\mathbf{y}_i}(\mathbf{y}_t)^2 \right)$$

- “Least squares” solution
- For translations, is equal to mean (average) displacement

Image Alignment Algorithm


Given images A and B

1. Compute image features for A and B
2. Match features between A and B
3. Compute homography between A and B using least squares on set of matches

What could go wrong?

Outliers


outliers



inliers

Robustness

- Let's consider a simpler example... linear regression




Problem: Fit a line to these datapoints


Least squares fit

- How can we fix this?

Least squares: linear regression



Linear regression




$$\text{Cost}(m, b) = \sum_{i=1}^n |y_i - (mx_i + b)|^2$$


Idea

- Given a hypothesized line
- Count the number of points that “agree” with the line
 - “Agree” = within a small distance of the line
 - I.e., the **inliers** to that line
- For all possible lines, select the one with the largest number of inliers

Counting inliers




Counting inliers



Inliers: 3


Counting inliers




How do we find the best line?

- Unlike least-squares, no simple closed-form solution
- Hypothesize-and-test
 - Try out many lines, keep the best one
 - Which lines?


Translations




Random Sample Consensus



Random Sample Consensus




Random Sample Consensus



RANSAC

- Idea:
 - All the inliers will agree with each other on the translation vector; the (hopefully small) number of outliers will (hopefully) disagree with each other
 - “All good matches are alike; every bad match is bad in its own way.”
 - Tolstoy via Alyosha Efros


RANSAC



RANSAC




- Back to linear regression
- How do we generate a hypothesis?



RANSAC



- Back to linear regression
- How do we generate a hypothesis?



RANSAC

- General version:
 1. Randomly choose s samples
 - Typically s = minimum sample size that lets you fit a model
 2. Fit a model (e.g., line) to those samples
 3. Count the number of inliers that approximately fit the model
 4. Repeat N times
 5. Choose the model that has the largest set of inliers

Final step: least squares fit

