

CS5222 Computer Networks and Internets

Security

Prof. Weifa Liang

Weifa.liang@cityu-dg.edu.cn

Slides based on book *Computer Networking: A Top-Down Approach.*

Network Security Roadmap

- What is network security?
- Principles of cryptography
- Message integrity, authentication
- Securing e-mail
- Securing TCP connections: TLS
- Network layer security: IPsec
- Security in wireless and mobile networks
- Operational security: firewalls and IDS




What is network security?

- **Confidentiality**: only sender and the intended receiver “understand” the message contents
 - sender encrypts message
 - receiver decrypts message
- **Integrity**: sender and receiver want to ensure the message not altered (in transit, or afterwards) without detection
- **Authentication**: sender and receiver want to confirm the identity of each other
- **Non-repudiation**: the assurance that someone cannot deny the validity of something
- **Access and availability**: services must be accessible and available to intended users

Friends and enemies: Alice, Bob, Trudy

- well-known in network security world
- Bob, Alice (lovers!) want to communicate “securely”
- Trudy (intruder) may intercept, delete, and add messages



Friends and enemies: Alice, Bob, Trudy

Who might Bob and Alice be?

- ... well, *real-life* Bobs and Alices!
- Web browser/server for electronic transactions (e.g., on-line purchases)
- on-line banking client/server
- DNS servers
- BGP routers exchanging routing table updates
- other examples?

There are bad guys (and girls) out there!

Q: What can a “bad guy” do?

A: A lot! (recall section 1.6)


- **eavesdrop**: intercept messages
- actively **insert** messages into connection
- **impersonation**: can fake (spoof) source address in packet (or any field in packet)
- **hijacking**: “take over” ongoing connection by removing sender or receiver, inserting himself in place
- **denial of service**: prevent service from being used by others (e.g., by overloading resources)
- **Ransom**: compromise a system/network, lock the access, and demand for payment

outline

- What is network security?
- Principles of cryptography
 - Message integrity, authentication
 - Securing e-mail
 - Securing TCP connections: TLS
 - Network layer security: IPsec
 - Security in wireless and mobile networks
 - Operational security: firewalls and IDS



The language of cryptography



m : plaintext message

$K_A(m)$: ciphertext, encrypted with key K_A

$m = K_B(K_A(m))$


Breaking an encryption scheme

- **cipher-text only attack:**
Trudy has ciphertext she can analyze

- **two approaches:**
 - brute force: search through all keys
 - statistical analysis

- **known-plaintext attack:**
Trudy has plaintext corresponding to ciphertext
 - *e.g.*, in monoalphabetic cipher, Trudy determines pairings for a,l,i,c,e,b,o,
- **chosen-plaintext attack:**
Trudy can get ciphertext for a chosen plaintext

Symmetric key cryptography



symmetric key crypto: Bob and Alice share the same (symmetric) key: K

- e.g., key is knowing substitution pattern in mono alphabetic substitution cipher

Q: how do Bob and Alice agree on key value?

Simple encryption scheme

substitution cipher: substituting one thing for another

- monoalphabetic cipher: substitute one letter for another

plaintext:	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
		↓																							↓	
ciphertext:	m	n	b	v	c	x	z	a	s	d	f	g	h	j	k	l	p	o	i	u	y	t	r	e	w	q

e.g.: Plaintext: bob. i love you. alice
ciphertext: nkn. s gktc wky. mgsbc

🔑 *Encryption key*: mapping from set of 26 letters
to set of 26 letters (e.g., shift positions)

A more sophisticated encryption approach

- n substitution ciphers, M_1, M_2, \dots, M_n
- cycling pattern:
 - e.g., $n=4$: M_1, M_3, M_4, M_3, M_2 ; M_1, M_3, M_4, M_3, M_2 ; ..
- for each new plaintext symbol, use subsequent substitution pattern in cyclic pattern
 - dog: d from M_1 , o from M_3 , g from M_4
- 🔑 **Encryption key:** n substitution ciphers, and cyclic pattern
 - key need not be just n-bit pattern

Symmetric key crypto: DES

DES: Data Encryption Standard

- US encryption standard [NIST 1993]
- 56-bit symmetric key, 64-bit plaintext input
- block cipher with cipher block chaining
- how secure is DES?
 - DES Challenge: 56-bit-key-encrypted phrase decrypted (brute force) in less than a day
 - no known good analytic attack
- making DES more secure:
 - 3DES: encrypt 3 times with 3 different keys

Reason to kill:

- Wang Xiaoyun (王 小 云), Shandong University
- In 2004, break MD5
- In 2005, break SHA1, which commonly used in most symmetric key crypto including DES
- Collision probability is reduced from 2^{80} to 2^{63}

AES: Advanced Encryption Standard

- symmetric-key NIST standard, replaced DES (Nov 2001)
- processes data in 128 bit blocks
- 128, 192, or 256 bit keys
- brute force decryption (try each key) taking 1 sec on DES, takes 149 trillion years for AES

Public Key Cryptography

symmetric key crypto:


- requires sender, receiver know a shared secret key
- Q: how to agree on key in first place (particularly if never “met”)?

public key crypto

- *radically* different approach [Diffie-Hellman76, RSA78]
- Sender and receiver do *not* share secret key
- *Public* encryption key known to *all*
- *Private* decryption key known only to the receiver



Public Key Cryptography



Wow - public key cryptography revolutionized 2000-year-old (previously only symmetric key) cryptography!

- similar ideas emerged at roughly same time, independently in US and UK (classified)

Public key encryption algorithms

requirements:

① need $K_B^+(\cdot)$ and $K_B^-(\cdot)$ such that

$$K_B^-(K_B^+(m)) = m$$

② given public key K_B^+ , it should be impossible to compute private key K_B^-

RSA: Rivest, Shamir, Adelson algorithm

Prerequisite: modular arithmetic

- $x \bmod n$ = remainder of x when divide by n

- facts:

$$[(a \bmod n) + (b \bmod n)] \bmod n = (a+b) \bmod n$$

$$[(a \bmod n) - (b \bmod n)] \bmod n = (a-b) \bmod n$$

$$[(a \bmod n) * (b \bmod n)] \bmod n = (a*b) \bmod n$$

- thus

$$(a \bmod n)^d \bmod n = a^d \bmod n$$

- example: $x=14$, $n=10$, $d=2$:

$$(x \bmod n)^d \bmod n = 4^2 \bmod 10 = 6$$

$$x^d = 14^2 = 196 \quad x^d \bmod 10 = 6$$

RSA: getting ready

- message: just a bit pattern
- bit pattern can be uniquely represented by an integer number
- thus, encrypting a message is equivalent to encrypting a number

example:

- $m = 10010001$. This message is uniquely represented by the decimal number 145.
- to encrypt m , we encrypt the corresponding number, which gives a new number (the ciphertext).

RSA: Creating public/private key pair

1. choose two large prime numbers p, q . (e.g., 1024 bits each)
2. compute $n = pq$, $z = (p-1)(q-1)$
3. choose e (with $e < n$) that has no common factors with z (e, z are “relatively prime”).
4. choose d such that $ed-1$ is exactly divisible by z . (in other words: $ed \bmod z = 1$).
5. *public* key is (n, e) . *private* key is (n, d) .
 $\underbrace{(n, e)}_{K_B^+}$ $\underbrace{(n, d)}_{K_B^-}$

RSA: encryption, decryption

0. given (n, e) and (n, d) as computed above
1. to encrypt message $m (< n)$, compute
$$c = m^e \bmod n$$
2. to decrypt received bit pattern, c , compute
$$m = c^d \bmod n$$

magic happens!

$$m = \underbrace{(m^e \bmod n)}_c^d \bmod n$$


RSA example:

Bob chooses $p=5$, $q=7$. Then $n=35$, $z=24$.

$e=5$ (so e , z relatively prime).

$d=29$ (so $ed-1$ exactly divisible by z).

encrypting 8-bit messages.



Why does RSA work?

- must show that $c^d \bmod n = m$, where $c = m^e \bmod n$
- fact: for any x and y : $x^y \bmod n = x^{(y \bmod z)} \bmod n$
 - ✓ where $n = pq$ and $z = (p-1)(q-1)$
- thus,
 $c^d \bmod n = (m^e \bmod n)^d \bmod n$
 - $= m^{ed} \bmod n$
 - $= m^{(ed \bmod z)} \bmod n$
 - $= m^1 \bmod n$
 - $= m$

➤ Euler's Theorem in Number Theory

- ✓ For any integers a and m relatively prime, we always have

$$a^{\phi(m)} = 1 \pmod{m}$$

where $\phi(m)$ is the Euler totient function

Examples: for primes p and q ,
 $\phi(pq) = (p-1)(q-1)$

RSA: another important property

The following property will be *very* useful later:

$$\underbrace{K_B^-(K_B^+(m))}_{\text{use public key first, followed by private key}} = m = \underbrace{K_B^+(K_B^-(m))}_{\text{use private key first, followed by public key}}$$

use public key
first, followed
by private key

use private key
first, followed
by public key

result is the same!

Why $K_B^-(K_B^+(m)) = m = K_B^+(K_B^-(m))$?

follows directly from modular arithmetic:

$$\begin{aligned}(m^e \bmod n)^d \bmod n &= m^{ed} \bmod n \\ &= m^{de} \bmod n \\ &= (m^d \bmod n)^e \bmod n\end{aligned}$$

Why is RSA secure?

- suppose you know Bob's public key (n,e) . How hard is it to determine d ?
- essentially need to find factors of n without knowing the two factors p and q
 - fact: factoring a big number is hard


RSA in practice: session keys

- exponentiation in RSA is computationally intensive
- DES is at least 100 times faster than RSA
- use public key crypto to establish secure connection, then establish second key – symmetric session key – for encrypting data


session key, K_s (Diffie-Hellman key exchange)

- Bob and Alice use RSA to exchange a symmetric session key K_s
- once both have K_s , they use symmetric key cryptography

Diffie-Hellman Protocol



- Alice and Bob never met and share no secrets
- Public info: p and g
 - p is a large prime number, g is a generator of \mathbb{Z}_p^*
 - ✓ $\mathbb{Z}_p^* = \{1, 2 \dots p-1\}$; $\forall a \in \mathbb{Z}_p^* \exists i$ such that $a = g^i \mod p$
 - ✓ Modular arithmetic: numbers “wrap around” after they reach p



Roadmap

- What is network security?
- Principles of cryptography
- **Authentication**, message integrity
- Securing e-mail
- Securing TCP connections: TLS
- Network layer security: IPsec
- Security in wireless and mobile networks
- Operational security: firewalls and IDS



Authentication

Goal: Bob wants Alice to “prove” her identity to him

Protocol ap1.0: Alice says “I am Alice”




failure scenario??



Authentication

Goal: Bob wants Alice to “prove” her identity to him

Protocol ap1.0: Alice says “I am Alice”




*in a network, Bob
cannot “see”
Alice, so Trudy
simply declares
herself to be Alice*



Authentication: another try

Goal: Bob wants Alice to “prove” her identity to him


Protocol ap2.0: Alice says “I am Alice” in an IP packet containing her source IP address



Authentication: another try

Goal: Bob wants Alice to “prove” her identity to him


Protocol ap2.0: Alice says “I am Alice” in an IP packet containing her source IP address



Authentication: a third try

Goal: Bob wants Alice to “prove” her identity to him

Protocol ap3.0: Alice says “I am Alice” Alice says “I am Alice” and sends her secret password to “prove” it.




failure scenario??

Authentication: a third try

Goal: Bob wants Alice to “prove” her identity to him

Protocol ap3.0: Alice says “I am Alice” Alice says “I am Alice” and sends her secret password to “prove” it.




*playback attack:
Trudy records
Alice's packet
and later
plays it back to Bob*

Authentication: a modified third try

Goal: Bob wants Alice to “prove” her identity to him


Protocol ap3.0: Alice says “I am Alice” Alice says “I am Alice” and sends her encrypted secret password to “prove” it.



Authentication: a modified third try

Goal: Bob wants Alice to “prove” her identity to him

Protocol ap3.0: Alice says “I am Alice” Alice says “I am Alice” and sends her encrypted secret password to “prove” it.



playback attack still works: Trudy records Alice's packet and later plays it back to Bob


Authentication: a fourth try

Goal: avoid playback attack

nonce: number (R) used only **once-in-a-lifetime**

protocol ap4.0: to prove Alice “live”, Bob sends Alice nonce, R

- Alice must return R, encrypted with shared secret key




Failures, drawbacks?

Authentication: ap5.0

ap4.0 requires shared symmetric key - can we authenticate using public key techniques?

ap5.0: use nonce, public key cryptography



Bob computes


$$K_A^+ (K_A^-(R)) = R$$

and knows only Alice could have the private key, that encrypted R such that

$$K_A^+ (K_A^-(R)) = R$$

Authentication: ap5.0 – there's still a flaw!

man (or woman) in the middle attack: Trudy poses as Alice (to Bob) and as Bob (to Alice)



Roadmap


- What is network security?
- Principles of cryptography
- Authentication, **message integrity**
- Securing e-mail
- Securing TCP connections: TLS
- Network layer security: IPsec
- Security in wireless and mobile networks
- Operational security: firewalls and IDS



Digital signatures

cryptographic technique analogous to hand-written signatures:

- sender (Bob) digitally signs document: he is document owner/creator.
- *verifiable, nonforgeable*: recipient (Alice) can prove to someone that Bob, and no one else (including Alice), must have signed document
- **simple digital signature for message m :**
 - Bob signs m by encrypting with his private key K_B , creating “signed” message, $K_B^-(m)$



Digital signatures

- suppose Alice receives msg m , with signature: $m, \bar{K}_B(m)$
- Alice verifies m signed by Bob by applying Bob's public key \bar{K}_B to $\bar{K}_B(m)$ then checks $\bar{K}_B(\bar{K}_B(m)) = m$.
- If $\bar{K}_B(\bar{K}_B(m)) = m$, whoever signed m must have used Bob's private key

Alice thus verifies that:

- Bob signed m
- no one else signed m
- Bob signed m and not m'

non-repudiation:


- ✓ Alice can take m , and signature $\bar{K}_B(m)$ to court and prove that Bob signed m

Message digests: Message Integrity

computationally expensive to public-key-encrypt long messages

goal: fixed-length, **easy-to-compute** digital “fingerprint”

- apply hash function H to m , get fixed size message digest, $H(m)$



Hash function properties:

- many-to-1
- produces fixed-size msg digest (fingerprint)
- given message digest x , computationally infeasible to find m such that $x = H(m)$

Internet checksum: poor crypto hash function

Internet checksum has some properties of hash function:


- produces fixed length digest (16-bit sum) of message
- is many-to-one

but given message with given hash value, it is easy to find another message with same hash value:


<u>message</u>	<u>HEX format</u>		<u>message</u>	<u>HEX format</u>
I O U 1	49 4F 55 31		I O U <u>9</u>	49 4F 55 <u>39</u>
0 0 . 9	30 30 2E 39		0 0 . <u>1</u>	30 30 2E <u>31</u>
9 B O B	39 42 4F 42		9 B O B	39 42 4F 42
<hr/>			<hr/>	
A2 B1 B2 AC		<i>different messages</i> <i>but identical checksums!</i>	B2 B1 B2 AC	

Digital signature = signed message digest

Bob sends digitally signed message:



Alice verifies signature, integrity of digitally signed message:




Hash function algorithms

- MD5 hash function widely used (RFC 1321)
 - computes 128-bit message digest in 4-step process.
 - arbitrary 128-bit string x , appears difficult to construct msg m whose MD5 hash is equal to x
- SHA-1 is also used
 - US standard [NIST, FIPS PUB 180-1]
 - 160-bit message digest

Authentication: ap5.0 – let's fix it!!

Recall the problem: Trudy poses as Alice (to Bob) and as Bob (to Alice)




Need for certified public keys

- motivation: Trudy plays pizza prank on Bob
 - Trudy creates e-mail order:
Dear Pizza Store, Please deliver to me four pepperoni pizzas. Thank you, Bob
 - Trudy signs order with her private key
 - Trudy sends order to Pizza Store
 - Trudy sends to Pizza Store her public key, but says it's Bob's public key
 - Pizza Store verifies signature; then delivers four pepperoni pizzas to Bob
 - Bob doesn't even like pepperoni




Public key Certification Authorities (CA)

- **certification authority (CA)**: binds public key to particular entity, E
- entity (person, website, router) registers its public key with CE provides “proof of identity” to CA: **CA is my witness, and CA is trustworthy!**
 - CA creates certificate binding identity E to E’s public key
 - certificate containing E’s public key digitally signed by CA: CA says “this is E’s public key”



Public key Certification Authorities (CA)

- when Alice wants Bob's public key:
 - gets Bob's certificate (Bob or elsewhere)
 - apply CA's public key to Bob's certificate, get Bob's public key



basic techniques.....

- cryptography (symmetric and public key)
- message integrity
- end-point authentication

.... used in many different security scenarios

- secure email
- secure transport (TLS)
- IP sec
- 802.11, 4G/5G

operational security: firewalls and IDS



Network Security (summary)