CS5351 Software Engineering 2024/2025 Semester B

Program Testing Exercise: Continuous Integration with Github Project

Overview:

- 1. Create a local project as the codebase to apply continuous integration (CI).
- 2. Link the project with Github, which provides the CI feature.
- 3. Modify the code locally and push it to GitHub in order to trigger CI.
- 4. Please upload the result of testing and any necessary screenshots/descriptions on Discussions of Canvas until 6:30 pm, March 25.

A. Prepare a Maven Project in Eclipse IDE

- 1. Download and install the newest Eclipse IDE
 - a. download link: https://www.eclipse.org/downloads/
 - b. Choose the option for JAVA developers.




(Fig.1)

2. Create a new Maven project on your local computer


Import Route 1: Use this example project: wkchanG7309/continuous-integration

a. Download the package: click the link->code->download ZIP




(Fig.2)

b. Open Eclipse ->import projects




(Fig.3)

c. Copy the location of the package just download, pick folder, and finish.



(Fig.4)


d. click "Move to package ... " for both two java files if package error appears.



(Fig.5)

Import Route 2:

a. Create via File > New > Other > Maven > Maven Project




b. Check the option "Create a simple project (skip archetype selection)"



(Fig.8)


c. Set the Maven project metadata as the following.



(Fig.9)

d. use the "ctrl+a" to select all the code and copy, the stucture is in fig 6. ROUTE 2 finish.


```
<?xml version="1.0" encoding="UTF-8"?>
cproject xmlns="http://maven.apache.org/PO
                                                                                                                                         import org.junit.jupiter.api.Test
      xmlns:xsi="http://www.w3.org/2001/XML
                                                                                                                                       import static org.junit.jupiter.a
pi.Assertions.*:
Schema-instance"
      xsi:schemaLocation="http://maven.apac
he.org/POM/4.0.0
                                                                    package Samples;
http://maven.apache.org/xsd/maven-
4.0.0.xsd">
                                                                                                                                        import Samples.*:
                                                                    public class FloorSquareRoot {
  public static int floorSqrt(int x) {
    if (x == 0 || x == 1) return x;
  <modelVersion>4.0.0</modelVersion>
                                                                                                                                        public class Test001 {
                                                                                                                                           @Test
public void testA() {
  <groupId>example</groupId>
<artifactId>junit5-maven</artifactId>
                                                                                                                                              assertEquals(3, FloorSquareRo
                                                                          int start = 1, end = x, ans = 0;
while (start <= end) {
  int mid = (start + end) / 2;
  if (mid * mid == x) return mid;
  if (mid * mid < x) {
    start = mid + 1;
    start = mid + 1;
}</pre>
                                                                                                                                        ot.floorSqrt(11));
  <version>1.0</version>
  cproperties>
     <java.version>1.8</java.version>
                                                                                                                                           public void testB() {
  assertEquals(4, FloorSquareRo
      <junit-jupiter.version>5.6.2</junit-</pre>
jupiter.version>
                                                                             ans = mid;
} else {
end = mid - 1;
   </properties>
                                                                                                                                        ot.floorSqrt(20));
  <denendencies>
     <dependency>
        <groupId>org.junit.jupiter</groupId>
<artifactId>junit-jupiter-
                                                                          System.out.println("floorSqrt(" + x +
engine</artifactId>
                                                                                + ans);
        <version>${junit-
                                                                          return ans;
jupiter.version}/version>
<scope>test</scope>
                                                                       }
      </dependency>
      <dependency>
```



(Fig.10)

Import Finish. Compile and run your code with tests. (Maven is a package manager that helps you to manage the dependencies and bootstrap the execution. More details can be found at

https://maven.apache.org/guides/)




(Fig.11)

(Fig.12)

B. Upload your project to GitHub

- 1. Install eGit in Eclipse IDE.
 - a. Since Eclipse has no built-in git client, we need to install a git client in order to communicate with the Github service.
 - b. Install via Help > Install New Software...




(Fig.13)

c. Click the "Add" button to add a source repository of eGit plugin.

Name: eGit

Location: http://download.eclipse.org/egit/updates




(Fig.14)

d. Check up all the components of eGit to install.

Available Software

Check the items that you wish to install.



(Fig.15)


2. Setup RSA keys for your SSH connection

(The git protocol requires connections via HTTP or SSH. For ease of entering the username and password every time pushing the code, we choose the <u>SSH</u> connection. SSH protocol requires asymmetric cryptography to communicate. Here we choose <u>RSA</u> algorithm.)

 a. Generate via Window > Preferences > General > Network Connections > SSH2 > Key Management

Note: leave the Passphrase field to be empty to avoid entering passphrase every time you use the private key.


b. Generate RSA Key... > Copy the public key in the box > Save Private Key... > Apply and Close



(Fig.16)


- c. Setup the SSH keys in your Github account
 - i. reference: Adding a new SSH key to your GitHub account
 - ii. open https://github.com in your browser.
 - iii. click the drop-down menu of your favicon and click "Settings".
 - iv. click "SSH and GPG keys" on the left list.
 - v. click the "New SSH key" green button.
 - vi. fill in the title with any name that could be identified to you.
 - vii. fill in the key with the public that is just copied.
 - viii. click "Add SSH key" button.

SSH keys




(Fig.17)

- 3. Use the Github account registered in Week3 and create a new repository.
 - a. There are two addresses that represent your repository. We choose the **SSH one** in our tutorial. e.g., git@github.com:Wsine/cs5351.git




(Fig.18)




(Fig.19)

- 4. Configure SSH connection with eGit to your Github repository
 - a. Come back to Eclipse IDE
 - b. Open Git repository pane via Window > Show View > Other... > Git > Git Repositories




(Fig.20)

- c. Create a new local Git repository under your current JAVA project.
 - i. Right click your project and select Team > Share Project...




(Fig.21)

ii. Check up the "Use or create repository..." option > Create Repository > Finish




(Fig.22)

- d. Create a new remote to link with your Github repository. (Display may be different according to your Eclipse version)
 - i. Right click Remotes in the "Git Repositories" pane and click "Create Remote".
 - ii. Fill in the remote name with 'origin'.
 - iii. Fill in the URI that is acquired in Fig. 10. The rest fields are filled automatically.
 - iv. There is no password in SSH protocol. Leave it blank.
 - v. The user field is 'git' as it is the default user in Github platform.




(Fig.25)


- 5. Upload your local code to the remote Github repository.
 - a. Commit the code first, only select the necessary code files to upload, and then push



(Fig.26)




(Fig.27)



(Fig.28)


- C. Create Github actions workflow (Continuous Integration)
- 1. Create Github Action
 - a. Switch to the [Actions] menu item.



(Fig.29)

b. Press the [Set up this workflow] button with card title "Java with Maven"

Suggested for this repository




(Fig.30)

c. Modify the file content as the below image shown.

```
cs5351 / .github / workflows / main.yml
                                                     in main
                                                                     name: Java CI with maven
  <> Edit new file
                    Preview
                                                                     on:
                                                                       push:
                                                                          branches: [ master ]
       name: Java CI with maven
                                                                       pull_request:
                                                                         branches: [ master ]
         push:
                                                                       workflow_dispatch:
           branches: [ main ]
    6
         pull request:
                                                                     jobs:
           branches: [ main ]
    8
         workflow_dispatch:
                                                                       build:
                                                                          runs-on: ubuntu-latest
   10
                                                                          steps:
   11
         build:
                                                                          - uses: actions/checkout@v2
           runs-on: ubuntu-latest
   12
                                                                          - name: Set up JDK 1.8
   13
           steps:
   14
           - uses: actions/checkout@v2
                                                                            uses: actions/setup-java@v1
   15
           - name: Set up JDK 1.8
                                                                            with:
   16
            uses: actions/setup-java@v1
                                                                              java-version: 1.8
   17
            with:
                                                                           name: Build with Maven
   18
              java-version: 1.8
   19
           - name: Build with Maven
                                                                            run: mvn test
   20
             run: mvn test
   21
```


(Fig.31)

d. Press the [Start commit] button, choose create a new branch option, and press [Propose new file] button.




(Fig.32)

e. Press the [Create pull request] button




(Fig.33)

- 2. Inspect the process of Continuous Integration
 - a. Wait a minute to let the CI finish.
 - b. Click [Show all checks] link and then [Details] link.



(Fig.34)

c. Check the result of testing



(Fig.35)

- d. Merge this pull request as what we did in Week 3.
- e. Thereafter, every time you commit new changes, it will automatically trigger the CI.
- 3. Exercise with Continuous Integration.
 - a. try to alter the code with a bug that would fail the test cases in the Github project, submit the code to a **new branch**, make a pull request, and inspect the CI.

Example:

```
3655 [Tror: FatBul.testA:11 expected: (3) but was: (5)
3656 [Fror: TestBul.testB:16 expected: (4) but was: (6)
3657 [TRO]
3658 [Fror: TestBul.testB:16 expected: (4) but was: (6)
3659 [INFO]
3658 [INFO]
3650 [INFO]
3650 [INFO]
3651 [INFO]
3651 [INFO]
3651 [INFO]
3652 [INFO]
3653 [INFO]
3654 [INFO]
3655 [INFO]
3656 [INFO]
3656 [INFO]
3656 [INFO]
3657 [INFO]
3658 [Fror: Failed to execute goal org.apache.maven.plugins:maven-surefire-plugin:2.22.2:test (default-test) on project junit5-maven: There are test failures.
3667 [Fror: Failed to execute goal org.apache.maven.plugins:maven-surefire-plugin:2.22.2:test (default-test) on project junit5-maven: There are test failures.
3678 [Fror: Please refer to /home/runner/work/5/5/target/surefire-reports for the individual test results.
3679 [Fror: Please refer to dump files (if any exist) [date].dump, [date].dump and [date].dumpstream.
3670 [Fror: 7]
3671 [Fror: To see the full stack trace of the errors, re-run Maven with the -e switch.
3672 [Fror: Re-run Maven using the -X switch to enable full debug logging.
3673 [Fror: [Help 1]] http://wwiki.apache.org/confluence/display/MAVEN/MoiofailureException
3674 [Fror: Process completed with exit code 1.
```

(Fig.36)

- i. Do not merge the erroneous pull request.
- b. try to fix the bug on the buggy branch and inspect the retriggered CI.
 - i. If all the tests are passed, merge the pull request.

*** END ***