

Import

```
import pandas as pd
import numpy as np
from sklearn.preprocessing import PolynomialFeatures, StandardScaler

train_url = "http://s3.amazonaws.com/assets.datacamp.com/course/Kaggle/train.csv"
test_url = "http://s3.amazonaws.com/assets.datacamp.com/course/Kaggle/test.csv"

train = pd.read_csv(train_url)
test = pd.read_csv(test_url)
```

Preprocess

```
print(train.head())
print("\n")
print(train.isnull().sum())
print("\n")
print(train.shape)
```

```
PassengerId  Survived  Pclass \
0            1         0       3
1            2         1       1
2            3         1       3
3            4         1       1
4            5         0       3
```

```
              Name  Sex  Age  SibSp \
0      Braund, Mr. Owen Harris   male  22.0    1
1  Cumings, Mrs. John Bradley (Florence Briggs Th...  female  38.0    1
2    Heikkinen, Miss. Laina   female  26.0    0
3  Futrelle, Mrs. Jacques Heath (Lily May Peel)  female  35.0    1
4    Allen, Mr. William Henry   male  35.0    0
```

```
   Parch  Ticket   Fare Cabin Embarked
0     0  A/5 21171   7.2500   NaN      S
1     0   PC 17599  71.2833   C85      C
2     0 STON/O2. 3101282   7.9250   NaN      S
3     0  113803  53.1000  C123      S
4     0  373450   8.0500   NaN      S
```

```
PassengerId    0
Survived       0
Pclass         0
Name           0
Sex            0
Age          177
SibSp         0
Parch         0
Ticket        0
Fare          0
Cabin        687
Embarked      2
dtype: int64
```

```
(891, 12)
```

```
# T8
train['Age'] = train['Age'].fillna(train['Age'].mode()[0])
train['Embarked'] = train['Embarked'].fillna(train['Embarked'].mode()[0])

test['Age'] = test['Age'].fillna(train['Age'].mode()[0])
test['Embarked'] = test['Embarked'].fillna(train['Embarked'].mode()[0])

print(f"Median Age = {train['Age'].median()}")
```

```
Median Age = 24.0
```

```
# T9
train.loc[train["Embarked"] == "S", "Embarked"] = 0
train.loc[train["Embarked"] == "C", "Embarked"] = 1
train.loc[train["Embarked"] == "Q", "Embarked"] = 2

train.loc[train["Sex"] == "male", "Sex"] = 0
train.loc[train["Sex"] == "female", "Sex"] = 1

test.loc[test["Embarked"] == "S", "Embarked"] = 0
test.loc[test["Embarked"] == "C", "Embarked"] = 1
test.loc[test["Embarked"] == "Q", "Embarked"] = 2

test.loc[test["Sex"] == "male", "Sex"] = 0
test.loc[test["Sex"] == "female", "Sex"] = 1
```

Model

```
import numpy as np

features = ["Pclass", "Sex", "Age", "Embarked"]
X_raw = train[features].values

poly = PolynomialFeatures(degree=2, include_bias=False)
X_poly = poly.fit_transform(X_raw)

scaler = StandardScaler()
X_scaled = scaler.fit_transform(X_poly)

y = np.array(train["Survived"].values, dtype=float)

m = len(y)
X_b = np.c_[np.ones((m, 1)), X_scaled]

def sigmoid(z):
    return 1 / (1 + np.exp(-z))

theta = np.zeros(X_b.shape[1])

learning_rate = 0.001
iterations = 100000

for i in range(iterations):
    z = np.dot(X_b, theta)
    h = sigmoid(z)
    gradient = np.dot(X_b.T, (h - y)) / m
    theta -= learning_rate * gradient

final_scores = sigmoid(np.dot(X_b, theta))

predictions = (final_scores >= 0.5).astype(int)

accuracy = np.mean(predictions == y)
print(f"Accuracy: {accuracy * 100:.2f}%")
```

Accuracy: 82.15%

Predict

```
X_test_raw = test[features].values

X_test_poly = poly.transform(X_test_raw)
X_test = scaler.transform(X_test_poly)

m_test = len(X_test)
X_test_b = np.c_[np.ones((m_test, 1)), X_test]

test_probabilities = sigmoid(np.dot(X_test_b, theta))
test_predictions = (test_probabilities >= 0.5).astype(int)
```

```
submission = pd.DataFrame({
    "PassengerId": test["PassengerId"],
    "Survived": test_predictions
})

submission.to_csv("submission_v2.csv", index=False)

print(submission.head())
```

	PassengerId	Survived
0	892	0
1	893	0
2	894	0
3	895	0
4	896	0