

Import

```
import pandas as pd

train_url = "http://s3.amazonaws.com/assets.datacamp.com/course/Kaggle/train.csv"
test_url = "http://s3.amazonaws.com/assets.datacamp.com/course/Kaggle/test.csv"

train = pd.read_csv(train_url)
test = pd.read_csv(test_url)
```

Preprocess

```
print(train.head())
print("\n")
print(train.isnull().sum())
print("\n")
print(train.shape)
```

```
   PassengerId  Survived  Pclass \
0             1         0       3
1             2         1       1
2             3         1       3
3             4         1       1
4             5         0       3
```

```
      Name      Sex  Age  SibSp \
0  Braund, Mr. Owen Harris   male  22.0    1
1  Cumings, Mrs. John Bradley (Florence Briggs Th...  female  38.0    1
2    Heikkinen, Miss. Laina  female  26.0    0
3  Futrelle, Mrs. Jacques Heath (Lily May Peel)  female  35.0    1
4    Allen, Mr. William Henry   male  35.0    0
```

```
   Parch  Ticket   Fare Cabin Embarked
0      0   A/5 21171  7.2500   NaN      S
1      0  PC 17599 71.2833   C85      C
2      0 STON/O2. 3101282  7.9250   NaN      S
3      0  113803 53.1000  C123      S
4      0  373450  8.0500   NaN      S
```

```
PassengerId    0
Survived       0
Pclass         0
Name           0
Sex            0
Age          177
SibSp         0
Parch         0
Ticket         0
Fare          0
Cabin        687
Embarked      2
dtype: int64
```

```
(891, 12)
```

```
# T8
train['Age'] = train['Age'].fillna(train['Age'].mode()[0])
train['Embarked'] = train['Embarked'].fillna(train['Embarked'].mode()[0])

test['Age'] = test['Age'].fillna(train['Age'].mode()[0])
test['Embarked'] = test['Embarked'].fillna(train['Embarked'].mode()[0])

print(f"Median Age = {train['Age'].median()}")
```

```
Median Age = 24.0
```

```
# T9
train.loc[train["Embarked"] == "S", "Embarked"] = 0
train.loc[train["Embarked"] == "C", "Embarked"] = 1
train.loc[train["Embarked"] == "Q", "Embarked"] = 2
```

```

train.loc[train["Sex"] == "male", "Sex"] = 0
train.loc[train["Sex"] == "female", "Sex"] = 1

test.loc[test["Embarked"] == "S", "Embarked"] = 0
test.loc[test["Embarked"] == "C", "Embarked"] = 1
test.loc[test["Embarked"] == "Q", "Embarked"] = 2

test.loc[test["Sex"] == "male", "Sex"] = 0
test.loc[test["Sex"] == "female", "Sex"] = 1

```

Model

```

import numpy as np

X = np.array(train[["Pclass", "Sex", "Age", "Embarked"]].values, dtype=float)
y = np.array(train["Survived"].values, dtype=float)

m = len(y)
X_b = np.c_[np.ones((m, 1)), X]

theta = np.zeros(X_b.shape[1])

learning_rate = 0.0001
iterations = 100000

for i in range(iterations):
    h = np.dot(X_b, theta)

    gradient = np.dot(X_b.T, (h - y)) / m
    theta -= learning_rate * gradient

    gradient = np.dot(X_b.T, (h - y)) / m

    theta -= learning_rate * gradient

final_scores = np.dot(X_b, theta)

predictions = (final_scores >= 0.5).astype(int)

accuracy = np.mean(predictions == y)

print(f"Accuracy: {accuracy * 100:.2f}%")

```

Accuracy: 78.68%

Predict

```

X_test = np.array(test[["Pclass", "Sex", "Age", "Embarked"]].values, dtype=float)
m_test = len(X_test)
X_test_b = np.c_[np.ones((m_test, 1)), X_test]

test_probabilities = np.dot(X_test_b, theta)
test_predictions = (test_probabilities >= 0.5).astype(int)

submission = pd.DataFrame({
    "PassengerId": test["PassengerId"],
    "Survived": test_predictions
})

submission.to_csv("submission_v4.csv", index=False)

print(submission.head())

```

	PassengerId	Survived
0	892	0
1	893	1
2	894	0
3	895	0

4	896	1
---	-----	---