

# **CFA Application using LISREL**

# Outline

1. The software

2. The input

3. The first program

4. The first output

# The software

- There is a number of software packages (e.g. AMOS, EQS, LAVAN, LISREL, MPLUS)
- We use LISREL.
- ... it is software that fits especially well with the path diagrams
- ... it is basic and, therefore, supports the understanding of how this method works
- ... it should be easy to switch to another software afterwards

# Outline

1. The software


2. The input

3. The first program

4. The first output


# The input

- Starting LISREL by clicking the icon on the desk top leads to ...




# The input

- Starting LISREL by clicking the icon leads to ...
- Next: click on „File“ - a new window opens
- Next: click on „New“ – another window opens.




# The input

- Next: click on „OK“ – to start a new statistical investigation.



# The input

- A window opens that is to be used for providing the input for the statistical investigation.





# Outline

1. The software

2. The input


3. The first program

4. The first output

# **The first program**

In the following a first program for investigating a model of measurement (a typical confirmatory factor model) is provided.

# The to-be-investigated model



# The first program: *the input*

```
FIRST SEM MODEL
DA NI=5 NO=500 MA=CM

! A model of measurement including 5 indicators and 1 latent variable

LA
I1 I2 I3 I4 I5

CM
0.148
0.033 0.178
0.024 0.033 0.153
0.034 0.028 0.033 0.117
0.023 0.023 0.027 0.037 0.106
```

First row: title

Second row: data description

NI – number of input variables


NO – number of observations

MA – type of input data

LA row: labels for input variables

CM: the covariances to be analyzed

# The to-be-investigated model



LISREL  
Notation

VA 1 PH 1 1

FR LX 1 1

FR LX 2 1

.....

FR TD 1 1

FR TD 2 2

# The first program: the model



FIRST SEM MODEL

DA NI=5 NO=500 MA=CM

! A model of measurement including 5 indicators and 1 latent variable

LA

I1 I2 I3 I4 I5

CM

0.148

0.033 0.178

0.024 0.033 0.153

0.034 0.028 0.033 0.117

0.023 0.023 0.027 0.037 0.106

MO NX=5 NK=1 TD=FU,FI PH=FU,FI

LK

LatVariable

FR LX 1 1

FR LX 2 1

FR LX 3 1

FR LX 4 1

FR LX 5 1

VA 1 PH 1 1

FR TD 1 1

FR TD 2 2

FR TD 3 3

FR TD 4 4

FR TD 5 5

First row: name of program

Second row: data description

NI – number of input variables

NO – number of observations

MA – type of input data

LA row: labels for input variables

CM: the covariances to be analyzed

MO row: characteristics of the model

LK row: labels of latent variables

-specification of factor loadings

- specification of variance of latent variables

- specification of thetas

# The first program: the output



FIRST SEM MODEL

DA NI=5 NO=500 MA=CM

! A model of measurement including 5 indicators and 1 latent variable

LA

I1 I2 I3 I4 I5

CM

0.148

0.033 0.178

0.024 0.033 0.153

0.034 0.028 0.033 0.117

0.023 0.023 0.027 0.037 0.106

MO NX=5 NK=1 TD=FU,FI PH=FU,FI

LK

LatVariable

FR LX 1 1

FR LX 2 1

FR LX 3 1

FR LX 4 1

FR LX 5 1

VA 1 PH 1 1

FR TD 1 1

FR TD 2 2

FR TD 3 3

FR TD 4 4

FR TD 5 5

PD

OU ML SC IT=1000 ND=3

First row: name of program

Second row: data description

NI – number of input variables

NO – number of observations

MA – type of input data

LA row: labels for input variables

CM: the covariances to be analyzed

MO row: characteristics of the model

LK row: labels of latent variables

-specification of factor loadings

- specification of variance of latent variables

- specification of thetas

- request of path diagram

OU row: characteristics of output

# The first program

Start the program by clicking the “**L**”.



# Outline

1. The software


2. The input

3. The first program

4. The first output

# The first output

## PATH DIAGRAM AS OUTPUT



Important fit information (rest is given in the output)

# The first output

DATE: 10/29/2018

TIME: 10:38

LISREL 8.80

BY

Karl G. Jöreskog & Dag Sörbom

The output starts with repeating the input information.

This program is published exclusively by

Scientific Software International, Inc.

7383 N. Lincoln Avenue, Suite 100

Lincolnwood, IL 60712, U.S.A.

Phone: (800)247-6113, (847)675-0720, Fax: (847)675-2140

Copyright by Scientific Software International, Inc., 1981-2006

Use of this program is subject to the terms specified in the

Universal Copyright Convention.

Website: [www.ssicentral.com](http://www.ssicentral.com)

The following lines were read from file C:\Users\dell\Documents\Schweizer\Lisrel\_Lat

FIRST SEM MODEL

DA NI=5 NO=500 MA=CM

! A model of measurement including 5 indicators and 1 latent variable

LA

I1 I2 I3 I4 I5

CM

0.148

0.033 0.178

0.024 0.033 0.153

0.034 0.028 0.033 0.117

# The first output

## FIRST SEM MODEL

Number of Iterations = 5

LISREL Estimates (Maximum Likelihood)

LAMBDA-X

LatVaria

I1	0.160 (0.022) 7.281
I2	0.157 (0.024) 6.536
I3	0.165 (0.022) 7.386
I4	0.208 (0.020) 10.160
I5	0.165 (0.019) 8.760

## Factor loadings

## Standard errors

## $t$ statistics

PHI

LatVaria

1.000

THETA-DELTA

I1	I2	I3	I4	I5
0.122 (0.009)	0.153 (0.011)	0.126 (0.009)	0.074 (0.008)	0.079 (0.007)
13.547	14.071	13.463	9.410	11.988

There is information on parameter estimation.

# The first output

## Goodness of Fit Statistics

Degrees of Freedom = 5

Minimum Fit Function Chi-Square = 5.768 (P = 0.329)

Normal Theory Weighted Least Squares Chi-Square = 5.786 (P = 0.328)

Estimated Non-centrality Parameter (NCP) = 0.786

90 Percent Confidence Interval for NCP = (0.0 ; 11.094)

Minimum Fit Function Value = 0.0116

Population Discrepancy Function Value (F0) = 0.00158

90 Percent Confidence Interval for F0 = (0.0 ; 0.0222)

Root Mean Square Error of Approximation (RMSEA) = 0.0178

90 Percent Confidence Interval for RMSEA = (0.0 ; 0.0667)

P-Value for Test of Close Fit (RMSEA < 0.05) = 0.823

Expected Cross-Validation Index (ECVI) = 0.0517

90 Percent Confidence Interval for ECVI = (0.0501 ; 0.0723)

ECVI for Saturated Model = 0.0601

ECVI for Independence Model = 0.509

Chi-Square for Independence Model with 10 Degrees of Freedom = 244.057

Independence AIC = 254.057

Model AIC = 25.786

Saturated AIC = 30.000

Independence CAIC = 280.130

Model CAIC = 77.932

Saturated CAIC = 108.219

Normed Fit Index (NFI) = 0.976

Non-Normed Fit Index (NNFI) = 0.993

Parsimony Normed Fit Index (PNFI) = 0.488

Comparative Fit Index (CFI) = 0.997

Incremental Fit Index (IFI) = 0.997

Relative Fit Index (RFI) = 0.953

Critical N (CN) = 1306.293

Root Mean Square Residual (RMR) = 0.00335

Standardized RMR = 0.0222

Goodness of Fit Index (GFI) = 0.995

Adjusted Goodness of Fit Index (AGFI) = 0.986

Parsimony Goodness of Fit Index (PGFI) = 0.332

There is information  
on model fit.

The fit statistics  
indicate that there is  
good model fit.

**The end**