Μονοπάτης Δημήτριος 4776

## Άσκηση [1]

Λίστα τροποποιηθέντων αρχείων

/usr/src/servers/vfs/stadir.c

Τροποποιήσεις

/usr/src/servers/vfs/stadir.c

Line	Code
92	printf("Current dir -> ");
93	printf(fullpath);
94	printf("\n");

# Screenshots αποτελεσμάτων

```
-bash-4.2# pwd
/root/mydir
-bash-4.2# cd ..
Current dir -> /root
-bash-4.2# _
```

# Άσκηση [2]

# Λίστα τροποποιηθέντων αρχείων

/usr/src/lib/libc/sys-minix/chdir.c /usr/include/minix/callnr.h /usr/src/servers/vfs/stadir.c /usr/src/servers/vfs/table.c /usr/src/servers/vfs/proto.h /usr/src/commands/ash/cd.c

## Τροποποιήσεις

#### /usr/include/minix/callnr.h

Line	Code	
68	#define MY_CHDIR	69

### /usr/src/servers/vfs/table.c

Line	Code
87	do_my_chdir

### /usr/src/servers/vfs/proto.h

Line	Code	
304	_PROTOTYPE(int do_my_chdir, (void)	);

#### /usr/src/servers/vfs/stadir.c

```
Code
Line
59-64
              PUBLIC int do_my_chdir()
              /* Perform the chdir(name) system call. */
               return my_change(&fp->fp_wd, m_in.name, m_in.name_length);
106-133
              PRIVATE int my_change(iip, name_ptr, len)
              struct vnode **iip;
                                           /* pointer to the inode pointer for the dir */
              char *name_ptr;
                                           /* pointer to the directory name to change to */
              int len:
                                   /* length of the directory name string */
              /* Do the actual work for chdir() and chroot(). */
               struct vnode *vp;
               struct vmnt *vmp;
               char fullpath[PATH MAX];
               struct lookup resolve;
               int r;
               lookup_init(&resolve, fullpath, PATH_NOFLAGS, &vmp, &vp);
               resolve.l_vmnt_lock = VMNT_READ;
               resolve.l_vnode_lock = VNODE_READ;
               /* Try to open the directory */
               if (fetch_name(name_ptr, len, M3, fullpath) != OK) return(err_code);
               if ((vp = eat_path(&resolve, fp)) == NULL) return(err_code);
               printf("Current dir -> ");
               printf(fullpath);
               printf("\n");
               r = change_into(iip, vp);
               unlock vnode(vp);
               unlock_vmnt(vmp);
               put_vnode(vp);
               return(r);
```

#### /usr/src/commands/ash/cd.c

Line	Code
206	if (updatepwd(badstat ? NULL : dest) $< 0 \parallel$ my_chdir(curdir) $< 0$ ) {
219	if (my_chdir(dest) < 0    updatepwd(NULL) < 0) {