

SQL queries.

-- Loading the dataset

```
SELECT *  
FROM indian_crime_dataset
```

-- Checking the dataset

```
PRAGMA table_info(indian_crime_dataset)
```

-- Checking total ROWS

```
SELECT count(*)  
FROM indian_crime_dataset
```

-- Checking Null VALUES

```
SELECT  
    SUM(CASE WHEN date_reported IS NULL THEN 1 ELSE 0 END) AS  
null_date_reported,  
    SUM(CASE WHEN date_of_occurrence IS NULL THEN 1 ELSE 0 END) AS  
null_date_of_occurrence,  
    SUM(CASE WHEN time_of_occurrence IS NULL THEN 1 ELSE 0 END) AS  
null_time_of_occurrence,  
    SUM(CASE WHEN city IS NULL THEN 1 ELSE 0 END) AS null_city,  
    SUM(CASE WHEN crime_description IS NULL THEN 1 ELSE 0 END) AS  
null_discription,  
    SUM(CASE WHEN victim_age IS NULL THEN 1 ELSE 0 END) AS null_age,  
    SUM(CASE WHEN victim_gender IS NULL THEN 1 ELSE 0 END) as null_gender,  
    SUM(CASE WHEN weapon_used IS NULL THEN 1 ELSE 0 END) AS null_weapon,  
    SUM(CASE WHEN case_closed IS NULL THEN 1 ELSE 0 END) AS null_case_result  
FROM indian_crime_dataset
```