

Computer System Design & Application

计算机系统设计与应用A

陶伊达 (TAO Yida)

taoyd@sustech.edu.cn




Lecture 4

- Streams API
- Optional<T>

Java Stream API Overview

```
public interface Stream<T>
```

- The Stream API is introduced in Java 8 (java.util.stream), **don't confuse it with I/O Streams!**
- Used to process collections of objects
 - Data stream is obtained from a **source**
 - Data stream is processed through chained **intermediate operations** (pipeline)
 - Getting the result from a **terminal operation**



Create a Stream

`default Stream<E> stream()`

Returns a sequential Stream with this collection as its source.

- Approach I: getting a Stream from a Java Collection, which has the `stream()` method

```
List<String> list = new ArrayList<String>();
```

```
list.add("a");
```

```
list.add("b");
```

```
Stream<String> stream = list.stream();
```

Create a Stream `static <T> Stream<T> generate(Supplier<T> s)`

- Approach II: using `Stream.generate()`, which needs a `Supplier` as input

```
Stream<String> echos = Stream.generate(() -> "Echo");
```

```
Stream<Double> randoms = Stream.generate(Math::random);
```

Could generate infinite streams

Create a Stream

```
static <T> Stream<T> of(T... values)
```

- Approach III: using `Stream.of()`, which has a varargs parameter (take any number of arguments)

```
Integer[] array = new Integer[]{1,2,3};  
Stream<Integer> istream = Stream.of(array);
```

```
Stream<String> sentence = Stream.of("This","is","Java","2");
```

What about `int[]`?

Working with int[]

- How to convert int[] to List<Integer>?

ORACLE Java Bug Database

Oracle Technology Network > Java > Java SE > Community > Bug Database

JDK-4993464 : Autoboxing on 1.5b1 does not work with Arrays.asList

Type: Bug	Priority: P4	Submitted: 2004-02-12
Component: specification	Status: Closed	Updated: 2004-06-04
Sub-Component: language	Resolution: Not an Issue	Resolved: 2004-06-04
Affected Version: 5.0	OS: windows_xp	
	CPU: x86	

```
int[] ints = new int[]{1,2,3,4,5};  
List<Integer> list1 = Arrays.stream(ints).boxed().toList();  
List<Integer> list2 = IntStream.of(ints).boxed().toList();
```

EVALUATION

Autoboxing of entire arrays is not specified behavior, for good reason.
It can be prohibitively expensive for large arrays.

###@###,### 2004-06-03

https://bugs.java.com/bugdatabase/view_bug.do?bug_id=4993464

Primitive Type Streams

- The stream library has specialized types `IntStream`, `LongStream`, and `DoubleStream` that store primitive values directly, without using wrappers (e.g., `Integer`).

```
IntStream stream = IntStream.of(1,2,3,5,8);
```

```
IntStream stream2 = IntStream.range(5,10);
```

```
Stream<String> sentences = Stream.of("This","is","Java","2");  
IntStream stream3 = sentences.mapToInt(String::length);
```


Intermediate Operations

- Intermediate (non-terminal) operations transform or filter the elements in the stream
 - `filter()`
 - `map()`
 - `sorted()`
 - `distinct()`
 - `peek()`, `limit()`, `skip()`
- We get a new stream back as the result when adding an intermediate operation to a stream
- [Lazy evaluation] All intermediate operations do not get executed until a terminal operation is invoked (discussed later)

filter()

`Stream<T> filter(Predicate<? super T> predicate)`

`Predicate<T>`

`boolean test(T t)`

The `Predicate` interface represents functions who take an argument and return a boolean

- Returns a stream consisting of the elements of this stream that match the given predicate.

```
List<Integer> list = Arrays.asList(10, 20, 33, 43, 54, 68);  
list.stream()  
    .filter(element -> (element % 2 == 0))  
    .forEach(element -> System.out.print(element + " "));
```

map()

`<R> Stream<R> map(Function<? super T,? extends R> mapper)`

`Function<T,R>`

`R apply(T t)`

The `Function` interface represents functions whose result and argument types could differ

- Returns a stream consisting of the results of applying/mapping the given function to the elements of this stream.

```
List<String> strList = new ArrayList<String>();  
strList.add("123");  
strList.add("456");
```

```
strList.stream() Stream<String>  
    .map(Integer::parseInt) Stream<Integer>  
    .forEach(System.out::println);
```

distinct()

- Returns a stream consisting of the distinct elements (removing duplicates and keeping only one of them)

```
List<String> strList = new ArrayList<String>();  
strList.add("apple");  
strList.add("orange");  
strList.add("banana");  
strList.add("apple");
```

```
List<String> result = strList.stream()  
    .distinct()  
    .collect(Collectors.toList());
```

sorted()

- `sorted()`: sort the elements by natural order
`list.stream().sorted().forEach(System.out::println)`
- `sorted(Comparator<? super T> comparator)`: sort the elements according to the given Comparator

```
class Point
{
    Integer x, y;
    Point(Integer x, Integer y) {
        this.x = x;
        this.y = y;
    }
}
```

} `Point's toString() is omitted here`

```
aList.stream()
    .sorted((p1, p2)->p1.x.compareTo(p2.x))
    .forEach(System.out::println);
```

Example: <https://www.geeksforgeeks.org/stream-sorted-in-java/>

Stream Pipeline/Chain Example

- A stream pipeline consists of a stream source, followed by **zero or more** intermediate operations, and a terminal operation.

```
List<Integer> ilist = Arrays.asList(1,2,3,4,5,6,7,8,9);  
ilist.stream()  
    .filter(element -> (element % 2 == 1))  
    .limit(3)  
    .map(element -> (element*element))  
    .forEach(System.out::println);
```

Terminal Operation

anyMatch()
allMatch()
noneMatch()
collect()
count()
findAny()
findFirst()
forEach()
min()
max()
reduce()
toArray()

- A terminal operation marks the end of the stream and is always the last operation in the stream pipeline
- A terminal operation returns a non-stream type of result
 - Return primitive type (count())
 - Return reference type (collect())
 - Return void (forEach())
- [Eager execution] Terminal operations are early executed (later)

The `Predicate` interface represents functions who take an argument and return a boolean

`anyMatch()` `Predicate<T>` `boolean test(T t)`

`boolean anyMatch(Predicate<? super T> predicate)`

- Returns whether any elements of this stream match the provided predicate (check whether any element in list satisfies a given condition)

```
boolean x = sList.stream().anyMatch((value) -> { return value.startsWith("Java"); });
```

```
boolean x = sList.stream().anyMatch(str -> Character.isUpperCase(str.charAt(1)));
```


findFirst()

- Returns an `Optional` describing the first element of this stream, or an empty `Optional` if the stream is empty

```
List<String> stringList = new ArrayList<String>();

stringList.add("one");
stringList.add("two");
stringList.add("three");

Stream<String> stream = stringList.stream();
Optional<String> result = stream.findFirst();

System.out.println(result.orElse("unknown"));
```

Collecting Results

```
Stream<String> stream = Stream.of("a", "bb", "cc", "ddd");
```

- When you are done with a stream, you often want to collect the result in a data structure

```
String[] result = stream.toArray(String[]::new)
```

- The Collectors class provides a set of factory methods for common collectors

```
List<String> result = stream.collect(Collectors.toList())
```

```
Set<String> result = stream.collect(Collectors.toSet())
```

```
TreeSet<String> result = stream.collect(Collectors.toCollection(TreeSet::new))
```

Common methods of Collectors

```
Stream<String> stream = Stream.of("a", "bb", "cc", "ddd");  
Map<String, Integer> map = stream.collect(Collectors.toMap(Function.identity(), String::length));
```

{bb=2, cc=2, a=1, ddd=3}

```
Stream<String> stream = Stream.of("a", "bb", "cc", "ddd");  
String joined = stream.collect(Collectors.joining("$"));
```

a\$bb\$cc\$ddd

```
Stream<String> stream = Stream.of("a", "bb", "cc", "ddd", "a", "bb");  
Map<String, Long> group = stream.collect(Collectors.groupingBy(Function.identity(), Collectors.counting()));
```

{cc=1, bb=2, a=2, ddd=1}

```
Stream<String> stream = Stream.of("a", "bb", "cc", "ddd", "a", "bb", "eee");  
Map<Integer, Set<String>> group = stream.collect(Collectors.groupingBy(String::length, Collectors.toSet()));
```

{1=[a], 2=[bb, cc], 3=[eee, ddd]}

```
Stream<String> stream = Stream.of("1a", "1bb", "1c", "2a", "2a", "2bb");  
Map<Character, Set<String>> group = stream.collect(Collectors.groupingBy(s->s.charAt(0),  
Collectors.mapping(s->s.substring(1), Collectors.toSet())));
```

{1=[bb, a, c], 2=[bb, a]}

Reduction

- A reduction is a terminal operation that aggregates a stream into a type or a primitive
- Reduction operations in Java Stream API
 - `min()`
 - `max()`
 - `average()`
 - `sum()`
 - `reduce()`: <- the general one

BinaryOperator<T> T apply(T t1, T t2)

reduce()

Optional<T> reduce(BinaryOperator<T> accumulator)


Next element: e.g., the next number in the stream

reduce((a, b) -> a + b)

Partial result: e.g., the sum of all processed numbers so far

Accumulator function: e.g., add two numbers

reduce() Example I



reduce() Example I

- To avoid the exception potentially thrown by get(), you may use:

```
int sum = arrayList.stream().reduce((a,b)->a+b).orElse(0);
```

```
int sum = arrayList.stream().reduce(0, (a,b)->a+b);
```



The identity element is both the initial value of the reduction and the default result if there are no elements in the stream

reduce() Example II

What's the output?

```
List<String> words = Arrays.asList("Java", "Python", "C", "C++", "JavaScript");  
  
String x = words.stream()  
    .reduce((word1, word2) -> word1.length() > word2.length() ? word1 : word2)  
    .orElse("");  
  
System.out.println(x);
```


Lazy Evaluation

Intermediate operations are lazily executed

- They only remember the operations, but don't do anything right away (lazy)

Benefits?

Terminal operations are eagerly executed

- When terminal operations are initiated, the remembered operations are performed one by one (eager)

Example


How many operations do we have to perform when the code is executed eagerly / lazily?

```
List<String> names = Arrays.asList("Brad", "Kate", "Kim", "Jack", "Joe", "Mike",  
"Susan", "George", "Robert", "Julia", "Parker", "Benson");  
  
final String firstNameWith3Letters = names.stream()  
    .filter(name -> length(name) == 3)  
    .map(name -> toUpper(name))  
    .findFirst()
```

Reference: https://blog.csdn.net/dm_vincent/article/details/40503685

```
List<String> names = Arrays.asList("Brad", "Kate", "Kim", "Jack", "Joe", "Mike",  
"Susan", "George", "Robert", "Julia", "Parker", "Benson");
```


Eager Execution



http://blog.csdn.net/dm_vincent/article/details/40503685 15 operations total

Lazy Execution

```
List<String> names = Arrays.asList("Brad", "Kate", "Kim", "Jack", "Joe", "Mike",  
"Susan", "George", "Robert", "Julia", "Parker", "Benson");
```



filter() finds the first matching element and pass it to map()

filter() and map() are executed only when findFirst() is called

The calculation terminates as long as we get the result.



Lecture 4

- Streams API
- Optional<T>

Tired of Null Pointer Exceptions? Consider Using Java SE 8's "Optional"!

by Raoul-Gabriel Urma
Published March 2014

Make your code more readable and protect it against **null pointer exceptions**.

SIMPLY EXPLAINED




NullPointerException

```
janv. 10, 2018 10:45:29 AM org.apache.catalina.core.StandardWrapperValve invoke
GRAVE: "Servlet.service()" pour la servlet cs a g n r  une exception
java.lang.NullPointerException
    at dao.ProduitDaoImpl.ProduitsParMC(ProduitDaoImpl.java:49)
    at web.ControleurServlet.doPost(ControleurServlet.java:47)
    at web.ControleurServlet.doGet(ControleurServlet.java:28)
    at javax.servlet.http.HttpServlet.service(HttpServlet.java:622)
    at javax.servlet.http.HttpServlet.service(HttpServlet.java:729)
    at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:230)
    at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:165)
    at org.apache.tomcat.websocket.server.WsFilter.doFilter(WsFilter.java:52)
    at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:192)
    at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:165)
    at org.apache.catalina.core.StandardWrapperValve.invoke(StandardWrapperValve.java:198)
    at org.apache.catalina.core.StandardContextValve.invoke(StandardContextValve.java:96)
    at org.apache.catalina.authenticator.AuthenticatorBase.invoke(AuthenticatorBase.java:474)
    at org.apache.catalina.core.StandardHostValve.invoke(StandardHostValve.java:140)
    at org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:79)
    at org.apache.catalina.valves.AbstractAccessLogValve.invoke(AbstractAccessLogValve.java:624)
    at org.apache.catalina.core.StandardEngineValve.invoke(StandardEngineValve.java:87)
    at org.apache.catalina.connector.CoyoteAdapter.service(CoyoteAdapter.java:349)
    at org.apache.coyote.http11.Http11Processor.service(Http11Processor.java:783)
    at org.apache.coyote.AbstractProcessorLight.process(AbstractProcessorLight.java:66)
    at org.apache.coyote.AbstractProtocol$ConnectionHandler.process(AbstractProtocol.java:798)
    at org.apache.tomcat.util.net.NioEndpoint$SocketProcessor.doRun(NioEndpoint.java:1434)
    at org.apache.tomcat.util.net.SocketProcessorBase.run(SocketProcessorBase.java:49)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(Unknown Source)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(Unknown Source)
    at org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
    at java.lang.Thread.run(Unknown Source)
```

Prevent Null Pointer Exception (NPE)

Works, but hard to read!



```
String version = "UNKNOWN";
if(computer != null){
    Soundcard soundcard = computer.getSoundcard();
    if(soundcard != null){
        USB usb = soundcard.getUSB();
        if(usb != null){
            version = usb.getVersion();
        }
    }
}
```

`String version = computer.getSoundcard().getUSB().getVersion();`

<https://www.oracle.com/technical-resources/articles/java/java8-optional.html>

The Optional<T> class

- Purpose: a type-level solution for representing optional values instead of null references
- A container object which may or may not contain a non-null value (safe alternative for "object or null")
- Help us to specify alternative values to return or alternative actions to take if the value is null, without having to use null checkers

`Optional<String> optionalString = ... // the value could be null (e.g., user input)`

```
String result = optionalString.orElse("");  
String result = optionalString.orElseGet(() -> System.getProperty("user.dir"));  
String result = optionalString.orElseThrow(IllegalStateException::new);
```

[https://horstmann.com/corejava/livelessons2/lesson02/index.html#\(23\)](https://horstmann.com/corejava/livelessons2/lesson02/index.html#(23))

Creating Optional Values

```
public final class Optional<T>  
    extends Object
```

```
static <T> Optional<T> empty()
```

Returns an empty `Optional` instance.


```
static <T> Optional<T> of(T value)
```

Returns an `Optional` with the specified present non-null value.

```
static <T> Optional<T> ofNullable(T value)
```

Returns an `Optional` describing the specified value, if non-null, otherwise returns an empty `Optional`.

Example



```
class Computer {  
    private Optional<Soundcard> soundcard;  
  
    public Optional<Soundcard> getSoundcard() {  
        return soundcard;  
    }  
  
    public void setSoundcard(Optional<Soundcard> soundcard) {  
        this.soundcard = soundcard;  
    }  
}
```

```
class Soundcard {  
    private Optional<USB> usb;  
  
    public void setUSB(Optional<USB> usb) {  
        this.usb = usb;  
    }  
  
    public Optional<USB> getUSB() {  
        return usb;  
    }  
}  
  
class USB{  
    String version;  
  
    public String getVersion() {  
        return version;  
    }  
  
    public void setVersion(String version) {  
        this.version = version;  
    }  
}
```

Example

```
public static String getUsbVersion(Computer computer) {  
    return computer.getSoundcard().Optional<Soundcard>  
        .flatMap(e -> e.getUsb()) Optional<USB>  
        .map(e -> e.getVersion()) Optional<String>  
        .orElse( other: "UNKNOWN");  
}
```

OR

```
public static String getUsbVersion(Computer computer) {  
    return computer.getSoundcard().Optional<Soundcard>  
        .flatMap(Soundcard::getUsb) Optional<USB>  
        .map(USB::getVersion) Optional<String>  
        .orElse( other: "UNKNOWN");  
}
```

1.0
UNKNOWN
UNKNOWN

TAO Yida@

```
public static void main(String[] args) {  
    USB usb = new USB();  
    usb.setVersion("1.0");  
  
    Soundcard soundcard1 = new Soundcard();  
    soundcard1.setUsb(Optional.of(usb));  
    Soundcard soundcard2 = new Soundcard();  
    soundcard2.setUsb(Optional.empty());  
  
    Computer computer1 = new Computer();  
    computer1.setSoundcard(Optional.of(soundcard1));  
  
    Computer computer2 = new Computer();  
    computer2.setSoundcard(Optional.of(soundcard2));  
  
    Computer computer3 = new Computer();  
    computer3.setSoundcard(Optional.empty());  
  
    System.out.println(getUsbVersion(computer1));  
    System.out.println(getUsbVersion(computer2));  
    System.out.println(getUsbVersion(computer3));  
}
```

flatMap vs map

```
public <U> Optional<U> map(Function<? super T,? extends U> mapper)
```

```
public <U> Optional<U> flatMap(Function<? super T,Optional<U>> mapper)
```

```
public static String getUsbVersion(Computer computer) {  
    return computer.getSoundcard() Optional<Soundcard>  
        .flatMap(Soundcard::getUsb) Optional<USB>  
        .map(USB::getVersion) Optional<String>  
        .orElse( other: "UNKNOWN");  
}
```

- Soundcard::getUsb returns `Optional<USB>`
- If using `map()`, we'll get `Optional<Optional<USB>>`, but we need to invoke `USB.getVersion()`
- If your function already returns an `Optional`, use `flatMap()` which doesn't double wrap it

```
public static String getUsbVersion(Computer computer) {  
    return computer.getSoundcard() Optional<Soundcard>  
        .map(Soundcard::getUsb) Optional<Optional<USB>>  
        .map(USB::getVersion) Optional<U>  
        .orElse( other: "UNKNOWN");  
}
```

Next Lecture

- I/O Streams
- Character Encoding