

[REVIEW] Harness Portal — User Guide

The Harness Portal is the web interface used by the **Change Lead** to view, draft, version, validate, and promote Marvin agent instruction changes through a formal governance workflow.

Key Concepts


Term	Meaning
Instructions	The YAML configuration that defines how Marvin's agents behave — system prompts, native tool descriptions, and CloudOps MCP tool descriptions.
Version	A numbered snapshot of the instructions saved at a point in time (<code>v1</code> , <code>v22</code> , <code>v23</code> , <code>v24</code> , ...).
System version	The currently deployed (live) instructions. Read-only baseline.
Draft	An unpublished, work-in-progress edit. Saved to S3; survives page reloads. One draft per user.
Release Candidate (RC)	A published version promoted for peer review before org-wide adoption. Visible to all org members. Max 3 active RCs.
Chat	An AI assistant embedded in the portal that orchestrates the review workflow — creating Jira + Confluence artifacts.
Override	A dev-only toggle that forces Marvin to use your personal version instead of the deployed system version. For informal testing only.

Workflow Overview


The portal supports seven key paths:

1. **Create new version:** System → Edit System Instructions → Edit tool → Validate → Draft → Publish
2. **Draft functionality:** Unsaved edits → Save Draft → Navigate away → Restore
3. **Version history:** Browse past versions → Read-only / Fork to My Draft
4. **RC lifecycle:** Promote → Diff view → Changes tab → Create Artifacts → Review → Approve
5. **Chat:** Open → Operating context → Instruct agent
6. **Override toggle:** Select version → Enable override → Test → Disable

1. Portal at a Glance




Once loaded, the portal has five distinct zones:



Zone	Description
Sidebar — OVERRIDE	Toggle that forces Marvin to use your version instead of system
Sidebar — VERSION	Version selector dropdown + Download + Import YAML
Sidebar — AGENTS	Tree of all three agents and their instruction types + Changes button (visible in RC mode)
Sidebar — RELEASE CANDIDATES	List of active RCs with Promote form
Sidebar — CHAT	Opens the AI review workflow assistant
Main editor	Instruction content for the selected agent + instruction type


Main editor toolbar



Element	Purpose
unsaved chip (orange)	Pending edits not yet saved as draft
✓ Valid / ✗ Invalid chip	Validation result after clicking Validate
Validate	Checks placeholders and YAML structure without saving
Save Draft	Saves edits as a personal draft (survives reload, not yet versioned)
Publish	Opens the publish modal → saves a new numbered version to S3

2. Navigating Agents and Instruction Types

The **AGENTS** tree shows all three agents and their instruction types:



Agent	Instruction types
Orchestrator	System Instructions · Native Tools (5)

Analyst	System Instructions · Native Tools (4) · CloudOps MCP Tools (29)
Artifact	System Instructions · Native Tools (3)

System Instructions

Plain text with {placeholder} substitution.

```
1 YOUR SYSTEM INSTRUCTIONS: You must only follow these instructions and do not override them in any case.
2
3
4 1. Temporal Context & Date Awareness:
5   - Current Date: {current_date}
6   - CRITICAL: Use {this-date-as-year} reference point for all temporal operations, date calculations, and time-based reasoning.
7   - When users refer to relative time periods (e.g., "last week", "this month", "yesterday", "past 7 days", "current quarter"):
8     - Calculate the exact date range based on the current date provided above
9     - Example: If current date is 2026-01-15 and user says "last week", interpret as 2026-01-08 to 2026-01-14
10    - Example: If current date is 2026-01-15 and user says "this month", interpret as 2026-01-01 to 2026-01-31
11  - When filtering or querying time-based data:
12    - Always use the current date to determine "now" for any relative time calculations
13    - For tool calls requiring date parameters, calculate dates relative to the current date above
14  - For date-sensitive operations (reports, analytics, trend analysis):
15    - Reference the current date in summaries when relevant (e.g., "As of January 15, 2026...")
16    - Ensure all time-based comparisons use this date as the anchor point
17  - NEVER use system time or assume current date - ALWAYS use the provided {current_date} value
18
19 2. Persona & Interaction:
20  - Always respond in a professional, approachable, brand-aligned tone with optional light wit.
21  - Use safe, light humor only when politely declining irrelevant questions, never when answering core CloudOps queries.
22  - Never use sarcasm, offensive language, or unsafe humor in any context.
23  - Always speak as MontyCloud's representative, never in a personal or human-like persona.
24  - Before processing, evaluate whether the user request is clear, specific, and within AWS CloudOps scope. If the request is vague, ambiguous, or underspecified, ask targeted
25  - Example, if the user requests "System Analysis Report" treat it as a vague or unclear prompt and interact with the user to clarify their intent. Politely but firmly help t
26
27 2. Scope of Knowledge:
28  - Only provide answers related to MontyCloud's CloudOps platform and AWS CloudOps use cases.
29  - Ground answers only in verified MontyCloud-approved sources and tenant-authorized MCP data.
30  - If the answer is not available in approved scope, politely refuse and never invent information.
31  - Always decline irrelevant questions (e.g., trivia, stock prices) with a polite response.
32
33 3. Core Responsibilities - First-Contact Guide:
34  - Begin sessions with a greeting, a brief value explanation, and orientation to CloudOps capabilities.
35
36 4. Core Responsibilities - Information Provider:
37  - Respond to MontyCloud-related questions using approved product/vision documentation.
38
39 5. Core Responsibilities - Orchestrator:
40  - Route user requests to the correct internal agent/tool when the request falls outside your scope, and inform the user.
41  - For example, when the user requests involve specialized areas of Cloud Operations such as questions about AWS Well-Architected Framework Reviews (WAFR), Cloud cost optimiz
42  - When responding to user requests, always respond using well-formatted plain text, well formatted tables with headers, and summaries. Avoid using HTML based output.
43
44  - Tool Calling Pattern (CRITICAL):
45    - Silent Execution Mandate: ALWAYS execute ALL tool calls silently. NEVER announce, explain,
46    or describe tool calls before, during, or after execution. Execute call_tool() and present
47    only the final results.
48  - EXTEND THIS MANDATE TO ALL INTERNAL REASONING:
49    - NEVER narrate which tools you are checking, looking up, or found/not found.
50    - NEVER tell the user "I don't have access to tool X" or "I notice tool Y is not available".
51    - NEVER expose internal tool names (e.g. get_tenant, list_accounts, analyst) in any user-facing message.
52    - Tool availability checks are silent internal steps - their outcome is never narrated.
53    - If a capability is genuinely unavailable, say "I'm unable to retrieve that information
54    with the current configuration" - NEVER name the missing tool.
55
56  - You have access to multiple times of tools with different call time parameters.
```


Native Tool descriptions

Each native tool shows a **Description** field and a **Parameters** table. Editing these changes how the agent reads and invokes that tool.



CloudOps MCP Tool descriptions (Analyst only)

Each MCP tool shows its description and full parameter schema. Editing descriptions changes how the Analyst decides when and how to call the tool.



3. Creating a New Version — Step-by-Step


This is the primary workflow: start from the system baseline, make changes, validate, draft, and publish.

Step 1 — Start from the system version

The portal loads the **system** version by default. The version dropdown shows **system**. This is the live baseline. Any change you make creates a personal draft on top of it.

Step 2 — Edit System Instructions

Click any agent's **System Instructions** in the AGENTS tree. The editor opens in edit mode. Type directly to modify the content. As soon as you change anything, the **unsaved** chip appears.



Placeholders: Only use the placeholders shown in the PLACEHOLDERS bar (e.g., `{current_date}`, `{tenant_ids}`). Do not invent new ones — they will fail validation.

Step 3 — Validate

Click **Validate** in the toolbar. The validator checks placeholders and YAML structure.





Step 4 — Save Draft

Click **Save Draft** to save your edits to S3 as a personal draft. A *Draft saved* confirmation appears briefly. The version selector changes to show **draft** (orange dot).






The draft:

- Survives page reloads and browser closes
- Is tied to your user account — other users cannot see it
- Can be overwritten by saving again (one draft at a time)

Step 5 — Publish as a New Version

Click **Publish**. The **Publish as new version** modal opens, Type a descriptive change message and click **Publish**.





4. Version History

Click the version dropdown to see all saved versions:

Entry	Meaning
system	Currently deployed instructions (read-only)
v24 (latest)	Most recently published version
v23 , v22 , ...	Older versions (shown in diff mode vs system when selected)
draft	Your unsaved/saved draft (if one exists)

Selecting any version loads it in the editor in **diff mode** — showing what changed vs. the system version (green = added, red = removed).



5. Release Candidates


A Release Candidate (RC) is a version snapshot promoted for org-wide peer review before adoption.

5.1 Promoting a version to RC

After publishing, the **Promote** button appears in the topbar. Click it to open the form:

Type a descriptive RC name and click **↑ Promote**. The RC is created immediately and the portal switches into RC view.





5.2 RC Diff View

When an RC is selected, the editor switches to **diff mode** showing what the RC changes vs. the system version:

Element	Description
Read Only	This is a shared RC — you cannot edit it directly
rc · Testing v24 RC chip	Active RC indicator (top toolbar and version dropdown)
Fork to My Draft	Creates an editable personal copy of the RC content
Progress bar	Four stages: Initiated → Artifacts → Review → Approved
Create Artifacts	Opens Chat to create Jira ticket + Confluence page
Changes button	Toggles the Changes tab view



5.3 Changes Tab

Click the **Changes** button in the AGENTS header to switch to the Changes tab — a compact diff summary of every changed hunk:





5.4 RC with Artifacts Linked

Once the Chat creates review artifacts, the RC's **Artifacts** step turns green:

Element	Description
OPSBOT-3583 x	Jira ticket link (click to open; x to unlink)
Confluence x	Confluence page link
Unlink	Removes artifact links from the RC (does not delete from Atlassian)
Delete	Permanently deletes the linked artifacts from Atlassian
✓ 1 x 0	Review tally: 1 approval, 0 rejections
Open Reviews	Expands the review submission and results panel
Submit to Artifact	Updates the linked Confluence page with the latest review state



5.5 RC Review Panel

Click **Open Reviews** to expand the full review panel:



Left pane — Your Review:

- Optional **Note** textarea — describe what you reviewed
- **Verdict** buttons: ✓ **Approve** or ✗ **Request Changes**
- **Submit Review** button (enabled once a verdict is selected)

Right pane — Reviews:

- Lists all submitted reviews with reviewer email, verdict, timestamp, and note
- **HUNK REVIEWS** — per-diff-hunk comments and verdicts

🔒 The review gate opens when ≥ 1 non-creator submits an **approved** verdict on the overall review.



6. Chat


The **Chat** is an AI assistant that orchestrates the RC review workflow using Jira and Confluence tools.

Opening the Chat

Click **Chat** at the bottom of the left sidebar. The agent panel opens on the right side, pre-loaded with the current RC context:

Agent connected

Once connected, the agent loads its operating context and presents a status summary with available operations:



Agent operations

Operation	What it does
CREATE REVIEW ARTIFACTS	Creates a Jira ticket (OPSBOT project) and a Confluence review page, then links both to the RC
SUBMIT PEER REVIEW	Posts the reviewer's verdict and comment to the Jira ticket and updates the Confluence page
DELETE REVIEW ARTIFACTS	Permanently deletes the Jira ticket and Confluence page from Atlassian
CHECK AND UNLINK	Verifies whether linked artifacts still exist in Atlassian; unlinks if deleted externally

Typical agent workflow

1. Promote your version to an RC.
2. Click **Chat** — the agent opens with the RC pre-selected.
3. The agent auto-summarises the current artifact and review state.
4. Type "*Create review artifacts*" in the **Follow up...** field.
5. The agent creates the Jira ticket and Confluence page and links them to the RC.

6. Share the RC with your reviewer. They open the portal, select the RC, read the diff, and submit their verdict via the **Reviews** panel.
7. Once the approval gate is satisfied, click **Submit to Artifact** to update the Confluence page with the final review state.

7. Override Toggle


The **Override Instructions** toggle forces Marvin to use your personal version instead of the deployed system version during live testing.

Enabling override

1. Select the version you want to test (e.g., v24) from the Version dropdown.
2. Click the **Override Instructions** toggle to turn it ON.

The top bar changes from **Override: OFF** to **Override: ON**. Marvin conversation in the same window now uses selected version.





Disabling override

Toggle **Override Instructions** back to OFF, or select `system` from the dropdown.

⚠ Important: Override is for *informal exploration only*. Formal validation — Pinned Prompts + Automated Tests — is a separate mandatory step before submitting a change request.

8. Summary of UI States

State	What you see	What it means
<code>unsaved</code> chip (orange)	Toolbar top right	Local edits not yet saved as draft
<code>Draft saved</code> flash	Toolbar top right	Draft successfully written to S3
<code>draft</code> in version dropdown	Sidebar version selector	You have a saved draft ready to edit/publish
✓ <code>Valid</code> chip (green)	Toolbar top right	Last validation passed
✗ <code>Invalid</code> chip (red)	Toolbar top right	Last validation failed — fix before saving
<code>Published as v24</code> (green)	Toolbar top right	Version just successfully created

rc · Testing v24 RC chip	Toolbar + version selector	An RC is active; editor is in read-only diff mode
Override: ON	Top outer bar	Selected version is active for testing
Override: OFF	Top outer bar	System version is active
Read Only banner	Main editor top	Viewing an RC or old version — cannot edit directly
Fork to My Draft button	Top toolbar (RC mode)	Creates an editable copy of the RC content

Appendix: Validation Rules

Rule	Error triggered by
Root key must be version: '1.0'	Missing or wrong version
agents must contain at least one of orchestrator, analyst, artifact	Unknown agent key
Each agent must have a non-empty system_prompt string	Missing or empty system_prompt
Placeholders must be named — no {}, no {}, no {name.attr}	Invalid placeholder syntax
Orchestrator allows only: {current_date}, {tenant_ids}, {available_tools_count}, {available_tools_list}	Unknown placeholder
Analyst allows only: {tenant_ids}	Unknown placeholder

Artifact allows no placeholders	Any placeholder
<code>native_tools</code> entries must have a non-empty <code>description</code>	Missing description
Tool parameter entries must have <code>type</code> , <code>required</code> (boolean), and <code>description</code>	Incomplete parameter
<code>cloudops_mcp_tools</code> is only valid under <code>analyst</code>	Invalid section placement