TRAIL OFBITS

Slither: API walkthrough

Ţ

Who am I?

Josselin Feist (@montyly)



ToB Twitter list

- Trail of Bits: <u>trailofbits.com</u>
 - We help developers build safer software
 - R&D focused: we use the latest program analysis techniques
 - Slither, Echidna, Tealer, Caracal, solc-select, ...

7

Hackathon rule

- https://github.com/crytic/ethdam
- Up to \$2k for the best project(s)
- Themes
 - UX/UI
 - Impression us with Slither-lsp + vscode
 - On-chain monitoring
 - Show the state variables evolution over time/block number
 - Machine learning
 - Build a RAG with langehain to do code understand / QA bot on solidity
- Criteria
 - Novelty
 - Reliance on Slither (the more the better)



Agenda

- What is Slither
- Slither internals & API
- SlithIR

Slides & hackathon details: https://github.com/crytic/ethdam

Slither

- Static analysis framework for Solidity & Vyper
 - Vulnerability detection
 - Optimization detection
 - Code understanding
 - Assisted code review




https://github.com/crytic/slither

pip3 install -u slither-analyzer

7

Slither



Generic Static Analysis Framework

TRAJL

Assisted code review

Tools

- slither-check-upgradeability: Review delegatecall -based upgradeability
- slither-prop: Automatic unit test and property generation
- slither-flat: Flatten a codebase
- slither-check-erc : Check the ERC's conformance
- slither-format : Automatic patch generation
- slither-read-storage : Read storage values from contracts
- slither-interface : Generate an interface for a contract

Python API

- Python API to help during a code review
 - Inspect contract information
 - Including data dependency/taint analysis

Python API

• Ex: What functions can modify a state variable:

```
slither = Slither('function_writing.sol')
contract = slither.get_contract_from_name('Contract')[0]
var_a = contract.get_state_variable_from_name('a')

functions_writing_a = contract.get_functions_writing_variable(var_a)

print('The function writing "a" are {}'.format([f.name for f in functions_writing_a]))
```


Slither Internals

TRAJL BIT

Slither Internals

• Input: solc AST

```
function safeAdd(uint256 a, uint256 b) ...
  if (a + b <= a) {
    revert();
  }
  return a + b;
}</pre>
```



Ţ

Slither Layers

- Compilation units
 - ~ group of files used by one call to solc
- Contracts
 - o Inheritance, state variables, functions
- Functions
 - Attributes, CFG
- Control Flow Graphs
 - Nodes
- Expression & IR
 - Operations

Slither object

```
from slither import Slither
# Create the slither object
sl = Slither("test.sol")
# Works with the other supported target, ie :
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7") # Load USDT
# Add etherscan_api_key for rate limit
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7", etherscan_api_key=".."
```

Compilation unit

- ~ group of files used by one call to solc
- Most targets have 1 compilation, but not always true
 - Partial compilation for optimization
 - Multiple solc version used
 - o Etc..

```
sl = Slither("test.sol")
sl.compilation_units # array of SlitherCompilationUnit
```

Compilation unit

- Why compilation unit matters?
 - Some APIs might be not intuitive
 - Ex: looking for a contract based on the name?
 - Can have multiple contracts
- For hacking you can (probably) use the first compilation unit
 - compilation_unit = sl.compilation_units[0]

Compilation unit - cheatsheet

- slither/core/compilation_unit.py
- contracts: List[Contract]
 - List of all the contracts
- contracts_derived(self): List[Contract]
 - List of the most derived contracts. I.e. contract not inherited
- get_contract_from_name(contract_name): List[Contract]
 - Usually: returns one contract
- Top level objects
 - [structures | enums | events | variables | functions]_top_level

Compilation unit - example

```
from slither import Slither
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7")
compilation_unit = sl.compilation_units[0]
# Print all the contracts from the USDT address
print([str(c) for c in compilation_unit.contracts])
# Print the most derived contracts from the USDT address
print([str(c) for c in compilation_unit.contracts_derived])
```

Compilation unit - example

```
% python test.py
['SafeMath', 'Ownable', 'ERC20Basic', 'ERC20', 'BasicToken', 'StandardToken', 'Pausable',
'BlackList', 'UpgradedStandardToken', 'TetherToken']
['SafeMath', 'UpgradedStandardToken', 'TetherToken']
```

Contract - cheatsheet

- slither/core/declarations/contract.py
- name: str
- Inheritance
 - o inheritance: List[Contract]: c3 linearization order
 - derived contracts: List[Contract]: contracts derived from it
- General objects
 - enums | events | structures
- Variables
 - state_variables: List[StateVariable]: list of accessible variables
 - state_variables_ordered: List[StateVariable]: all variable ordered by declaration
- get_function_from_signature(sig)

Contract - example

```
from slither import Slither
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7")
compilation_unit = sl.compilation_units[0]
```

```
# Print all the state variables of the USDT token
contract = compilation_unit.get_contract_from_name("TetherToken")[0]
print([str(v) for v in contract.state_variables])
```

Contract - example

```
% python test.py
['owner', 'paused', '_totalSupply', 'balances', 'basisPointsRate', 'maximumFee',
'allowed', 'MAX_UINT', 'isBlackListed', 'name', 'symbol', 'decimals', 'upgradedAddress',
'deprecated']
```

Function - cheatsheet

- core/declarations/function.py
- solidity_signature: str
- entry_point: Node
- Elements
 - expressions, variables, nodes, modifiers
- Operations
 - [state |local]_variable_[read |write]
 - All can be prefixed by "all_" for recursive lookup
 - Ex: all_state_variable_read: return all the state variables read in internal calls
 - slithir_operations

```
from slither import Slither
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7")
compilation_unit = sl.compilation_units[0]
contract = compilation_unit.get_contract_from_name("TetherToken")[0]
```

```
# Print all the state variables read by the totalSupply function
totalSupply = contract.get_function_from_signature("totalSupply()")
print([str(v) for v in totalSupply.state_variables_read])
```

```
% python test.py
['_totalSupply', 'deprecated', 'upgradedAddress']
```

[..]

```
transfer = contract.get_function_from_signature("transfer(address,uint256)")

# Print all the state variables read by the transfer function
print([str(v) for v in transfer.state_variables_read])

# Print all the state variables read by the transfer function and its internal calls
print([str(v) for v in transfer.all_state_variables_read])
```

```
% python test.py
['deprecated', 'isBlackListed', 'upgradedAddress']

['owner', 'basisPointsRate', 'deprecated', 'paused', 'isBlackListed', 'maximumFee', 'upgradedAddress', 'balances']

function transfer(address _to, uint _value) public whenNotPaused {
    require(!isBlackListed[msg.sender]);
    if (deprecated) {
        return UpgradedStandardToken(upgradedAddress).transferByLegacy(msg.sender, _to, _value);
    } else {
        return super.transfer(_to, _value);
    }
}
```



• https://secure-contracts.com/program-analysis/slither/exercise1.html

Exercise 1: Function Overridden Protection

The goal is to create a script that performs a feature that was not present in previous version of Solidity: function overriding protection.

exercises/exercise1/coin.sol contains a function that must never be overridden:

```
_mint(address dst, uint256 val)
```

Use Slither to ensure that no contract inheriting Coin overrides this function.

Use solc-select install 0.5.0 && solc-select use 0.5.0 to switch to solc 0.5.0

```
# Iterate over all the contracts
for contract in slither.contracts:
    # If the contract is derived from MyContract
    if coin in contract.inheritance:
        # Get the function definition
        mint = contract.get_function_from_signature('_mint(address,uint256)')
        # If the function was not declared by coin, there is a bug !
        # Detect error only for contracts overriding the '_mint' function
        if mint.contract_declarer == contract:
            print(f'Error, {contract} overrides {mint}')
```

• https://secure-contracts.com/program-analysis/slither/exercise2.html

Exercise 2: Access Control

The exercises/exercise2/coin.sol file contains an access control implementation with the onlyowner modifier. A common mistake is forgetting to add the modifier to a crucial function. In this exercise, we will use Slither to implement a conservative access control approach.

Our goal is to create a script that ensures all public and external functions call onlyowner, except for the functions on the whitelist.

```
slither = Slither('coin.sol')
whitelist = ['balanceOf(address)']
for contract in slither.contracts:
    for function in contract functions:
        if function.full_name in whitelist:
            continue
        if function.is_constructor:
            continue
        if function.visibility in ['public', 'external']:
            if not 'onlyOwner()' in [m.full_name for m in function.modifiers]:
                print(f'{function.full_name} is unprotected!')
```

https://secure-contracts.com/program-analysis/slither/exercise3.html

Exercise 3: Find function that use a given variable in a condition

The exercises/exercise3/find.sol file contains a contract that use my_variable variable in multiple locations.

Our goal is to create a script that list all the functions that use my_variable in a conditional or require statement.

```
slither = Slither('find.sol')
find = slither.get_contract_from_name('Find')[0]
assert find
# Get the variable
my_variable = find.get_state_variable_from_name("my_variable")
assert my_variable
function_using_a_as_condition = [
    for f in find functions
   if f.is_reading_in_conditional_node(my_variable) or f.is_reading_in_require_or_assert(my_variable)
# Print the result
print(f'The function using "a" in condition are {[f.name for f in function_using_a_as_condition]}')
```

TRAJL BIT.

- New VScode plugin that leverages slither
 - o Go to implementations/definitions
 - Find all references
 - Show call / type hierarchy
 - 0 ...
- Backend: <u>slither-lsp</u>
 - Full access to slither's power

```
∨ 

Owned.onlyOwner()

                                          × src > • Owned.sol
 > ① Owned.setOwner(address)
                                                      contract Owned {
                                                           address public owner;
 > ProtocolFees.setProtocolFeeController(IProtocolFeeCo...
                                                          bytes12 private STORAGE_PLACEHOLDER;
                                                          error InvalidCaller();
                                                 10
                                                          ·/// @notice Emitted when the owner of the factory is changed
                                                          ·/// @param · oldOwner · The · owner · before · the · owner · was · changed
                                                 12
                                                          ·/// @param newOwner The owner after the owner was changed
                                                 13
                                                          event · OwnerChanged(address · indexed · oldOwner, · address · indexed · newOwner);
                                                 14
                                                 15
                                                          modifier onlyOwner() {
                                                 16
                                                          if (msg.sender != owner) revert InvalidCaller();
                                                 17
                                                 18
                                                 19
                                                 20
                                                          ·constructor() {
                                                 21
                                                         owner = msg.sender;
                                                 22
                                                              emit OwnerChanged(address(0), msg.sender);
                                                 23
                                                 24
                                                 25 ~
                                                          -function setOwner(address _owner) external onlyOwner {
                                                 26
                                                              emit OwnerChanged(owner, _owner);
                                                 27
                                                              owner = _owner;
                                                 28
                                                 29
```


- Easy to hack on top of it
 - See slither-lsp's README to add a new command
 - https://github.com/crytic/slither-lsp
 - See contract-explorer's DEV.md page
 - https://github.com/crytic/contract-explorer/blob/master/DEV.md

Where to start

TRAJL

Where to start

- <u>secure-contracts.com</u>
 - program-analysis/slither
 - Base API + exercises
- Demo project
 - o git clone git@github.com;crytic/slither.git
 - o cd slither/tools/demo/
 - Default folder with argument parsing + Slither object creation
- Read <u>slither/detectors</u> code
 - o APIs' usage



Slither

Open source framework to build custom analysis

- Hackathon: https://github.com/crytic/ethdam
 - o \$2k to win
- Need help?
 - EthDam Discord (#trail-of-bits) (@josselin trailofbits)
 - Github (<u>issues</u>, <u>discussions</u>)
 - Slack (https://slack.empirehacking.nyc/, #ethereum)

