TRAIL OFBITS

Slither: Advanced usage

Who am I?

Josselin Feist (@montyly)



ToB Twitter list

- Trail of Bits: <u>trailofbits.com</u>
 - We help developers build safer software
 - R&D focused: we use the latest program analysis techniques
 - o Slither, Echidna, Tealer, Caracal, solc-select, ...

Agenda

- What is Slither
- Advanced usage
- Python API

7

Slither


- Static analysis framework for Solidity & Vyper
 - Vulnerability detection
 - Optimization detection
 - Code understanding
 - Assisted code review



https://github.com/crytic/slither

pip3 install -u slither-analyzer

Slither



Ţ

Vulnerability Detection

TRAIL

Detectors

- 90+ public detectors
- From high severity to optimization
- Based on audit reports
- Proven track of vulnerabilities

	vulnerabilities that were found by Slither. If you found a se with the relevant information.	curity vulnerability usi
Project	Vulnerability	Date
Parity	Incorrect constructor name	July 2018
Parity	Deletion of a mapping with structure	July 2018
Parity	Uninitialized state variables	July 2018
Basis	Missing return value check	Oct 2018
Origin protocol	Reentrancy	Nov 2018
Numeral	Deletion of a mapping with structure	Jul 2019
Numerai	Missing return value	Jul 2019
Flexa	Reentrancy (events out of order)	Sep 2019
<u>0x</u>	Missing return value	Oct 2019
Token mint	Reentrancies	Dec 2019
Airswap	Missing return value check	Feb 2020
Stake Technologies Locks	Iron Dangarous strict equality	Mar 2020

Num	Detector	What it Detects	Impact
1	abiencoderv2- array	Storage abiencoderv2 array	High
2	arbitrary- send-erc20	transferFrom uses arbitrary from	High
3	array-by- reference	Modifying storage array by value	High
4	encode-packed- collision	ABI encodePacked Collision	High
5	incorrect- shift	The order of parameters in a shift instruction is incorrect.	High
6	multiple- constructors	Multiple constructor schemes	High
7	name-reused	Contract's name reused	High
8	protected- vars	Detected unprotected variables	High
9	<pre>public- mappings- nested</pre>	Public mappings with nested variables	High

Detectors cheatsheet

- List the detectors
 - slither –list-detectors
- Run a given detector
 - slither [target] -detect DETECTOR_NAME

- Triage a detector
 - //slither-disable-next-line DETECTOR_NAME
 - // slither-disable-start [detector] ... // slither-disable-end [detector]
- Triage a reentrancy
 - o @custom:security non-reentrant

```
// slither-disable-start reentrancy-eth
function withdraw(uint amount) public{
    require(amount <= balances[msg.sender]);
    Receiver(msg.sender).send_funds{value: amount}();
    balances[msg.sender] -= amount;
}
// slither-disable-end reentrancy-eth</pre>
```

7


```
/// @custom:security non-reentrant

OwnerContract owner_contract;

function withdraw(uint amount) public{
    require(amount <= balances[msg.sender]);
    owner_contract.external_call{value: amount}();
    balances[msg.sender] -= amount;
}</pre>
```

7

- Interactive triage mode
 - slither . --triage-mode
 - o Create a slither.db.json file
- GH action <u>crytic/slither-action</u>



Target cheatsheet

- slither [target]
 - [target] must be compileable
- Direct solc
 - slither file.sol
 - Not recommended if remapping is needed
- Compilation framework
 - [target] is the root directory of the project
 - Support for foundry, hardhat, truffle, dapp, etc.
 - If you run from the directory, run "slither ."
- Extra foundry support
 - slither src/file.sol supports foundry remapping automatically

Target cheatsheet


Onchain analysis

- o slither 0x...
 - Require source code on etherscan
- slither NETWORK:0x...
 - mainet,optim,goerli,sepolia,tobalaba,bsc,testnet.bsc,arbi,testnet.arbi,poly,mumbai,av ax,testnet.avax,ftm,goerli.base,base,gno,polyzk
 - Default mainet



Printers

- Visual representation of the code
- Quick review
 - human-summary
 - inheritance-graph
 - contract-sumarry
 - loc
- In-depth review
 - o call-graph
 - o cfg
 - function-summary
 - vars-and-auth
 - o not-pausable



Printers cheatsheet

- List printers
 - o slither –list-printers
- Run a printer
 - slither [target] -print PRINTER_NAME

Generic Static Analysis Framework

TRAJŁ

Assisted code review

Tools

- slither-check-upgradeability: Review delegatecall -based upgradeability
- slither-prop : Automatic unit test and property generation
- slither-flat: Flatten a codebase
- slither-check-erc : Check the ERC's conformance
- slither-format : Automatic patch generation
- slither-read-storage : Read storage values from contracts
- slither-interface : Generate an interface for a contract

Ţ

Python API

- Python API to help during a code review
 - Inspect contract information
 - Including data dependency/taint analysis

Slither object

```
from slither import Slither
# Create the slither object
sl = Slither("test.sol")
# Works with the other supported target, ie :
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7") # Load USDT
# Add etherscan_api_key for rate limit
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7", etherscan_api_key=".."
```

Slither Layers

- Compilation units
 - ~ group of files used by one call to solc
- Contracts
 - o Inheritance, state variables, functions
- Functions
 - Attributes, CFG
- Control Flow Graphs
 - Nodes
- Expression & IR
 - Operations

Compilation unit

- ~ group of files used by one call to solc
- Most targets have 1 compilation, but not always true
 - o Partial compilation for optimization
 - Multiple solc version used
 - o Etc..

```
sl = Slither("test.sol")
sl.compilation_units # array of SlitherCompilationUnit
```

7

Compilation unit

- Why compilation unit matters?
 - Some APIs might be not intuitive
 - Ex: looking for a contract based on the name?
 - Can have multiple contracts
- For hacking you can (probably) use the first compilation unit
 - compilation_unit = sl.compilation_units[0]

Compilation unit - cheatsheet

- slither/core/compilation_unit.py
- contracts: List[Contract]
 - List of all the contracts
- contracts_derived(self): List[Contract]
 - List of the most derived contracts. I.e. contract not inherited
- get_contract_from_name(contract_name): List[Contract]
 - Usually: returns one contract
- Top level objects
 - [structures | enums | events | variables | functions]_top_level

Compilation unit - example

```
from slither import Slither
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7")
compilation_unit = sl.compilation_units[0]
# Print all the contracts from the USDT address
print([str(c) for c in compilation_unit.contracts])
# Print the most derived contracts from the USDT address
print([str(c) for c in compilation_unit.contracts_derived])
```

Compilation unit - example

```
% python test.py
['SafeMath', 'Ownable', 'ERC20Basic', 'ERC20', 'BasicToken', 'StandardToken', 'Pausable',
'BlackList', 'UpgradedStandardToken', 'TetherToken']
['SafeMath', 'UpgradedStandardToken', 'TetherToken']
```

Contract - cheatsheet

- slither/core/declarations/contract.py
- name: str
- Inheritance
 - o inheritance: List[Contract]: c3 linearization order
 - derived contracts: List[Contract]: contracts derived from it
- General objects
 - enums | events | structures
- Variables
 - state_variables: List[StateVariable]: list of accessible variables
 - state_variables_ordered: List[StateVariable]: all variable ordered by declaration
- get_function_from_signature(sig)

Contract - example

```
from slither import Slither
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7")
compilation_unit = sl.compilation_units[0]
```

```
# Print all the state variables of the USDT token
contract = compilation_unit.get_contract_from_name("TetherToken")[0]
print([str(v) for v in contract.state_variables])
```

Contract - example

```
% python test.py
['owner', 'paused', '_totalSupply', 'balances', 'basisPointsRate', 'maximumFee',
'allowed', 'MAX_UINT', 'isBlackListed', 'name', 'symbol', 'decimals', 'upgradedAddress',
'deprecated']
```

7

Function - cheatsheet

- core/declarations/function.py
- solidity_signature: str
- entry_point: Node
- Elements
 - expressions, variables, nodes, modifiers
- Operations
 - [state |local]_variable_[read |write]
 - All can be prefixed by "all_" for recursive lookup
 - Ex: all_state_variable_read: return all the state variables read in internal calls
 - slithir_operations

```
from slither import Slither
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7")
compilation_unit = sl.compilation_units[0]
contract = compilation_unit.get_contract_from_name("TetherToken")[0]
```

```
# Print all the state variables read by the totalSupply function
totalSupply = contract.get_function_from_signature("totalSupply()")
print([str(v) for v in totalSupply.state_variables_read])
```

```
% python test.py
['_totalSupply', 'deprecated', 'upgradedAddress']
```

[..]

```
transfer = contract.get_function_from_signature("transfer(address,uint256)")

# Print all the state variables read by the transfer function
print([str(v) for v in transfer.state_variables_read])

# Print all the state variables read by the transfer function and its internal calls
print([str(v) for v in transfer.all_state_variables_read])
```

```
% python test.py
['deprecated', 'isBlackListed', 'upgradedAddress']

['owner', 'basisPointsRate', 'deprecated', 'paused', 'isBlackListed', 'maximumFee', 'upgradedAddress', 'balances']

function transfer(address _to, uint _value) public whenNotPaused {
    require(!isBlackListed[msg.sender]);
    if (deprecated) {
        return UpgradedStandardToken(upgradedAddress).transferByLegacy(msg.sender, _to, _value);
    } else {
        return super.transfer(_to, _value);
    }
}
```

Ţ


Control flow graph

- CFG
- Common code representation

```
function safeAdd(uint256 a, uint256 b) ...

if (a + b <= a) {
    revert();
}

return a + b;
}</pre>
```



Control flow graph

- core/cfg/node.py
- If order does not matter
 - o for node in function.nodes
- If order matters
 - Walk through the nodes

```
def visit_node(node: Node, visited: List[Node]):
    if node in visited:
        return
    visited += [node]

# custom action
    for son in node.sons:
        visit_node(son, visited)
```

Control flow graph

- If need to iterate more than once:
 - Bound the iteration X times
 - Create a fix-point abstract interpretation style analysis

Only for advanced usages



SlithIR

- Slither Intermediate Representation
 - Solidity -> Human usage
 - SlithIR -> Code analysis usage

SlithIR

- Less than 40 instructions
- Linear IR (no jump)
- Based on Slither CFG
- Flat IR
- Code transformation/simplification
 - Ex: remove of ternary operator

SlithIR Instructions

Binary/Unary

```
LVALUE = RVALUE + RVALUELVALUE = ! RVALUE...
```

Index

```
O REFERENCE -> LVALUE [ RVALUE ]
```

SlithIR Instructions

- Member
 - REFERENCE -> LVALUE . RVALUE
- New
 - O LVALUE = NEW_ARRAY ARRAY_TYPE DEPTH
 - O LVALUE = NEW_CONTRACT CONSTANT
 - LVALUE = **NEW STRUCTURE** STRUCTURE

note: no new_structure operator in Solidity

SlithIR Instructions

Expression: allowance[_from][msg.sender] -= _value

IRs:


REF_1 -> allowance[_from]

REF_2 -> REF_1[msg.sender]

REF_2 -= _value

÷5 **7**

SlithIR hierarchie



Ţ

SlithIR - example

```
from slither import Slither
sl = Slither("0xdac17f958d2ee523a2206206994597c13d831ec7")
compilation_unit = sl.compilation_units[0]
contract = compilation_unit.get_contract_from_name("TetherToken")[0]
totalSupply = contract.get_function_from_signature("totalSupply()")
```

```
# Print the external call made in the totalSupply function
for ir in totalSupply.slithir_operations:
   if isinstance(ir, HighLevelCall):
        print(f"External call found {ir} ({ir.node.source_mapping})")
```

SlithIR - example

```
% python test.py
External call found HIGH_LEVEL_CALL, [...] (...TetherToken.sol#339)
```

SlithIR Advanced

- Data dependencies
- SSA (Static Single Assignment) support
 - Include state variables
 - o Precise data dependency analysis
- Alias analysis on storage references
 - Allow analysis of complex codebase


Only for advanced usages

Where to start

TRAJL

Where to start

- <u>secure-contracts.com</u>
 - program-analysis/slither
 - Base API + exercises
- Demo project
 - o git clone git@github.com:crytic/slither.git
 - cd slither/tools/demo/
 - Default folder with argument parsing + Slither object creation
- Read <u>slither/detectors</u> code
 - o APIs' usage



Slither

- https://secure-contracts.com/
- github.com/crytic/slither
- Open source framework to build custom analysis
- Need help?
 - Github (<u>issues</u>, <u>discussions</u>)
 - Slack (https://slack.empirehacking.nyc/, #ethereum)
 - @montyly (twitter / tg)