```
public static void main(String[] args) {
        // TODO Auto-generated method stub
        System.out.println("Hello");
        System.out.print("Bye");
        System.out.println("Okay");

    }
```

Java divides the into the following groups:

- Arithmetic operators
- Assignment operators
- Comparison operators
- Logical operators
- Bitwise operators

Arithmetic Operators

Arithmetic operators are used to perform common mathematical operations.

Operator	Name	Description	Example	Try it
+	Addition	Adds together two values	x + y	Try it »
-	Subtraction	Subtracts one value from another	x - y	Try it »
*	Multiplication	Multiplies two values	x * y	Try it »
/	Division	Divides one value by another	x / y	Try it »
%	Modulus	Returns the division remainder	x % y	Try it »
++	Increment	Increases the value of a variable by 1	++x	Try it »
--	Decrement	Decreases the value of a variable by 1	--x	Try it »

ADVERTISEMENT

Java Assignment Operators

Assignment operators are used to assign values to variables.

In the example below, we use the **assignment** operator (=) to assign the value **10** to a variable called **x**:

Example

```
intx =10;
```

Try it Yourself »

The **addition assignment** operator (+=) adds a value to a variable:

Example

```
intx =10;x +=5;
```

Try it Yourself »

A list of all assignment operators:

Operator	Example	Same As	Try it
=	x = 5	x = 5	Try it »
+=	x += 3	x = x + 3	Try it »
-=	x -= 3	x = x - 3	Try it »
*=	x *= 3	x = x * 3	Try it »
/=	x /= 3	x = x / 3	Try it »
%=	x %= 3	x = x % 3	Try it »
&=	x &= 3	x = x & 3	Try it »
|=	x |= 3	x = x | 3	Try it »
^=	x ^= 3	x = x ^ 3	Try it »
>>=	x >>= 3	x = x >> 3	Try it »
<<=	x <<= 3	x = x << 3	Try it »

Java Comparison Operators

Comparison operators are used to compare two values:

Operator	Name	Example	Try it
==	Equal to	x == y	Try it »
!=	Not equal	x != y	Try it »
>	Greater than	x > y	Try it »
<	Less than	x < y	Try it »
>=	Greater than or equal to	x >= y	Try it »
<=	Less than or equal to	x <= y	Try it »

Java Logical Operators

Logical operators are used to determine the logic between variables or values:

Operator	Name	Description	Example	Try it
&&	Logical and	Returns true if both statements are true	x < 5 && x < 10	Try it »
||	Logical or	Returns true if one of the statements is true	x < 5 || x < 4	Try it »
!	Logical not	Reverse the result, returns false if the result is true		

```
public static void main(String[] args) {
    // TODO Auto-generated method stub
    int x = 8;
//  x++;// x = x+ 1;
//  x--;// x = x - 1;
//  System.out.println(x++);// Post Increment
//  System.out.println(x);
    System.out.println(--x);// Pre Decrement
    System.out.println(x);
  }
```

```
int i = x++ - ++x + x++ - --x + --x;//
```

```
int i = ++x - ++x + --x - --x + x++;//
```

```
public static void main(String[] args) {
        // TODO Auto-generated method stub
        int n = 88;
        if(n%2==0) {// yes
            System.out.println("Even");
        }
        else {// No
            System.out.println("Odd");
        }
    }
```

```
public static void main(String[] args) {
        // TODO Auto-generated method stub
        int n = 89;
        if(n%2==0) {// yes
            System.out.println("Even");
        }
        else {// No
            System.out.println("Odd");
        }
    }
```

```
public static void main(String[] args) {
        // TODO Auto-generated method stub
        int a = 21;
        int b = 10;
        int c = 17;
        if(b>=b && b>=c) {
            System.out.println(a);
        }
        else if(b>=a && b>=c) {
            System.out.println(b);
        }
        else {
            System.out.println(c);
        }

    }
```