# A350 ILS APPROACH

Cockpit test guide | Generic procedure | iniBuilds A350 / MSFS 2024

## Purpose

Use this document as a follow-along reference on your next simulator flight. It covers FMS approach selection, ILS tuning, FCU approach capture, FMA monitoring, landing configuration and go-around decisions.

## Before you begin

- ☐ Select the intended landing runway and obtain its current ILS chart.
- ☐ Have current weather, QNH, approach minima and runway information available.
- ☐ Confirm destination fuel and landing performance are acceptable.
- ☐ Review the published missed-approach procedure.

## How to use this guide

Complete the steps in order. Items marked VERIFY describe the cockpit indication or result to confirm before continuing. The procedure is generic: do not copy runway, speed, altitude, frequency or minima figures from another flight.

## Key indications at a glance

LS displays localiser and glideslope scales on the PFD; it does not engage approach mode. APPR on the FCU arms the ILS approach guidance. Blue FMA labels indicate armed modes; green labels indicate modes capturing or active.

**AUTOPILOT GUIDANCE**

Always confirm what the FMA actually displays. A selected approach in the FMS is not proof that the aircraft has captured the ILS.

## Flight test record

**Flight / callsign** _____

**Departure -> destination** _____

**Approach / runway** _____

**ILS frequency / course** _____

**QNH / weather** _____

# 1. FMS & approach preparation

Complete before the localiser intercept.

### 1 Select the destination arrival

On the KCCU/FMS, open the active flight plan. Select the destination airport and open ARRIVAL.

VERIFY: Correct destination airport shown.

### 2 Choose the correct ILS

Select the landing runway and its published ILS approach. Set the appropriate STAR, VIA and transition if required.

VERIFY: Runway, approach and procedure match the chart and clearance.

### 3 Review temporary route changes

Inspect the proposed flight plan (TMPY), including arrival legs, altitude/speed constraints and any discontinuities.

VERIFY: No unexplained route gaps or wrong runway.

### 4 Commit the flight plan

Select INSERT TMPY when the proposed arrival is correct. Reopen the active route and verify that the modifications have taken effect.

VERIFY: Arrival is active, not still a yellow temporary proposal.

### 5 Enter approach performance

Open PERF > APPR. Enter or verify QNH, temperature, wind, minima, landing configuration and approach speed using current flight data.

VERIFY: Performance data align with conditions and the landing plan.

### 6 Check the landing calculation

On OIS LDG PERF, check runway, runway condition, wind and landing weight. Calculate the appropriate landing data.

VERIFY: Landing configuration and performance acceptable.

**IMPORTANT**

The route in the recordings was Sydney to Makassar; this guide intentionally uses no route-specific example values. Check the aircraft against your current flight plan.

# 2. Tune, intercept & capture

Use the ILS chart and ATC clearance to establish a suitable intercept.

### 7 Verify ILS data

Open RAD NAV as needed. Verify the displayed ILS identifier, frequency and inbound course against the chart. The system may tune automatically.

VERIFY: Correct ILS identified; do not assume auto-tune chose the intended runway.

### 8 Display the ILS scales

Select LS on the relevant glare-shield panel to show localiser and glideslope indications on the PFD.

VERIFY: ILS deviation scales visible on PFD.

### 9 Arrange the intercept

Establish an appropriate heading/track and cleared or published altitude to intercept the localiser. Normally intercept the descending glideslope from below.

VERIFY: Aircraft is positioned to capture without excessive speed or descent.

### 10 Check approach phase

On the FMS PERF pages, verify the approach phase is active. Activate it manually if needed in your installed aircraft version.

VERIFY: Approach-speed logic and relevant targets are appropriate.

### 11 Arm approach guidance

Press APPR on the FCU when appropriately established for the ILS intercept.

VERIFY: LOC and G/S (or equivalent) armed indications appear on FMA.

### 12 Confirm localiser capture

Watch the aircraft intercept the runway centreline and monitor the FMA.

VERIFY: LOC* then LOC in green, if displayed by this aircraft version.

### 13 Confirm glideslope capture

Monitor the vertical guidance as the glideslope is intercepted.

VERIFY: G/S* then G/S in green; descent path and altitude consistent with the chart.

**IF CAPTURE FAILS**

Check intercept geometry, selected guidance modes, ILS identification and aircraft altitude. Do not force a steep descent to chase a glideslope from above.

# 3. Final approach & landing

Continue only with appropriate aircraft configuration and stable guidance.

**14** **Reduce speed and configure**

Manage speed and select flaps progressively according to displayed limits, aircraft configuration and the applicable checklist.

VERIFY: Speed targets and configuration agree with the landing plan.

**15** **Extend landing gear**

Select gear DOWN at the appropriate point and complete the landing checklist, including spoilers and braking configuration.

VERIFY: Landing gear and required landing indications confirmed.

**16** **Monitor the FMA**

Continuously confirm the expected guidance modes and deviation from the localiser and glideslope.

VERIFY: LOC and G/S tracking remain satisfactory.

**17** **Decide landing method**

For manual landing, disconnect autopilot when ready and follow valid approach guidance. For autoland, verify dual autopilot and required landing capability indications.

VERIFY: Do not assume APPR alone guarantees autoland.

**18** **Check stability**

Confirm landing configuration, runway alignment, flight path, descent rate, speed and landing clearance according to the applicable criteria.

VERIFY: Aircraft stable by the required gate; otherwise go around.

**19** **Land or go around**

If continuing, fly the flare/touchdown and deceleration using the aircraft procedures. If guidance, clearance or stability is unsuitable, execute the published go-around.

VERIFY: After landing: vacate runway and complete the after-landing flow.

**GO-AROUND**

Use the aircraft's prescribed go-around thrust, guidance, configuration and published missed approach. Never continue a clearly unstable ILS solely because the autopilot is

# Quick check & flight-test notes

Use this page during the test, then mark any steps needing revision.

## Approach flow - condensed

- [ ] FMS ARRIVAL: runway, ILS, STAR, VIA and TRANS checked.
- [ ] TMPY reviewed and inserted; active F-PLN correct.
- [ ] PERF APPR: QNH, wind, minima, configuration and VAPP checked.
- [ ] RAD NAV: ILS ident, frequency and course verified.
- [ ] LS ON: localiser / glideslope scales visible.
- [ ] Intercept set up at a suitable altitude and angle.
- [ ] FCU APPR armed; LOC and G/S appear armed on FMA.
- [ ] LOC green; G/S green; descent and alignment monitored.
- [ ] Gear/flaps/landing checklist complete; approach stable.
- [ ] Manual landing or verified autoland; go around if unstable.

## FMA interpretation

LOC / G/S BLUE = armed. LOC* / G/S* GREEN = capturing. LOC / G/S GREEN = captured or active. Exact annunciation may vary with the current aircraft version.

## What happened differently in the sim?

**ILS / approach** _____

**APPR armed at (NM / ALT)** _____

**LOC captured at** _____

**G/S captured at** _____

**Autopilot / landing mode** _____

**Unexpected indication** _____

**Procedure change to test** _____

Test notes: identify the step number, the control selected, the exact FMA/message shown, and the result. Screenshots of the FMS, FCU and PFD are especially useful.