清華大學
i-VisionGroup

Personal Research and Research Proposal

Jinpeng Liu

liujp22@mails.tsinghua.edu.cn

Education Background

- 2022.08-(exp. 2025) Tsinghua University, M.E. in Data Science
  - Supervisor: Yansong Tang
  - **Leader of Multimodal Generation and Interaction Team at IVG@SZ**
- 2018.08-2022.07 Sun Yat-sen University, B. E. in Intelligent Science and Technology

Industrial Experience

TEXAS The University of Texas at Austin

- Project: **3D Avatar Mesh Recovery**
- Works with Dr. Georgios Pavlakos, Dr. Qixing Huang

Tencent 腾讯

- Project: **3D Object & Scene Generation**
- Works with Dr. Xintao Wang, Dr. Ying Shan

Microsoft

- Project: **3D Avatar Animation**
- Works with Dr. Chunyu Wang, Dr. Xin Tong



Outline

Timeline of previous research

- **2022.06 - 2023.02 (3D-Avatar).** **Jinpeng Liu***, Yansong Tang*, Aoyang Liu*, Bin Yang, Wenxun Dai, Yongming Rao, Jiwen Lu, Jie Zhou, Xiu Li. ***FLAG3D: A 3D Fitness Activity Dataset with Language Instruction.*** **[Accepted by CVPR 2023]**
- **2023.02 - 2023.11 (3D-Avatar).** **Jinpeng Liu**, Wenxun Dai, Chunyu Wang, Yiji Cheng, Yansong Tang, Xin Tong. ***Posture, Plan and Go: Towards Open-world Motion Generation.*** **[Accepted by ECCV 2024]**
- **2023.11 - 2024.04 (3D-Avatar).** Wenxun Dai, Ling-Hao Chen, Jingbo Wang, **Jinpeng Liu**, Bo Dai, Yansong Tang. ***MotionLCM: Realtime Controllable Motion Generation via Latent Consistency Model.*** **[Accepted by ECCV 2024]**
- **2024.04 - 2024.10 (3D-Object).** **Jinpeng Liu**, Jiale Xu, Weihao Cheng, Yiming Gao, Xintao Wang, Ying Shan, Yansong Tang. ***NovelGS: Consistent Novel-view Denoising via Large Gaussian Reconstruction Model.*** **[Submitted to CVPR]**
- **2023.02 - 2024.03 (3D&Video).** Yansong Tang, Aoyang Liu, **Jinpeng Liu**, Shiyi Zhang, Wenxun Dai, Jie Zhou, Xiu Li, Jiwen Lu. ***FLAG3D++: A Benchmark for 3D Fitness Activity Comprehension with Language Instruction.*** **[Submitted to TPAMI]**

Others

- Kun Xiang, Xing Zhang, Jinwen She, **Jinpeng Liu**, Haohan Wang, Shiqi Deng, Shancheng Jiang. Toward robust diagnosis: a contour attention preserving adversarial defense for COVID-19 detection. **[Accepted by AAAI 2023]**
- Jinwen She, **Jinpeng Liu**, et. al. A universal computer-aided diagnosis system for cross-regional skin lesion recognition using deep graph-based network. **[Submitted to NAT COMMUN.]**

Outline

- **Research Projects**
  - Avatar: Controllable & Generable
  - Object: Efficient & Diverse
- **Future Research Proposal**
  - Think deeper about “avatar & object”
    - Avatar-object-scene interaction



Broad Application

- Demand for creative digital products is increasing
- Research results are expected to promote digital life system

Microsoft Minecraft

Meta Quest 2

Apple Vision Pro

Task Description

“Knee raising” →



Language-guided Motion Generation

Low Quantity and Poor Quality of Data



ACTOR
[Petrovich et al. ICCV2021]



MDM
[Tevet et al. ICLR2023]

Text-to-motion
[Guo et al. CVPR2022]



Ours. CVPR2023



清華大學
i-VisionGroup

FLAG3D: A 3D Fitness Activity Dataset with Language Instruction

Jinpeng Liu*, Yansong Tang*, Aoyang Liu*,

Bin Yang, Wenxun Dai, Yongming Rao, Jiwen Lu, Jie Zhou, Xiu Li

Tsinghua University

清華大學

JUNE 18-22, 2023
CVPR
VANCOUVER, CANADA






VICON





FLAG3D features the following three aspects:

Data

Dataset	Subjs	Cats	Seqs	Frames	LA	K3D	SMPL	Resource	Task
PoseTrack [7]	-	-	550	66K	×	×	×	Nat.	HPE
Human3.6M [33]	11	17	839	3.6M	×	✓	-	Lab	HAR,HPE,HMR
CMU Panoptic [37]	8	5	65	594K	×	✓	-	Lab	HPE
MPI-INF-3DHP [57]	8	8	-	>1.3M	×	✓	-	Lab+Nat.	HPE,HMR
3DPW [96]	7	-	60	51k	×	×	✓	Nat.	HMR
ZJU-MoCap [68]	6	6	9	>1k	×	✓	✓	Lab	HAR,HMR
NTU RGB+D 120 [51]	106	120	114k	-	×	✓	-	Lab	HAR,HAG
HuMMan [11]	1000	500	400K	60M	×	✓	✓	Lab	HAR,HMR
HumanML3D [26]	-	-	14K	-	✓	✓	✓	Lab	HAG
KIT Motion Language [71]	111	-	3911	-	✓	✓	-	Lab	HAG
HumanAct12 [28]	12	12	1191	90K	×	×	✓	Lab	HAG
UESTC [35]	118	40	25K	> 5M	×	✓	-	Lab	HAR,HAG
Fit3D [22]	13	37	-	> 3M	×	✓	✓	Lab	HPE,RAC
EC3D [115]	4	3	362	-	×	✓	-	Lab	HAR
Yoga-82 [95]	-	82	-	29K	×	×	×	Nat.	HAR,HPE
FLAG3D (Ours)	10+10+4	60	180K	20M	✓	✓	✓	Lab+Syn.+Nat.	HAR,HMR,HAG

FLAG3D **20M** << LAION-5B **2.3B**

a man walks forward



In-distribution

A man dances the waltz

Out-of-distribution

[1] Tevet G, Raab S, Gordon B, et al. Human Motion Diffusion Model[C]//The Eleventh International Conference on Learning Representations. 2022.

清華大學 i-VisionGroup

Plan, Posture and Go:
Towards Open-vocabulary Text-to-Motion Generation

Jinpeng Liu[1], Wenxun Dai[1], Chunyu Wang[2], Yiji Cheng[1], Yansong Tang[1], Xin Tong[2]

[1]Tsinghua University [2]Microsoft

清華大學

Microsoft

ECCV

Formulation

"The language of movement cannot be translated into words."

——Barbara Mettler(Dancer)

Is there a novel formulation of the motion generation task that can address general text-to-motion problem without relying on paired text-motion data?

Formulation

Motion ? ⇨ **Pose sequence** + **Global Information**

Text → **Motion**

Text → **{Desc.$_1$, Desc.$_2$, … Desc.$_n$}**

{Pose$_1$, Pose$_2$, … Pose$_n$} → **Motion**

Robust Motion In-betweening. SIGGRAPH 20.

Pipeline

divide-and-conquer



Motion Generated by Our Model

Outline

- **Research Projects**
  - Avatar: Controllable & Generable
  - **Object: Efficient & Diverse**
- **Future Research Proposal**
  - Think deeper about “avatar & object”
    - Avatar-object-world interaction



Task Description

Image to 3D

Motivation

3D Representation

- ❌ Point Cloud: Poor visual result
- ❌ Voxel, Mesh : GPU-unfriendly
- ❌ Triplane: Time consuming
- ✅ Gaussian: Real time and easy to scale up





Rendering 2s (60 frames) video cost **1.5min!**

Formulation

- Pixel-aligned Gaussian



Pipeline


Transformer-based Denoiser
3D Gaussians
Positional Encoding
timestep
Transformer
Cross-view Attention
MLP
deconv
linear heads
Rendering loss
Camera Ray Embedding
Clean + Noisy Images
Image tokens
Cross-view Attention
Clean + Noisy Images in Next Step
Time Step T
Time Step T-1

Results

Visualization

Outline

- **Research Projects**
  - Avatar: Controllable & Generable
  - **Object: Efficient & Diverse**
- **Future Research Proposal**
  - Think deeper about “avatar & object”
    - Avatar-object-scene interaction





Task Description

Input: Language & Scene

Output: Interaction





HUMANISE: Language-conditioned Human Motion Generation in 3D Scenes. NeurIPS2023

Localization Error

Walk to the glass doors











Physical Error

Walk to the bed









Potential Solutions

- Physical Error & Localization Error

Physics-based Optimization[1] — *Difficult to design and inflexible*

More Data — Hard to require

Early Fusion[2] — It's not the essence

We need the foundation model !

Physical Knowledge & Object Properties



[1] Diffusion-based Generation, Optimization, and Planning in 3D Scenes. CVPR23
[2] LAVT: Language-Aware Vision Transformer for Referring Image Segmentation. CVPR22

Some Thoughts

Thoughts

- In the last ten years
  - Recommendation beat Search
- In the future ten years
  - Generation beat Recommendation

Basis

- Vision Pro is the iPhone 1. When iPhone 4 will arrive?
- Aim high. Settled down.